




# nonconform: Conformal Anomaly Detection (Python)

Oliver Hennhöfer <sup>1</sup>

<sup>1</sup> Intelligent Systems Research Group, Karlsruhe University of Applied Sciences, Karlsruhe, Germany

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

Quantifying uncertainty is fundamental for AI systems in safety-critical, high-cost-of-error domains, as reliable decision-making depends on it. The Python package nonconform offers statistically principled uncertainty quantification for semi-supervised anomaly detection based on one-class classification (Tax, 2001). It implements methods from conformal anomaly detection (Bates et al., 2023; Jin & Candès, 2025; Laxhammar & Falkman, 2010), grounded in conformal inference (Lei & Wasserman, 2013; Papadopoulos et al., 2002; Vovk et al., 2005).

The package nonconform calibrates anomaly detection models to produce statistically valid  $p$ -values from raw anomaly scores. Conformal calibration uses a hold-out set  $\mathcal{D}_{\text{calib}}$  of size  $n$  containing normal instances, while the model is trained on a separate normal dataset. For a new observation  $X_{n+1}$  with anomaly score  $\hat{s}(X_{n+1})$ , the  $p$ -value is computed by comparing this score to the empirical distribution of calibration scores  $\hat{s}(X_i)$  for  $i \in \mathcal{D}_{\text{calib}}$ . The conformal  $p$ -value  $\hat{u}(X_{n+1})$  is defined as the normalized rank of  $\hat{s}(X_{n+1})$  among the calibration scores (Liang et al., 2024):

$$\hat{u}(X_{n+1}) = \frac{|\{i \in \mathcal{D}_{\text{calib}} : \hat{s}(X_i) \leq \hat{s}(X_{n+1})\}|}{n}.$$

By framing anomaly detection as a sequence of statistical hypothesis tests, these  $p$ -values enable systematic control of the *marginal* (average) false discovery rate (FDR) (Bates et al., 2023; Benjamini & Hochberg, 1995) at a predefined significance level via appropriate statistical procedures. The library integrates seamlessly with the widely used pyod library (Chen et al., 2025; Zhao et al., 2019), extending conformal techniques to a broad range of anomaly detection models.

## Statement of Need

A major challenge in anomaly detection lies in setting an appropriate anomaly threshold, as it directly influences the false positive rate. In high-stakes domains such as fraud detection, medical diagnostics, and industrial quality control, excessive false alarms can lead to *alert fatigue* and render systems impractical.

The package nonconform mitigates this issue by replacing raw anomaly scores with  $p$ -values, enabling formal control of the FDR. Consequently, conformal methods become effectively *threshold-free*, since anomaly thresholds are implicitly determined by underlying statistical procedures.

$$FDR = \frac{\text{Efforts Wasted on False Alarms}}{\text{Total Efforts}}$$

(Benjamini et al., 2009)

34 Conformal methods are *nonparametric* and *model-agnostic*, applying to any model that  
 35 produces consistent anomaly scores on arbitrarily distributed data. Their key requirement is  
 36 the assumption of *exchangeability* between calibration and test data, ensuring the validity of  
 37 resulting conformal  $p$ -values.

38 Exchangeability only requires that the joint data distribution is invariant under permutations,  
 39 making it more general—and less restrictive—than the independent and identically distributed  
 40 (*i.i.d.*) assumption common in classical machine learning.

41 To operationalize this assumption, nonconform constructs calibration sets from training data  
 42 using several strategies, including approaches for low-data regimes (Hennhofer & Preisach,  
 43 2024) that do not require a dedicated hold-out set. Based on these calibration sets, the  
 44 package computes *standard* or *weighted* conformal  $p$ -values (Jin & Candès, 2025), which are  
 45 particularly useful under covariate shift, when exchangeability is only approximate.

46 These tools enable practitioners to build anomaly detectors whose outputs are statistically  
 47 controlled to maintain the FDR at a chosen nominal level.

48 Overall, reliance on exchangeability makes these methods well-suited to cross-sectional data  
 49 but less appropriate for time series applications, where temporal ordering conveys essential  
 50 information.

## 51 Acknowledgements

52 This work was conducted in part under the research projects *Biflex Industrie* (Grant no.  
 53 01MV23020A) funded by the *German Federal Ministry of Economic Affairs and Climate Action*.

## 54 References

- 55 Bates, S., Candès, E., Lei, L., Romano, Y., & Sesia, M. (2023). Testing for outliers with  
 56 conformal  $p$ -values. *The Annals of Statistics*, 51(1). <https://doi.org/10.1214/22-aos2244>
- 57 Benjamini, Y., Heller, R., & Yekutieli, D. (2009). Selective inference in complex research.  
 58 *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering*  
 59 *Sciences*, 367(1906), 4255–4271. <https://doi.org/10.1098/rsta.2009.0127>
- 60 Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: A practical and  
 61 powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B*  
 62 *(Methodological)*, 57(1), 289–300. <https://doi.org/10.1111/j.2517-6161.1995.tb02031.x>
- 64 Chen, S., Qian, Z., Siu, W., Hu, X., Li, J., Li, S., Qin, Y., Yang, T., Xiao, Z., Ye, W., Zhang,  
 65 Y., Dong, Y., & Zhao, Y. (2025). PyOD 2: A python library for outlier detection with  
 66 LLM-powered model selection. *Companion Proceedings of the ACM on Web Conference*  
 67 2025, 2807–2810. <https://doi.org/10.1145/3701716.3715196>
- 68 Hennhofer, O., & Preisach, C. (2024). Leave-One-Out-, Bootstrap- and Cross-Conformal  
 69 Anomaly Detectors. *2024 IEEE International Conference on Knowledge Graph (ICKG)*,  
 70 110–119. <https://doi.org/10.1109/ICKG63256.2024.00022>
- 71 Jin, Y., & Candès, E. J. (2025). Model-free selective inference under covariate shift via weighted  
 72 conformal  $p$ -values. *Biometrika*, asaf066. <https://doi.org/10.1093/biomet/asaf066>
- 73 Laxhammar, R., & Falkman, G. (2010). Conformal prediction for distribution-independent  
 74 anomaly detection in streaming vessel data. *Proceedings of the First International Workshop*  
 75 *on Novel Data Stream Pattern Mining Techniques*, 47–55. <https://doi.org/10.1145/1833280.1833287>
- 77 Lei, J., & Wasserman, L. (2013). Distribution-free prediction bands for non-parametric  
 78 regression. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 76(1),

- 71–96. <https://doi.org/10.1111/rssb.12021>
- 80 Liang, Z., Sesia, M., & Sun, W. (2024). Integrative conformal p-values for out-of-distribution  
81 testing with labelled outliers. *Journal of the Royal Statistical Society Series B: Statistical*  
82 *Methodology*, 86(3), 671–693. <https://doi.org/10.1093/jrsssb/qkad138>
- 83 Papadopoulos, H., Proedrou, K., Vovk, V., & Gammerman, A. (2002). Inductive confidence  
84 machines for regression. In *Machine learning: ECML 2002* (pp. 345–356). Springer Berlin  
85 Heidelberg. [https://doi.org/10.1007/3-540-36755-1\\_29](https://doi.org/10.1007/3-540-36755-1_29)
- 86 Tax, D. (2001). *One-class classification; concept-learning in the absence of counter-examples*  
87 [Dissertation (TU Delft)]. Delft University of Technology. ISBN: 90-75691-05-X
- 88 Vovk, V., Gammerman, A., & Shafer, G. (2005). *Algorithmic learning in a random world*.  
89 Springer. <https://doi.org/10.1007/b106715>
- 90 Zhao, Y., Nasrullah, Z., & Li, Z. (2019). PyOD: A python toolbox for scalable outlier detection.  
91 *Journal of Machine Learning Research*, 20(96), 1–7. [http://jmlr.org/papers/v20/19-011.](http://jmlr.org/papers/v20/19-011.html)  
92 [html](http://jmlr.org/papers/v20/19-011.html)

DRAFT