GetSL1_1I__C__dE_GetS_x_pI_load -- GetS_AckL1_2 -> GetSL1_1I__C__dE_GetS_x_pS

GetSL1_1I__C__dE_GetS_x_pI_load GetSL1_1I__C__dE_GetS_x_pS <GetS_AckL1_2 || response

GetSL1_1I__C__dS_x_pI_load

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

S__C__S

<WBL1_2; (COND_WBL1_2.src==ownerL1_2; NCOND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

S__C__I

<WBL1_2; (COND_WBL1_2.src==ownerL1_2; COND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

<GetS_AckL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

<GetS_AckL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

<GetS_AckL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

<GetS_AckL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

<GetSL1_1; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || access_hit

<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<GetSL1_2; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetS_AckL1_2@resp || access_hit

<PutSL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<GetSL1_1; (COND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || access_hit

<PutEL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

M__C__I

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_ADL1_1@resp; InvL1_1@fwd || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_ADL1_1@resp; InvL1_1@fwd || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_DL1_1@resp || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_DL1_1@resp || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_ADL1_1@resp; InvL1_1@fwd || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_ADL1_1@resp; InvL1_1@fwd || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_DL1_1@resp || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >InvL1_2@fwd; GetM_Ack_DL1_1@resp || access_request

GetML1_1S__C__dM_x_pI_store_GetM_Ack_AD

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

I__C__S

<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<GetSL1_2; (COND_SETFUNC_cacheL1_1.count()==0) ; >GetS_AckL1_2@resp || access_hit

I__C__M

<GetML1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src; NCOND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >InvL1_1@fwd; GetM_Ack_ADL1_2@resp; InvL1_2@fwd || access_request

<GetML1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src; NCOND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >InvL1_1@fwd; GetM_Ack_ADL1_2@resp; InvL1_2@fwd || access_request

<GetML1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src; COND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >InvL1_1@fwd; GetM_Ack_ADL1_2@resp; InvL1_2@fwd || access_request

<GetML1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src; COND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >InvL1_1@fwd; GetM_Ack_ADL1_2@resp; InvL1_2@fwd || access_request

GetML1_2dM_x_pI_store_GetM_Ack_AD__C__S

<GetML1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

<GetML1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

<GetML1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

<GetML1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

<GetSL1_1; (COND_ownerL1_2==msg_PutEL1_2.src) ; >GetS_AckL1_1@resp || access_hit

<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (COND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (NCOND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (NCOND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (COND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<GetML1_1; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_ADL1_1@resp; InvL1_1@fwd || access_hit

<GetML1_1; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_DL1_1@resp || access_hit

<GetML1_1; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_ADL1_1@resp; InvL1_1@fwd || access_hit

<GetML1_1; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_DL1_1@resp || access_hit

<GetML1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >InvL1_1@fwd; GetM_Ack_ADL1_2@resp || access_request

<GetML1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >InvL1_1@fwd; GetM_Ack_ADL1_2@resp || access_request

I__C__I

<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

GetML1_2dM_x_pI_store_GetM_Ack_AD__C__I <GetML1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request
<GetML1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

I__C__E

<GetSL1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >InvL1_1@fwd; GetM_Ack_DL1_2@resp || access_request

<GetSL1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >InvL1_1@fwd; GetM_Ack_DL1_2@resp || access_request

GetSL1_2dM_x_pI_store_GetM_Ack_AD__C__I

<GetSL1_2; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

<GetSL1_2; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

<GetML1_1; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src) ; >Fwd_GetML1_1@fwd || access_hit

<PutSL1_1; (NCOND_ownerL1_1==PutSL1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (COND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (NCOND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (NCOND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (COND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_1; (COND_ownerL1_1==PutSL1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

GetSL1_1M_GetS__C__I

<GetSL1_1; (COND_ownerL1_2==msg_PutEL1_2.src) ; >Fwd_GetSL1_1@fwd || access_hit

GetML1_2dM_x_pI_store__C__I

<GetML1_2; >Fwd_GetML1_1@fwd || access_request

GetSL1_2dM_x_pI_store__C__I

<GetSL1_2; >Fwd_GetML1_1@fwd || access_request

<Inv_AckL1_2; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_ADL1_1@resp; InvL1_1@fwd || response

<Inv_AckL1_2; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_DL1_1@resp || response

<Inv_AckL1_2; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; COND_SETFUNC_cacheL1_1.contains(proxy_msg.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_ADL1_1@resp; InvL1_1@fwd || response

<Inv_AckL1_2; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src; NCOND_SETFUNC_cacheL1_1.contains(proxy_msg.src); COND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_DL1_1@resp || response

<Inv_AckL1_2; (NCOND_acksExpectedL1_2==acksReceivedL1_2) || response

<Inv_AckL1_2; (NCOND_acksExpectedL1_2==acksReceivedL1_2) || response

<Inv_AckL1_2; (NCOND_acksExpectedL1_2==acksReceivedL1_2) || response

<Inv_AckL1_2; (NCOND_acksExpectedL1_2==acksReceivedL1_2) || response

<GetSL1_1; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || access_hit

<GetSL1_2; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetS_AckL1_2@resp || access_hit

<GetSL1_1; (COND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || access_hit

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src) ; >InvL1_2@fwd; GetM_Ack_DL1_1@resp || access_request

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src) ; >InvL1_2@fwd; GetM_Ack_DL1_1@resp || access_request

<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<GetSL1_2; (COND_SETFUNC_cacheL1_1.count()==0) ; >GetS_AckL1_2@resp || access_hit

<PutSL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<GetML1_2; (COND_ownerL1_1==msg_PutML1_1.src; NCOND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >GetM_Ack_ADL1_2@resp; InvL1_2@fwd || access_hit

<GetML1_2; (COND_ownerL1_1==msg_PutML1_1.src; COND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >GetM_Ack_ADL1_2@resp; InvL1_2@fwd || access_hit

<PutEL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

GetML1_1I__C__dM_x_pI_store_GetM_Ack_AD

<GetML1_1; (NCOND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<GetML1_1; (COND_SETFUNC_cacheL1_2.contains(msg_GetML1_2.src); NCOND_acksExpectedL1_2==acksReceivedL1_2) ; >InvL1_2@fwd || access_request

<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<GetML1_2; (COND_ownerL1_1==msg_PutML1_1.src) ; >Fwd_GetML1_2@fwd || access_hit

<PutEL1_2; (NCOND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (NCOND_ownerL1_2==PutSL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (NCOND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (COND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_ownerL1_2==PutSL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (COND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

GetSL1_1I__C__dM_GetS_x_pI_load

<GetSL1_1; >Fwd_GetSL1_2@fwd || access_request

GetML1_1I__C__dM_x_pI_store

<GetML1_1; >Fwd_GetML1_2@fwd || access_request

GetSL1_2I__C__M_GetS

<GetSL1_2; (COND_SETFUNC_cacheL1_1.count()==0) ; >Fwd_GetSL1_2@fwd || access_hit

GetSL1_2S__C__M_GetS

<GetSL1_2; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Fwd_GetSL1_2@fwd || access_hit

<Inv_AckL1_1; (COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src; NCOND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >GetM_Ack_ADL1_2@resp; InvL1_2@fwd || response

<Inv_AckL1_1; (COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src; COND_SETFUNC_cacheL1_2.contains(proxy_msg.src)) ; >GetM_Ack_ADL1_2@resp; InvL1_2@fwd || response

<Inv_AckL1_1; (NCOND_acksExpectedL1_1==acksReceivedL1_1) || response

<Inv_AckL1_1; (NCOND_acksExpectedL1_1==acksReceivedL1_1) || response

<GetSL1_1; (COND_ownerL1_2==msg_PutEL1_2.src) ; >GetS_AckL1_1@resp || access_hit

<GetML1_1; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src) ; >GetM_Ack_DL1_1@resp || access_hit

<GetML1_2; (COND_ownerL1_1==msg_PutML1_1.src) ; >GetM_Ack_ADL1_2@resp || access_hit

<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_2; (NCOND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (COND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutML1_2; (NCOND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_SETFUNC_cacheL1_2.count()==0) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (NCOND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (COND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<GetSL1_2; (COND_ownerL1_1==msg_PutML1_1.src) ; >GetM_Ack_DL1_2@resp || access_hit

<Inv_AckL1_1; (COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >GetM_Ack_ADL1_2@resp || response

<Inv_AckL1_1; (NCOND_acksExpectedL1_1==acksReceivedL1_1) || response

<GetSL1_1; >Fwd_GetSL1_2@fwd || access_request

<GetML1_2; (COND_ownerL1_1==msg_PutML1_1.src) ; >Fwd_GetML1_2@fwd || access_hit

<PutML1_2; (COND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (COND_ownerL1_2==PutSL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (COND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response

<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response

<PutML1_2; (NCOND_ownerL1_2==PutML1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutSL1_2; (NCOND_ownerL1_2==PutSL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<PutEL1_2; (NCOND_ownerL1_2==PutEL1_2.src) ; >Put_AckL1_2@fwd || remote_response

<GetML1_1; >Fwd_GetML1_2@fwd || access_request

GetSL1_2I__C__E_GetS

<GetSL1_2; (COND_SETFUNC_cacheL1_1.count()==0) ; >Fwd_GetSL1_2@fwd || access_hit

GetSL1_2S__C__E_GetS

<GetSL1_2; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Fwd_GetSL1_2@fwd || access_hit

<Inv_AckL1_1; (COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >GetM_Ack_DL1_2@resp || response

<Inv_AckL1_1; (NCOND_acksExpectedL1_1==acksReceivedL1_1) || response

<WBL1_1; (COND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (COND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (COND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (COND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (NCOND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (NCOND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (NCOND_WBL1_1.src==ownerL1_1) || response

<WBL1_1; (NCOND_WBL1_1.src==ownerL1_1) || response

<GetM_Ack_DL1_1; (COND_ownerL1_1==msg_PutML1_1.src) ; >GetM_Ack_ADL1_2@resp || response

<Inv_AckL1_1 || response

<GetM_Ack_DL1_1; (COND_ownerL1_1==msg_PutML1_1.src) ; >GetM_Ack_DL1_2@resp || response

<Inv_AckL1_1 || response

<Inv_AckL1_2; (COND_acksExpectedL1_2==acksReceivedL1_2; COND_ownerL1_2==msg_PutML1_2.src) ; >GetM_Ack_DL1_1@resp || response

<Inv_AckL1_2; (NCOND_acksExpectedL1_2==acksReceivedL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

GetSL1_1I__C__dM_GetS_x_pS <GetS_AckL1_2 || response

<GetM_Ack_DL1_2; (COND_ownerL1_2==msg_PutML1_2.src) ; >GetM_Ack_DL1_1@resp || response

<GetM_Ack_DL1_2; (COND_ownerL1_2==msg_PutML1_2.src) ; >GetM_Ack_DL1_1@resp || response

<Inv_AckL1_2 || response

<Inv_AckL1_2 || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (NCOND_WBL1_2.src==ownerL1_2) || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2; NCOND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response

<WBL1_2; (COND_WBL1_2.src==ownerL1_2; COND_SETFUNC_cacheL1_2.count()==0) ; >GetS_AckL1_1@resp || response