*store; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >InvL1_1@fwd || access_request
*load; (COND_SETFUNC_cacheL1_1.count()==0) || access_hit
<PutML1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response
*store; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) ; >InvL1_1@fwd || access_request
*load; (NCOND_SETFUNC_cacheL1_1.count()==0) || access_hit
<GetSL1_1; >GetS_AckL1_1@resp || remote_response
<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response
*store; (COND_ownerL1_1==msg_PutML1_1.src) || access_hit
<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response
<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response
*load; (COND_SETFUNC_cacheL1_1.count()==0) || access_hit
<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response
I
<GetM_Ack_DL1_1; (COND_ownerL1_1==msg_PutML1_1.src) || response
<GetML1_1; >GetM_Ack_DL1_1@resp || remote_response
<Inv_AckL1_1 || response
dM_x_pI_store
*store; >Fwd_GetML1_1@fwd || access_request
<PutML1_1; (COND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response
<Inv_AckL1_1; (COND_acksExpectedL1_1==acksReceivedL1_1; COND_ownerL1_1==msg_PutML1_1.src) || response
<PutSL1_1; (COND_ownerL1_1==PutSL1_1.src) ; >Put_AckL1_1@fwd || remote_response
<GetML1_1; >Fwd_GetML1_1@fwd || remote_response
<PutML1_1; (NCOND_ownerL1_1==PutML1_1.src) ; >Put_AckL1_1@fwd || remote_response
<PutSL1_1; (NCOND_ownerL1_1==PutSL1_1.src) ; >Put_AckL1_1@fwd || remote_response
M
<GetML1_1; (NCOND_SETFUNC_cacheL1_1.contains(GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_ADL1_1@resp; InvL1_1@fwd || remote_response
<PutSL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response
<PutML1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response
<GetSL1_1; >GetS_AckL1_1@resp || remote_response
*load; (NCOND_SETFUNC_cacheL1_1.count()==0) || access_hit
S
<GetSL1_1; >Fwd_GetSL1_1@fwd || remote_request
<GetML1_1; (COND_SETFUNC_cacheL1_1.contains(GetML1_1.src); COND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_DL1_1@resp || remote_response
<WBL1_1; (COND_WBL1_1.src==ownerL1_1) || response
<WBL1_1; (NCOND_WBL1_1.src==ownerL1_1) || response
M_GetS
<GetML1_1; (NCOND_SETFUNC_cacheL1_1.contains(GetML1_1.src); COND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_DL1_1@resp || remote_response
*load; >Fwd_GetSL1_1@fwd || access_request
<WBL1_1; (COND_WBL1_1.src==ownerL1_1; NCOND_SETFUNC_cacheL1_1.count()==0) || response
dM_GetS_x_pI_load
<GetS_AckL1_1 || response
dM_GetS_x_pS
<GetML1_1; (COND_SETFUNC_cacheL1_1.contains(GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0) ; >GetM_Ack_ADL1_1@resp; InvL1_1@fwd || remote_response
<WBL1_1; (COND_WBL1_1.src==ownerL1_1; COND_SETFUNC_cacheL1_1.count()==0) || response
<WBL1_1; (COND_WBL1_1.src==ownerL1_1) || response
<GetS_AckL1_1; (NCOND_SETFUNC_cacheL1_1.count()==0) || response
dS_x_pI_load
<GetS_AckL1_1; (COND_SETFUNC_cacheL1_1.count()==0) || response
<PutSL1_1; (COND_SETFUNC_cacheL1_1.count()==0) ; >Put_AckL1_1@fwd || remote_response
<Inv_AckL1_1; (NCOND_acksExpectedL1_1==acksReceivedL1_1) || response
dM_x_pI_store_GetM_Ack_AD
*store; (NCOND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request
*store; (COND_SETFUNC_cacheL1_1.contains(msg_GetML1_1.src); NCOND_SETFUNC_cacheL1_1.count()==0; NCOND_acksExpectedL1_1==acksReceivedL1_1) ; >InvL1_1@fwd || access_request

Spec: directoryL1_1