



# Imperative Event Handling: The Observer Pattern

Principles of Functional Programming

Martin Odersky

# The Observer Pattern

The Observer Pattern is widely used when views need to react to changes in a model.

Variants of it are also called

- ▶ publish/subscribe
- ▶ model/view/controller (MVC).

## A Publisher Trait

```
trait Publisher with  
  
  private var subscribers: Set[Subscriber] = Set()  
  
  def subscribe(subscriber: Subscriber): Unit =  
    subscribers += subscriber  
  
  def unsubscribe(subscriber: Subscriber): Unit =  
    subscribers -= subscriber  
  
  def publish(): Unit =  
    subscribers.foreach(_.handler(this))
```

## A Subscriber Trait

```
trait Subscriber with  
  def handler(pub: Publisher)
```

## Observing Bank Accounts

Let's make BankAccount a Publisher:

```
class BankAccount extends Publisher with  
  private var balance = 0  
  
  def deposit(amount: Int): Unit =  
    if amount > 0 then  
      balance = balance + amount  
  
  def withdraw(amount: Int): Unit =  
    if 0 < amount && amount <= balance then  
      balance = balance - amount  
  
    else throw Error("insufficient funds")
```

## Observing Bank Accounts

Let's make BankAccount a Publisher:

```
class BankAccount extends Publisher with
  private var balance = 0
  def currentBalance: Int = balance           // <---
  def deposit(amount: Int): Unit =
    if amount > 0 then
      balance = balance + amount
      publish()                               // <---
  def withdraw(amount: Int): Unit =
    if 0 < amount && amount <= balance then
      balance = balance - amount
      publish()                               // <---
    else throw Error("insufficient funds")
```

## An Observer

A Subscriber to maintain the total balance of a list of accounts:

```
class Consolidator(observed: List[BankAccount]) extends Subscriber with
  observed.foreach(_.subscribe(this))

  private var total: Int = _ // Don't initialize 'total' yet ...
  compute()                  // ... it is assigned in 'compute()'

  private def compute() =
    total = observed.map(_.currentBalance).sum

  def handler(pub: Publisher) = compute()
  def totalBalance = total
end Consolidator
```

## Observer Pattern, The Good

- ▶ Decouples views from state
- ▶ Allows to have a varying number of views of a given state
- ▶ Simple to set up



## Observer Pattern, The Bad

- ▶ Forces imperative style, since handlers are Unit-typed
- ▶ Many moving parts that need to be co-ordinated
- ▶ Concurrency makes things more complicated
- ▶ Views are still tightly bound to one state; view update happens immediately.

To quantify (Adobe presentation from 2008):

- ▶  $1/3^{rd}$  of the code in Adobe's desktop applications is devoted to event handling.
- ▶  $1/2$  of the bugs are found in this code.

## How to Improve?

During the rest of this session we will explore a different way, namely *functional reactive programming*, in which we can improve on the imperative view of reactive programming embodied in the observer pattern.