

ACPoller — Operations guide

This document is written for whoever runs the service day to day, not for whoever built it. It answers questions in the order they actually come up in production.

1. Where things live

Path	Contents	Critical
C:\Program Files\ACPoller\appsettings.json	Configuration, encrypted secrets	Yes
C:\Program Files\ACPoller\logs\	Service logs	No
C:\ProgramData\ACPoller\work\	Working units in progress	No
C:\ProgramData\ACPoller\work\state\processed.db	Processed-message log	Critical
C:\ProgramData\ACPoller\work_quarantine\	Abandoned units, kept 30 days	No
C:\ProgramData\ACPoller\ui-settings.default.json	Interface address and token	No
%APPDATA%\ACPoller\ui-settings.json	Each operator's own settings	No

Backup

Two items belong in the server backup:

- C:\ProgramData\ACPoller\work\state\processed.db
- C:\Program Files\ACPoller\appsettings.json

Losing processed.db causes everything still in the mailboxes to be processed again, hence duplicates in the ECM. It is the only file whose loss has an irreversible consequence: the others can be rebuilt, this one carries the history of what has already been delivered.

appsettings.json can be rebuilt, but every secret would have to be entered again, an afternoon's work across a hundred mailboxes.

2. Checking that things are fine

Open the interface, **Dashboard** tab. Four numbers are enough:

Success rate. Below 100 %, the per-configuration breakdown at the bottom names the mailbox involved.

95th percentile duration. A wide gap with the average points to slow messages holding concurrent slots. Other mailboxes wait meanwhile.

Graph throttling. Non-zero in steady state means concurrency must come down or spacing must go up, in the Protocol tab of the configuration concerned.

Free disk. Below 15 % the indicator turns red. At saturation, capture stops.

Without the interface, the same information in one command:

```
curl -H "X-ACPoller-Token: <token>" http://127.0.0.1:5199/api/status
```

3. The five common incidents

A message comes back every cycle

Marking is not happening, or the deduplication key is not stable.

First check that **delivery succeeds**: marking only happens once delivery is confirmed, deliberately. A duplicate can be spotted and corrected, a silent loss cannot.

If delivery succeeds, look at the disposition in the Protocol tab: with **None**, the message stays unread and will be read again every cycle. That is useful during acceptance testing, not in production.

The merged PDF is empty or incomplete

Open the information file next to the PDF and look at the status of each part:

Status	Meaning
Converted	Faithful PDF, present in the merged document
PassThrough	Already a PDF, taken as is
PassThroughUnverified	Delivered alongside, ABSENT from the merged file
Substituted	Not converted : a page carrying the reason replaces it
Failed	Nothing reached the ECM for this part
Excluded	Deliberately dropped: extension filter or signature image

The three statuses in bold mean the ECM does not have the document.

If every office document fails, LibreOffice is missing or misconfigured. Test it from the interface, **Test** button.

The disk fills up

The working directory is only cleaned up once delivery is confirmed. A build-up therefore points to failed deliveries.

The **Maintenance** button triggers an immediate pass: it quarantines unfinished units older than seven days and removes orphan directories.

If the volume does not drop, look at `_quarantaine`: units are kept there for thirty days, with the original message. That is intended, but it takes space.

The service does not start

The start-up log says everything:

```
findstr /i "worker(s) démarre" logs\acpoller-*.log
```

The line `N worker(s) démarre(s), M ecarte(s)` gives the count. If `M` is not zero, the reasons are just above, at `Error` level.

A configuration set aside does NOT stop the others from running: that is deliberate. It appears in the interface with its issues in red.

The interface says the token is rejected

The token in `%APPDATA%\ACPoller\ui-settings.json` does not match the service one. Open **Connection**, then **Test connection**: the message tells an unreachable service apart from a rejected token.

The token in clear text sits in `C:\ProgramData\ACPoller\ui-settings.default.json`, left there by the installer.

4. Replaying a message

The original message is kept in the working directory of that message, under the name `message.eml`, and in quarantine for abandoned units.

1. Copy the `.eml` into a folder, say `D:\replay\`
2. Create a configuration using the **folder** protocol pointing at it
3. Give it the same targets as the original configuration, or test targets
4. Start it

The message is replayed identically, without touching the mailbox or the network. This is also how a customer incident is reproduced on a development machine.

Careful: the processed-message log applies in folder mode too. To replay the same message twice, either change the configuration name or purge the log.

5. Reading the information file

A file accompanies every PDF, in the format declared in the configuration.

What to look at first:

- **CorrelationId**: unique identifier of the processing, present in every log line. It is the key to reconstructing what happened.
- **FailedCount**: above zero, parts are missing.
- **Warnings**: the reason for each failure, in plain words.

- **Items** : one entry per part, with its status.
- **Fields** : the custom fields declared in the configuration.

To trace the full processing of a message:

```
findstr /i "<CorrelationId>" logs\acpoller-*.log
```

6. Routine tasks

Suspending a mailbox

Clear **Configuration active** in the General tab, save. The worker stops, the settings are kept.

Changing a password

Protocol tab, enter the new value, save. The secret is encrypted by the service on first access.

Leaving the field empty keeps the current value. The interface never receives secrets, so it cannot send them back.

Adding a mailbox to an existing fleet

Use a **template**: the new configuration then comes down to its name, the template and the address. The Templates tab shows the existing ones and how many mailboxes inherit from each.

Changing a service setting

Service button. These settings are not reloadable: after saving, an amber banner appears and a notification shows in the system tray. Restart with:

```
Restart-Service ACPoller
```

Changing the log level without a rebuild

```
setx ACPOLLER_LOGLEVEL Debug /M
Restart-Service ACPoller
```

The variable avoids editing `nlog.config`, but the service still has to restart to read it.

7. What not to do

Do not delete `processed.db` to “start clean”. Everything still in the mailboxes will be processed again.

Do not edit `appsettings.json` **by hand while the service runs**. The interface detects concurrent changes and refuses to overwrite, but the reverse is not true: a manual edit during a save from the interface would be lost.

Do not delete the `appsettings.json.*.bak` **files without reading them**. They are the automatic backups taken before each change, and the only way back. The `.clear.*.bak` **files, however, hold the secrets IN CLEAR TEXT** and must be deleted once encryption is verified.

Do not raise the extraction bounds without reason. They protect against a crafted archive, and processed files arrive by mail, therefore from anyone.

8. Resuming after a long outage

After several days down, the mailboxes hold the backlog.

1. Check disk space before starting
2. Temporarily lower the per-cycle message cap to spread the load
3. Watch Graph throttling on the dashboard during the first hour
4. Restore nominal values once the backlog is cleared

The random startup delay already spreads the first cycle, but on a large fleet the catch-up remains the most exposed moment.