

ACPoller — Installation guide

Prerequisites

Item	Requirement
Operating system	Windows Server 2016 or later
.NET runtime	None: the build is self-contained
LibreOffice	Optional, but without it no office document is converted
qpdf	Optional, repairs PDFs the reader engine refuses
Disk space	500 MB for the product, plus the working volume

Windows Server 2012 R2 is not supported: .NET 10 does not run on it.

The service account

This is the installation decision with the heaviest consequences.

The Local System account has NO network identity. A service running under it can neither reach a UNC share nor authenticate against an internal FTP server. The error only surfaces at the first delivery, hours after installation.

Plan for a dedicated domain account, with:

- **Log on as a service** in the local policy
- **Modify** on the ECM delivery folder
- **Read** on the certificate private key, if Graph authentication uses a certificate

The account does not need to be a server administrator.

Installation

1. Run `ACPoller-x.y.z-setup.exe` as administrator
2. Accept the licence, pick the components
3. **Enter the service account** on the dedicated page
4. Tick LibreOffice and qpdf if they are not already installed

The installer creates the directories under `ProgramData`, generates the control token, sets the NTFS permissions and registers the service as delayed automatic start with automatic restart after failure.

Installing LibreOffice silently takes several minutes. The progress page looks frozen during that time, which is normal.

First configuration

The service is installed but does nothing: no mailbox is declared yet.

1. Launch **ACPoller** from the Start menu
2. The interface connects on its own, the token having been left for it
3. **New** button, fill in the source and at least one target
4. **Test** button before saving
5. Tick **Configuration active**

The floor date

Set it at go-live if history is not being imported. Without it, the first run processes everything sitting in the mailbox, which can amount to thousands of messages.

General tab, *Never process messages older than*.

Across several mailboxes

Create a **template** first, carrying everything that is common: tenant, credentials, targets, output mode. Each mailbox then comes

down to its name, the template and its address.

The day the client secret changes, one edit is enough.

After the first start

Secrets entered in clear text are encrypted on first access. The service keeps a copy of the original file as `appsettings.json.clear*.bak`.

Those files hold the secrets IN CLEAR TEXT. Check that encryption took place, then delete them:

```
findstr /i "ENC:" "C:\Program Files\ACPoller\appsettings.json"
del "C:\Program Files\ACPoller\appsettings.json.clear*.bak"
```

Upgrading

A new version's installer:

- stops the service, replaces the binaries, restarts it
- **keeps** `appsettings.json` and drops the new reference version as `appsettings.json.nouveau`
- **keeps** the processed-message log

Compare `appsettings.json.nouveau` with the configuration in place to pick up the settings the new version added.

Uninstalling

The installer deliberately keeps:

- `C:\Program Files\ACPoller\appsettings.json`, holding the secrets and the configuration
- `C:\ProgramData\ACPoller`, holding the processed-message log

Deleting the processed-message log causes the entire history to be processed again at the next installation, hence duplicates in the ECM.

LibreOffice is not uninstalled: it may have been installed before ACPoller or serve something else on that server.

Go-live checklist

To be run on the customer server before declaring the service operational.

Check	How	Expected
Service started	Get-Service ACPoller	Running
Active workers	Start-up log	N started, 0 set aside
Source reachable	Test button	Every component green
Targets reachable	Test button	Actual write confirmed
LibreOffice	Start-up log	Path resolved, no warning
qpdf	Start-up log	Path resolved
Account network access	Test a UNC target	Delivery succeeds
First message	Drop a test message	PDF and information file in the ECM
Idempotence	Wait for a second cycle	The message is not processed again
Restart	Restart-Service ACPoller	Resumes without duplicates

The **account network access** row is the one that fails most often, and it only fails against a real share: a local test does not cover it.