

Hostname:

```
[berserk@Centos-Router-OYL ~]$ hostname  
Centos-Router-OYL.OYL.internal  
[berserk@Centos-Router-OYL ~]$
```

Nano-Vim:

```
[berserk@Centos-Router-OYL ~]$ dnf list installed | grep nano  
nano.x86_64 8.1-3.el10 @baseos  
[berserk@Centos-Router-OYL ~]$ dnf list installed | grep vim  
vim-common.x86_64 2:9.1.083-15.el10 @appstream  
vim-data.noarch 2:9.1.083-15.el10 @anaconda  
vim-enhanced.x86_64 2:9.1.083-15.el10 @appstream  
vim-filesystem.noarch 2:9.1.083-15.el10 @baseos  
vim-minimal.x86_64 2:9.1.083-15.el10 @anaconda
```

Selinux:

```
[berserk@Centos-Router-OYL ~]$ grep SELINUX= /etc/selinux/config  
getenforce  
# SELINUX= can take one of these three values:  
# NOTE: In earlier Fedora kernel builds, SELINUX=disabled would also  
SELINUX=permissive  
Permissive
```

Users and groups:

```
[berserk@Centos-Router-OYL ~]$ id berserk  
id pingu  
getent group allow_ssh  
uid=1000(berserk) gid=1000(berserk) groups=1000(berserk),10(wheel),1002(allow_ss  
h)  
uid=1001(pingu) gid=1001(pingu) groups=1001(pingu),10(wheel),1002(allow_ssh)  
allow_ssh:x:1002:berserk,pingu  
[berserk@Centos-Router-OYL ~]$
```

SSH AllowGroups:

```
[berserk@Centos-Router-OYL ~]$ sudo grep AllowGroups /etc/ssh/sshd_config  
[sudo] password for berserk:  
AllowGroups allow_ssh  
[berserk@Centos-Router-OYL ~]$
```

IP Plan:

IP Address	Subnet Mask	Status	Description	DNS	MAC Address
192.168.224.1	255.255.255.0	Used	Centos-Router-OYL		52:54:00:48:0e:73
192.168.224.2	255.255.255.0	Used	Centos-jump-OYL		52:54:00:ba:a4:b4
192.168.224.3	255.255.255.0	Used	Centos-ns1-OYL		52:54:00:af:45:47
192.168.224.4	255.255.255.0	Used	Centos-ns2-OYL		52:54:00:e6:02:63
192.168.224.5	255.255.255.0	Used	Fedora-GUI		52:54:00:3c:4c:30

AutomaticUpdates:

```
• dnf-automatic.timer - dnf-automatic timer
  Loaded: loaded (/usr/lib/systemd/system/dnf-automatic.timer; enabled; pres>
  Active: active (waiting) since Mon 2026-08-10 13:00:42 CEST; 57min ago
  Invocation: bfa4a09d72254b2e8c4436896d3a819d
  Trigger: Tue 2026-08-11 06:48:03 CEST; 16h left
  Triggers: • dnf-automatic.service

Aug 10 13:00:42 Centos-Router-OYL.OYL.internal systemd[1]: Started dnf-automati>
```

Network (LAN):

```
=====
                        Connection profile details (enp2s0)
=====
connection.id:                enp2s0
connection.uuid:               56ea1699-760f-3046-b281-cee7bdde2459
connection.stable-id:         --
connection.type:               802-3-ethernet
connection.interface-name:     enp2s0
connection.autoconnect:        yes
connection.autoconnect-priority: -999
connection.autoconnect-retries: -1 (default)
connection.multi-connect:      0 (default)
connection.auth-retries:       -1
connection.timestamp:          1786359643
connection.permissions:        --
connection.zone:               internal
connection.controller:         --
connection.master:             --
connection.slave-type:         --
connection.port-type:          --
connection.autoconnect-slaves: -1 (default)
connection.autoconnect-ports:  -1 (default)
connection.down-on-poweroff:    -1 (default)
connection.secondaries:        --
connection.gateway-ping-timeout: 0
connection.ip-ping-timeout:     0
connection.ip-ping-addresses:   --
connection.ip-ping-addresses-require-all: -1 (default)
connection.metered:             unknown
lines 1-29
```

Firewall Internal:

```
[berserk@Centos-Router-OYL ~]$ sudo firewall-cmd --zone=internal --list-all
[sudo] password for berserk:
internal (active)
  target: default
  ingress-priority: 0
  egress-priority: 0
  icmp-block-inversion: no
  interfaces: enp2s0
  sources:
  services:
  ports: 67/udp 53/udp 53/tcp
  protocols:
  forward: yes
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
[berserk@Centos-Router-OYL ~]$
```

Firewall Secure:

```
[berserk@Centos-Router-OYL ~]$ sudo firewall-cmd --zone=secure --list-all
secure (active)
  target: default
  ingress-priority: 0
  egress-priority: 0
  icmp-block-inversion: no
  interfaces:
  sources: 192.168.224.2
  services:
  ports: 22/udp 22/tcp 53/tcp 53/udp 67/udp
  protocols:
  forward: no
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
[berserk@Centos-Router-OYL ~]$
```

Firewall External:

```
[berserk@Centos-Router-OYL ~]$ sudo firewall-cmd --zone=external --list-all
external (active)
  target: default
  ingress-priority: 0
  egress-priority: 0
  icmp-block-inversion: no
  interfaces: enp1s0
  sources:
  services:
  ports:
  protocols:
  forward: yes
  masquerade: yes
  forward-ports:
    port=22:proto=tcp:toport=22:toaddr=192.168.224.2
  source-ports:
  icmp-blocks:
  rich rules:
[berserk@Centos-Router-OYL ~]$
```

Policy:

```
[berserk@Centos-Router-OYL ~]$ sudo firewall-cmd --permanent --info-policy=lan2wan
an
[sudo] password for berserk:
lan2wan
  disable: no
  priority: 100
  target: ACCEPT
  ingress-zones: internal secure
  egress-zones: external
  services:
  ports:
  protocols:
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
[berserk@Centos-Router-OYL ~]$
```

IP Forwarding:

```
[berserk@Centos-Router-OYL ~]$ sysctl net.ipv4.ip_forward
net.ipv4.ip_forward = 1
[berserk@Centos-Router-OYL ~]$ cat /etc/sysctl.d/ipforward.conf
net.ipv4.ip_forward=1
[berserk@Centos-Router-OYL ~]$ nmcli -f ipv4.method,ipv4.addresses,connection.autoconnect connection show enp2s0
ipv4.method:                               manual
ipv4.addresses:                            192.168.224.1/24
connection.autoconnect:                   yes
[berserk@Centos-Router-OYL ~]$
```

dnsmasq:

```
[berserk@Centos-Router-OYL ~]$ ss -ulnp | grep -E '53|67'
UNCONN 0      0      0.0.0.0:53      0.0.0.0:*
UNCONN 0      0      0.0.0.0:67      0.0.0.0:*
UNCONN 0      0      [::]:53        [::]:*
[berserk@Centos-Router-OYL ~]$ grep -E 'interface|listen-address|domain|dhcp-range|dhcp-option|host-record|dhcp-host' /etc/dnsmasq.d/dhcp.conf
interface=enp2s0
listen-address=192.168.224.1
domain=OYL.internal
dhcp-range=192.168.224.50,192.168.224.100,12h
dhcp-option=option:router,192.168.224.1
dhcp-option=option:dns-server,192.168.224.1
host-record=Centos-Router-OYL,Centos-Router-OYL.OYL.internal,192.168.224.1
host-record=Centos-jump-OYL,Centos-jump-OYL.OYL.internal,192.168.224.2
host-record=Centos-ns1-OYL,Centos-ns1-OYL.OYL.internal,192.168.224.3
host-record=Centos-ns2-OYL,Centos-ns2-OYL.OYL.internal,192.168.224.4
dhcp-host=52:54:00:ba:a4:b4,192.168.224.2
dhcp-host=52:54:00:af:45:47,192.168.224.3
dhcp-host=52:54:00:e6:02:63,192.168.224.4
[berserk@Centos-Router-OYL ~]$
```