

Statistics 452: Statistical Learning and Prediction

Chapter 8, Part 4: Regression Trees Lab

Brad McNeney

2018-11-02

Boston Data

- ▶ Recall the Boston dataset in which the response is the median house price in \$1000 and there are 13 predictors.
- ▶ As on the midterm, I've replaced the variable `black` by `predAA`, an indicator that takes value 1 if the town is predominantly African American and 0 otherwise.


Training and Test Data

- Split the data in half for training and testing.

```
set.seed(1)
train <- sample(1:nrow(Boston),nrow(Boston)/2)
```


Regression Tree

```
library(tree)
tt <- tree(medv ~ ., data=Boston, subset=train)
plot(tt) # only rm, lstat, tax and dis used
text(tt)
```



Cross-Validation to Prune Tree

```
cvt <- cv.tree(tt)
plot(cvt) # No pruning required -- could use size 5
```



based on parsimony

Test Set Error

- Use the unpruned tree

```
yhat <- predict(tt,newdata=Boston[-train,])  
y <- Boston[-train,"medv"]  
mean((y-yhat)^2)
```

```
## [1] 25.04559
```

Bagging

```
library(randomForest)
set.seed(1) # for bootstrapping
btt <- randomForest(medv ~ ., data=Boston, subset=train,
                    mtry=13) # mtry=p for bagging
yhat <- predict(btt, newdata=Boston[-train,])
mean((y-yhat)^2)
```

```
## [1] 12.93789
```

Random Forest

```
set.seed(1) # for bootstrapping
rtt <- randomForest(medv ~ ., data=Boston, subset=train,
                    mtry=sqrt(13), importance=TRUE)
yhat <- predict(rtt, newdata=Boston[-train,])
mean((y-yhat)^2)
```

```
## [1] 11.5727
```

```
importance(rtt)
```

```
##           %IncMSE IncNodePurity
## crim      13.624844      1302.46550
## zn         3.063279       130.58952
## indus     10.751141     1233.05949
## chas       2.449582       115.44442
## nox       13.646660     1447.61798
## rm        28.120867     5476.38837
## age        9.398114       715.14472
## dis       13.575117     1382.47645
## rad        5.028803       162.43799
## tax        9.512444       642.01260
## ptratio   11.263839     1315.85311
## lstat     26.179457     6210.01315
## predAA     7.248321        60.13087
```


Boosting

```
library(gbm)
bott <- gbm(medv ~ ., data=Boston[train,],
            distribution="gaussian",n.trees=1000) #M
yhat <- predict(bott,newdata=Boston[-train,],n.trees=1000)
mean((y-yhat)^2)
```

```
## [1] 13.81823
```

Boosting with Greater Interaction Depth

```
bott <- gbm(medv ~ ., data=Boston[train,], interaction.depth=4,  
            distribution="gaussian",n.trees=1000)  
yhat <- predict(bott,newdata=Boston[-train,],n.trees=1000)  
mean((y-yhat)^2)
```

```
## [1] 10.05349
```

Boosting with Less Shrinkage

```
bott <- gbm(medv ~ ., data=Boston[train,], interaction.depth=4,  
            shrinkage=0.001, # decrease from default 0.1  
            distribution="gaussian",n.trees=1000)  
yhat <- predict(bott,newdata=Boston[-train,],n.trees=1000)  
mean((y-yhat)^2)
```

```
## [1] 29.02575
```