

Plan recovery in reactive HTNs using symbolic planning

Lydia OULD OUALI

LIMSI-CNRS, UPR 3251, Orsay, France

Univ. Paris-Sud, Orsay, France

Email: ouldouali@limsi.fr

Charles RICH

Worcester Polytechnic Institute

Worcester, MA, USA

Email: rich@wpi.edu

Nicolas SABOURET

LIMSI-CNRS, UPR 3251, Orsay, France

Univ. Paris-Sud, Orsay, France

Email: Nicolas.Sabouret@limsi.fr

Abstract—

I. INTRODUCTION

Automatic planning is an important field of controlling artificial agents in complex and dynamic environments where research built two different approaches. The first one is symbolic planning: this approach consists in constructing a complete symbolic and logical model of the environment that allows the agent to reason about this model and define a complete plan to carry out its goals. The most popular architecture used to describe the environment is the hierarchical architecture HTN (Hierarchical Tasks Network) [Ero96], which allows a recursive decomposition of complex goals into sub-goals or primitive actions. The HTN architecture eases the design of the environment and gives more expressiveness. Multiple planning systems using this approach were developed such as SHOP [NCLMA99], SIPE [Wil88] or NOAH [Sac75]. Symbolic planning assumes that the environment is fully defined. By consequence, the agent is able to predict all the possible situations and to plan in advance. Nevertheless, it becomes clear that authoring a complete representation of a dynamic and complex environment such as simulation of human behavior [CGS98] or the definition of dialog systems [AF02] requires significant knowledge-engineering effort [ZHH⁺09], and even reveals to be impossible [Mae90]. However, with incomplete knowledge the agent cannot anticipate the future and the generated plan might be not executed as expected. Therefore, if at any point of the execution the plan breakdowns (i.e action execution fails), the planner has to stop the execution and build another plan that achieves the agent's goals. Such operation might be costly in terms of time and resources.

Because of these limitations, another planning approach called reactive planning was proposed [Fir87]. Reactive planning avoids long-term prediction and leaves all the planning during the execution phase: the agent plans only for the next step to be executed from the current defined state of the environment. Thus, it can adapt the next step according to the observed changes. The main advantage of reactive planning systems is they don't need a complete definition of the environment. Instead, they aim to define the policy of the agent in its environment by running through a pre-authored HTN structure with procedural knowledge. Procedural knowledge defines conditions in the HTN domain knowledge as black-box

procedures (for example : JavaScript code) that contains no logical information (i.e no symbolic knowledge). This type of reactive HTN eases the design, reduce the complexity of planning and still can cope with complex dynamic environments [Bro05]. They are used in numerous application domains, such as dialog systems [BR03] and simulating human behavior [Bro05].

Nevertheless, breakdowns can still appear in reactive planning. An action execution can fail and leads the HTN to a state where no action can be applicable to achieve the goal. In such situation, the agent has to stop and think about a new solution to reach its goal. However, without symbolic knowledge, the agent has nothing to reason about. The execution thus stops and the agent cannot recover from its breakdown.

In order to deal with this limitation, we propose in this paper to extend reactive HTNs with a linear symbolic planner. For this reason, we propose to the HTN author to extend the procedural knowledge of the HTN with some symbolic knowledge that allows the symbolic planner to compute local recovery plans. We study the capacity of such model to recover from breakdowns in reactive planning.

In section 2, we briefly present existing works in this domain. In section 3 we formalize the proposed solution *Discolog* and describe its implementation. Section 4, presents the experiments and discusses the obtained solutions. At the end, we discuss the future works to validate and extend our solution to different domains and uses.

II. BACKGROUND AND RELATED WORKS

A. Hierarchical and linear symbolic planning

- Basic structure of linear planning STRIPS action structure + planning solution [FN72]
- HTN architecture: hierarchical structure in AND/OR tree. Compound task . Planning : task decomposition until primitive tasks are reached. [Ero96]

B. Related works and previous approaches

- Reactive planning becomes very popular in AI such in controlling mobile agents [BBC⁺05], simulating human behaviour [BS01] or Gaming with the name of behaviour trees. Behaviours trees have the same hierarchical structure of HTNs and do Real time decision which can be seen as reactive planning. Nevertheless, As reactive planning is

used for highly dynamic environments it presents certain limits as discussed below:

- C. Brom [Bro05] proposes in his work an educational toolkit for prototyping human-like behaviour. the proposed reactive architecture was based on the work proposed in [BS01]. Nevertheless, this reactive planning system faces some limits such as : impossibility to add new goals during the execution or inhibit an undesirable subtask. unnatural switching between behaviour.
- R. James Firby [Fir87]
- plan repair by extending the generated plan with graph containing the causal links between the HTN's tasks [AKYG07] [WHLUMA07] [VDKDW05] [BD02]
- plan repair using heuristic [HTHO06]

III. MOTIVATION

Include symbolic knowledge to allow the agent on reasoning.
Example : such as the robot moving an object from room 1 to room 2

IV. DISCOLOG

A. overview of the solution

present the concept of the hybrid planning system that include a reactive HTN and a simple linear planner: Describe the architecture of HTN and how to use it to integrate symbolic planning system. and propose to the HTN author to extends the boolean structure that approach a symbolic structure.

1. How a breakdown is detected
2. Use the algorithm to describe the plan recovery steps.
 - 2.1. Calculate candidates: Detect the failed task and all the tasks affected by the breakdown
 - 2.2. How linear planner constructs its domain knowledge, build a plan recovery and calculates the best one.
 - 2.3. Transform the symbolic plan to a procedural one.

B. Implementation : Discolog

1. Brief presentation of the main architecture of Disco + ref + STRIPS in prolog
- Describe how Discolog runs on an example :

V. EXPERIMENTS AND RESULTS

1. Approach of the experiments: Test the capability of Discolog to recover from a breakdown given a certain amount of symbolic knowledge.
2. Benchmark creation:
Random HTNs with synthetic data. Breakdown caused in each primitive task. The purpose is to study the ability of Discolog to find a plan recovery for all possible breakdowns in the HTN. Symbolic data generation : the variation of the level of symbolic knowledge to insert in the linear planner domain knowledge
3. Present the obtained results and discuss them.

results obtained of tree (5,4,1) (2,3,2) (3,3,3)

Discuss the fact that the more symbolic knowledge we have the more recovery we get. Expose the fact that we can not have a 100 of symbolic knowledge and its is limited to the representation of the HTN author which is also incomplete.

VI. CONCLUSION

Remind the context of our work. the proposition and its advantages. the future work :

1. present system support for authoring reactive HTNs.
2. dialog system using Discolog

REFERENCES

- [AF02] James Allen and George Ferguson. Human-machine collaborative planning. In *Proceedings of the Third International NASA Workshop on Planning and Scheduling for Space*, pages 27–29, 2002.
- [AKYG07] N Fazil Ayan, Ugur Kuter, Fusun Yaman, and Robert P Goldman. Hotride: Hierarchical ordered task replanning in dynamic environments. In *Planning and Plan Execution for Real-World Systems—Principles and Practices for Planning in Execution: Papers from the ICAPS Workshop*. Providence, RI, 2007.
- [BBC⁺05] Eric Beaudry, Yannick Brosseau, Carle Côté, Clément Raïevsky, Dominic Létourneau, Froduald Kabanza, and François Michaud. Reactive planning in a motivated behavioral architecture. In *Proceedings of the National Conference on Artificial Intelligence*, volume 20, page 1242. Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2005.
- [BD02] Guido Boella and Rossana Damiano. A replanning algorithm for a reactive agent architecture. In *Artificial Intelligence: Methodology, Systems, and Applications*, pages 183–192. Springer, 2002.
- [BR03] Dan Bohus and Alexander I Rudnický. Ravenclaw: Dialog management using hierarchical task decomposition and an expectation agenda. 2003.
- [Bro05] Cyril Brom. Hierarchical reactive planning: Where is its limit. *Proceedings of MNAS: Modelling Natural Action Selection*. Edinburgh, Scotland, 2005.
- [BS01] Joanna J Bryson and Lynn Andrea Stein. Modularity and design in reactive intelligence. In *International Joint Conference on Artificial Intelligence*, volume 17, pages 1115–1120. LAWRENCE ERLBAUM ASSOCIATES LTD, 2001.
- [CGS98] Rosaria Conte, Nigel Gilbert, and Jaime Simão Sichman. Mas and social simulation: A suitable commitment. In *Multi-agent systems and agent-based simulation*, pages 1–9. Springer, 1998.
- [Ero96] Kutluhan Erol. Hierarchical task network planning: formalization, analysis, and implementation. 1996.
- [Fir87] R James Firby. An investigation into reactive planning in complex domains. In *AAAI*, volume 87, pages 202–206, 1987.
- [FN72] Richard E Fikes and Nils J Nilsson. Strips: A new approach to the application of theorem proving to problem solving. *Artificial intelligence*, 2(3):189–208, 1972.
- [HTHO06] Hisashi Hayashi, Seiji Tokura, Tetsuo Hasegawa, and Fumio Ozaki. Dynagent: An incremental forward-chaining htn planning agent in dynamic domains. In *Declarative Agent Languages and Technologies III*, pages 171–187. Springer, 2006.
- [Mae90] Pattie Maes. *Designing autonomous agents: Theory and practice from biology to engineering and back*. MIT press, 1990.

- [NCLMA99] Dana Nau, Yue Cao, Amnon Lotem, and Hector Muñoz-Avila. Shop: Simple hierarchical ordered planner. In *Proceedings of the 16th international joint conference on Artificial intelligence-Volume 2*, pages 968–973. Morgan Kaufmann Publishers Inc., 1999.
- [Sac75] Earl D Sacerdoti. A structure for plans and behavior. Technical report, DTIC Document, 1975.
- [VDKDW05] Roman Van Der Krogt and Mathijs De Weerd. Plan repair as an extension of planning. In *ICAPS*, volume 5, pages 161–170, 2005.
- [WHLUMA07] Ian Warfield, Chad Hogg, Stephen Lee-Urban, and Héctor Muñoz-Avila. Adaptation of hierarchical task network plans. In *FLAIRS Conference*, pages 429–434, 2007.
- [Wil88] David E Wilkins. *Practical planning: Extending the classical AI planning paradigm*. Morgan Kaufmann Publishers Inc., 1988.
- [ZHH⁺09] Hankz Hankui Zhuo, Derek Hao Hu, Chad Hogg, Qiang Yang, and Hector Muñoz-Avila. Learning htn method preconditions and action models from partial observations. In *IJCAI*, pages 1804–1810, 2009.