

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-230041-01

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

Placed on the market under the name or trade mark of: Jadeed Ajar General Trading L.L.C.,  
19, Tawakal Building, Al Burj Street, Banlyas, Deira, Dubai.

and produced in the manufacturing plant(s): SG-15852

Product(s): Building hardware - Single-axis hinges - Requirements and test methods  
(refer to attached appendix for details and conditions)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

EN 1935:2002+AC:2003

Under System 1 for the performances set out in this certificate are applied and that the performance of the construction product fulfils all the prescribed requirements for these performances

This certificate was first issued on **2023-01-16** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performances of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body



*The issued document and statement(s) herein makes reference only to a presumption of conformity in accordance with the CPR Regulations EU 305/2011 (as amended). However, it is the manufacturer's or their authorised representative's sole responsibility to affix the CE logo and, by doing so, confirms full compliance and conformity to all other European mandatory directives and regulations that may also apply.*

Signature:



115690 DocuSign

Date: 2023-01-16

Issue: 01

Name: Dipl.-Ing. Roland Heine

Position: Certification Manager

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-230041-01

## APPENDIX TO: Certificate of Constancy of Performance

Brand Ajar

Model Ref: BBH01433, BBH0143.53, BBH01443, BBH014.533, BBH014.53.53, BBH014.543, BBH014.54.53, BBH01533, BBH0153.53, BBH01543, BBH0154.53

Table A1. Product Description for Hinges from Jadeed Ajar General Trading L.L.C.,

Model No.	Size L * W * T	Type <sup>1</sup>	Blade Material <sup>2</sup>	Finish
BBH01433	4*3*3	2BB butt hinge	SS304	Satin
BBH0143.53	4*3.5*3	2BB butt hinge	SS304	Satin
BBH01443	4*4*3	2BB butt hinge	SS304	Satin
BBH014.533	4.5*3*3	2BB butt hinge	SS304	Satin
BBH014.53.53	4.5*3.5*3	2BB butt hinge	SS304	Satin
BBH014.543	4.5*4*3	2BB butt hinge	SS304	Satin
BBH014.54.53	4.5*4.5*3	2BB butt hinge	SS304	Satin
BBH01533	5*3*3	2BB butt hinge	SS304	Satin
BBH0153.53	5*3.5*3	2BB butt hinge	SS304	Satin
BBH01543	5*4*3	2BB butt hinge	SS304	Satin
BBH0154.53	5*4.5*3	2BB butt hinge	SS304	Satin

Notes:

1. BB-ball bearings, five knuckles
2. Refer to EN 10088-1 for European Designation (EN) for SS304 (stainless steels).

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen

Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de/directory

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-230041-01

**Table A2. Mechanical test report(s) and product classification for hinges from Jadeed Ajar General Trading L.L.C.,**

Mechanical test reports	Model Tested	Product Classification							
190926121GZU-001	BBH01433	4	7	6	1 <sup>1</sup>	1	4	0	13
Model numbers assessed as having same performance: BBH0143.53, BBH01443, BBH014.533, BBH014.53.53, BBH014.543, BBH014.54.53, BBH01533, BBH0153.53, BBH01543, BBH0154.53.									

Notes:

- Digit 4 becomes "1" after successful outcome of fire resistance test (refer to Table A3).
- Single axis hinges are to be installed in accordance with the installation instructions for the product(s).

**Table A3. Fire test report(s) for hinges from Jadeed Ajar General Trading L.L.C.,**

Fire test reports	Model Tested	Test Method	Fire Resistance (minutes)
			Integrity (E)
191025003SHF-001	BBH01433	EN 1634-1:2014+A1: 2018	260
Test configuration:	Single leaf single action swing steel door assembly		
Orientation:	Open away from the furnace		
Model numbers were assessed as having same performance: BBH0143.53, BBH01443, BBH014.533, BBH014.53.53, BBH014.543, BBH014.54.53, BBH01533, BBH0153.53, BBH01543, BBH0154.53.			

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-230041-01

**Table A4. Single axis hinges - EN 1935 Table ZA.1 Clauses for Hinges from Jadeed Ajar General Trading L.L.C.,**

<b>Product:</b>	Single-axis hinges as defined in clause 1 of this standard.	
<b>Intended Uses:</b>	On fire/smoke compartmentation doors fitted with door closing devices (to enable such doors to close reliably and thus achieve self-closing in the event of fire)	
<b>Requirement / characteristic</b>	<b>Requirement clauses in this European Standard</b>	<b>Results</b>
Self-closing	5.1 Initial friction torque	Less than 4,0 Nm with door mass 120 kg
	5.2 Static load - Load deformation	Grade 13, with a displacement under load (240 kg mass): - Lateral < 4 mm; - Vertical < 2 mm. And a residual displacement after unloading: - Lateral < 0.3 mm; - Vertical < 0.15 mm.
	5.2 Static load - Overload	Grade 13, Overload mass 360 kg
	5.3 Shear strength	No breakage and cracking Lateral deformation under loading < 3 mm Additional lateral and vertical displacement after unloading < 1 mm
	5.6 Hinges for use on fire-resistant and/or smoke-control doors	Grade 1: suitable for use on fire resistant door assemblies (see Table A3).
Durability	5.4 Durability	Grade 7 (200,000 cycles) Maximum wear: - Lateral < 0.5 mm - Vertical < 0.2 mm Maximum frictional torque: - After 20 cycles and completion of 200,000 cycles, less than 4.0 Nm.
	5.5 Corrosion resistance	Grade 4, Neutral Salt Spray (NSS) – 240 hours
Dangerous substances	Note 1 of ZA 1	No dangerous substances declared for this product/intended use

END OF DOCUMENT

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

**Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen**

**Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de/directory**