
 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

Aim: Practical based on NumPy ndarray

IDE:

NumPy is a Python package created in 2005 that performs numerical calculations. It is generally used for working with arrays. NumPy also includes a wide range of mathematical functions, such as linear algebra, Fourier transforms, and random number generation, which can be applied to arrays.

Import NumPy in Python

We can import NumPy in Python using the import statement.

```
import numpy as np
```

The code above imports the numpy package in our program as an alias np. After this import statement, we can use NumPy functions and objects by calling them with np.

NumPy Array Creation

An array allows us to store a collection of multiple values in a single data structure. The NumPy array is similar to a list, but with added benefits such as being faster and more memory efficient. There are multiple techniques to generate arrays in NumPy.


Create Array Using Python List


We can create a NumPy array using a Python List. For example,

Example

```
import numpy as np
list1 = [2, 4, 6, 8]
array1 = np.array(list1)
print(array1)
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189



```

lab-7.py > ...
1  import numpy as np
2  list1 = [2, 4, 6, 8]
3  array1 = np.array(list1)
4  print(array1)
5

```

Terminal (Ctrl+`)

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI\YEAR2\SEM3\PYTHON\lab-7.py"
[2 4 6 8]

```


Example

```

import numpy as np
array1 = np.array([2, 4, 6, 8])
print(array1)

```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

lab-7.py > ...
4   # print(array1)
5   import numpy as np
6   array1 = np.array([2, 4, 6, 8])
7   print(array1)
8

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u '
[2 4 6 8]

```

Create an Array Using np.zeros()

The np.zeros() function allows us to create an array filled with all zeros. For example,


Example

```

import numpy as np
array1 = np.zeros(4)
print(array1)

```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

lab-7.py > ...
7   # print(array1)
8   import numpy as np
9   array1 = np.zeros(4)
10  print(array1)
11

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

python -u "d:\M
[0. 0. 0. 0.]

```

Create an Array With np.arange()

The np.arange() function returns an array with values within a specified interval. For example,


Example

```

import numpy as np
# create an array with values from 0 to 4
array1 = np.arange(5)
print("Using np.arange(5):", array1)
# create an array with values from 1 to 8 with a step of 2
array2 = np.arange(1, 9, 2)
print("Using np.arange(1, 9, 2):", array2)

```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

lab-7.py > ...
11
12 import numpy as np
13 array1 = np.arange(5)
14 print("Using np.arange(5):", array1)
15 array2 = np.arange(1, 9, 2)
16 print("Using np.arange(1, 9, 2):", array2)
17

PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL

▼ TERMINAL

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI\YEAR2\SEM3\PYTHON\lab-7.py"
Using np.arange(5): [0 1 2 3 4]
Using np.arange(1, 9, 2): [1 3 5 7]

```

Create an Array With np.random.rand()

The np.random.rand() function is used to create an array of random numbers. Let's see an example to create an array of 5 random numbers,

Example


```
import numpy as np
```

```
# generate an array of 5 random numbers
```

```
array1 = np.random.rand(5)
```

```
print(array1)
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

17
18     import numpy as np
19     array1 = np.random.rand(5)
20     print(array1)
21

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

▼ **TERMINAL**

```

... PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI\YE
● [0.8131881  0.21702449 0.10892568 0.63327835 0.1324565 ]

```

Taks:


import numpy as np

Example 1: Creation of 1D array

arr1=np.array([10,20,30])

print("My 1D array:\n",arr1)

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

22 # Example 1: Creation of 1D array
23 import numpy as np
24 arr1=np.array([10,20,30])
25 print("My 1D array:\n",arr1)
26

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL


▼ **TERMINAL**

```

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MA
● My 1D array:
  [10 20 30]

```

Example 2: Create a 2D numpy array
arr2 = np.array([[10,20,30],[40,50,60]])
print("My 2D numpy array:\n", arr2)
Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

28     import numpy as np
29     arr2 = np.array([[10,20,30],[40,50,60]])
30     print("My 2D numpy array:\n", arr2)
31

```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

✓ **TERMINAL**

My 2D numpy array:

[[10 20 30]

✧ [[10 20 30]

[40 50 60]]



Example 3: Create a sequence of integers

from 0 to 20 with steps of 3

arr= np.arange(0, 20, 3)

print ("A sequential array with steps of 3:\n", arr)

Output

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

lab-7.py > ...
32  # Example 3: Create a sequence of integers
33  # from 0 to 20 with steps of 3
34  import numpy as np
35  arr= np.arange(0, 20, 3)
36  print ("A sequential array with steps of 3:\n", arr)
37

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

● PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI\YEAR2\SE
A sequential array with steps of 3:
..  [ 0  3  6  9 12 15 18]


```

Example 4: Create a sequence of 5 values in range 0 to 3

```
arr= np.linspace(0, 3, 5)
```

```
print ("A sequential array with 5 values between 0 and 5:\n", arr)
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```
lab-7.py > ...
38 # Example 4: Create a sequence of 5 values in range 0 to 3
39 import numpy as np
40 arr= np.linspace(0, 3, 5)
41 print ("A sequential array with 5 values between 0 and 5:\n", arr)
42
43
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL


▼ **TERMINAL** Code + ▾

```
PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI\YEAR2\SEM3\PYTHON\lab
● A sequential array with 5 values between 0 and 5:
[0.  0.75 1.5  2.25 3.  ]
```

Example 5: Use ones() create array

```
arr = np.ones((2,3))
print("numpy array:\n", arr)
print("Type:", type(arr))
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

lab-7.py > ...

43  # Example 5: Use ones() create array
44  import numpy as np
45  arr = np.ones((2,3))
46  print("numpy array:\n", arr)
47  print("Type:", type(arr))
48

PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL

```

TERMINAL

● PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MAR
numpy array:
[[1. 1. 1.]
 [1. 1. 1.]]
Type: <class 'numpy.ndarray'>



NumPy Data Types

A data type is a way to specify the type of data that will be stored in an array. For example,
array1 = np.array([2, 4, 6])

NumPy Data Types

NumPy offers a wider range of numerical data types than what is available in Python. Here's the list of most commonly used numeric data types in NumPy:

1. int8, int16, int32, int64 - signed integer types with different bit sizes
2. uint8, uint16, uint32, uint64 - unsigned integer types with different bit sizes
3. float32, float64 - floating-point types with different precision levels
4. complex64, complex128 - complex number types with different precision levels

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

Check Data Type of a NumPy Array

```
import numpy as np
```

```
# create an array of integers
```

```
int_array = np.array([-3, -1, 0, 1])
```

```
# create an array of floating-point numbers
```

```
float_array = np.array([0.1, 0.2, 0.3])
```

```
# create an array of complex numbers
```

```
complex_array = np.array([1+2j, 2+3j, 3+4j])
```

```
# check the data type of int_array
```

```
print(int_array.dtype) # prints int64
```


```
# check the data type of float_array
```

```
print(float_array.dtype) # prints float64
```

```
# check the data type of complex_array
```

```
print(complex_array.dtype) # prints complex128
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

1  import numpy as np
2  int_array = np.array([-3, -1, 0, 1])
3  float_array = np.array([0.1, 0.2, 0.3])
4  complex_array = np.array([1+2j, 2+3j, 3+4j])
5  print(int_array.dtype) # prints int64
6  print(float_array.dtype) # prints float64
7  print(complex_array.dtype) # prints complex128
8

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

▼ **TERMINAL**

```

● PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI\YEAR
int64
float64
complex128

```


Creating NumPy Arrays With a Defined Data Type

In NumPy, we can create an array with a defined data type by passing the dtype parameter while calling the np.array() function. For example,

```

import numpy as np
# create an array of 8-bit integers

```


 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

NumPy Type Conversion

In NumPy, we can convert the data type of an array using the `astype()` method. For example,

```
import numpy as np
# create an array of integers
int_array = np.array([1, 3, 5, 7])
# convert data type of int_array to float
float_array = int_array.astype('float')
# print the arrays and their data types
print(int_array, int_array.dtype)
print(float_array, float_array.dtype)
```

Output

```

1  import numpy as np
2  int_array = np.array([1, 3, 5, 7])
3  float_array = int_array.astype('float')
4  print(int_array, int_array.dtype)
5  print(float_array, float_array.dtype)
6

```

Debug Console (Ctrl+Shift+Y)



PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI
● [1 3 5 7] int64
  [1. 3. 5. 7.] float64

```

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

NumPy Array Attributes

In NumPy, attributes are properties of NumPy arrays that provide information about the array's shape, size, data type, dimension, and so on.

Common NumPy Attributes


Here are some of the commonly used NumPy attributes:

Attributes	Description
ndim	returns number of dimension of the array
size	returns number of elements in the array
dtype	returns data type of elements in the array
shape	returns the size of the array in each dimension.
itemsize	returns the size (in bytes) of each elements in the array
data	returns the buffer containing actual elements of the array in memory

The ndim attribute returns the number of dimensions in the numpy array. For example,

```
import numpy as np
# create a 2-D array
array1 = np.array([[2, 4, 6],
                   [1, 3, 5]])
# check the dimension of array1
print(array1.ndim)
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

1  import numpy as np
2  array1 = np.array([[2, 4, 6],
3  [1, 3, 5]])
4  print(array1.ndim)
5

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

2

NumPy Array size Attribute


The size attribute returns the total number of elements in the given array.

```

import numpy as np
array1 = np.array([[1, 2, 3],
[6, 7, 8]])
# return total number of elements in array1
print(array1.size)

```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

1  import numpy as np
2  array1 = np.array([[2, 4, 6],
3  [1, 3, 5]])
4  print(array1.ndim)
5

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

2

NumPy Array shape Attribute


In NumPy, the shape attribute returns a tuple of integers that gives the size of the array in each dimension. For example,

```

import numpy as np
array1 = np.array([[1, 2, 3],
                  [6, 7, 8]])
# return a tuple that gives size of array in each dimension
print(array1.shape)

```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

1  import numpy as np
2  array1 = np.array([[1, 2, 3],
3                    [6, 7, 8]])
4  print(array1.shape)
5

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MAR

```

● (2, 3)

NumPy Array dtype Attribute

We can use the dtype attribute to check the datatype of a NumPy array. For example,

```
import numpy as np
```


```
# create an array of integers
```

```
array1 = np.array([6, 7, 8])
```

```
# check the data type of array1
```

```
print(array1.dtype)
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```

1  import numpy as np
2  array1 = np.array([6, 7, 8])
3  print(array1.dtype)

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

int64

NumPy Array itemsize Attribute

In NumPy, the itemsize attribute determines size (in bytes) of each element in the array. For example,

```

import numpy as np
# create a default 1-D array of integers
array1 = np.array([6, 7, 8, 10, 13])
# create a 1-D array of 32-bit integers
array2 = np.array([6, 7, 8, 10, 13], dtype=np.int32)
# use of itemsize to determine size of each array element of array1 and array2
print(array1.itemsize) # prints 8
print(array2.itemsize) # prints 4



```

Output

NumPy Array data Attribute

In NumPy, we can get a buffer containing actual elements of the array in memory using the data attribute.


In simpler terms, the data attribute is like a pointer to the memory location where the array's data is stored in the computer's memory.

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```
import numpy as np
array1 = np.array([6, 7, 8])
array2 = np.array([[1, 2, 3],
                  [6, 7, 8]])
# print memory address of array1's and array2's data
print("\nData of array1 is: ",array1.data)
print("Data of array2 is: ",array2.data)
```

Task
Multiplication of two given matrixes

```
import numpy as np
p = [[1, 0], [0, 1]]
q = [[1, 2], [3, 4]]
print("Original matrices:")
print(p)
print(q)
# Perform matrix multiplication using np.dot
result1 = np.dot(p, q)
print("Result of the matrix multiplication:")
print(result1)
Output
```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No: 92400133189

```

3   q = [[1, 2], [3, 4]]
4   print("Original matrices:")
5   print(p)
6   print(q)
7   # Perform matrix multiplication using np.dot
8   result1 = np.dot(p, q)
9   print("Result of the matrix multiplication:")
10  print(result1)



```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL


▼
TERMINAL

- Original matrices:
[[1, 0], [0, 1]]
[[1, 2], [3, 4]]
Result of the matrix multiplication:
[[1 2]
[3 4]]

Compute the determinant of a given square array.

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

```
import numpy as np
from numpy import linalg as LA
a = np.array([[1, 0], [1, 2]])
# Display the original 2x2 array 'a'
print("Original 2-d array")
print(a)
print("Determinant of the said 2-D array:")
print(np.linalg.det(a))
Output
```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

```

1  import numpy as np
2  from numpy import linalg as LA
3  a = np.array([[1, 0], [1, 2]])
4  # Display the original 2x2 array 'a'
5  print("Original 2-d array")
6  print(a)
7  print("Determinant of the said 2-D array:")
8  print(np.linalg.det(a))

```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

✓ **TERMINAL**


● PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "d:\MARWADI

Original 2-d array

```
[[1 0]
 [1 2]]
```

Determinant of the said 2-D array:

2.0

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

Post Lab Exercise:

- a. Write a NumPy program to create a 3x3 matrix with values ranging from 2 to 10.

```

1  import numpy as np
2  a = np.arange(2, 11).reshape(3, 3)
3  print(a)
4

```


PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

▼ **TERMINAL**


```

[[ 2  3  4]
 [ 5  6  7]
 [ 8  9 10]]

```


 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No: 92400133189

c. Write a NumPy program to find common values between two arrays.



```

7-3 > ...
1  import numpy as np
2
3  arr1 = np.array([1, 2, 3, 4, 5])
4  arr2 = np.array([4, 5, 6, 7, 8])
5
6  common = np.intersect1d(arr1, arr2)
7  print(common)
8

```


PROBLEMS OUTPUT DEBUG CONSOLE **TERMINAL**

✓ **TERMINAL** Code + - [] [X] ... PORTS

• \7> python -u "d:\MARWADI\YEAR2\SEM3\PYTHON\PythonPostLab\7\7-3"

[4 5]

No forwarded locally running

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

d. Write a NumPy program to repeat array elements.

```

7-4 > ...
1  import numpy as np
2  arr = np.array([1, 2, 3])
3  repeated = np.repeat(arr, 3)
4  print(repeated)
5

```


PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

PS D:\MARWADI\YEAR2\SEM3\PYTHON\PythonPostLab\7> python -u "d:\tLab\7\7-4"
[1 1 1 2 2 2 3 3 3]

```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

e. Write a NumPy program to find the memory size of a NumPy array.

```

1  import numpy as np
2  e = np.array([1, 2, 3, 4, 5])
3  print(e.size * e.itemsize)
4


```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

▼ **TERMINAL**

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u "

● 40

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray
Experiment No: 07	Date: Enrollment No:92400133189

f. Write a NumPy program to create an array of ones and zeros.

```

1  import numpy as np
2  print(np.ones((2, 2)))
3  print(np.zeros((2, 2)))
4

```


PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

✓ **TERMINAL**

```

[1.  1.]
[[0.  0.]
 [0.  0.]]

```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on NumPy ndarray	
Experiment No: 07	Date:	Enrollment No:92400133189

g. Write a NumPy program to find the 4th element of a specified array.

```

1  import numpy as np
2  g = np.array([10, 20, 30, 40, 50])
3  print(g[3])
4

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

▼ **TERMINAL**

PS D:\MARWADI\YEAR2\SEM3\PYTHON> python -u

python -u

● 40