Indian Institute of Information Technology, Nagpur

Team Blank

I/O

```
import sys,math,cmath,random,os,
   psutil
from heapq import heappush,heappop
from bisect import bisect_right,
   bisect_left
from collections import Counter,
   deque,defaultdict
from itertools import permutations,
   combinations
from io import BytesIO, IOBase
from decimal import Decimal,
   getcontext
process = psutil.Process(os.getpid()
   )
BUFSIZE = 8192
class FastIO(IOBase):
   newlines = 0
   def __init__(self, file):
      self._file = file
      self._fd = file.fileno()
      self.buffer = BytesIO()
      self.writable = "x" in file.
         mode or "r" not in file.mode
      self.write = self.buffer.write
         if self.writable else None
   def read(self):
      while True:
         b = os.read(self._fd, max(
            os.fstat(self._fd).
            st_size, BUFSIZE))
         if not b:
            break
         ptr = self.buffer.tell()
         self.buffer.seek(0, 2),
            self.buffer.write(b),
            self.buffer.seek(ptr)
      self.newlines = 0
      return self.buffer.read()
   def readline(self):
      while self.newlines == 0:
         b = os.read(self._fd, max(
            os.fstat(self._fd).
            st_size, BUFSIZE))
         self.newlines = b.count(b"\
            n") + (not b)
         ptr = self.buffer.tell()
         self.buffer.seek(0, 2),
            self.buffer.write(b),
            self.buffer.seek(ptr)
      self.newlines -= 1
      return self.buffer.readline()
   def flush(self):
      if self.writable:
         os.write(self._fd, self.
            buffer.getvalue())
         self.buffer.truncate(0),
            self.buffer.seek(0)
class IOWrapper(IOBase):
   def __init__(self, file):
      self.buffer = FastIO(file)
      self.flush = self.buffer.flush
      self.writable = self.buffer.
         writable
      self.write = lambda s: self.
         buffer.write(s.encode("ascii
         "))
      self.read = lambda: self.
         buffer.read().decode("ascii"
         )
      self.readline = lambda: self.
         buffer.readline().decode("
         ascii")
sys.stdin, sys.stdout = IOWrapper(
   sys.stdin), IOWrapper(sys.stdout)
MOD = 10**9 + 7
RANDOM = random.randrange(1,2**62)
def gcd(a,b):
   while b:a,b = b,a%b;return a
def lcm(a,b):return a//gcd(a,b)*b
II = lambda : int(sys.stdin.readline
   ().strip())
LII = lambda : list(map(int, sys.
   stdin.readline().split()))
SI = lambda : sys.stdin.readline().
   strip()
LII_1 = lambda : list(map(lambda x:
   int(x)-1, sys.stdin.readline().
   split()))
if True:
   base = os.path.dirname(os.path.
      abspath(__file__))
   sys.stdin = open(os.path.join(
      base, "input.txt"), "r")
   sys.stdout = open(os.path.join(
      base, "output.txt"), "w")
   sys.stderr = open(os.path.join(
      base, "error.txt"), "w")
def solve():
   return
solve()
```

Number Theory

```
def miller_is_prime(n):
   if n < 5 or n & 1 == 0 or n % 3
      == 0:return 2 <= n <= 3
   s = ((n - 1) & (1 - n)).
      bit_length() - 1
   d = n >> s
   for a in [2, 325, 9375, 28178,
      450775, 9780504, 1795265022]:
      p = pow(a, d, n)
      if p == 1 or p == n - 1 or a %
         n == 0:continue
      for _ in range(s):
         p = (p * p) % n
         if p == n - 1:break
      else:return False
   return True
def is_prime(n):
   if n <= 1:return False
   if n <= 3:return True
   if n % 2 == 0 or n % 3 == 0:
      return False
   i = 5
   while i * i <= n:
      if n % i == 0 or n % (i + 2)
         == 0:return False
      i += 6
   return True
```

```
def sieve(n):
   primes = [];isp = [1] * (n+1)
   isp[0] = isp[1] = 0
   for i in range(2,n+1):
      if isp[i]:
         primes.append(i)
         for j in range(i*i,n+1,i):
            isp[j] = 0
   return primes
def sieve_unique(N):
   mini = [i for i in range(N)]
   for i in range(2,N):
      if mini[i]==i:
         for j in range(2*i,N,i):
            mini[j] = i
   return mini
MAX_N = 10**6+1
Lmini = sieve_unique(MAX_N)
def prime_factors(k,typ=0):
   if typ==0:ans = Counter()
   elif typ==1:ans = set()
   else:ans = []
   while k!=1:
      if typ==0:ans[Lmini[k]] += 1
      elif typ==1:ans.add(Lmini[k])
      else:ans.append(Lmini[k])
      k //= Lmini[k]
   return ans
def all_factors(x):
```

```
    L = list(prime_factors(x).items()
        )
    st = [1]
    for i in range(len(L)):
        for j in range(len(st)
            -1,-1,-1):
            k = L[i][0]
            for l in range(L[i][1]):
                st.append(st[j]*k)
                k *= L[i][0]
    return st
```

```
def pollard_rho(n):
    # works upto 1e18
    if (n == 1):
        return n
    if (n % 2 == 0):
        return 2
    for _ in range(50):
        x = random.randint(2,n-1)
        c = random.randint(1,n-1)
        y = x
        d = 1
        while (d == 1):
            x = (pow(x, 2, n) + c + n)%
                n
            y = (pow(y, 2, n) + c + n)%
                n
            y = (pow(y, 2, n) + c + n)%
                n
            d = gcd(abs(x - y), n)
            if (d == n):
                break
        if d!=1 and d!=n:
            return n

    return None
def miller_pollard_rho(n):
    # returns a random factor of n,
        works upto 1e18
    if n&1==0:return 2
    if n%3==0:return 3
    s = ((n-1)&(1-n)).bit_length() -
        1
    d = n>>s
    for a in [2, 325, 9375, 28178,
        450775, 9780504, 1795265022]:
        p = pow(a, d, n)
        if p == 1 or p == n - 1 or a %
            n == 0:continue
        for _ in range(s):
            prev = p
            p = (p * p) % n
            if p == 1:return gcd(prev -
                1, n)
            if p == n - 1:break
        else:
            for i in range(2, n):
                x, y = i, (i * i + 1) %
                    n
                f = gcd(abs(x - y), n)
                while f == 1:
                    x, y = (x * x + 1) %
                        n, (y * y + 1) % n
                    y = (y * y + 1) % n
                    f = gcd(abs(x - y), n
                        )
                if f != n:return f
    return n

@memodict
def prime_factors_large(n):
    # returns prime factor in n^(1/4)
        but is probablistic
    if n <= 1:return Counter()
    f = miller_pollard_rho(n) #
        pollard_rho is another option
    return Counter([n]) if f == n
        else prime_factors_large(f) +
        prime_factors_large(n // f)

def discrete_log(a, b, mod):
    # returns smalest x such that pow
        (a,x,mod) = b
    # given gcd(a,mod)==1
    n = int(mod**0.5) + 1
    tiny_step, e = {}, 1
    for j in range(1, n + 1):
        e = e * a % mod
        if e == b:
            return j
        tiny_step[b * e % mod] = j
    factor = e
    for i in range(2, n + 2):
        e = e * factor % mod
        if e in tiny_step:
            j = tiny_step[e]
            return n * i - j if pow(a,
                n * i - j, mod) == b else
                None
    return None

def extended_gcd(a, b):
    # returns gcd(a, b), s, r s.t. a
        * s + b * r == gcd(a, b)
    s, old_s = 0, 1
    r, old_r = b, a
    while r:
        q = old_r // r
        old_r, r = r, old_r - q * r
        old_s, s = s, old_s - q * s
    return old_r, old_s, (old_r -
        old_s * a) // b if b else 0

def composite_crt(b, m):
    # returns x s.t. x = b[i] (mod m[
        i]) for all i
    x, m_prod = 0, 1
    for bi, mi in zip(b, m):
        g, s, _ = extended_gcd(m_prod,
            mi)
        if ((bi - x) % mi) % g:
            return None
        x += m_prod * (s * ((bi - x) %
            mi) // g)
        m_prod = (m_prod * mi) // gcd(
            m_prod, mi)
    return x % m_prod

def phi(n):
    ph = [i if i & 1 else i // 2 for
        i in range(n + 1)]
    for i in range(3,n+1,2):
        if ph[i]==i:
            for j in range(i,n+1,i):
                ph[j] = (ph[j]//i)*(i-1)
    return ph
```

Matrix

```
class Matrix:
    MOD = 10**9+7
    @staticmethod
    def transpose(mat):
        return [list(c) for c in zip(*
            mat)]
    def __init__(self,M):
        self.M=M
    def minmul(self,o):
        L,B=self.M,o.M
        r=len(L); c=len(B[0])
        return Matrix([[min(L[i][k]+B[
            k][j] for k in range(len(B))
            )%self.MOD for j in range(c)
            ] for i in range(r)])
    def __matmul__(self,o):
        L,B=self.M,o.M
        r=len(L); c=len(B[0])
        return Matrix([[sum(L[i][k]*B[
            k][j] for k in range(len(B))
            )%self.MOD for j in range(c)
            ] for i in range(r)])
    def __pow__(self,p):
        M=self; n=len(M.M)
```

```
        R=Matrix([[i==j for j in range
            (n)] for i in range(n)])
        while p:
            R = R@M if p&1 else R
            M = M@M
            p//=2
        return R
    @staticmethod
    def gauss(A,mod=10**9+7):
        m,n=len(A),len(A[0])-1; r=0; L
            =[-1]*n
        for c in range(n):
            for i in range(r,m):
                if A[i][c]: A[r],A[i]=A[
                    i],A[r]
                break
            else:
                continue
            k=pow(A[r][c],-1,mod)
            for j in range(c,n+1):
                A[r][j]=A[r][j]*k%mod
            for i in range(m):
                if i!=r and A[i][c]:
                    f=A[i][c]
                    for j in range(c,n+1)
                        :
                        A[i][j]=(A[i][j]-f
                            *A[r][j])%mod
            L[c]=r
            r+=1
        if any(A[i][n] for i in range(
            r,m)):
            return None
        return [A[L[i]][n] if L[i]!=-1
             else 0 for i in range(n)]
    def __str__(self):
        return '\n'.join(' '.join(map(
            str,row)) for row in self.M)
    def __repr__(self):
        return f"Matrix({self.M})"
    def __iter__(self):
        return iter(self.M)
```

Combinatorics

```
class Factorial:
    def __init__(self, N, mod):
        self.mod = mod
        self.f = [1 for _ in range(N)]
        self.g = [1 for _ in range(N)]
        for i in range(1, N):self.f[i]
            = self.f[i - 1] * i % self.
            mod
        self.g[-1] = pow(self.f[-1],
            mod - 2, mod)
        for i in range(N - 2, -1, -1):
            self.g[i] = self.g[i + 1] *
            (i + 1) % self.mod
    def derangements(self,n):
        # Number of permutations of n
            objects where no object
            appears in its original
            position
        return int(self.fac(n)/math.e
            +0.5)
    def der(self, n):
        if n==0: return 1
        if n==1: return 0
        a, b = 1, 0 # der(0), der(1)
        for i in range(2,n+1):
            a,b = b,((i-1)*(a+b)) %
                self.mod
        return b
    def stirling_2(self,n,k):
        # Number of ways to partition
            n elements into k non-empty
            subsets
        return sum(((-1)**(k - j)) *
            math.comb(k, j) * (j**n) for
             j in range(k + 1)) // math.
            factorial(k)
    def stirling_2_mod(self,n,k):
        return (sum(((-1)**(k - j))*
            self.combi(k, j)*pow(j,n,
            self.mod) for j in range(k +
             1)) * self.fac_inv(k))%self
            .mod
    def partition(self,n,k):
        # Ways to partition n into k
            or fewer parts of size 1 or
            greater
        # add dp[(n,k)] and memoize it
             if using it.
        if n<0 or (k<1 and n>0):return
             0
        if n==0:return 1
        return 1 if n==1 else self.
            partition(n,k-1)+self.
            partition(n-k,k)
    def lucas_nCk(self,n,k):
        # Lucas's theorem for finding
            ((nCk)%p) for large n,k
        # in log p(n)
        ans = 1
        p = self.mod
        while n or k:
            x = n%p
            y = k%p
            ans *= self.combi(x,y)
            ans %= p
            n //= p
            k //= p
        return ans
    def catalan(self, n):
        return (self.combi(2 * n, n) -
             self.combi(2 * n, n - 1)) %
             self.mod
    def fac(self, n):
        return self.f[n]
    def fac_inv(self, n):
        return self.g[n]
    def combi(self, n, m):
        if m == 0: return 1
        if n < m or m < 0 or n < 0:
            return 0
        return self.f[n] * self.g[m] %
             self.mod * self.g[n - m] %
            self.mod
    def permu(self, n, m):
        if n < m or m < 0 or n < 0:
            return 0
        return self.f[n] * self.g[n -
            m] % self.mod
    def inv(self, n):
        return self.f[n-1] * self.g[n]
            % self.mod
    def beggar(self,n,sumi):
        # number of ways n elements
            >=0 have sum sumi
        return self.combi(n+sumi-1,
            sumi)
```

Geometry

```
## here onwards, it is for
    intersection only, even the point
    class is different
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y
def onSegment(p, q, r):
    if ( (q.x <= max(p.x, r.x)) and (
        q.x >= min(p.x, r.x)) and
            (q.y <= max(p.y, r.y)) and (
                q.y >= min(p.y, r.y))):
        return True
    return False
def orientation(p, q, r):
    # to find the orientation of an
        ordered triplet (p,q,r)
```

```
    # function returns the following
       values:
    # 0 : Collinear points
    # 1 : Clockwise points
    # 2 : Counterclockwise
    val = ((q.y - p.y) * (r.x - q.x))
        - ((q.x - p.x) * (r.y - q.y))
    if (val > 0):
        return 1
    elif (val < 0):
        return 2
    else:
        return 0
def doIntersect(p1,q1,p2,q2):
    o1 = orientation(p1, q1, p2)
    o2 = orientation(p1, q1, q2)
    o3 = orientation(p2, q2, p1)
    o4 = orientation(p2, q2, q1)
    if ((o1 != o2) and (o3 != o4)):
        return True
    if ((o1 == 0) and onSegment(p1,
       p2, q1)):
        return True
    if ((o2 == 0) and onSegment(p1,
       q2, q1)):
        return True
    if ((o3 == 0) and onSegment(p2,
       p1, q2)):
        return True
    if ((o4 == 0) and onSegment(p2,
       q1, q2)):
        return True
    return False
##
## lines
# 2d line: ax + by + c = 0 is (a, b,
    c)
#   ax + by + c = 0 ((a, b, c),
# 3d line: dx + ez + f = 0 is (d, e,
    f),
#   gy + hz + i = 0 (g, h, i))
def get_2dline(p1, p2):
    if p1 == p2:
        return (0, 0, 0)
    _p1, _p2 = min(p1, p2), max(p1,
       p2)
    a, b, c = _p2[1] - _p1[1], _p1[0]
        - _p2[0], _p1[1] * _p2[0] -
       _p1[0] * _p2[1]
    g = gcd(gcd(a, b), c)
    return (a // g, b // g, c // g)
dist = lambda p1, p2: sum((a - b) *
    (a - b) for a, b in zip(p1, p2))
    **0.5
get_line = lambda p1, p2: map(
    get_2dline, combinations(p1, 2),
    combinations(p2, 2))
is_parallel = lambda l1, l2: l1[0] *
     l2[1] == l2[0] * l1[1]
is_same = lambda l1, l2: is_parallel
    (l1, l2) and (l1[1] * l2[2] == l2
    [1] * l1[2])
collinear = lambda p1, p2, p3:
    is_same(get_2dline(p1, p2),
    get_2dline(p2, p3))
intersect = (lambda l1, l2: None if
    is_parallel(l1, l2) else (
    (l2[1] * l1[2] - l1[1] * l2[2]) /
        (l2[0] * l1[1] - l1[0] * l2
       [1]),
    (l1[0] * l2[2] - l1[2] * l2[0]) /
        (l2[0] * l1[1] - l1[0] * l2
       [1]),
))
rotate = lambda p, theta, origin=(0,
     0): (
    origin[0] + (p[0] - origin[0]) *
       math.cos(theta) - (p[1] -
       origin[1]) * math.sin(theta),
    origin[1] + (p[0] - origin[0]) *
       math.sin(theta) + (p[1] -
       origin[1]) * math.cos(theta),
)
##
## polygons
dist = lambda p1, p2: sum((a - b) *
    (a - b) for a, b in zip(p1, p2))
    **0.5
perimeter = lambda *p: sum(dist(i, j
    ) for i, j in zip(p, p[1:] + p
    [:1]))
# shoelace theorem
area = lambda *p: abs(sum(i[0] * j
    [1] - j[0] * i[1] for i, j in zip(
    p, p[1:] + p[:1]))) / 2
centroid = lambda p: (
    sum((i[0] + j[0]) * (i[0] * j[1]
       - j[0] * i[1])
        for i, j in zip(p, p[1:] + p
           [:1]))
    / (3 * sum(i[0] * j[1] - j[0] * i
       [1] for i, j in zip(p, p[1:] +
       p[:1]))),
    sum((i[1] + j[1]) * (i[0] * j[1]
       - j[0] * i[1])
        for i, j in zip(p, p[1:] + p
           [:1]))
    / (3 * sum(i[0] * j[1] - j[0] * i
       [1] for i, j in zip(p, p[1:] +
       p[:1])))
)
## above 2 functions can be done on
    a range of points in O(1)
is_in_circle = lambda p, c, r: sum(i
    * i - j * j for i, j in zip(p, c)
    ) < r * r
incircle_radius = lambda a, b, c:
    area(a, b, c) / (perimeter(a, b, c
    ) / 2)
circumcircle_radius = lambda a, b, c
    : (dist(a, b) * dist(b, c) * dist(
    c, a)) / (4 * area(a, b, c))
##
def convex_hull(P):
    if len(P)<=1:return P
    cross = lambda a,b,c: (a[0] - b
       [0]) * (c[1] - b[1]) - (a[1] -
       b[1]) * (c[0] - b[0])
    P = sorted(P)
    def f(P):
        lower = []
        for p in P:
            while len(lower) >= 2 and
               cross(lower[-2], lower
               [-1], p) < 0:
                lower.pop()
            lower.append(p)
        return lower
    return f(P)[:-1]+f(P[::-1])[:-1]
```

Linear Algebra

```
def solve_quadratic(a, b, c):
    if a == 0:return None
    D = b*b - 4*a*c
    if D < 0:return None
    s = math.isqrt(D)
    if s*s != D:return None
    den = 2*a
    if den == 0:return None
    x1, r1 = divmod(-b + s, den)
    x2, r2 = divmod(-b - s, den)
    if r1!=0 or r2!=0:return None
    return (x1, x2)

def solve_cubic(a, b, c, d):
    if a == 0:return None
    roots = []
    for x in range(-math.isqrt(abs(d)
       ) - 1, math.isqrt(abs(d)) + 2):
        if a*x*x*x + b*x*x + c*x + d
           == 0:
            roots.append(x)
```

```
    return tuple(roots) if roots else
        None

def compute_rank(A):
    EPS = 1e-9
    A = [row[:] for row in A]
    n = len(A)
    m = len(A[0])
    rank = 0
    row_selected = [False] * n
    for i in range(m):
        j = 0
        while j < n:
            if not row_selected[j] and
               abs(A[j][i]) > EPS:
                break
            j += 1
        if j != n:
            rank += 1
            row_selected[j] = True
            for p in range(i + 1, m):
                A[j][p] /= A[j][i]
            for k in range(n):
                if k != j and abs(A[k][i
                    ]) > EPS:
                    for p in range(i + 1,
                        m):
                        A[k][p] -= A[j][p]
                            * A[k][i]
    return rank

class XorBasis:
    def __init__(self,A=[]):
        self.reduced_base = {}
        self.how = {}
        self.base = {}
        for i in A:
            self.add(i)
    def max(self):
        base = self.base; reduced_base
            = self.reduced_base
        how = self.how
        x = 0;tmp = 0;ans=[]
        for j in sorted(reduced_base,
            reverse=True):
            if not x & (1 << j):
                x ^= reduced_base[j]
                tmp ^= how[j]
                ans.append(base[j])
        # xor of these elements return
            the max element
        return ans
    def make(self,k):
        # returns True if can make x
            with these elements
        reduced_base = self.
            reduced_base
        for j in range(k.bit_length()
            -1,-1,-1):
            if ((1<<j)&k):
                if j in reduced_base:
                    k ^= reduced_base[j]
                else:
                    return False
        return k==0
    def add(self,a):
        # adds a to the basis
        reduced_base = self.
            reduced_base
        how = self.how;base = self.
            base
        tmp = 0
        while a:
            b = a.bit_length() - 1
            if b in reduced_base:
                a ^= reduced_base[b]
                tmp ^= how[b]
            else:
                reduced_base[b] = a
                how[b] = tmp | (1 << len
                    (base))
                base[b] = a
                break

def simplex_bland(c, A, b, frac=
    False):
    # maximize ci.xi
    # given ai.xi <= bi and xi >= 0
    if not frac:
        n = len(c)
        m = len(b)
        T = [A[i] + [0]*i + [1] +
            [0]*(m-i-1) + [b[i]] for i
            in range(m)]
        T.append([-ci for ci in c] +
            [0]*m + [0])
        N = list(range(n)) # non-basic
        B = list(range(n, n+m)) #
            basic
        def pivot(r, s):
            # Make coeffecient of pivot
                row 1 and Eliminate
                column s in all other
                rows
            T[r] = [v / T[r][s] for v
                in T[r]]
            for i in range(len(T)):
                if i != r:
                    fac = T[i][s]
                    T[i] = [T[i][j] - fac
                        * T[r][j] for j in
                        range(len(T[0]))]
        while True:
            s = None
            for j in range(len(T[0]) -
                1):
                if T[-1][j] < 0:
                    s = j
                    break
            if s is None:
                break
            # leaving row
            r = None
            for i in range(m):
                if T[i][s] > 1e-12:
                    ratio = T[i][-1] / T[
                        i][s]
                    if r is None or ratio
                        < T[r][-1] / T[r][
                        s]:
                        r = i
            if r is None:
                return None
            pivot(r, s)
            B[r], N[s] = N[s], B[r]
        x = [0] * (n + m)
        for i in range(m):
            x[B[i]] = T[i][-1]
        return x[:n], T[-1][-1]
    else:
        from fractions import Fraction
        n = len(c)
        m = len(b)
        c = [Fraction(ci) for ci in c]
        A = [[Fraction(aij) for aij in
            row] for row in A]
        b = [Fraction(bi) for bi in b]
        T = [A[i] + [Fraction(1 if i
            == j else 0) for j in range(
            m)] + [b[i]]
            for i in range(m)]
        T.append([-ci for ci in c] + [
            Fraction(0)] * (m + 1))
        N = list(range(n))
        B = list(range(n, n+m))
        def pivot(r, s):
            piv = T[r][s]
            T[r] = [v / piv for v in T[
                r]]
            for i in range(m + 1):
                if i != r:
                    fac = T[i][s]
                    T[i] = [T[i][j] - fac
                        * T[r][j] for j in
```

```
                    range(len(T[0]))]
        while True:
            s = None
            for j in range(len(T[0]) -
                1):
                if T[-1][j] < 0:
                    s = j
                    break
            if s is None:
                break
            r = None
            for i in range(m):
                if T[i][s] > 0:
                    ratio = T[i][-1] / T[
                        i][s]
                    if r is None or ratio
                         < T[r][-1] / T[r][
                        s]:
                        r = i
            if r is None:
                return None
            pivot(r, s)
            B[r], N[s] = N[s], B[r]
        x = [Fraction(0)] * (n + m)
        for i in range(m):
            x[B[i]] = T[i][-1]
        return x[:n], T[-1][-1]

def s_lr(l,r,pow=1):
    if l>r:return 0
    if pow==1:return (r*(r+1)//2) -
        ((l-1)*l//2)
    elif pow==2:return (r*(r+1)*(2*r
        +1)//6) - ((l-1)*l*(2*l-1)//6)
    elif pow==3:return (r*(r+1)//2)
        **2 - ((l-1)*l//2)**2
    else:return None

class DiophantineEquations:
    """
        used for solving equations of
            the form a*x + b*y = c,
        solnll takes the lower limit
            as well
    """
    def __init__(self):pass
    def euclidean_gcd(self,a, b):
        """
            euclidean gcd , returns x
                and y such that
            a*x + b*y = gcd(a,b)
        """
        if b == 0:
            return a,1,0
        g,x1,y1 = self.euclidean_gcd(b
            , a % b)
        x = y1
        y = x1-(a//b)*y1
        return g,x,y
    def soln(self,a,b,c,t=10**18,t1
        =10**18):
        """
            return m and n such that a*
                m + b*n = c and 0<=m<=t
                and 0<=n<=t1
            don't input t,t1 for any
                possible value
        """
        g = gcd(a, b)
        if c%g!=0:
            return -1,-1
        _, x, y = self.euclidean_gcd(a
            , b)
        k3 = x*(c//g)
        n1 = y*(c//g)
        k1 = max(math.ceil(-k3*g/b),
            math.ceil((n1-t1)/(a/g)))
        kmaxi = min(math.floor((t-k3)
            /(b/g)), math.floor(n1/(a/g)
            ))
        if k1<=kmaxi:
            k = k1
            m = k3+k*(b//g)
            n = n1-k*(a//g)
            return m, n
        else:
            return -1,-1
    def sollnll(self,a,b,c,t,t1,
        m_lower,n_lower):
        """
            return m and n such that a*
                m + b*n = c and
            m_lower <= m <= t and
                n_lower <= n <= t1
        """
        g = gcd(a, b)
        if c % g != 0:
            return -1, -1
        _, x, y = self.euclidean_gcd(a
            , b)
        k3 = x * (c // g)
        n1 = y * (c // g)
        k1 = max(math.ceil((m_lower -
            k3 * g) / b), math.ceil((n1
            - t1) / (a / g)))
        kmaxi = min(math.floor((t - k3
            ) / (b / g)), math.floor((n1
             - n_lower) / (a / g)))
        if k1 <= kmaxi:
            k = k1
            m = k3 + k * (b // g)
            n = n1 - k * (a // g)
            if m_lower <= m <= t and
                n_lower <= n <= t1:
                return m, n
            else:
                return -1,-1
        else:
            return -1, -1
```

Data Structures

Disjoint Set Union

```
class DisjointSetUnion:
    def __init__(self, n):
        self.parent = list(range(n))
        # self.s = set(self.parent)
        self.size = [1] * n
    def find(self, a):
        acopy = a
        while a != self.parent[a]:
            a = self.parent[a]
        while acopy != a:
            self.parent[acopy], acopy =
                a, self.parent[acopy]
        return a
    def union(self, a, b):
        a, b = self.find(a), self.find
            (b)
        if a != b:
            if self.size[a] < self.size
                [b]:
                a, b = b, a
            # self.s.remove(b)
            self.parent[b] = a
            self.size[a] += self.size[b
                ]
    def set_size(self, a):
        return self.size[self.find(a)]
    def __len__(self):
        return len(self.s)
    def notfind(self, a):
        k = self.find(a)
        for j in self.s:
            if j!=k:
                return j
        return -1
```

Persistent DSU

```
class PersistentDSU:
    def __init__(self,n):
        self.parent = list(range(n))
        self.size = [1]*n
        self.time = [float('inf')]*n
    def find(self,node,version):
```

```
        # returns root at given
          version
        while not (self.parent[node]==
           node or self.time[node]>
           version):
           node = self.parent[node]
        return node
    def union(self,a,b,time):
        # merges a and b
        a = self.find(a,time)
        b = self.find(b,time)
        if a==b:
           return False
        if self.size[a]>self.size[b]:
           a,b = b,a
        self.parent[a] = b
        self.time[a] = time
        self.size[b] += self.size[a]
        return True
    def isconnected(self,a,b,time):
        return self.find(a,time)==self
           .find(b,time)


class RollbackDSU:
    def __init__(self,n):
        self.p=list(range(n)); self.sz
           =[1]*n; self.st=[]
    def find(self,x):
        while x!=self.p[x]: x=self.p[x
           ]
        return x
    def union(self,a,b):
        a,b=self.find(a),self.find(b)
        if a==b: self.st.append
           ((-1,-1,-1)); return
        if self.sz[a]>self.sz[b]: a,b=
           b,a
        self.st.append((a,b,self.sz[b
           ]))
        self.p[a]=b; self.sz[b]+=self.
           sz[a]
    def rollback(self):
        a,b,s=self.st.pop()
        if a==-1: return
        self.p[a]=a; self.sz[b]=s
```

Fenwick Tree

```
class BIT:
    #Faster than segment tree so use
       if possbile
    def __init__(self, x):
        self.bit = x
        for i in range(len(x)):
           j = i | (i + 1)
           if j < len(x):
              x[j] += x[i]
    def update(self, idx, x):
        """updates bit[idx] += x"""
        while idx < len(self.bit):
           self.bit[idx] += x
           idx |= idx + 1
    def query(self, end):
        """calc sum(bit[:end])"""
        #gives sum of element before
           end
        x = 0
        while end:
           x += self.bit[end - 1]
           end &= end - 1
        return x
    def findkth(self, k):
        """Find largest idx such that
           sum(bit[:idx]) <= k"""
        idx = -1
        for d in reversed(range(len(
           self.bit).bit_length())):
           right_idx = idx + (1 << d)
           if right_idx < len(self.bit
              ) and k >= self.bit[
              right_idx]:
              idx = right_idx
              k -= self.bit[idx]
        return idx + 1
```

2-D Fenwick Tree

```
class BIT2D:
    def __init__(self, arr):
        self.n = len(arr)
        self.m = len(arr[0]) if self.n
            > 0 else 0
        # self.bit = [row[:] for row
           in arr]
        self.bit = arr # assuming that
            arr is not used after this
        for i in range(self.n):
           for j in range(self.m):
              ni = i | (i + 1)
              if ni < self.n:
                 self.bit[ni][j] +=
                    self.bit[i][j]
        for i in range(self.n):
           for j in range(self.m):
              nj = j | (j + 1)
              if nj < self.m:
                 self.bit[i][nj] +=
                    self.bit[i][j]
    def add(self, x, y, delta):
        # 0-based in log n * log m
        i = x
        while i < self.n:
           j = y
           while j < self.m:
              self.bit[i][j] += delta
              j |= j + 1
           i |= i + 1
    def sum(self, x, y):
        # sum from 0,0 to x,y
           inclusive in log n * log m
        if not (0<=x<self.n) or not
           (0<=y<self.m):
           return 0
        res = 0
        i = x
        while i >= 0:
           j = y
           while j >= 0:
              res += self.bit[i][j]
              j = (j & (j + 1)) - 1
           i = (i & (i + 1)) - 1
        return res
    def query(self, x1, y1, x2, y2):
        # sum of L[x1:x2+1][y1:y2+1]
        return (self.sum(x2,y2)-self.
           sum(x1-1,y2)-self.sum(x2,y1
           -1)+(self.sum(x1-1,y1-1)))
```

Bucket Sorted List

```
from typing import Generic, Iterable
   , Iterator, List, Tuple, TypeVar,
   Optional
T = TypeVar('T')
class SortedList(Generic[T]):
    BUCKET_RATIO = 16
    SPLIT_RATIO = 24
    def __init__(self, a: Iterable[T]
       = []) -> None:
        a = list(a)
        n = self.size = len(a)
        if any(a[i] > a[i + 1] for i
           in range(n - 1)):
           a.sort()
        num_bucket = int(math.ceil(
           math.sqrt(n / self.
           BUCKET_RATIO)))
        self.a = [a[n * i //
           num_bucket : n * (i + 1) //
           num_bucket] for i in range(
           num_bucket)]
    def __iter__(self) -> Iterator[T
       ]:
        for i in self.a:
```

```
            for j in i: yield j
    def __reversed__(self) ->
        Iterator[T]:
            for i in reversed(self.a):
                for j in reversed(i): yield
                    j
    def __eq__(self, other) -> bool:
        return list(self) == list(other
            )
    def __len__(self) -> int:return
        self.size
    def __repr__(self) -> str:return
        "SortedMultiset" + str(self.a)
    def __str__(self) -> str:
        s = str(list(self))
        return "{" + s[1 : len(s) - 1]
            + "}"
    def _position(self, x: T) ->
        Tuple[List[T], int, int]:
            for i, a in enumerate(self.a):
                if x <= a[-1]: break
            return (a, i, bisect_left(a, x
                ))
    def __contains__(self, x: T) ->
        bool:
            if self.size == 0: return
                False
            a, _, i = self._position(x)
            return i != len(a) and a[i] ==
                x
    def count(self, x: T) -> int:
        return self.index_right(x) -
            self.index(x)
    def add(self,x):return self.
        insert(x)
    def insert(self, x: T) -> None:
        if self.size == 0:
            self.a = [[x]]
            self.size = 1
            return
        a, b, i = self._position(x)
        a.insert(i, x)
        self.size += 1
        if len(a) > len(self.a) * self
            .SPLIT_RATIO:
            mid = len(a) >> 1
            self.a[b:b+1] = [a[:mid], a
                [mid:]]
    def _pop(self, a: List[T], b: int
        , i: int) -> T:
        ans = a.pop(i)
        self.size -= 1
        if not a: del self.a[b]
        return ans
    def remove(self, x: T) -> bool:
        if self.size == 0: return
            False
        a, b, i = self._position(x)
        if i == len(a) or a[i] != x:
            return False
        self._pop(a, b, i)
        return True
    def lt(self, x: T) -> Optional[T
        ]:
        for a in reversed(self.a):
            if a[0] < x:
                return a[bisect_left(a,
                    x) - 1]
    def le(self, x: T) -> Optional[T
        ]:
        for a in reversed(self.a):
            if a[0] <= x:
                return a[bisect_right(a,
                    x) - 1]
    def gt(self, x: T) -> Optional[T
        ]:
        for a in self.a:
            if a[-1] > x:
                return a[bisect_right(a,
                    x)]
    def ge(self, x: T) -> Optional[T
        ]:
        for a in self.a:
            if a[-1] >= x:
                return a[bisect_left(a,
                    x)]
    def __getitem__(self, i: int) ->
        T:
        if i < 0:
            for a in reversed(self.a):
                i += len(a)
                if i >= 0: return a[i]
        else:
            for a in self.a:
                if i < len(a): return a[
                    i]
                i -= len(a)
        raise IndexError
    def pop(self, i: int = -1) -> T:
        if i < 0:
            for b, a in enumerate(
                reversed(self.a)):
                i += len(a)
                if i >= 0: return self.
                    _pop(a, ~b, i)
        else:
            for b, a in enumerate(self.
                a):
                if i < len(a): return
                    self._pop(a, b, i)
                i -= len(a)
        raise IndexError
    def bisect_left(self,x):return
        self.index(x)
    def index(self, x: T) -> int:
        ans = 0
        for a in self.a:
            if a[-1] >= x:
                return ans + bisect_left
                    (a, x)
            ans += len(a)
        return ans
    def bisect_right(self,x):return
        self.index_right(x)
    def index_right(self, x: T) ->
        int:
        ans = 0
        for a in self.a:
            if a[-1] > x:
                return ans +
                    bisect_right(a, x)
            ans += len(a)
        return ans
    def find_closest(self, k: T) ->
        Optional[T]:
        if self.size == 0:return None
        ltk = self.le(k);gtk = self.ge
            (k)
        if ltk is None:return gtk
        if gtk is None:return ltk
        return ltk if abs(k-ltk)<=abs(
            k-gtk) else gtk
```

Trie

```
class Trie:
    def __init__(self):
        self.root = {}
    def add(self, word):
        current_dict = self.root
        for letter in word:
            current_dict = current_dict
                .setdefault(letter, {})
        current_dict[0] = True
```

Convex Hull

```
class LiChao:
    __slots__ = ("lo","hi","mid","m",
        "b","left","right")
    # lo = min value of x that you
        will query
    def __init__(self,lo,hi):
        self.lo = lo
        self.hi = hi
```

```
        self.mid = (lo+hi)>>1
        self.m = None
        self.b = None
        self.left = None
        self.right = None
    def add_line(self,m,b):
        node = self
        while True:
            lo,hi,mid = node.lo,node.hi
                ,node.mid
            if node.m is None:
                node.m,node.b = m,b
                return
            cur_m,cur_b = node.m,node.b
            if m*mid+b>cur_m*mid+cur_b:
                node.m,m = m,cur_m
                node.b,b = b,cur_b
                cur_m,cur_b = node.m,
                    node.b
            if lo==hi:
                return
            if m*lo+b>cur_m*lo+cur_b:
                if node.left is None:
                    node.left = LiChao(lo
                        ,mid)
                node = node.left
            elif m*hi+b>cur_m*hi +cur_b
                :
                if node.right is None:
                    node.right = LiChao(
                        mid+1,hi)
                node = node.right
            else:
                return
    def query(self,x):
        node = self
        res = -10**18
        while node:
            if node.m is not None:
                v = node.m*x+node.b
                if v>res:
                    res = v
            if node.lo==node.hi:
                break
            if x<=node.mid:
                node = node.left
            else:
                node = node.right
        return res
```

Heavy Light Decomposition

```
class HLD:
    def __init__(self, adj, values,
        root=0,func=max,unit=float('-
        inf')):
        self.adj = adj
        self.values = values
        self.parent = [-1] * len(adj)
        self.depth = [0] * len(adj)
        self.size = [0] * len(adj)
        self.heavy = [-1] * len(adj)
        self.head = [0] * len(adj)
        self.pos = [0] * len(adj)
        self.flat = [0] * len(adj)
        self.unit = unit
        self.func = func
        self._dfs(root)
        self._decompose(root)
        self.seg = SegmentTree([self.
            values[self.flat[i]] for i
            in range(len(self.adj))],
            func,unit)
    def _dfs(self,start=0):
        visited = [False] * len(self.
            adj)
        stack = [start]
        while stack:
            start = stack[-1]
            if not visited[start]:
                visited[start] = True
                for child in self.adj[
                    start]:
                    if not visited[child
                        ]:
                        self.parent[child]
                            = start
                        self.depth[child]
                            = self.depth[
                            start]+1
                        stack.append(child
                            )
            else:
                self.size[stack.pop()] =
                    1
                k = 0
                for child in self.adj[
                    start]:
                    if self.parent[start
                        ]!=child:
                        self.size[start]
                            += self.size[
                            child]
                        if self.size[child
                            ]>k:
                            k = self.size[
                                child]
                            self.heavy[
                                start] =
                                child
        return visited
    def _decompose(self, root):
        stack = [(root,root)]
        time = 0
        while stack:
            u, h = stack.pop()
            self.head[u] = h
            self.flat[time] = u
            self.pos[u] = time
            time += 1
            for v in reversed(self.adj[
                u]):
                if v!=self.parent[u] and
                    v!=self.heavy[u]:
                    stack.append((v, v))
            if self.heavy[u] != -1:
                stack.append((self.heavy
                    [u], h))
    def query(self, u, v):
        res = self.unit
        while self.head[u] != self.
            head[v]:
            if self.depth[self.head[u]]
                < self.depth[self.head[v
                ]]:
                u, v = v, u
            res = self.func(res, self.
                seg.query(self.pos[self.
                head[u]], self.pos[u] +
                1))
            u = self.parent[self.head[u
                ]]
        if self.depth[u] > self.depth[
            v]:
            u, v = v, u
        return self.func(res, self.seg
            .query(self.pos[u], self.pos
            [v] + 1))
    def update(self, u, value):
        self.seg.update(self.pos[u],
            value)
    def update_path(self, u, v, value
        ):
        while self.head[u] != self.
            head[v]:
            if self.depth[self.head[u]]
                < self.depth[self.head[v
                ]]:
                u, v = v, u
            self.seg.range_update(self.
                pos[self.head[u]], self.
                pos[u], value)
            u = self.parent[self.head[u
                ]]
        if self.depth[u] > self.depth[
            v]:
            u, v = v, u
```

```
        self.seg.range_update(self.pos
            [u], self.pos[v], value)
    def add_to_subtree(self, u, value
        ):
        self.seg.range_update(self.pos
            [u], self.pos[u] + self.size
            [u] - 1, value)
```

Mono Deque

```
from typing import Callable, TypeVar
    , Generic, List
T = TypeVar('T')
class MonoStack(Generic[T]):
    def __init__(self, op: Callable[[
        T, T], T], e: Callable[[], T]):
        self.s: List[T] = []
        self.sMono: List[T] = []
        self.op = op
        self.e = e
    def push(self, x: T):
        self.s.append(x)
        if not self.sMono:
            self.sMono.append(x)
        else:
            self.sMono.append(self.op(
                self.sMono[-1], x))
    def pop(self) -> T:
        if not self.s:
            return self.e()
        self.sMono.pop()
        return self.s.pop()
    def get(self) -> T:
        return self.sMono[-1] if self.
            sMono else self.e()
    def empty(self) -> bool:
        return not self.s
class MonoDeque(Generic[T]):
    def __init__(self, op: Callable[[
        T, T], T] = lambda a,b: max(a,b
        ), e: Callable[[], T] = lambda
        : -float('inf')):
        # e is the unit value in form
            of lambda : 0
        # The Function op must be
            associative, f(a,b)==f(b,a)
        self.op = op
        self.e = e
        self.front = MonoStack(op, e)
        self.back = MonoStack(op, e)
    def push_back(self, x: T):
        self.back.push(x)
    def pop_front(self):
        if self.front.empty():
            while not self.back.empty()
                :
                self.front.push(self.
                    back.pop())
            self.front.pop()
    def get(self) -> T:
        # returns the function op of
            the elements present in the
            deque
        return self.op(self.front.get
            (), self.back.get())
```

Merge Sort Tree

```
class MergeSortTree:
    def merge(L,L1):
        L2 = []
        L = list(L);L1 = list(L1)
        i = j = 0
        while j<len(L) and i<len(L1):
            if L[j]<L1[i]:
                L2.append(L[j])
                j += 1
            else:
                L2.append(L1[i])
                i += 1
        L2.extend(L[j:]+L1[i:])
        return L2
    def __init__(self, data):
        self.n = len(data)
        self.tree = [SortedList() for
            _ in range(2 * self.n)]
        self.build(data)
    def build(self, data):
        for i in range(self.n):
            self.tree[self.n + i].
                insert(data[i])
        for i in range(self.n - 1, 0,
            -1):
            self.tree[i] = SortedList(
                MergeSortTree.merge(self.
                tree[i << 1],self.tree[i
                <<1|1]))
    def query(self, left, right,l,r):
        res = 0
        left += self.n
        right += self.n
        while left < right:
            if left & 1:
                res += self.func(self.
                    tree[left], l, r);left
                    += 1
            if right & 1:
                right -= 1;res += self.
                    func(self.tree[right],
                    l, r)
            left >>= 1;right >>= 1
        return res
    def func(self, L, l, r):
        return L.bisect_right(r)-L.
            bisect_left(l)
    def update(self,pos,value):
        pos += self.n;old_val = self.
            tree[pos][0]
        self.tree[pos].remove(old_val)
        self.tree[pos].add(value)
        while pos:
            pos >>= 1
            self.tree[pos].remove(
                old_val)
            self.tree[pos].add(value)
```

Persistent Segment Tree

```
class PersistentSegmentTree:
    # Everything is 0 based indexing
        and [l,r]
    class Node:
        def __init__(self, value=0,
            left=None, right=None):
            self.value = value
            self.left = left
            self.right = right
    @staticmethod
    def func(a, b):
        return a+b
    def __init__(self, data):
        self.n = len(data)
        self.versions = []
        self.versions.append(self.
            _build(data))
    def _build(self, data):
        stack = [(0, self.n - 1, False
            )]
        nodes = {}
        while stack:
            left, right, visited =
                stack.pop()
            if left == right:
                nodes[(left, right)] =
                    self.Node(data[left])
            else:
                if visited:
                    mid = (left + right)
                        // 2
                    left_child = nodes[(
                        left, mid)]
                    right_child = nodes[(
                        mid + 1, right)]
                    nodes[(left, right)]
                        = self.Node(self.
```

```
                func(left_child.
                value,right_child.
                value),left_child,
                right_child)
            else:
                stack.append((left,
                right, True))
                mid = (left + right)
                // 2
                stack.append((mid +
                1, right, False))
                stack.append((left,
                mid, False))
    return nodes[(0, self.n - 1)]
def update(self, version, pos,
    value):
    # Returns the root to the new
    tree,
    # now you must add it to
    versions yourself
    # seg.versions[version] = seg.
    update(version, pos, value)
    old_root = self.versions[
    version]
    stack, path = [(old_root, 0,
    self.n - 1)], []
    while stack:
        node, left, right = stack.
        pop()
        path.append((node, left,
        right))
        if left == right:
            break
        mid = (left + right) // 2
        if pos <= mid:
            stack.append((node.left,
            left, mid))
        else:
            stack.append((node.right
            , mid + 1, right))
    new_nodes = {}
    for node, left, right in
    reversed(path):
        if left == right:
            k = value
            # k = self.func(node.
            value,value) # if i
            want to update
            new_nodes[(left, right)]
            = self.Node(k)
        else:
            mid = (left + right) //
            2
            left_child = new_nodes.
            get((left, mid), node.
                left)
            right_child = new_nodes.
            get((mid + 1, right),
            node.right)
            new_nodes[(left, right)]
            = self.Node(self.func
            (left_child.value,
            right_child.value),
            left_child,
            right_child)
    return new_nodes[(0, self.n -
    1)]
def create_version(self, version,
    pos, value):
    new_root = self.update(version
    , pos, value)
    self.versions.append(new_root)
    return len(self.versions) - 1
def query(self, version, ql, qr):
    node, left, right = self.
    versions[version], 0, self.n
    - 1
    stack = [(node, left, right)]
    result = 0 # change this
    depending on the problem
    while stack:
        node, left, right = stack.
        pop()
        if ql > right or qr < left:
            continue
        if ql <= left and right <=
        qr:
            result = self.func(
            result,node.value)
        else:
            mid = (left + right) //
            2
            stack.append((node.left,
            left, mid))
            stack.append((node.right
            , mid + 1, right))
    return result
```

Suffix Automaton

```
class State:
    def __init__(self):
        self.next = {}
        self.link = -1
        self.len = 0
        self.first_pos = -1
        self.occurrence = 0

class SuffixAutomaton:
    def __init__(self, s):
        self.s = s
        self.states = [State()]
        self.size = 1
        self.last = 0
        for ch in s:
            self.add(ch)
        self._prepare_occurrences() #
        comment out if taking time
        self._count_substrings()
    def add(self, ch):
        p = self.last
        cur = self.size
        self.states.append(State())
        self.size += 1
        self.states[cur].len = self.
        states[p].len + 1
        self.states[cur].first_pos =
        self.states[cur].len - 1
        self.states[cur].occurrence =
        1
        while p != -1 and ch not in
        self.states[p].next:
            self.states[p].next[ch] =
            cur
            p = self.states[p].link
        if p == -1:
            self.states[cur].link = 0
        else:
            q = self.states[p].next[ch]
            if self.states[p].len + 1
            == self.states[q].len:
                self.states[cur].link =
                q
            else:
                clone = self.size
                self.states.append(State
                ())
                self.size += 1
                self.states[clone].len =
                self.states[p].len +
                1
                self.states[clone].next
                = self.states[q].next.
                copy()
                self.states[clone].link
                = self.states[q].link
                self.states[clone].
                first_pos = self.
                states[q].first_pos
                while p != -1 and self.
                states[p].next[ch] ==
                q:
                self.states[p].next[
                ch] = clone
                p = self.states[p].
                link
```

```
            self.states[q].link =
                self.states[cur].link
                = clone
        self.last = cur
    def _prepare_occurrences(self):
        order = sorted(range(self.size
            ), key=lambda x: -self.
            states[x].len)
        for i in order:
            if self.states[i].link !=
                -1:
                self.states[self.states[
                    i].link].occurrence +=
                     self.states[i].
                    occurrence
    def _count_substrings(self):
        self.dp = [0] * self.size
        for i in range(self.size):
            self.dp[i] = 1
        order = sorted(range(self.size
            ), key=lambda x: self.states
            [x].len)
        for u in reversed(order):
            for v in self.states[u].
                next.values():
                self.dp[u] += self.dp[v]
    def is_substring(self, s):
        current = 0
        for ch in s:
            if ch not in self.states[
                current].next:
                return False
            current = self.states[
                current].next[ch]
        return True
    def count_occurrences(self, s):
        current = 0
        for ch in s:
            if ch not in self.states[
                current].next:
                return 0
            current = self.states[
                current].next[ch]
        return self.states[current].
            occurrence
    def count_distinct_substrings(
        self):
        return sum(self.states[i].len
            - self.states[self.states[i
            ].link].len for i in range
            (1, self.size))
    def kth_lex_substring(self, k):
        # kth distinct substring
        result = []
        current = 0
        while k:
            for ch in sorted(self.
                states[current].next):
                next_state = self.states
                    [current].next[ch]
                if self.dp[next_state] <
                     k:
                    k -= self.dp[
                        next_state]
                else:
                    result.append(ch)
                    k -= 1
                    current = next_state
                    break
        return ''.join(result)
    def enumerate_all_substrings(self
        ):
        result = []
        def dfs(state, path):
            for ch in sorted(self.
                states[state].next):
                next_state = self.states
                    [state].next[ch]
                result.append(path + ch)
                dfs(next_state, path +
                    ch)
        dfs(0, "")
        return result
    def longest_common_substring(self
        , t):
        v = 0;l = 0;best = 0;bestpos =
            0
        for i in range(len(t)):
            while v and t[i] not in
                self.states[v].next:
                v = self.states[v].link
                l = self.states[v].len
            if t[i] in self.states[v].
                next:
                v = self.states[v].next[
                    t[i]]
                l += 1
            if l > best:
                best = l
                bestpos = i
        return t[bestpos - best + 1:
            bestpos + 1]
    def all_occurrences(self, s):
        current = 0
        for ch in s:
            if ch not in self.states[
                current].next:
                return []
            current = self.states[
                current].next[ch]
        positions = []
        def collect(state):
            if self.states[state].
                occurrence:
                pos = self.states[state
                    ].first_pos - len(s) +
                     1
                positions.append(pos)
            for v in self.states[state
                ].next.values():
                collect(v)
        collect(current)
        return sorted(set(positions))
    def missing_sub(self):
        visited = set()
        q = deque([(0, "")])
        while q:
            state, path = q.popleft()
            for c in map(chr, range(97,
                 123)):
                if c not in self.states[
                    state].next:
                    return path + c
                next_state = self.states
                    [state].next[c]
                if (next_state, path + c
                    ) not in visited:
                    visited.add((
                        next_state, path +
                        c))
                    q.append((next_state,
                         path + c))
        return None
```

Segment Tree

```
class SegmentTree:
    @staticmethod
    def func(a, b):
        # Change this function
            depending upon needs
        return max(a, b)
    def __init__(self, data):
        self.n = len(data)
        self.tree = [0] * (self.n<<1)
        self.build(data)
    def build(self, data):
        for i in range(self.n):
            self.tree[self.n + i] =
                data[i]
        for i in range(self.n - 1, 0,
            -1):
            self.tree[i] = self.func(
                self.tree[i<<1], self.
                tree[(i<<1) + 1])
```

```
    def update(self, pos, value):
        # Update the value at the leaf
            node
        pos += self.n
        # For updating
        self.tree[pos] = value
        # self.tree[pos] += value
        # If you want to add rather
            than update
        while pos > 1:
            pos >>= 1
            self.tree[pos] = self.func(
                self.tree[pos<<1], self.
                tree[(pos<<1) + 1])
    def query(self, left, right):
        # Query the maximum value in
            the range [left, right)
        left += self.n
        right += self.n
        # Change the initializer
            depending upon the self.func
        max_val = float('-inf')
        ##
        while left < right:
            if left&1:
                max_val = self.func(
                    max_val, self.tree[
                    left])
                left += 1
            if right&1:
                right -= 1
                max_val = self.func(
                    max_val, self.tree[
                    right])
            left >>= 1
            right >>= 1
        return max_val
    def __repr__(self):
        values = [str(self.query(i, i
            + 1)) for i in range(self.n)
            ]
        return f"Seg[{', '.join(values
            )}]"
```

Sparse Table

```
class SparseTable:
    @staticmethod
    def func(a,b):
        # func(a,a) should be a
        return gcd(a,b)
    def __init__(self, arr):
        self.n = len(arr)
        self.table = [[0 for i in
            range(int((math.log(self.n,
            2)+1)))] for j in range(self
            .n)]
        self.build(arr)
    def build(self, arr):
        for i in range(0, self.n):
            self.table[i][0] = arr[i]
        j = 1
        while (1 << j) <= self.n:
            i = 0
            while i <= self.n - (1 << j
                ):
                self.table[i][j] = self.
                    func(self.table[i][j -
                    1], self.table[i + (1
                    << (j - 1))][j - 1])
                i += 1
            j += 1
    def query(self, L, R):
        # query from [L,R]
        j = int(math.log2(R - L + 1))
        return self.func(self.table[L
            ][j], self.table[R - (1 << j
            ) + 1][j])
```

BitArray

```
class BitSet:
    ADDRESS_BITS_PER_WORD = 12
    BITS_PER_WORD = 1 <<
        ADDRESS_BITS_PER_WORD
    WORD_MASK = -1
    def __init__(self, sz):
        self.sz = sz
        self.words = [0] * (self.
            _wordIndex(sz - 1) + 1)
    def _wordIndex(self, bitIndex):
        if bitIndex >= self.sz:
            raise ValueError("out of
                bound index", bitIndex)
        return bitIndex >> BitSet.
            ADDRESS_BITS_PER_WORD
    def flip(self, bitIndex):
        wordIndex = self._wordIndex(
            bitIndex)
        self.words[wordIndex] ^= 1 <<
            (bitIndex % BitSet.
            BITS_PER_WORD)
    def flip_range(self, l, r):
        startWordIndex = self.
            _wordIndex(l)
        endWordIndex = self._wordIndex
            (r)
        firstWordMask = BitSet.
            WORD_MASK << (l % BitSet.
            BITS_PER_WORD)
        rem = (r+1) % BitSet.
            BITS_PER_WORD
        lastWordMask = BitSet.
            WORD_MASK if rem == 0 else
            ~(BitSet.WORD_MASK << rem)
        if startWordIndex ==
            endWordIndex:
            self.words[startWordIndex]
                ^= (firstWordMask &
                lastWordMask)
        else:
            self.words[startWordIndex]
                ^= firstWordMask
            for i in range(
                startWordIndex + 1,
                endWordIndex):
                self.words[i] ^= BitSet.
                    WORD_MASK
            self.words[endWordIndex] ^=
                lastWordMask
    def __setitem__(self, bitIndex,
        value):
        wordIndex = self._wordIndex(
            bitIndex)
        if value:
            self.words[wordIndex] |= 1
                << (bitIndex % BitSet.
                BITS_PER_WORD)
        else:
            self.words[wordIndex] &=
                ~(1 << (bitIndex % BitSet
                .BITS_PER_WORD))
    def __getitem__(self, bitIndex):
        wordIndex = self._wordIndex(
            bitIndex)
        return self.words[wordIndex] &
            (1 << (bitIndex % BitSet.
            BITS_PER_WORD)) != 0
    def nextSetBit(self, fromIndex):
        wordIndex = self._wordIndex(
            fromIndex)
        word = self.words[wordIndex] &
            (BitSet.WORD_MASK << (
            fromIndex % BitSet.
            BITS_PER_WORD))

        while True:
            if word != 0:
                return wordIndex *
                    BitSet.BITS_PER_WORD +
                    (word & -word).
                    bit_length() - 1
            wordIndex += 1
            if wordIndex > len(self.
                words) - 1:
```

```
            return -1
        word = self.words[wordIndex
            ]
    def nextClearBit(self, fromIndex)
        :
        wordIndex = self._wordIndex(
            fromIndex)
        word = ~self.words[wordIndex]
            & (BitSet.WORD_MASK << (
            fromIndex % BitSet.
            BITS_PER_WORD))

        while True:
            if word != 0:
                index = wordIndex *
                    BitSet.BITS_PER_WORD +
                     (word & -word).
                    bit_length() - 1
                return index if index <
                    self.sz else - 1
            wordIndex += 1
            if wordIndex > len(self.
                words) - 1:
                return -1
            word = ~self.words[
                wordIndex]
    def lastSetBit(self):
        wordIndex = len(self.words) -
            1
        word = self.words[wordIndex]

        while wordIndex >= 0:
            if word != 0:
                return wordIndex *
                    BitSet.BITS_PER_WORD +
                     (word.bit_length() -
                    1 if word > 0 else
                    BitSet.BITS_PER_WORD -
                     1)
            wordIndex -= 1
            word = self.words[wordIndex
                ]
        return -1
    def __str__(self):
        res = []
        st = 0
        while True:
            i = self.nextSetBit(st)
            if i != -1:
                res += [0] * (i - st)
                j = self.nextClearBit(i)
                if j != -1:
                    res += [1] * (j-i)
                    st = j
                else:
                    res += [1] * (self.sz
                        - i)
                    break
            else:
                res += [0] * (self.sz -
                    st)
                break

        return "".join(str(v) for v in
            res)
    def __repr__(self):
        return "Bitset(%s)" % str(self
            )
    def __iter__(self):
        for i in self[:]:
            yield i
    def __len__(self):
        return self.sz
    def __or__(self, other):
        if self.sz != other.sz:
            raise ValueError("BitSets
                must be of equal size")
        res = BitSet(self.sz)
        res.words = [a | b for a, b in
            zip(self.words, other.words
            )]
        return res
    def __add__(self, other):
        if self.sz != other.sz:
            raise ValueError("BitSets
                must be of equal size")
        res = BitSet(self.sz)
        carry = 0
        for i in range(len(self.words)
            ):
            total = self.words[i] +
                other.words[i] + carry
            res.words[i] = total &
                BitSet.WORD_MASK
            carry = total >> BitSet.
                BITS_PER_WORD
        return res
    def __and__(self, other):
        if self.sz != other.sz:
            raise ValueError("BitSets
                must be of equal size")
        res = BitSet(self.sz)
        res.words = [a & b for a, b in
            zip(self.words, other.words
            )]
        return res
    def __xor__(self, other):
        if self.sz != other.sz:
            raise ValueError("BitSets
                must be of equal size")
        res = BitSet(self.sz)
        res.words = [a ^ b for a, b in
            zip(self.words, other.words
            )]
        return res
    def __invert__(self):
        res = BitSet(self.sz)
        res.words = [~a & BitSet.
            WORD_MASK for a in self.
            words]
        return res
    def add(self, val):
        self.flip_range(val, self.
            nextClearBit(val))
    def rem(self, val):
        self.flip_range(val, self.
            nextSetBit(val))
```

Graphs

Basics

```
def dfs(d,start=0):
    n = len(d)
    visited = [False]*n
    dp = [0]*n
    finished = [False]*n
    stack = [start]
    while stack:
        start = stack[-1]
        if not visited[start]:
            visited[start] = True
            for child in d[start]:
                if not visited[child]:
                    stack.append(child)
        else:
            stack.pop()
            dp[start] += 1
            for child in d[start]:
                if finished[child]:
                    dp[start] += dp[child
                        ]
            finished[start] = True
    return dp

def dijkstra(d,start=0):
    n = len(d)
    dist = [float("inf")]*n
    # parents = [-1]*n
    dist[start] = 0
    queue = [(0, start)]
    while queue:
        path_len, v = heappop(queue)
        if path_len == dist[v]:
            for w, edge_len in d[v]:
```

```
            new_dist = edge_len+
               path_len
            if new_dist<dist[w]:
               dist[w] = new_dist
               # parents[w] = v
               heappush(queue, (
                  new_dist, w))
   return dist
```

Others

```
def euler_path(d):
   start = [1]
   ans = []
   while start:
      cur = start[-1]
      if len(d[cur])==0:
         ans.append(start.pop())
         continue
      k1 = d[cur].pop()
      d[k1].remove(cur) # if
         undirected
      start.append(k1)
   return ans

def floyd_warshall(n, edges):
   dist = [[0 if i == j else float("
      inf") for i in range(n)] for j
      in range(n)]
   pred = [[None] * n for _ in range
      (n)]
   for u, v, d in edges:
      dist[u][v] = d
      pred[u][v] = u
   for k in range(n):
      for i in range(n):
         for j in range(n):
            if dist[i][k] + dist[k][
               j] < dist[i][j]:
               dist[i][j] = dist[i][
                  k] + dist[k][j]
               pred[i][j] = pred[k][
                  j]
   return dist, pred

def toposort(graph):
   res, found = [], [0] * len(graph)
   stack = list(range(len(graph)))
   while stack:
      node = stack.pop()
      if node < 0:
         res.append(~node)
      elif not found[node]:
         found[node] = 1
         stack.append(~node)
         stack += graph[node]
      for node in res:
         if any(found[nei] for nei in
            graph[node]):
            return None
         found[node] = 0
   return res[::-1]
```

Advance

```
class AuxiliaryTree:
   def __init__(self, edge, root =
      0):
      self.n = len(edge)
      self.order = [-1] * self.n
      self.path = [-1] * (self.n-1)
      self.depth = [0] * self.n
      if self.n == 1: return
      parent = [-1] * self.n
      que = [root]
      t = -1
      while que:
         u = que.pop()
         self.path[t] = parent[u]
         t += 1
         self.order[u] = t
         for v in edge[u]:
            if self.order[v] == -1:
               que.append(v)
               parent[v] = u
               self.depth[v] = self.
                  depth[u] + 1
      self.n -= 1
      self.h = self.n.bit_length()
      self.data = [0] * (self.n *
         self.h)
      self.data[:self.n] = [self.
         order[u] for u in self.path]
      for i in range(1, self.h):
         for j in range(self.n -
            (1<<i) + 1):
            self.data[i*self.n + j]
               = min(self.data[(i-1)*
               self.n + j], self.data
               [(i-1)*self.n + j
               +(1<<(i-1))])

   def lca(self, u, v):
      if u == v: return u
      l = self.order[u]
      r = self.order[v]
      if l > r:
         l,r = r,l
      level = (r - l).bit_length() -
         1
      return self.path[min(self.data
         [level*self.n + l], self.
         data[level*self.n + r-(1<<
         level)])]

   def dis(self, u, v):
      if u == v: return 0
      l = self.order[u]
      r = self.order[v]
      if l > r:
         l,r = r,l
      level = (r - l).bit_length() -
         1
      p = self.path[min(self.data[
         level*self.n + l], self.data
         [level*self.n + r-(1<<level)
         ])]
      return self.depth[u] + self.
         depth[v] - 2 * self.depth[p]

   def make(self, vs):
      k = len(vs)
      vs.sort(key = self.order.
         __getitem__)

      par = dict()
      edge = dict()
      edge[vs[0]] = []

      st = [vs[0]]

      for i in range(k - 1):
         l = self.order[vs[i]]
         r = self.order[vs[i+1]]
         level = (r - l).bit_length
            () - 1
         w = self.path[min(self.data
            [level*self.n + l], self.
            data[level*self.n + r
            -(1<<level)])]
         if w != vs[i]:
            p = st.pop()
            while st and self.depth[
               w] < self.depth[st
               [-1]]:
               par[p] = st[-1]
               edge[st[-1]].append(p
                  )
               p = st.pop()

            if not st or st[-1] != w
               :
               st.append(w)
               edge[w] = [p]
            else:
               edge[w].append(p)
            par[p] = w

         st.append(vs[i+1])
```

```
            edge[vs[i+1]] = []
        for i in range(len(st) - 1):
            edge[st[i]].append(st[i+1])
            par[st[i+1]] = st[i]
        par[st[0]] = -1
        return st[0], edge, par
class binary_lift:
    def __init__(self, graph, f=max,
        root=0, flag=False):
        n = len(graph)
        parent = [-1] * (n + 1)
        depth = self.depth = [-1] * n
        bfs = [root]
        depth[root] = 0
        data = [0]*n
        for node in bfs:
            # for nei,w in graph[node]:
            for nei in graph[node]:
                if depth[nei] == -1:
                    # data[nei] = w
                    parent[nei] = node
                    depth[nei] = depth[
                        node] + 1
                    bfs.append(nei)
        parent = self.parent = [parent
            ]
        self.f = f
        if flag:
            data = self.data = [data]
            for _ in range(max(depth).
                bit_length()):
                old_data = data[-1]
                old_parent = parent[-1]
                data.append([f(val,
                    old_data[p]) for val,p
                     in zip(old_data,
                    old_parent)])
                parent.append([
                    old_parent[p] for p in
                     old_parent])
        else:
            for _ in range(max(depth).
                bit_length()):
                old_parent = parent[-1]
                parent.append([
                    old_parent[p] for p in
                     old_parent])
    def lca(self, a, b):
        depth = self.depth
        parent = self.parent
        if depth[a] < depth[b]:
            a,b = b,a
        d = depth[a] - depth[b]
        for i in range(d.bit_length())
            :
            if (d >> i) & 1:
                a = parent[i][a]
        for i in range(depth[a].
            bit_length())[::-1]:
            if parent[i][a] != parent[i
                ][b]:
                a = parent[i][a]
                b = parent[i][b]
        if a != b:
            return parent[0][a]
        else:
            return a
    def distance(self, a, b):
        return self.depth[a] + self.
            depth[b] - 2 * self.depth[
            self.lca(a,b)]
    def kth_ancestor(self, a, k):
        parent = self.parent
        if self.depth[a] < k:
            return -1
        for i in range(k.bit_length())
            :
            if (k >> i) & 1:
                a = parent[i][a]
        return a
    def __call__(self, a, b, c=0):
        depth = self.depth
        parent = self.parent
        data = self.data
        f = self.f
        c = self.lca(a, b)
        val = c
        for x,d in (a, depth[a] -
            depth[c]), (b, depth[b] -
            depth[c]):
            for i in range(d.bit_length
                ()):
                if (d >> i) & 1:
                    val = f(val, data[i][
                        x])
                    x = parent[i][x]
        return val
```

Graph-Flatten

```
def dfs(graph):
    starttime = [[0,0] for i in range
        (len(graph))]
    time = 0
    stack = [(0,-1,0)]
    while stack:
        cur, prev, state = stack.pop()
        if state == 0:
            starttime[cur][0] = time
            time += 1
            stack.append((cur, prev, 1)
                )
            for neighbor in graph[cur]:
                if neighbor == prev:
                    continue
                stack.append((neighbor,
                    cur, 0))
        elif state == 1:
            starttime[cur][1] = time
    return starttime
```

2-sat

```
def find_SCC(graph):
    SCC, S, P = [], [], []
    depth = [0] * len(graph)
    stack = list(range(len(graph)))
    while stack:
        node = stack.pop()
        if node < 0:
            d = depth[~node] - 1
            if P[-1] > d:
                SCC.append(S[d:])
                del S[d:], P[-1]
                for node in SCC[-1]:
                    depth[node] = -1
        elif depth[node] > 0:
            while P[-1] > depth[node]:
                P.pop()
        elif depth[node] == 0:
            S.append(node)
            P.append(len(S))
            depth[node] = len(S)
            stack.append(~node)
            stack += graph[node]
    return SCC[::-1]

class TwoSat:
    def __init__(self, n):
        self.n = n
        self.graph = [[] for _ in
            range(2 * n)]
    def negate(self, x):
        return x+self.n if x<self.n
            else x-self.n
    def _imply(self, x, y):
        # agar x hoga , toh y hoga
        self.graph[x].append(y)
        self.graph[self.negate(y)].
            append(self.negate(x))
    def either(self, x, y):
        # koi ek true ho sakta hain ya
            dono bhi
        self._imply(self.negate(x),y)
        self._imply(self.negate(y),x)
```

```
    def set(self, x):
        self._imply(self.negate(x),x)
    def solve(self):
        SCC = find_SCC(self.graph)
        order = [0] * (2 * self.n)
        for i, comp in enumerate(SCC):
            for x in comp:
                order[x] = i
        for i in range(self.n):
            if order[i] == order[self.
                negate(i)]:
                return False, None
        return True, [+(order[i] >
            order[self.negate(i)]) for i
             in range(self.n)]
```

Bridges and Aritculation Points

```
    def find_bridges(adj):
    # returns all bridges
    bridges = []
    n = len(adj)
    timer = 0
    visited = [False]*n
    tin = [-1]*n
    low = [-1]*n
    for start in range(n):
        if visited[start]:
            continue
        stack = [(start, -1, 0, False)
            ]
        visited[start] = True
        tin[start] = low[start] =
            timer
        timer += 1
        while stack:
            v, parent, idx, backtrack =
                stack.pop()
            if backtrack:
                to = adj[v][idx]
                low[v] = min(low[v], low
                    [to])
                if low[to] > tin[v]:
                    bridges.append((v,to)
                        )
                continue
            if idx < len(adj[v]):
                to = adj[v][idx]
                stack.append((v, parent,
                    idx + 1, False))
                if to == parent:
                    continue
                if visited[to]:
                    low[v] = min(low[v],
                        tin[to])
                else:
                    visited[to] = True
                    tin[to] = low[to] =
                        timer
                    timer += 1
                    stack.append((v,
                        parent, idx, True))
                    stack.append((to, v,
                        0, False))
    return bridges
def bridges_on_path(adj):
    # returns all bridges on path
        from 1 to n
    n = len(adj)
    timer = 0
    visited = [False]*n
    tin = [-1]*n
    low = [-1]*n
    bridges = []
    for start in range(n):
        if visited[start]:
            continue
        stack = [(start, -1, 0, False)
            ]
        visited[start] = True
        tin[start] = low[start] =
            timer
        timer += 1
        while stack:
            v, parent, idx, backtrack =
                stack.pop()
            if backtrack:
                to = adj[v][idx]
                low[v] = min(low[v], low
                    [to])
                if low[to] > tin[v]:
                    bridges.append((v, to
                        ))
                continue
            if idx < len(adj[v]):
                to = adj[v][idx]
                stack.append((v, parent,
                    idx+1, False))
                if to == parent:
                    continue
                if visited[to]:
                    low[v] = min(low[v],
                        tin[to])
                else:
                    visited[to] = True
                    tin[to] = low[to] =
                        timer
                    timer += 1
                    stack.append((v,
                        parent, idx, True))
                    stack.append((to, v,
                        0, False))
    comp_id = [-1]*n
    comp = 0
    bridge_set = set(bridges)
    for i in range(n):
        if comp_id[i] != -1:
            continue
        stack = [i]
        comp_id[i] = comp
        while stack:
            v = stack.pop()
            for to in adj[v]:
                if comp_id[to] == -1 and
                    (v, to) not in
                    bridge_set and (to, v)
                     not in bridge_set:
                    comp_id[to] = comp
                    stack.append(to)
        comp += 1

    tree = [[] for _ in range(comp)]
    for u, v in bridges:
        cu, cv = comp_id[u], comp_id[v
            ]
        tree[cu].append((cv, (u, v)))
        tree[cv].append((cu, (u, v)))

    c1, cN = comp_id[0], comp_id[n-1]
    if c1 == cN:
        return []
    parent = {c1: None}
    edge_used = {c1: None}
    stack = [c1]
    while stack:
        u = stack.pop()
        for v, e in tree[u]:
            if v not in parent:
                parent[v] = u
                edge_used[v] = e
                stack.append(v)
    path_bridges = []
    cur = cN
    while cur != c1:
        path_bridges.append(edge_used[
            cur])
        cur = parent[cur]
    return [(u,v) for u, v in
        path_bridges]
def lowlink(edge):
    n = len(edge)
    parent = [-1] * n
    visited = [False] * n
```

```
    for s in range(n):
        if not visited[s]:
            que = [s]
            while que:
                now = que.pop()
                if visited[now]:
                    continue
                visited[now] = True
                for nxt in edge[now]:
                    if not visited[nxt]:
                        parent[nxt] = now
                        que.append(nxt)
    order = [-1] * n
    low = [-1] * n
    is_articulation = [False] * n
    articulation = []
    bridge = []
    def dfs(s):
        idx = 0
        cnt = 0
        que = [~s,s]
        while que:
            now = que.pop()
            if now >= 0:
                order[now] = low[now] =
                    idx
                idx += 1
                for nxt in edge[now]:
                    if parent[nxt] == now
                        :
                        que.append(~nxt)
                        que.append(nxt)
                    elif parent[now] !=
                        nxt and order[nxt]
                        != -1:
                        low[now] = min(low
                            [now], order[nxt
                            ])
            else:
                now = ~now
                par = parent[now]
                if par == s: cnt += 1
                if now == s:
                    is_articulation[now]
                        |= (cnt >= 2)
                    if is_articulation[
                        now]:
                        articulation.
                            append(now)
                    return
                if is_articulation[now]:
                    articulation.append(
                        now)
                if now != parent[par]:
                    low[par] = min(low[
                        par], low[now])
                    is_articulation[par] |=
                        (par != s) and (order[
                        par] <= low[now])
                if order[par] < low[now
                    ]:
                    bridge.append((par,
                        now))
        for i in range(n):
            if parent[i] == -1:
                dfs(i)
        return articulation, bridge

    def find_2ecc(edges,d):
        # returns a new graph, in which
            two nodes are connected
        # if and only if they are part of
            same cycle.
        _,bridges = lowlink(d)
        newd = [[] for i in range(len(d))
            ]
        bridges = set((w(i[0]),w(i[1]))
            for i in bridges)
        for u,v in edges:
            if (w(u),w(v)) not in bridges
                and (w(v),w(u)) not in
                bridges:
                newd[u].append(v)
                newd[v].append(u)
        return newd
```

Strings

String Hashing

```
HMOD = 2147483647
HBASE1 = random.randrange(HMOD)
HBASE2 = random.randrange(HMOD)
class Hashing:
    def __init__(self, s, mod=HMOD,
        base1=HBASE1, base2=HBASE2):
        self.mod, self.base1, self.
            base2 = mod, base1, base2
        self._len = _len = len(s)
        f_hash, f_pow = [0] * (_len +
            1), [1] * (_len + 1)
        for i in range(_len):
            f_hash[i + 1] = (base1 *
                f_hash[i] + s[i]) % mod
            f_pow[i + 1] = base1 *
                f_pow[i] % mod
        self.f_hash, self.f_pow =
            f_hash, f_pow
    def hashed(self, start, stop):
        return (self.f_hash[stop] -
            self.f_pow[stop - start] *
            self.f_hash[start]) % self.
            mod
```

String Functions

```
def LCPArray(L,SA=None):
    # Longest Common prefix in
        between S[i:] and S[i+1:]
    if not SA:
        SA = SuffArr(L)
    n = len(L)
    rank = [0] * n
    for i in range(n):
        rank[SA[i]] = i
    LCP = [0] * (n - 1)
    k = 0
    for i in range(n):
        l = rank[i]
        if l==n-1:
            k = 0
            continue
        j = SA[l+1]
        while i+k<n and L[i+k] == L[j+
            k]:
            k += 1
        LCP[l] = k
        k -= k > 0
    return LCP

def z_function(S):
    # return: the Z array, where Z[i]
        = length of the longest common
        prefix of S[i:] and S
    n = len(S)
    Z = [0] * n
    l = r = 0
    for i in range(1, n):
        z = Z[i - l]
        if i + z >= r:
            z = max(r - i, 0)
            while i + z < n and S[z] ==
                S[i + z]:
                z += 1
            l, r = i, i + z
        Z[i] = z
    Z[0] = n
    return Z

def manacher(s):
    # returns longest palindrome in s
    t = '#' + '#'.join(s) + '#'
    n = len(t)
    L = [0] * n
    c = r = 0
```

```
    ml = 0
    mc = 0
    for i in range(n):
        mirror = 2*c-i
        if i<r:
            L[i] = min(r-i,L[mirror])
        a = i+L[i]+1
        b = i-L[i]-1
        while a<n and b>=0 and t[a]==t
            [b]:
            L[i] += 1
            a += 1
            b -= 1
        if i+L[i]>r:
            c = i
            r = i+L[i]
        if L[i]>ml:
            ml = L[i]
            mc = i
    start = (mc-ml)//2
    return s[start:start+ml]
def SuffArray(s):
    # Starting position of ith suffix
    # in lexographic order
    s += "$"
    n = len(s)
    k = 0
    rank = [ord(c) for c in s]
    tmp = [0] * n
    sa = list(range(n))
    def sort_key(i):
        return (rank[i], rank[i + (1
            << k)] if i + (1 << k) < n
            else -1)
    while True:
        sa.sort(key=sort_key)
        tmp[sa[0]] = 0
        for i in range(1, n):
            tmp[sa[i]] = tmp[sa[i-1]] +
                (sort_key(sa[i-1]) !=
                sort_key(sa[i]))
        rank, tmp = tmp, rank
        k += 1
        if (1 << k) >= n:
            break
    return sa
```

FFT

FFT

```
class FastFFT:
    # This is a bit faster, one log n
        factor is less but it's
        accuracy is not 100%
    # use this when coeffecient does
        not matter(set coeffecient to 1
         repeatedly)
    # or you could just risk it :)
    def __init__(self, MOD=998244353)
        :
        FastFFT.MOD = MOD
        # g = self.
            primitive_root_constexpr()
        g = 3
        ig = pow(g, FastFFT.MOD - 2,
            FastFFT.MOD)
        FastFFT.W = [pow(g, (FastFFT.
            MOD - 1) >> i, FastFFT.MOD)
            for i in range(30)]
        FastFFT.iW = [pow(ig, (FastFFT
            .MOD - 1) >> i, FastFFT.MOD)
             for i in range(30)]
    def primitive_root_constexpr(self
        ):
        if FastFFT.MOD == 998244353:
            return 3
        elif FastFFT.MOD == 200003:
            return 2
        elif FastFFT.MOD == 167772161:
            return 3
        elif FastFFT.MOD == 469762049:
            return 3
        elif FastFFT.MOD == 754974721:
            return 11
        divs = [0] * 20
        divs[0] = 2
        cnt = 1
        x = (FastFFT.MOD - 1) // 2
        while x % 2 == 0:
            x //= 2
        i = 3
        while i * i <= x:
            if x % i == 0:
                divs[cnt] = i
                cnt += 1
                while x % i == 0:
                    x //= i
            i += 2
        if x > 1:
            divs[cnt] = x
            cnt += 1
        g = 2
        while 1:
            ok = True
            for i in range(cnt):
                if pow(g, (FastFFT.MOD -
                    1) // divs[i],
                    FastFFT.MOD) == 1:
                    ok = False
                    break
            if ok:
                return g
            g += 1
    def fft(self, k, f):
        for l in range(k, 0, -1):
            d = 1 << l - 1
            U = [1]
            for i in range(d):
                U.append(U[-1] * FastFFT
                    .W[l] % FastFFT.MOD)
            for i in range(1 << k - l):
                for j in range(d):
                    s = i * 2 * d + j
                    f[s], f[s + d] = (f[s
                        ] + f[s + d]) %
                        FastFFT.MOD, U[j] *
                         (f[s] - f[s + d])
                        % FastFFT.MOD
    def ifft(self, k, f):
        for l in range(1, k + 1):
            d = 1 << l - 1
            for i in range(1 << k - l):
                u = 1
                for j in range(i * 2 * d
                    , (i * 2 + 1) * d):
                    f[j+d] *= u
                    f[j], f[j + d] = (f[j
                        ] + f[j + d]) %
                        FastFFT.MOD, (f[j]
                        - f[j + d]) %
                        FastFFT.MOD
                u = u * FastFFT.iW[l]
                    % FastFFT.MOD
    def convolve(self, A, B):
        n0 = len(A) + len(B) - 1
        k = (n0).bit_length()
        n = 1 << k
        A += [0] * (n - len(A))
        B += [0] * (n - len(B))
        self.fft(k, A)
        self.fft(k, B)
        A = [a * b % FastFFT.MOD for a
            , b in zip(A, B)]
        self.ifft(k, A)
        inv = pow(n, FastFFT.MOD - 2,
            FastFFT.MOD)
        del A[n0:]
        for i in range(n0):
            A[i] = (A[i]*inv)%FastFFT.
                MOD
        return A
class FFT:
```

```
    def __init__(self, MOD=998244353,
        MOD1=469762049):
        FFT.MOD = MOD
        FFT.MOD1 = MOD1
        FFT.MOD2 = pow(MOD,MOD1-2,MOD1
            )
        FFT.mod_inv = (self.XT_GCD(MOD
            ,MOD1)[1])%MOD1
        # g = self.
            primitive_root_constexpr()
        g = 3
        ig = pow(g, FFT.MOD - 2, FFT.
            MOD)
        ig1 = pow(g, FFT.MOD1 - 2, FFT
            .MOD1)
        FFT.W = [pow(g, (FFT.MOD - 1)
            >> i, FFT.MOD) for i in
            range(30)]
        FFT.W1 = [pow(g, (FFT.MOD1 -
            1) >> i, FFT.MOD1) for i in
            range(30)]
        FFT.iW = [pow(ig, (FFT.MOD -
            1) >> i, FFT.MOD) for i in
            range(30)]
        FFT.iW1 = [pow(ig1, (FFT.MOD1
            - 1) >> i, FFT.MOD1) for i
            in range(30)]
    def primitive_root_constexpr(self
        ):
        if FFT.MOD == 998244353:
            return 3
        elif FFT.MOD == 200003:
            return 2
        elif FFT.MOD == 167772161:
            return 3
        elif FFT.MOD == 469762049:
            return 3
        elif FFT.MOD == 754974721:
            return 11
        divs = [0] * 20
        divs[0] = 2
        cnt = 1
        x = (FFT.MOD - 1) // 2
        while x % 2 == 0:
            x //= 2
        i = 3
        while i * i <= x:
            if x % i == 0:
                divs[cnt] = i
                cnt += 1
                while x % i == 0:
                    x //= i
            i += 2
        if x > 1:
            divs[cnt] = x
            cnt += 1
        g = 2
        while 1:
            ok = True
            for i in range(cnt):
                if pow(g, (FFT.MOD - 1)
                    // divs[i], FFT.MOD)
                    == 1:
                    ok = False
                    break
            if ok:
                return g
            g += 1
    def fft(self, k, f,f1):
        for l in range(k, 0, -1):
            d = 1 << l - 1
            U = [(1,1)]
            for i in range(d):
                U.append((U[-1][0] * FFT
                    .W[l] % FFT.MOD,U
                    [-1][1] * FFT.W1[l] %
                    FFT.MOD1))
            for i in range(1 << k - l):
                for j in range(d):
                    s = i * 2 * d + j
                    f[s], f[s + d] = (f[s
                        ] + f[s + d]) % FFT
                        .MOD, U[j][0] * (f[
                        s] - f[s + d]) %
                        FFT.MOD
                    f1[s], f1[s + d] = (
                        f1[s] + f1[s + d])
                        % FFT.MOD1, U[j][1]
                         * (f1[s] - f1[s +
                        d]) % FFT.MOD1
    def ifft(self, k, f,f1):
        for l in range(1, k + 1):
            d = 1 << l - 1
            for i in range(1 << k - l):
                u = 1
                u1 = 1
                for j in range(i * 2 * d
                    , (i * 2 + 1) * d):
                    f[j+d] *= u
                    f[j], f[j + d] = (f[j
                        ] + f[j + d]) % FFT
                        .MOD, (f[j] - f[j +
                         d]) % FFT.MOD
                    u = u * FFT.iW[l] %
                        FFT.MOD
                    f1[j+d] *= u1
                    f1[j], f1[j + d] = (
                        f1[j] + f1[j + d])
                        % FFT.MOD1, (f1[j]
                        - f1[j + d]) % FFT.
                        MOD1
                    u1 = u1 * FFT.iW1[l]
                        % FFT.MOD1
    def XT_GCD(self,a,b):
        if b == 0:
            return a,1,0
        g,x1,y1 = self.XT_GCD(b,a%b)
        x = y1
        y = x1-(a//b)*y1
        return g,x,y
    def CRT(self,a, mod1, b, mod2):
        k = (a+(b-a)*self.mod_inv%mod2
            *mod1)%(mod1*mod2)
        return k
    def convolve(self, A, B):
        n0 = len(A) + len(B) - 1
        k = (n0).bit_length()
        n = 1 << k
        A += [0] * (n - len(A))
        B += [0] * (n - len(B))
        A1 = A[:]
        B1 = B[:]
        self.fft(k, A,A1)
        self.fft(k, B,B1)
        A = [a * b % FFT.MOD for a, b
            in zip(A, B)]
        A1 = [a * b % FFT.MOD1 for a,
            b in zip(A1, B1)]
        self.ifft(k, A,A1)
        inv = pow(n, FFT.MOD - 2, FFT.
            MOD)
        inv1 = pow(n, FFT.MOD1 - 2,
            FFT.MOD1)
        del A[n0:]
        for i in range(n0):
            A[i] = self.CRT(A[i]*inv,
                FFT.MOD,A1[i]*inv1,FFT.
                MOD1)
        return A
```

FWHT

```
def fwht(a, invert=False):
    # In-place Fast Walsh Hadamard
        Transform for XOR convolution.
    # invert: if True, computes
        inverse transform
    n = len(a);step = 1
    while step<n:
        for i in range(0,n,step*2):
            for j in range(step):
                a[i+j],a[i+j+step] = a[i
                    +j]+a[i+j+step],a[i+j
                    ]-a[i+j+step]
        step *= 2
    if invert:
```

```
        for i in range(n):
            a[i] //= n
def fwt_or(a, invert=False):
    n = len(a);step = 1
    while step<n:
        for i in range(0,n,step*2):
            for j in range(step):
                u = a[i+j]
                v = a[i+j+step]
                if not invert:
                    a[i+j+step] = u+v
                else:
                    a[i+j+step] = v-u
        step *= 2
def fwt_and(a, invert=False):
    n = len(a);step = 1
    while step<n:
        for i in range(0,n,step*2):
            for j in range(step):
                u = a[i+j]
                v = a[i+j+step]
                if not invert:
                    a[i+j] = u+v
                else:
                    a[i+j] = u-v
        step *= 2
def convolution(A, B, fwt=fwht):
    # Computes XOR convolution of
      arrays A and B using FWHT
    # res[i] = summation of A[j]*B[k]
      such that j xor k = i
    n = 1;x = max(len(A),len(B))
    while n<x:n <<= 1
    n <<= 1
    fa = A + [0] * (n - len(A))
    fb = B + [0] * (n - len(B))
    fwt(fa)
    fwt(fb)
    for i in range(n):
        fa[i] *= fb[i]
    fwt(fa, invert=True)
    return fa
```

Miscellaneous

Bootstrap

```
from types import GeneratorType
def bootstrap(f, stack=[]):
    def wrappedfunc(*args, **kwargs):
        if stack:
            return f(*args, **kwargs)
        to = f(*args, **kwargs)
        while True:
            if type(to) is
               GeneratorType:
                stack.append(to)
                to = next(to)
            else:
                stack.pop()
                if not stack:
                    break
                to = stack[-1].send(to)
        return to
    return wrappedfunc
```

MCMF

```
class MCMF:
    # better when the flow is not
      constant
    # O(FEV)
    def __init__(self, n):
        self.n = n
        self.g = [[] for _ in range(n)
          ]
    def add_edge(self, u, v, cap,
       cost):
        self.g[u].append([v, cap, cost
          , len(self.g[v]), cap])
        self.g[v].append([u, 0, -cost,
           len(self.g[u]) - 1, 0])
    def min_cost(self, s, t, maxf=
       float('inf')):
        n = self.n
        flow, cost = 0, 0
        pot = [0] * n
        while flow < maxf:
            dist = [float('inf')] * n
            parent = [(-1, -1)] * n
            dist[s] = 0
            pq = [(0, s)]
            while pq:
                d, u = heappop(pq)
                if d > dist[u]:
                    continue
                for i, (v, cap, w, rev,
                   _) in enumerate(self.g
                   [u]):
                    if cap > 0:
                        nd = d + w + pot[u
                          ] - pot[v]
                        if nd < dist[v]:
                            dist[v] = nd
                            parent[v] = (u,
                               i)
                            heappush(pq, (
                               nd, v))
            if dist[t] == float('inf'):
                break
            for i in range(n):
                if dist[i] < float('inf'
                   ):
                    pot[i] += dist[i]
            f = maxf - flow
            cur = t
            while cur != s:
                u, i = parent[cur]
                f = min(f, self.g[u][i
                   ][1])
                cur = u
            flow += f
            cost += f * pot[t]
            cur = t
            while cur != s:
                u, i = parent[cur]
                v, cap, w, rev, orig =
                   self.g[u][i]
                self.g[u][i][1] -= f
                self.g[cur][rev][1] += f
                cur = u
        return flow, cost
    def used_edges(self):
        res = []
        for u in range(self.n):
            for v, cap, cost, rev, orig
               in self.g[u]:
                if orig > 0 and cap ==
                   0:
                    res.append((u, v,
                       cost))
        return res
def hungarian(cost):
    # better when the flow is 1 for
      every edge
    # for i in range(n):print(i+1,
      match[i]+1)
    # this is the final edges taken
    # O(n3)
    n = len(cost)
    u = [0]*(n+1)
    v = [0]*(n+1)
    p = [0]*(n+1)
    way = [0]*(n+1)
    for i in range(1, n+1):
        p[0] = i
        j0 = 0
        minv = [float('inf')]*(n+1)
        used = [False]*(n+1)
        while True:
            used[j0] = True
            i0 = p[j0]
```

```
            delta = float('inf')
            j1 = 0
            for j in range(1, n+1):
                if not used[j]:
                    cur = cost[i0-1][j-1]
                        - u[i0] - v[j]
                    if cur < minv[j]:
                        minv[j] = cur
                        way[j] = j0
                    if minv[j] < delta:
                        delta = minv[j]
                        j1 = j
            for j in range(n+1):
                if used[j]:
                    u[p[j]] += delta
                    v[j] -= delta
                else:
                    minv[j] -= delta
            j0 = j1
            if p[j0] == 0:
                break
        while True:
            j1 = way[j0]
            p[j0] = p[j1]
            j0 = j1
            if j0 == 0:
                break
    match = [-1]*n
    for j in range(1, n+1):
        if p[j] != 0:
            match[p[j]-1] = j-1
    return -v[0], match
```

Treap

```
class Node:
    __slots__ = ("val", "priority", "
        left", "right", "size")
    def __init__(self, val):
        self.val = val
        self.priority = random.random
            ()
        self.left = None
        self.right = None
        self.size = 1
class Treap:
    def __init__(self, iterable=None)
        :
        self.root = None
        if iterable:
            for x in iterable:
                self.root = Treap._merge
                    (self.root, Node(x))
    @staticmethod
    def _size(node):
        return node.size if node else
            0
    @staticmethod
    def _update(node):
        if node:
            node.size = 1 + Treap._size
                (node.left) + Treap._size
                (node.right)
    @staticmethod
    def _merge(left, right):
        if not left or not right:
            return left or right

        if left.priority > right.
            priority:
            left.right = Treap._merge(
                left.right, right)
            Treap._update(left)
            return left
        else:
            right.left = Treap._merge(
                left, right.left)
            Treap._update(right)
            return right
    def _kth(node, k):
        if not node:
            return None

        left_size = Treap._size(node.
            left)

        if k < left_size:
            return Treap._kth(node.left
                , k)
        elif k == left_size:
            return node.val
        else:
            return Treap._kth(node.
                right, k - left_size - 1)
    def kth(self, k):
        if k < 0 or k >= Treap._size(
            self.root):
            return None
        return Treap._kth(self.root, k
            )
    @staticmethod
    def merge(t1, t2):
        t = Treap()
        t.root = Treap._merge(t1.root,
            t2.root)
        return t
    @staticmethod
    def _split(node, k):
        if not node:
            return (None, None)
        left_size = Treap._size(node.
            left)
        if k <= left_size:
            left, node.left = Treap.
                _split(node.left, k)
            Treap._update(node)
            return (left, node)
        else:
            node.right, right = Treap.
                _split(node.right, k -
                left_size - 1)
            Treap._update(node)
            return (node, right)
    def insert(self, pos, val):
        new_node = Node(val)
        left, right = Treap._split(
            self.root, pos)
        merged = Treap._merge(left,
            new_node)
        self.root = Treap._merge(
            merged, right)
    def split(self, k):
        left_root, right_root = Treap.
            _split(self.root, k)
        t1 = Treap()
        t2 = Treap()
        t1.root = left_root
        t2.root = right_root
        return t1, t2
    def __iter__(self):
        stack = []
        node = self.root
        while stack or node:
            while node:
                stack.append(node)
                node = node.left

            node = stack.pop()
            yield node.val
            node = node.right
```

DP Optimizations

```
def Knuths(n,C = lambda x: x):
    # conditions
    # For all a<=b<=c<=d:
    # cost(a,c)+cost(b,d)<=cost(a,d)+
        cost(b,c)
    # opt[l][r-1] <= opt[l][r] <= opt
        [l+1][r]
    dp = [[0]*n for _ in range(n)]
    opt = [[0]*n for _ in range(n)]
    for i in range(n):
        dp[i][i] = 0
        opt[i][i] = i
```

```
    for i in range(n-2,-1,-1):
        for j in range(i+1,n):
            cost = C(i, j)
            mini = float('inf')
            L = opt[i][j-1]
            R = min(j-1, opt[i+1][j])
            for k in range(L, R+1):
                val = dp[i][k] + dp[k
                    +1][j] + cost
                if val<=mini:
                    mini = val
                    opt[i][j] = k
            dp[i][j] = mini
    return dp[0][n-1]

def DnC(prev, dp, cost):
    # conditions
    # opt[i][j] <= opt[i][j+1]

    # for i in range(1, K + 1):
    # DnC(dp_prev, dp_cur, cost, n)
    # dp_prev, dp_cur = dp_cur,
      dp_prev
    def solve(l, r, opt_l, opt_r):
        if l > r:
            return

        mid = (l + r) // 2
        best_k = -1
        best_val = float('inf')
        end = max(0,min(mid - 1, opt_r
            ))
        for k in range(opt_l, end + 1)
            :
            val = prev[k] + cost(k, mid
                )
            if val < best_val:
                best_val = val
                best_k = k
        dp[mid] = best_val
        solve(l, mid - 1, opt_l,
            best_k)
        solve(mid + 1, r, best_k,
            opt_r)
    solve(0,len(dp)-1,0,len(dp)-1)
```

Maximal Bipartite Matching

```
def kuhn(d,n,m):
    # n -> left side
    # m -> right side
    # d[left side] -> [right side]
    # Maximal Bipartite matching
    # O(E V)
    match_r = [-1]*m
    match_l = [-1]*n
    for start in range(n):
        if match_l[start]!=-1:
            continue
        stack = [start]
        parent_l = [-1]*n
        parent_r = [-1]*m
        vis_r = [False]*m
        found_v = -1
        while stack:
            u = stack.pop()
            for v in d[u]:
                if vis_r[v]:
                    continue
                vis_r[v] = True
                parent_r[v] = u

                if match_r[v]==-1:
                    found_v = v
                    stack = []
                    break
                else:
                    next_u = match_r[v]
                    if parent_l[next_u
                        ]==-1:
                        parent_l[next_u] =
                            v
                        stack.append(
                            next_u)
        if found_v==-1:
            continue
        v = found_v
        while v!=-1:
            u = parent_r[v]
            next_v = match_l[u]
            match_l[u] = v
            match_r[v] = u
            v = next_v
    result = []
    for u in range(n):
        if match_l[u]!=-1:
            result.append((u, match_l[u
                ]))
    return result

class HopcroftKarp:
    # n_left on left side and n_right
      on right side
    # O(E root(V))
    def __init__(self, n_left,
        n_right):
        self.n_left = n_left
        self.n_right = n_right
        self.g = [[] for _ in range(
            n_left)]
        self.matchL = [-1] * n_left
        self.matchR = [-1] * n_right
        self.dist = [-1] * n_left
    def add(self, u, v):
        self.g[u].append(v)
    def bfs(self):
        q = deque()
        for u in range(self.n_left):
            if self.matchL[u] == -1:
                self.dist[u] = 0
                q.append(u)
            else:
                self.dist[u] = -1
        while q:
            u = q.popleft()
            for v in self.g[u]:
                if self.matchR[v] != -1
                    and self.dist[self.
                    matchR[v]] == -1:
                    self.dist[self.matchR
                        [v]] = self.dist[u]
                        + 1
                    q.append(self.matchR[
                        v])
    def dfs(self, u):
        for v in self.g[u]:
            if self.matchR[v] == -1 or
                (self.dist[self.matchR[v
                ]] == self.dist[u] + 1
                and self.dfs(self.matchR[
                v])):
                self.matchL[u] = v
                self.matchR[v] = u
                return True
        return False
    def max_matching(self,flag=True):
        flow = 0
        if flag:
            for adj in self.g:
                random.shuffle(adj)
        while True:
            self.bfs()
            aug = 0
            for u in range(self.n_left)
                :
                if self.matchL[u] == -1:
                    if self.dfs(u):
                        aug += 1
            if aug == 0:
                break
            flow += aug
        return flow
    def get_edges(self):
        return [(u, self.matchL[u])
            for u in range(self.n_left)
            if self.matchL[u] != -1]
```

```
    def vertex_cover(self):
        visL = [False]*self.n_left
        visR = [False]*self.n_right
        q = deque()
        for u in range(self.n_left):
            if self.matchL[u]==-1:
                q.append(u)
                visL[u] = True
        while q:
            u = q.popleft()
            for v in self.g[u]:
                if not visR[v] and self.
                    matchL[u]!=v:
                    visR[v] = True
                    if self.matchR[v]!=-1
                        and not visL[self.
                        matchR[v]]:
                        visL[self.matchR[v
                            ]] = True
                        q.append(self.
                            matchR[v])
        coverL = [u for u in range(
            self.n_left) if not visL[u]]
        coverR = [v for v in range(
            self.n_right) if visR[v]]
        return coverL,coverR
```

Graph Max Flow

```
class HLPP:
    # O(VE), still sometime
        unexpectedly faster than Dinic
    def __init__(self,n):
        self.n=n
        self.g=[[] for _ in range(n)]
    def add_edge(self,u,v,c):
        self.g[u].append([v,c,len(self
            .g[v])])
        self.g[v].append([u,0,len(self
            .g[u])-1])
    def maxflow(self,s,t):
        n,g=self.n,self.g
        h=[0]*n; ex=[0]*n
        seen=[0]*n
        h[s]=n
        for v,c,rev in g[s]:
            if c:
                g[v][rev][1]+=c
                ex[v]+=c
        q=deque([i for i in range(n)
            if i!=s and i!=t and ex[i
            ]>0])
        def push(u,e):
            v,c,rev=e
            d=min(ex[u],c)
            if h[u]==h[v]+1 and d>0:
                e[1]-=d; g[v][rev][1]+=d
                ex[u]-=d; ex[v]+=d
                if ex[v]==d and v!=s and
                    v!=t:
                    q.append(v)
                return True
            return False
        def relabel(u):
            h[u]=min(h[v]+1 for v,c,_
                in g[u] if c>0)
        while q:
            u=q[0]
            while ex[u]:
                if seen[u]<len(g[u]):
                    if not push(u,g[u][
                        seen[u]]):
                        seen[u]+=1
                else:
                    relabel(u)
                    seen[u]=0
            q.popleft()
        return ex[t]

class Dinic:
    # O(VE)
    # Unit capacities/bipartite/DAG:
        ~O(EV)
    def __init__(self, n):
        self.lvl = [0] * n
        self.ptr = [0] * n
        self.q = [0] * n
        self.adj = [[] for _ in range(
            n)]
    def add_edge(self, a, b, c, rcap
        =0):
        self.adj[a].append([b, len(
            self.adj[b]), c, 0])
        self.adj[b].append([a, len(
            self.adj[a]) - 1, rcap, 0])
    def dfs(self, v, t, f):
        if v == t or not f:
            return f
        for i in range(self.ptr[v],
            len(self.adj[v])):
            e = self.adj[v][i]
            if self.lvl[e[0]] == self.
                lvl[v] + 1:
                p = self.dfs(e[0], t,
                    min(f, e[2] - e[3]))
                if p:
                    self.adj[v][i][3] +=
                        p
                    self.adj[e[0]][e
                        [1]][3] -= p
                    return p
            self.ptr[v] += 1
        return 0
    def calc(self, s, t):
        INF = float('inf')
        flow, self.q[0] = 0, s
        for l in range(31): # l = 30
            maybe faster for random data
            while True:
                self.lvl, self.ptr = [0]
                    * len(self.q), [0] *
                    len(self.q)
                qi, qe, self.lvl[s] = 0,
                    1, 1
                while qi < qe and not
                    self.lvl[t]:
                    v = self.q[qi]
                    qi += 1
                    for e in self.adj[v]:
                        if not self.lvl[e
                            [0]] and (e[2] -
                            e[3]) >> (30 -
                            l):
                            self.q[qe] = e
                                [0]
                            qe += 1
                            self.lvl[e[0]]
                                = self.lvl[v]
                                + 1
                p = self.dfs(s, t, INF)
                while p:
                    flow += p
                    p = self.dfs(s, t,
                        INF)
                if not self.lvl[t]:
                    break
        return flow
    def get_paths(self,s,t):
        # returns that paths taken for
            the maxflow
        paths=[]
        while True:
            stack=[(s,[],float('inf'),
                set([s]))]
            found=False
            while stack:
                v,path,f,vis=stack.pop()
                if v==t:
                    pushed=f
                    res_path=path
                    found=True
                    break
                for i,e in enumerate(
                    self.adj[v]):
                    to,rev,cap,flow=e
                    if flow>0 and to not
                        in vis:
```

```
                    stack.append((to,
                       path+[(v,to)],
                       min(f,flow),vis
                       |{to}))
            if not found:
               break
            f=pushed
            for u,w in res_path:
               for e in self.adj[u]:
                  if e[0]==w and e
                     [3]>0:
                     e[3]-=f
                     self.adj[w][e
                        [1]][3]+=f
                     break
            paths.append((pushed,
               res_path))
      return paths
```

Link Cut Tree

```
class LinkCutTree:
   class Node:
      __slots__=('l','r','p','rev','
         val','sm')
      def __init__(self,val=0):
         self.l=-1
         self.r=-1
         self.p=-1
         self.rev=False
         self.val=val
         self.sm=val
   def __init__(self,n):
      self.n=n
      self.t=[self.Node() for _ in
         range(n)]
   def _is_root(self,x):
      p=self.t[x].p
      return p==-1 or (self.t[p].l!=
         x and self.t[p].r!=x)
   def _push(self,x):
      if x==-1:
         return
      t=self.t[x]
      if t.rev:
         t.l,t.r=t.r,t.l
         if t.l!=-1:
            self.t[t.l].rev^=1
         if t.r!=-1:
            self.t[t.r].rev^=1
         t.rev=False
   def _pull(self,x):
      t=self.t[x]
      t.sm=t.val
      if t.l!=-1:
         t.sm+=self.t[t.l].sm
      if t.r!=-1:
         t.sm+=self.t[t.r].sm
   def _rotate(self,x):
      p=self.t[x].p
      g=self.t[p].p
      if self.t[p].l==x:
         b=self.t[x].r
         self.t[x].r=p
         self.t[p].l=b
         if b!=-1:
            self.t[b].p=p
      else:
         b=self.t[x].l
         self.t[x].l=p
         self.t[p].r=b
         if b!=-1:
            self.t[b].p=p
      self.t[p].p=x
      self.t[x].p=g
      if g!=-1:
         if self.t[g].l==p:
            self.t[g].l=x
         elif self.t[g].r==p:
            self.t[g].r=x
      self._pull(p)
      self._pull(x)
   def _splay(self,x):
      stk=[]
      y=x
      while True:
         stk.append(y)
         if self._is_root(y):
            break
         y=self.t[y].p
      while stk:
         self._push(stk.pop())
      while not self._is_root(x):
         p=self.t[x].p
         g=self.t[p].p
         if not self._is_root(p):
            if (self.t[g].l==p)==(
               self.t[p].l==x):
               self._rotate(p)
            else:
               self._rotate(x)
         self._rotate(x)
   def _access(self,x):
      last=-1
      while x!=-1:
         self._splay(x)
         self.t[x].r=last
         self._pull(x)
         last=x
         x=self.t[x].p
   def makeroot(self,x):
      self._access(x)
      self._splay(x)
      self.t[x].rev^=1
   def findroot(self,x):
      self._access(x)
      self._splay(x)
      while True:
         self._push(x)
         if self.t[x].l==-1:
            break
         x=self.t[x].l
      self._splay(x)
      return x
   def connected(self,u,v):
      return self.findroot(u)==self.
         findroot(v)
   def link(self,u,v):
      self.makeroot(u)
      if self.findroot(v)==u:
         return False
      self.t[u].p=v
      return True
   def cut(self,u,v):
      self.makeroot(u)
      self._access(v)
      self._splay(v)
      if self.t[v].l!=u or self.t[u
         ].r!=-1:
         return False
      self.t[u].p=-1
      self.t[v].l=-1
      self._pull(v)
      return True
   def set_value(self,u,val):
      self._access(u)
      self._splay(u)
      self.t[u].val=val
      self._pull(u)
   def path_sum(self,u,v):
      self.makeroot(u)
      self._access(v)
      self._splay(v)
      return self.t[v].sm
```

Centroid Decomposition

```
def shallowest_decomposition_tree(
   graph, root=0):
   # returns a root and a directed
      tree, iterate on it and you
   # will find the new centroid
   # slightly faster than
      centroid_decomposition_tree
```

```
ctz = lambda x:(x & -x).
   bit_length()-1
n = len(graph)
forbidden = [0] * n
decomposition_tree = [[] for _ in
    range(n)]
stacks = [[] for _ in range(n.
   bit_length())]
def extract_chain(labels, u):
   while labels:
      label = labels.bit_length()
          - 1
      labels ^= 2**label
      v = stacks[label].pop()
      decomposition_tree[u].
         append(v)
      u = v
dfs = [root]
while dfs:
   u = dfs.pop()
   if u >= 0:
      forbidden[u] = -1
      dfs.append(~u)
      for v in graph[u]:
         if not forbidden[v]:
            dfs.append(v)
   else:
      u = ~u
      forbidden_once =
         forbidden_twice = 0
      for v in graph[u]:
         forbidden_twice |=
            forbidden_once & (
            forbidden[v] + 1)
         forbidden_once |=
            forbidden[v] + 1
      forbidden[u] =
         forbidden_once | (2**
         forbidden_twice.
         bit_length() - 1)
      label_u = ctz(forbidden[u]
         + 1)
      stacks[label_u].append(u)
      for v in graph[u]:
         extract_chain((forbidden
            [v] + 1) & (2**label_u
             - 1), u)
max_label = (forbidden[root] + 1)
   .bit_length() - 1
decomposition_root = stacks[
   max_label].pop()
extract_chain((forbidden[root] +
   1) & (2**max_label - 1),
   decomposition_root)
return decomposition_tree,
   decomposition_root

def centroid_decomposition_tree(
   graph):
   # returns a root and a directed
      tree, iterate on it and you
   # will find the new centroid
   n = len(graph)
   graph = [c[:] for c in graph]
   bfs = [0]
   for node in bfs:
      bfs += graph[node]
      for nei in graph[node]:
         graph[nei].remove(node)
   size = [0] * n
   for node in reversed(bfs):
      size[node] = 1 + sum(size[
         child] for child in graph[
         node])
   decomposition_tree = [[] for _ in
       range(n)]
   def centroid_reroot(u):
      N = size[u]
      while True:
         for v in graph[u]:
            if size[v] > N // 2:
               size[u] = N - size[v]
               graph[u].remove(v)
               graph[v].append(u)
               u = v
               break
         else:
            decomposition_tree[u] =
               [centroid_reroot(v)
               for v in graph[u]]
            return u
   decomposition_root =
      centroid_reroot(0)
   return decomposition_tree,
      decomposition_root
```

Lazy Segment Tree

```
class SegmentTree:
   def __init__(self, data, default
      =0, mode='s',func=lambda x,y:x+
      y):
      self.func = func
      self.mode = mode
      self._default = default
      self.n = len(data)
      self.size = 1 << (self.n - 1).
         bit_length()
      self.tree = [default] * (2 *
         self.size)
      self._size = [0] * (2 * self.
         size)
      self._size[self.size:] = [1] *
          self.size
      for i in range(self.size - 1,
         0, -1):
         self._size[i] = self._size[
            i << 1] + self._size[i <<
             1 | 1]
      self.lazy_add = 0
      self.lazy_set = None
      self.lazy_add = [0] * self.
         size
      self.lazy_set = [None] * self.
         size
      for i in range(self.n):
         self.tree[self.size + i] =
            data[i]
      for i in range(self.size - 1,
         0, -1):
         self.tree[i] = self.func(
            self.tree[i << 1], self.
            tree[i << 1 | 1])
   def _apply_set(self, pos, value):
      if self.mode == 's':
         self.tree[pos] = value *
            self._size[pos]
      else:
         self.tree[pos] = value
      if pos < self.size:
         self.lazy_set[pos] = value
         self.lazy_add[pos] = 0
   def _apply_add(self, pos, value):
      if self.mode == 's':
         self.tree[pos] += value *
            self._size[pos]
      else:
         self.tree[pos] += value
      if pos < self.size:
         if self.lazy_set[pos] is
            not None:
            self.lazy_set[pos] +=
               value
         else:
            self.lazy_add[pos] +=
               value
   def _build(self, pos):
      while pos > 1:
         pos >>= 1
         self.tree[pos] = self.func(
            self.tree[pos << 1], self
            .tree[pos << 1 | 1])
```

```
        if self.lazy_set[pos] is
           not None:
            if self.mode == 's':
                self.tree[pos] = self
                   .lazy_set[pos] *
                   self._size[pos]
            else:
                self.tree[pos] = self
                   .lazy_set[pos]
        if self.lazy_add[pos] != 0:
            if self.mode == 's':
                self.tree[pos] +=
                   self.lazy_add[pos]
                   * self._size[pos]
            else:
                self.tree[pos] +=
                   self.lazy_add[pos]
    def _push(self, pos):
        for shift in range(self.size.
           bit_length() - 1, 0, -1):
            i = pos >> shift
            set_val = self.lazy_set[i]
            if set_val is not None:
                self._apply_set(i << 1,
                   set_val)
                self._apply_set(i << 1 |
                    1, set_val)
                self.lazy_set[i] = None
            add_val = self.lazy_add[i]
            if add_val != 0:
                self._apply_add(i << 1,
                   add_val)
                self._apply_add(i << 1 |
                    1, add_val)
                self.lazy_add[i] = 0
    def range_update(self, left,
       right, value,flag=True):
        # Range Update in [L,R] if
           flag, then add
        if flag:
            l = left + self.size
            r = right + self.size
            l0, r0 = l, r
            self._push(l0)
            self._push(r0)
            while l <= r:
                if l & 1: self.
                   _apply_add(l, value);
                   l += 1
                if not r & 1: self.
                   _apply_add(r, value);
                   r -= 1
                l >>= 1; r >>= 1
            self._build(l0)
            self._build(r0)
        else:
            l = left + self.size
            r = right + self.size
            l0, r0 = l, r
            self._push(l0)
            self._push(r0)
            while l <= r:
                if l & 1: self.
                   _apply_set(l, value);
                   l += 1
                if not r & 1: self.
                   _apply_set(r, value);
                   r -= 1
                l >>= 1; r >>= 1
            self._build(l0)
            self._build(r0)
    def range_query(self, left, right
       ):
        # Range Query in [L,R]
        l = left + self.size
        r = right + self.size
        self._push(l)
        self._push(r)
        res = self._default
        while l <= r:
            if l & 1: res = self.func(
               res, self.tree[l]); l +=
               1
            if not r & 1: res = self.
               func(res, self.tree[r]);
               r -= 1
            l >>= 1; r >>= 1
        return res
    def __repr__(self):
        return f"SegmentTree({[self.
           range_query(i,i) for i in
           range(self.n)]})"
```

Utils

```
getcontext().prec = 50;sys.
   setrecursionlimit(10**6)
sys.set_int_max_str_digits(10**5)
import builtins
globals()['print'] = lambda *args,
   **kwargs: builtins.print(*args,
   flush=True, **kwargs)
```

Definitions

Extended GCD Computes x, y s.t. $ax + by = \gcd(a, b)$.

CRT Finds smallest a satisfying $a \equiv b_i \pmod{m_i}$.

$\phi(n)$ Count of integers $< n$ coprime with n.

Suffix Array Starting indices of suffixes sorted lexicographically.

Euler Path Uses every edge exactly once.

Bridge Edge whose removal increases components.

Articulation Point Vertex whose removal increases components.

2ECC Maximal subgraph where every pair lies on a cycle.

C++ Notes

Use `get<i>(tuple)` for tuple access.
Custom sort: `[](auto& a,auto& b){return get<2>(a)<get<2>(b);}`
2D vector init: `vector<vector<int>> dp(n, vector<int>(m,0));`
Prefer `emplace_back` for complex objects.
Min-heap: `priority_queue<pi,vector<pi>,gre pq;`

CP - C++

```
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.
   hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
using namespace std;

#define int long long
#define INF LLONG_MAX
#define fastio ios::sync_with_stdio(
   false); cin.tie(0);
#define len(arr) arr.size()
#define f first
#define s second
#define pb push_back
using vi = vector<int>;
using vii = vector<vector<int>>;
using pi = pair<int,int>;
#pragma GCC optimize("O3,unroll-
   loops")
#pragma GCC target("avx2,bmi,bmi2,
   lzcnt,popcnt")

template <typename T>
using ordered_multiset = tree<
   std::pair<T, int>,
```

```
    null_type,
    std::less<std::pair<T, int>>,
    rb_tree_tag,
    tree_order_statistics_node_update
>;

int II(){int a;cin>>a;return a;}
string SI(){string s;cin>>s;return s
    ;}
vi LII(int n){vi a(n);cin>>a;return
    a;}

void solve() {

}

int32_t main() {
    fastio
    int t=1;
    cin >> t;
    while (t--) solve();
    return 0;
}
```

Sorted List - C++

```
template <typename T>
class SortedList {
    ordered_multiset<T> os;
    int uid = 0;
public:
    void insert(T x) {
        os.insert({x, uid++});
    }
    void erase_one(T x) {
        auto it = os.lower_bound({x,
            0});
        if (it != os.end() && it->
            first == x)
            os.erase(it);
    }
    int index(T x) {
        return os.order_of_key({x, 0})
            ;
    }
    int count(T x) {
        return os.order_of_key({x,
            INT_MAX}) - os.order_of_key
            ({x, 0});
    }
    T operator[](int k) {
        return os.find_by_order(k)->
            first;
    }
    int size() const {
        return os.size();
    }
    void print() {
        for (int i = 0; i < size(); i
            ++) std::cout << (*this)[i]
            << " ";
        std::cout << "\n";
    }
};
```

Lazy Segment Tree - C++

```
class SegmentTree {
public:
    int n;
    vector<int> tree;
    vector<int> lazy_add;
    vector<int> lazy_set;
    int NO_ASSIGNMENT = LLONG_MIN;
    SegmentTree(vector<int>& arr) {
        n = arr.size();
        tree.assign(4 * n, 0);
        lazy_add.assign(4 * n, 0);
        lazy_set.assign(4 * n,
            NO_ASSIGNMENT);
        build_tree(1, 0, n - 1, arr);
    }
    static int func(int a, int b) {
        return a + b;
    }
    void build_tree(int node, int
        start, int end, vector<int>&
        arr) {
        if (start == end) {
            tree[node] = arr[start];
        } else {
            int mid = start + (end -
                start) / 2;
            build_tree(2 * node, start,
                mid, arr);
            build_tree(2 * node + 1,
                mid + 1, end, arr);
            tree[node] = func(tree[2 *
                node], tree[2 * node +
                1]);
        }
    }
    void propagate_lazy(int node, int
        start, int end) {
        int current_range_size = (end
            - start + 1);
        if (lazy_set[node] !=
            NO_ASSIGNMENT) {
            tree[node] = lazy_set[node]
                * current_range_size;
            if (start != end) {
                lazy_set[2 * node] =
                    lazy_set[node];
                lazy_set[2 * node + 1] =
                    lazy_set[node];
                lazy_add[2 * node] = 0;
                lazy_add[2 * node + 1] =
                    0;
            }
            lazy_set[node] =
                NO_ASSIGNMENT;
        }
        if (lazy_add[node] != 0) {
            tree[node] += lazy_add[node
                ] * current_range_size;
            if (start != end) {
                lazy_add[2 * node] +=
                    lazy_add[node];
                lazy_add[2 * node + 1]
                    += lazy_add[node];
            }
            lazy_add[node] = 0;
        }
    }
    void update(int node, int start,
        int end, int l, int r, int
        value, bool is_add) {
        propagate_lazy(node, start,
            end);
        if (start > r || end < l) {
            return;
        }
        if (start >= l && end <= r) {
            if (is_add) {
                tree[node] += value * (
                    end - start + 1);
                if (start != end) {
                    lazy_add[2 * node] +=
                        value;
                    lazy_add[2 * node +
                        1] += value;
                }
            } else {
                tree[node] = value * (
                    end - start + 1);
                if (start != end) {
                    lazy_set[2 * node] =
                        value;
                    lazy_set[2 * node +
                        1] = value;
                    lazy_add[2 * node] =
                        0;
                    lazy_add[2 * node +
                        1] = 0;
                }
```

```
        }
        return;
      }
      int mid = start + (end - start
         ) / 2;
      update(2 * node, start, mid, l
         , r, value, is_add);
      update(2 * node + 1, mid + 1,
         end, l, r, value, is_add);
      tree[node] = func(tree[2 *
         node], tree[2 * node + 1]);
   }
   int query(int node, int start,
      int end, int l, int r) {
      propagate_lazy(node, start,
         end);
      if (start > r || end < l) {
         return 0;
      }
      if (start >= l && end <= r) {
         return tree[node];
      }
      int mid = start + (end - start
         ) / 2;
      return func(query(2 * node,
         start, mid, l, r), query(2 *
          node + 1, mid + 1, end, l,
         r));
   }
   void range_update(int l, int r,
      int value, bool is_add = true)
      {
      update(1, 0, n - 1, l, r,
         value, is_add);
   }
   int range_query(int l, int r) {
      return query(1, 0, n - 1, l, r
         );
   }
   vector<int> to_list() {
      vector<int> result(n);
      for (int i = 0; i < n; ++i) {
         result[i] = range_query(i,
            i);
      }
      return result;
   }
};
```

FFT - C++

```
class FFT {
public:
   static const int MOD = 998244353;
   static const int MOD1 =
      469762049;
   int MOD2, mod_inv;
   vector<int> W, W1, iW, iW1;
   FFT() {
      MOD2 = power(MOD, MOD1 - 2,
         MOD1);
      mod_inv = XT_GCD(MOD, MOD1).
         second % MOD1;
      int g = 3;
      int ig = power(g, MOD - 2, MOD
         );
      int ig1 = power(g, MOD1 - 2,
         MOD1);
      W.resize(30); W1.resize(30);
      iW.resize(30); iW1.resize
         (30);
      for (int i = 0; i < 30; ++i) {
         W[i] = power(g, (MOD - 1)
            >> i, MOD);
         W1[i] = power(g, (MOD1 - 1)
            >> i, MOD1);
         iW[i] = power(ig, (MOD - 1)
            >> i, MOD);
         iW1[i] = power(ig1, (MOD1 -
            1) >> i, MOD1);
      }
   }
   int power(int base, int exp, int
      mod) {
      int res = 1;
      while (exp) {
         if (exp % 2) res = res *
            base % mod;
         base = base * base % mod;
         exp /= 2;
      }
      return res;
   }
   pair<int, int> XT_GCD(int a, int
      b) {
      if (b == 0) return {a, 1};
      pair<int,int> k9 = XT_GCD(b, a
         % b);
      int g = k9.first;int x1 = k9.
         second;
      return {g, x1 - (a / b) * x1};
   }
   int CRT(int a, int mod1, int b,
      int mod2) {
      return (a + (b - a) * mod_inv
         % mod2 * mod1) % (mod1 *
         mod2);
   }
   void fft(int k, vector<int>& f,
      vector<int>& f1) {
      for (int l = k; l > 0; --l) {
         int d = 1 << (l - 1);
         vector<pair<int, int>> U =
            {{1, 1}};
         for (int i = 0; i < d; ++i)
            U.emplace_back(U.back().
               first * W[l] % MOD, U.
               back().second * W1[l]
               % MOD1);
         for (int i = 0; i < (1 << (
            k - l)); ++i) {
            for (int j = 0; j < d;
               ++j) {
               int s = i * 2 * d + j
                  ;
               int tmp_f = f[s] - f[
                  s + d];
               int tmp_f1 = f1[s] -
                  f1[s + d];
               f[s] = (f[s] + f[s +
                  d]) % MOD;
               f[s + d] = U[j].first
                  * tmp_f % MOD;
               f1[s] = (f1[s] + f1[s
                  + d]) % MOD1;
               f1[s + d] = U[j].
                  second * tmp_f1 %
                  MOD1;
            }
         }
      }
   }
   void ifft(int k, vector<int>& f,
      vector<int>& f1) {
      for (int l = 1; l <= k; ++l) {
         int d = 1 << (l - 1);
         for (int i = 0; i < (1 << (
            k - l)); ++i) {
            int u = 1, u1 = 1;
            for (int j = i * 2 * d;
               j < (i * 2 + 1) * d;
               ++j) {
               f[j + d] = f[j + d] *
                  u % MOD;
               f[j] = (f[j] + f[j +
                  d]) % MOD;
               f[j + d] = (f[j] - f[
                  j + d] + MOD) % MOD
                  ;
               u = u * iW[l] % MOD;
               f1[j + d] = f1[j + d]
                  * u1 % MOD1;
```

```
                f1[j] = (f1[j] + f1[j
                    + d]) % MOD1;
                f1[j + d] = (f1[j] -
                    f1[j + d] + MOD1) %
                    MOD1;
                u1 = u1 * iW1[l] %
                    MOD1;
            }
        }
    }
    vector<int> convolve(vector<int>
        A, vector<int> B) {
        int n0 = A.size() + B.size() -
            1;
        int k = 0;
        while ((1 << k) < n0) ++k;
        int n = 1 << k;
        A.resize(n, 0);
        B.resize(n, 0);
        vector<int> A1 = A, B1 = B;
        fft(k, A, A1);
        fft(k, B, B1);
        for (int i = 0; i < n; ++i) {
            A[i] = A[i] * B[i] % MOD;
            A1[i] = A1[i] * B1[i] %
                MOD1;
        }
        ifft(k, A, A1);
        int inv = power(n, MOD - 2,
            MOD);
        int inv1 = power(n, MOD1 - 2,
            MOD1);
        A.resize(n0);
        for (int i = 0; i < n0; ++i) {
            A[i] = CRT(A[i] * inv % MOD
                , MOD, A1[i] * inv1 %
                MOD1, MOD1);
        }
        return A;
    }
};
```

I/O - Shubham

```
#define all(a) (a).begin(),(a).end()
#define pb push_back
#define sz(a) ((int)(a).size())
#define mp make_pair
#define fi first
#define se second

typedef pair<int,int> pint;
typedef long long ll;
typedef unsigned long long ull;
typedef vector<int> vi;
sort(v.begin(), v.end());
v.resize(unique(v.begin(), v.end())
    - v.begin());
__builtin_popcount(unsigned int)->no
    of set bits
__builtin_ffs(int)->most right set
    bit(lsb)
memset(dp, -1, sizeof(dp));

    int n;
    cin >> n;
    int arr[n];
    for(int i=0;i<n;i++){
        cin >> arr[i];
    }

bitset<8> decimalBitset(15);
to_ullong()
to_string()
flip()
set()
reset()
count()
bitset<4> allSet("1111"), allUnset;

*min_element(a.begin(), a.end());

#define int long long
#define fr(i, a, b) for (int i = (a)
    ; i < (int)(b); i++)
is_sorted(A, A + range1)
count(arr, arr + n, 3);
int n = sizeof(arr) / sizeof(arr[0])
    ;


ios_base::sync_with_stdio(false);
cin.tie(NULL);

map<int, int>::iterator it = myMap.
    find(key);
int position = distance(myMap.begin
    (), it);

    int arr[n];
    map<int,int,greater<int>> m;
    for(int i=0;i<=30;i++) m[i]=0;
    for(int i=0;i<n;i++){
        cin >> arr[i];
        for(int j=0;j<31;j++){
            if((arr[i]>>j)&1!=0) m[j
                ]++;
            }
    }

int n = stoi(s);

template <class T1, class T2, class
    Pred = std::less<T2> >
struct sort_pair_second {
    bool operator()(const std::pair<
        T1,T2>&left, const std::pair<T1
        ,T2>&right) {
        Pred p;
        return p(left.second, right.
            second);
    }
};

std::sort(v.begin(), v.end(),
    sort_pair_second<int, int>());

std::sort(v.begin(), v.end(),
    sort_pair_second<int, int, std::
    greater<int> >());


int n,e;
cin >> n >> e;
while(e--){
    int x,y;
    cin >> x >> y;
    g[x].push_back(y);
    g[y].push_back(x);
}
```

DFS - Shubham

```
// for dfs
const int N=1e5+10;
vector<int> g[N];
bool check[N];
void dfs(int vertex){
    check[vertex]=true;
    for(auto child: g[vertex]){
        if(check[child]) continue;

        dfs(child);
    }
    return;
}
```

Maths - Shubham

```
vector<int> prime;
for(int i=2;i*i<=n;i++){
```

```
    while(n%i==0){
    prime.push_back(i);
    n/=i;
    }
}
if(n>1) prime.push_back(n);
int ans=LLONG_MAX;

vector<int> primenums(int n) {
vector<int> isprime(n + 1, 1);
isprime[0] = isprime[1] = 0;

for (int i = 2; i * i <= n; ++i) {
    if (isprime[i]) {
        for (int j = i * i; j <= n; j
            += i) {
            isprime[j] = 0;
        }
    }
}

vector<int> primes;
for (int i = 2; i <= n; ++i) {
    if (isprime[i]) {
        primes.push_back(i);
    }
}

return primes;
}

int n = 100;
vector<int> primes=primenums(n);

vector<int> getFactors(int n) {
    vector<int> factors;
    for(int i = 1; i <= sqrt(n); i++)
        {
        if(n % i == 0) {
            factors.push_back(i);
            if(i != n / i) {
                factors.push_back(n / i)
                    ;
            }
        }
    }
    sort(factors.begin(), factors.end
        ());
    return factors;
}
```

Strings - Shubham

```
vector<int> rabin_karp(string const&
    s, string const& t) {
    const int p = 31;
    const int m = 1e9 + 9;
    int S = s.size(), T = t.size();

    vector<long long> p_pow(max(S, T)
        );
    p_pow[0] = 1;
    for (int i = 1; i < (int)p_pow.
        size(); i++)
        p_pow[i] = (p_pow[i-1] * p) %
            m;

    vector<long long> h(T + 1, 0);
    for (int i = 0; i < T; i++)
        h[i+1] = (h[i] + (t[i] - 'a' +
            1) * p_pow[i]) % m;
    long long h_s = 0;
    for (int i = 0; i < S; i++)
        h_s = (h_s + (s[i] - 'a' + 1)
            * p_pow[i]) % m;

    vector<int> occurrences;
    for (int i = 0; i + S - 1 < T; i
        ++) {
        long long cur_h = (h[i+S] + m
            - h[i]) % m;
        if (cur_h == h_s * p_pow[i] %
            m)
            occurrences.push_back(i);
    }
    return occurrences;
}

class Solution {
public:
    int M=1e9+7;
    int strStr(string haystack,
        string needle) {
        int n=haystack.size();
        int m=needle.size();
        if(m>n) return -1;
        map<long long,int> mp;
        int pm=31;
        vector<long long> p_pow(n+1);
        p_pow[0]=1;
        for(int i=1;i<=n;i++){
            p_pow[i]=(p_pow[i-1]*pm)%M;
        }
        vector<long long> h(n+1,0);
        h[1]=(haystack[0]-'a'+1);
        for(int i=0;i<n;i++){
            h[i+1]=(h[i]+(haystack[i]-'
                a'+1)*p_pow[i])%M;
        }

        int hash=0;
        for(int i=0;i<m;i++){
            hash+=((needle[i]-'a'+1)*(
                p_pow[i]))%M;
            hash%=M;
        }

        for(int i=0;i<(n-m+1);i++){
            int curr=(h[i+m]-h[i]+M)%M;
            if(curr==(hash*p_pow[i])%M)
                return i;
        }
        return -1;
    }
};
```

Modular Exponentation - Shubham

```
int modularExponentiation(int base,
    int exp, int mod) {
    int result = 1;
    base = base % mod;
    while (exp > 0) {
        if (exp % 2 == 1) {
            result = (result * base) %
                mod;
        }
        exp = exp >> 1;
        base = (base * base) % mod;
    }
    return result;
}
```

Usage

```
- **Number Theory 1(numtheory)**:
    - **miller_isprime**: Calculates
      if a number is prime or not in
      7log2n, better for bigger
      numbers.
- **Number Theory 2(numrare)**:
    - **pollard_rho**: Returns a
      random factor of n.
    - **miller_pollard_rho**: Miller
      along with combination of
      pollard rho.
    - **prime_factors_large**:
      Probablistic algo, returns
      prime factors in n^(1/4).
    - **Discrete Log**: returns
      smallest x such that pow(a,x,
      mod)=b
    - **composite_crt**: Chinese
      Remainder Theorem. **
    - **phi**: Computes Phi(n) for
      all n. **
```

- **Linear Algebra**:
  - **compute_rank**: Computes rank of a matrix using Gaussian Elimination.
  - **Xor Basis**: Returns array of elements such that any element added to the data structure can be made using their combination.
  - **Simplex Bland**: Solves LPP Problems using Simplex Method.
  - **s_lr**: Computer Summation of i**power for l<=i<=r, given power<=3
- **Combinatorics(pnc)**:
  - **catalan**: (1/(n+1)) * (2nCn)
  - **derangements**: Number of permutations of n objects where no object appears in its original position
  - **stirling_2**: Number of ways to partition n elements into k non-empty subsets
  - **partition**: Ways to partition n into k or fewer parts of size 1 or greater
  - **Lucas nCk**: Used to find nCk for huge n and k modulo p in log p(n)
  - **beggar**: number of ways to choose k elements >= 0 such that their sum is n
- **Geometry**:
  - **onSegment**: returns True if q lies on pr
  - **orientation**: Checks orientation of p,q,r
  - **doIntersect**: Checks if two line segments intersect
  - **get_2dline**: Returns normalized 2d line
  - **is_parallel**: Checks if lines are parallel
  - **is_same**: Checks if two lines are same
  - **collinear**: Checks if three points are collinear
  - **intersect**: Returns intersection point of 2 lines
  - **rotate**: Rotates point p around origin by thetha(radians)
  - **perimeter**: Gives perimeter of a polygon
  - **area**: Polygon area (shoelace formula)
  - **centroid**: Returns the centroid of a polygon
  - **is_in_circle**: checks if point p is inside circle centered at c with radius r
  - **incircle_radius**: Radius incircle of triangle
  - **circumecircle_radius**: Radius of circumcircle
  - **Convex Hull**: Returns minimal set of points, within which all other points are contained
- **String Functions(sf)**:
  - **KMP**: Longest Prefix Matching ending at position i.
  - **Z-function**: Longest Prefix Matching starting at position i.
  - **Manacher's Algorithm**: Longest Palindrome.
  - **Suffix Array**: Suffix Array. **
    - **SuffArr**: O(N) theoretical complexity but slower
    - **SuffArray**: O(NlogN) but faster, due to less constant time
  - **LCP**: Longest common prefix between adjacent elements in Suffix Array.
- **Graph 8(graph_decom)**: Centroid Decompositon (Similar to Merge Sort)
  - **Shallowest Decomposition Tree **: O(N) Decomposition
  - **Centroid Decomposition Tree **: O(N log N) Standard Decomposition
- **Graph 9(graphflow)**: Graph Flow
  - **Dinic**: Maximal graph flow V2E
  - **HLPP**: Maximal Graph flow V2root(E)
- **Graph 10(graphmatch)**: Maximal Bipartite Matching
  - **Kuhn's Algorithm**: E*V
  - **Hopcroft Karp Algorithm**: E* root(V) - Maximal Bipartite Matching -> return min vertex cover/ max edges
- **Graph 11(lct)**: LCT
  - **Link Cut Tree**: O(log n) complexity to remove, create edge, check connectivity, distance, need to add more such functions
- **DP Optimizations**:
  - **Knuth's Optimization**:

    dp[i][j] = min(dp[i][k]+dp[k+1][j] over all k)+cost(i,j)

    Condition:

    For all a<=b<=c<=d:
    cost(a,c)+cost(b,d)<= cost(a,d)+cost(b,c)
    opt[l][r-1] <= opt[l][r] <= opt[l+1][r]

  - **Divide and Conquer Optimization**:

    dp[i][j] = min(dp[l][j-1]+cost(l,i) over all l)

    Condition:

    opt[i][j] <= opt[i][j+1]
- **FWHT**: Convolution such that ans[i] = summation of a[j]*b[k], where j logical condition k = i
- **Min Cost Max Flow**: Minimum cost that can be used while maximizing the flow
  - **MCMF**: To be used when the flow in between edges is non constant, O(F E V)
  - **Hungarian**: To be used when flow is constant, and you have a cost matrix O(n3)