

Practical No. 2

PROGRAM:

```
#Create a simulator object
set ns [new Simulator]

#Open the nam trace file
set nf [open out.nam w]
$ns namtrace-all $nf

#Define a 'finish' procedure
proc finish {} {
    global ns nf
    $ns flush-trace
    #Close the trace file
    close $nf
    #Executenam on the trace file
    exec nam out.nam &
    exit 0
}

#Create five nodes
set n0 [$ns node]
set n1 [$ns node]
set n2 [$ns node]
set n3 [$ns node]
set n4 [$ns node]
set n5 [$ns node]
#Create links between the nodes
$ns duplex-link $n0 $n1 1Mb 10ms DropTail
$ns duplex-link $n1 $n2 1Mb 10ms DropTail
```

```

$ns duplex-link $n2 $n3 1Mb 10ms DropTail
$ns duplex-link $n3 $n4 1Mb 10ms DropTail
$ns duplex-link $n4 $n5 1Mb 10ms DropTail
$ns duplex-link $n5 $n0 1Mb 10ms DropTail

#Create a TCP agent and attach it to node n0
set tcp0 [new Agent/TCP]
$tcp0 set class_ 1
$ns attach-agent $n1 $tcp0
#Create a TCP Sink agent (a traffic sink) for TCP and attach it to node n3
set sink0 [new Agent/TCPSink]
$ns attach-agent $n3 $sink0
#Connect the traffic sources with the traffic sink
$ns connect $tcp0 $sink0

# Create a CBR traffic source and attach it to tcp0
set cbr0 [new Application/Traffic/CBR]
$cbr0 set packetSize 500
$cbr0 set interval_ 0.01
$cbr0 attach-agent $tcp0

#Schedule events for the CBR agents
$ns at 0.5 "$cbr0 start"
$ns at 4.5 "$cbr0 stop"

#Call the finish procedure after 5 seconds of simulation time
$ns at 5.0 "finish"

#Run the simulation
$ns run

```

Practical No. 7

```
# Filename: test5.tcl

#create links between the nodes

$ns duplex-link $n0 $n2 2Mb 10ms DropTail

$ns duplex-link $n1 $n2 2Mb 10ms DropTail

$ns simplex-link $n2 $n3 0.3Mb 100ms DropTail

$ns simplex-link $n3 $n2 0.3Mb 100ms DropTail

$ns duplex-link $n3 $n4 0.5Mb 40ms DropTail

$ns duplex-link $n3 $n5 0.5Mb 30ms DropTail

#Set Queue Size of link (n2-n3) to 10

$ns queue-limit $n2 $n3 20

#Setup a TCP connection

set tcp [new Agent/TCP/Newreno]

$ns attach-agent $n0 $tcp

set sink [new Agent/TCPSink/DelAck]

$ns attach-agent $n4 $sink

$ns connect $tcp $sink

$tcp set fid_ 1

$tcp set window_ 8000

$tcp set packetSize_ 552

#Setup a FTP over TCP connection

set ftp [new Application/FTP]

$ftp attach-agent $tcp

$ftp set type_ FTP
```

```

#Setup a UDP connection

set udp [new Agent/UDP]

$ns attach-agent $n1 $udp

set null [new Agent/Null]

$ns attach-agent $n5 $null

$ns connect $udp $null

$udp set fid_ 2

#Setup a CBR over UDP connection

set cbr [new Application/Traffic/CBR]

$cbr attach-agent $udp

$cbr set type_ CBR

$cbr set packet_size_ 1000

$cbr set rate_ 0.01mb

$cbr set random_ false

$ns at 0.1 "$cbr start"

$ns at 1.0 "$ftp start"

$ns at 10.0 "$ftp stop"

$ns at 10.5 "$cbr stop"

# ----- FINISH PROCEDURE -----#

proc finish {
    global ns nf nt
    $ns flush-trace
    close $nf
    puts "running nam..."
    exec nam Tcpred3.nam &
    exit 0
}

#Calling finish procedure
$ns at 15.0 "finish"
$ns run

```

Practical No. 8

Aim: To create scenario and study the performance of CSMA / CD protocol through simulation.

CSMA/CD

```
set ns [new Simulator]
#Define different colors for data flows (for NAM)
$ns color 1 Blue
$ns color 2 Red
#Open the Trace files
set file1 [open out.tr w]
set winfile [open WinFile w]
$ns trace-all $file1
#Open the NAM trace file
set file2 [open out.nam w]
$ns namtrace-all $file2
#Define a 'finish' procedure
proc finish {} {
    global ns file1 file2
    $ns flush-trace
    close $file1
    close $file2
    exec nam out.nam &
    exit 0
}
#Create six nodes
set n0 [$ns node]
set n1 [$ns node]
set n2 [$ns node]
set n3 [$ns node]
set n4 [$ns node]
set n5 [$ns node]
$n1 color red
$n1 shape box
```

```

#Create links between the nodes
$ns duplex-link $n0 $n2 2Mb 10ms DropTail
$ns duplex-link $n1 $n2 2Mb 10ms DropTail
$ns simplex-link $n2 $n3 0.3Mb 100ms DropTail
$ns simplex-link $n3 $n2 0.3Mb 100ms DropTail
set lan [$ns newLan "$n3 $n4 $n5" 0.5Mb 40ms LL Queue/DropTail MAC/Csma/Cd Channel]
Setup a TCP connection
set tcp [new Agent/TCP/Newreno]
$ns attach-agent $n0 $tcp
set sink [new Agent/TCPSink/DelAck]
$ns attach-agent $n4 $sink
$ns connect $tcp $sink
$tcp set fid_ 1
$tcp set window_ 8000
$tcp set packetSize_ 552
#Setup a FTP over TCP connection
set ftp [new Application/FTP]
$ftp attach-agent $tcp
$ftp set type_ FTP
#Setup a UDP connection
set udp [new Agent/UDP]
$ns attach-agent $n1 $udp
set null [new Agent/Null]
$ns attach-agent $n5 $null
$ns connect $udp $null
$udp set fid_ 2
#Setup a CBR over UDP connection
set cbr [new Application/Traffic/CBR]
$cbr attach-agent $udp
$cbr set type_ CBR
$cbr set packet_size_ 1000

```

```

$cbrr set rate_ 0.01mb
$cbrr set random_ false
$ns at 0.1 "$cbrr start"
$ns at 1.0 "$ftp start"
$ns at 124.0 "$ftp stop"
$ns at 124.5 "$cbrr stop"
# next procedure gets two arguments: the name of the
# tcp source node, will be called here "tcp",
# and the name of output file.
proc plotWindow {tcpSource file} {
    global ns
    set time 0.1
    set now [$ns now]
    set cwnd [$tcpSource set cwnd_]
    set wnd [$tcpSource set window_]
    puts $file "$now $cwnd"
    $ns at [expr $now+$time] "plotWindow $tcpSource $file" }
$ns at 0.1 "plotWindow $tcp $winfile"
$ns at 5 "$ns trace-annotate \"packet drop\""
# PPP
$ns at 125.0 "finish"
$ns run

```