

Received 11 February 2025, accepted 11 March 2025, date of publication 13 March 2025, date of current version 21 March 2025.

Digital Object Identifier 10.1109/ACCESS.2025.3551095

RESEARCH ARTICLE

Our Digital Traces in Cybersecurity: Bridging the Gap Between Anonymity and Identification

ARBENA MUSA¹, KAMER VISHI², EDLIRA MARTIRI³, AND BLERIM REXHA¹ 

¹Faculty of Electrical and Computer Engineering, University of Pristina, 10000 Pristina, Kosovo

²The Norwegian Agency for Local Governments, 0125 Oslo, Norway

³Department of Statistics and Applied Informatics, University of Tirana, 1010 Tirana, Albania

Corresponding author: Blerim Rexha (blerim.rexha@uni-pr.edu)

This work was supported by the Ministry of Education, Science, Technology, and Innovation (MESTI) of Kosovo under Grant 2-2282-1.

ABSTRACT The rapid expansion of digital interactions has led to the formation of unique digital traces, often referred to as digital fingerprints, which play a crucial role in modern cybersecurity. These fingerprints, constructed from data related to user devices, browsers, and behavioral patterns, serve to identify users across different platforms and sessions. This identification aids in enhancing security, such as fraud detection, identity verification, and multi-factor authentication. However, digital fingerprints also pose significant privacy challenges, as they can be used to track individuals without their knowledge or consent. This paper provides an in-depth analysis of digital fingerprints, tracing the evolution of tracking technologies from simple browser cookies to sophisticated methods like machine learning-enhanced fingerprinting. It explores how digital fingerprints are created, the kinds of data used, and the ways these traces are utilized to bridge the gap between ensuring digital security and maintaining user anonymity. Through detailed literature review, we investigate the application of digital fingerprints in various domains, such as web browsing, online banking, and e-commerce, revealing both the security benefits and the privacy risks. The paper also discusses emerging techniques for mitigating these risks and highlights the importance of balancing personalization and privacy. Our paper concludes by addressing the ongoing debate between privacy and security, emphasizing the need for privacy-enhancing technologies that can coexist with the benefits of digital fingerprints in today's interconnected digital landscape.

INDEX TERMS Internet security, user privacy, digital traces, web browsing, digital fingerprinting.

I. INTRODUCTION

In the early days of the Internet, its value was seen primarily in providing easy access to information and enabling instant communication. It was specifically designed to simplify the sharing of information, making the process faster and more efficient. This capability not only connected people across long distances but also broadened access to a wide range of resources and knowledge worldwide. Today, however, technology has evolved beyond mere connectivity, focusing instead on delivering personalized experiences for users. Achieving this level of personalization requires a deep understanding of the user, their activities, and their

preferences. As a result, the web has transformed into a space where every interaction contributes to the creation of a digital identity.

Just as our identity in the physical world is shaped by who we are, what we value, and the relationships we build with others, so too can our digital identity be constructed. This identity is built through data collected from our online activities as what we browse, communicate, and engage with. Even without directly revealing personal information, websites, and platforms can track, analyze, and piece together various aspects of who we are.

The Internet, along with the multitude of connected devices, generates a large amount of data, each interaction leaving behind distinct digital traces. These traces can serve as unique identifiers, offering insights into the devices,

The associate editor coordinating the review of this manuscript and approving it for publication was Lukasz Wisniewski .

browsers, and even the behavior patterns of users therefore often are referred to as digital fingerprints. Unlike physical fingerprints, which remain largely unchanged over time, digital fingerprints are dynamic. They evolve and adapt as the user's configurations change, whether through software updates, new browser settings, or changes in device usage patterns.

Digital fingerprints are composed of data points such as IP addresses, browser versions, operating systems, screen resolutions, installed plugins, and even interaction metrics like typing speed or mouse movements. These seemingly innocuous details, when aggregated, create a distinctive profile that can be used to identify and track individuals across multiple sessions and websites. This evolving nature of digital fingerprints makes them both powerful tools for user identification and challenging to avoid, as they constantly shift in response to user activity and environmental changes.

Although, with many added benefits over the years, there has been a constant need to anonymize the activity on the Internet, preserving the identity of active users. People who consume the services offered over the Internet must have the right not to be seen, followed, targeted and identified. Not being seen by others and out of the limelight is one of the most comfortable feelings. Psychologically, too, feeling free to act without being watched and judged for who you are or what you do reflects comfort. But today the Internet exposes what we are and what we do in the open, contributing to the parallel construction of our virtuous image. Such exposure, in certain cases, may cause restrictions of expression, action and access in relation to the data found and exchanged on the Internet.

While this process of constructing a digital identity enables personalized services, it also raises significant concerns about privacy, surveillance, and the erosion of anonymity. The question that arises is how to strike a balance between harnessing the benefits of personalization and protecting users' privacy, especially as digital fingerprints which are unique identifiers left behind by user devices, browsers, and online activities, make it easier to track and profile users without their explicit consent. The line between anonymity and identification grows increasingly thin. The same mechanisms that enable user identification for security purposes also empower companies and entities to track individuals across the web, often without their knowledge or consent.

Anonymous networks or anonymous communication systems have been built from the request to preserve the privacy of users on the Internet, during operation in which the user is supposed to be protected from identification, monitoring, tracking and targeting. What keeps the curiosity awake and the concern still present is the answer to the question: Has continued consistency been achieved in ensuring the preservation of privacy in such ways? Anonymous systems, although proven for their functionality and efficiency, it has been shown that they cannot be invulnerable to external

threats and new opportunities are constantly explored to overcome privacy protection mechanisms.

This paper aims to explore the role of digital fingerprints in cybersecurity, discussing how they operate, their applications, and the ongoing debate between privacy and security. The focus will be on how digital fingerprinting techniques bridge the gap between ensuring secure digital identities and preserving user anonymity. It makes a significant contribution to the ongoing discourse on digital fingerprinting in cybersecurity by offering a comprehensive review of its evolution, applications, and implications. It bridges the gap between security and privacy concerns, presenting a detailed analysis of existing techniques, highlighting their benefits in enhancing security, and addressing associated privacy challenges. The research is particularly targeted at cybersecurity professionals, privacy advocates, and policymakers who face the challenge of balancing robust security measures with the preservation of user anonymity. Additionally, it is highly relevant to industries such as online banking, e-commerce, and social media platforms, where digital fingerprints are extensively used for fraud detection, identity verification, and user tracking.

By examining the evolving landscape of digital fingerprinting, this paper proposes actionable insights for developing privacy-preserving technologies and provides a framework for future research and regulatory considerations. These contributions aim to address critical gaps in understanding how digital fingerprints can simultaneously strengthen security and pose significant privacy risks, ensuring the paper's relevance to both theoretical and practical domains of cybersecurity.

A. BREAKING IT DOWN

Digital fingerprinting technologies have become increasingly sophisticated, presenting a dual-edged challenge, leveraging their utility for enhanced security while addressing significant privacy concerns. While many studies delve into individual fingerprinting techniques, they often fail to consider their cumulative impact on user autonomy and anonymity. This paper seeks to address these gaps by exploring the trade-offs between privacy-preserving technologies and the growing reliance on digital traces. By examining these challenges holistically, this work aims to offer a comprehensive understanding of the complexities involved in balancing security and privacy.

To achieve this, we conducted a structured review of the existing literature, focusing on the evolution, applications, and implications of digital traces. The methodology involved several key steps: defining the research problem and objectives, systematically collecting relevant materials, and analyzing them to synthesize insights and compare case studies. A broad literature search was conducted using databases such as IEEE Xplore, ACM Digital Library, Elsevier's ScienceDirect, SpringerLink, Google Scholar, and Web of Science. The inclusion criteria emphasized selecting studies with a direct connection to digital traces, focusing on

recent works published within the last three years to ensure timeliness, and maintaining academic rigor by prioritizing peer-reviewed research. Exclusion criteria were applied to remove non-peer-reviewed, off-topic, or duplicate studies, ensuring the relevance and quality of the reviewed literature.




FIGURE 1. Methodology workflow for exploring digital traces.

The selected literature was analyzed thematically, identifying key patterns, consensus points, and gaps. Studies were categorized into themes such as technological foundations, privacy concerns, and implications for cybersecurity and policy. This thematic analysis enabled a nuanced discussion that highlights the state of the field while identifying directions for future research. Figure 1 illustrates the methodology workflow adopted in this study, outlining the key steps and parallel processes involved in exploring digital fingerprints, from data collection to thematic analysis and the identification of future research directions.

B. COMPARING PERSPECTIVES

This literature review contributes to existing research on digital fingerprinting techniques, exploring their applications in cybersecurity and the associated privacy concerns. While many studies have delved into specific aspects of fingerprinting such as device, browser, or website fingerprinting there is a need for reviews that address the broader implications of these techniques.

Our work stands out for several reasons:

- **Comprehensive Coverage** - we analyze a wide range of fingerprinting methods, including device, browser, and website fingerprinting, providing a unified understanding of their roles in cybersecurity.
- **Focus on Privacy and Security Balance** - unlike studies that primarily highlight technical aspects, our review

emphasizes the delicate balance between enhancing security and preserving user privacy.

- **Consideration of Ethical Implications** - we explore the ethical dimensions of digital fingerprinting, discussing the potential consequences of these technologies on user anonymity and autonomy.
- **Practical Mitigation Strategies** - our work identifies practical solutions for mitigating the privacy risks associated with fingerprinting, highlighting the importance of scalable, system-wide approaches.
- **Relevance to Multiple Domains** - we discuss how digital fingerprinting impacts various industries, such as online banking, e-commerce, and social media, illustrating the widespread implications of these techniques.
- **Call for Integrated Approaches** - we stress out the importance of developing integrated, privacy-preserving technologies that can coexist with current security measures.

In summary, our research not only consolidates existing body of knowledge on digital fingerprinting but also highlights the need for balanced, ethical, and practical approaches to managing digital traces in cybersecurity.

II. THE JOURNEY OF DIGITAL TRACKING

The evolution of digital fingerprinting has been a dynamic journey marked by rapid technological advancements and an ever-increasing demand for personalized online experiences. Figure 2 provides a visual timeline of key milestones in this journey, illustrating the progression from early tracking methods like third-party cookies to advanced techniques such as machine learning-enhanced fingerprinting and privacy-enhancing technologies. This timeline not only contextualizes the technological advancements but also underscores the increasingly fine balance between ensuring security and protecting user privacy. As the Internet matured in the 1990s, the introduction of HTTP cookies revolutionized the way web applications interacted with users. Initially, cookies facilitated session management, allowing websites to remember user preferences and login states [1]. However, this innovation quickly evolved into a tool for tracking user behavior across different websites [2], paving the way for the widespread adoption of third-party cookies in the early 2000s. These third-party cookies enabled advertisers and analytics services to monitor users' online activities, leading to a growing awareness of privacy concerns and the emergence of ad-blocking technologies [3].

As the need for more robust tracking mechanisms became apparent, the concept of device fingerprinting gained traction around 2010. Unlike traditional cookies, which could be deleted or blocked, device fingerprinting combined various device-specific attributes—such as browser type, operating system, screen resolution, and installed plugins—into a unique identifier [4]. This technique proved particularly effective at evading privacy controls, allowing websites to track users even when they employed private browsing modes. Key studies, such as [5], highlighted the efficacy of




FIGURE 2. A simplified timeline: The milestones on the journey of digital tracking.

this method and underscored the potential for persistent user identification.

The journey further progressed with the introduction of more sophisticated techniques like canvas and audio fingerprinting in the early 2010s [4], [6]. These methods exploited the unique ways in which different devices rendered graphics or processed sound, creating a new layer of tracking that was even harder to circumvent. Studies conducted on [6] emphasized the persistent nature of these tracking mechanisms, revealing the challenges users faced in maintaining their online anonymity.

As digital fingerprinting evolved, so too did the methods of data collection. Various technologies, including JavaScript and HTTP headers, emerged as essential tools for gathering user information without direct interaction [2]. Researchers began to identify a range of data types collected through fingerprinting, including IP addresses, browser versions, and more, enhancing the understanding of how digital identities were constructed.

The distinction between browser and device fingerprinting became a critical focus in the latter half of the 2010s. While browser fingerprinting primarily relied on software configurations and settings, device fingerprinting encompassed hardware characteristics, further complicating the landscape of digital tracking. This shift was accompanied by a growing awareness of the correlation between diverse data points, allowing for more precise user identification across multiple devices.

The implementation of regulations such as the General Data Protection Regulation (GDPR) in 2018 marked a pivotal moment in the journey of digital fingerprinting. GDPR introduced stringent requirements regarding data collection, consent, and user rights, compelling organizations

to reassess their tracking practices. While fingerprinting was not explicitly outlawed, it came under increased scrutiny, leading to a reevaluation of its ethical implications and the need for transparency.

As technology advanced, cross-device fingerprinting emerged, allowing for the tracking of users across smartphones, tablets, and personal computers. In the early 2020s, machine learning began to play a crucial role in enhancing digital fingerprinting techniques [7]. By leveraging advanced algorithms to analyze and predict user behavior, organizations improved the accuracy and persistence of their tracking methods. This shift marked a new frontier in digital fingerprinting, one that brought both opportunities for personalized experiences and challenges in protecting user privacy.

Today, the conversation around digital fingerprinting continues to evolve, with the introduction of privacy-enhancing technologies (PETs) designed to counteract tracking practices. As organizations and individuals navigate the delicate balance between personalization and privacy, the journey of digital fingerprinting stands as a testament to the ongoing struggle between innovation and the protection of personal data. The future of this technology will undoubtedly be shaped by the interplay of regulatory frameworks, technological advancements, and societal attitudes toward privacy.

A. APPLICATION IN CYBERSECURITY

Digital fingerprinting has become an indispensable tool in modern cybersecurity, pivotal in protecting users and platforms from various online threats. The increasing complexity of cyber threats, ranging from fraud to unauthorized access, has necessitated advanced identification and tracking

TABLE 1. Types of online platforms on which the digital fingerprints can be essential.

Platform	Purpose of Digital Fingerprinting	Usable Fingerprinting Technique	Common Privacy Concerns	User Experience Impact
Streaming Services	Utilize digital fingerprinting primarily to detect account sharing and fraudulent logins. By analyzing device characteristics and user behavior, these platforms can identify when an account is accessed from an unrecognized device, thus preventing unauthorized access and ensuring that only legitimate users can stream content. This helps maintain the integrity of user accounts and protects content licensing agreements. Additionally, these platforms enhance user experience by personalizing content recommendations based on unique user behavior.	Device and behavioral fingerprinting	Concerns include tracking user behavior without consent, excessive data collection for personalized recommendations, and potential misuse of data by third parties.	Enhances personalized recommendations, but could lead to discomfort due to a feeling of surveillance. May occasionally cause false positives in fraud detection, leading to access issues.
E-commerce Sites	Implement digital fingerprinting to prevent payment fraud and ensure that transactions are legitimate. By capturing unique identifiers related to devices and monitoring user behavior during the purchasing process, these platforms can detect suspicious activities, such as attempts to use stolen credit card information. This proactive approach minimizes financial losses for both the retailer and its customers.	Device fingerprinting and user behavior analysis	Collection of sensitive payment data, potential profiling of users based on purchasing habits, and the risk of data breaches that expose personal financial information.	Improved shopping experience through personalized recommendations, but concerns over excessive monitoring of shopping behavior.
Social Media Networks	Employ digital fingerprinting to enhance account security and prevent unauthorized access. By analyzing various device and browser characteristics, these platforms can identify unusual login attempts from unknown devices or locations. This allows them to implement additional verification measures, helping to protect user data and maintain trust in social networking services.	Device browser fingerprinting	Privacy concerns related to the creation of comprehensive user profiles, tracking users across different platforms, and lack of transparency in data sharing with advertisers.	Targeted ads may feel invasive. Enhanced security may improve user trust, but fingerprinting for marketing could reduce user satisfaction.
Online Marketplaces	Use digital fingerprinting to identify and block fraudulent listings, enhancing user security and trust. By monitoring the unique characteristics of devices used to access the platform, these marketplaces can detect suspicious activities, such as multiple fraudulent listings created from the same device or IP address. This practice helps protect users from scams and maintains the credibility of the platform's offerings.	Device fingerprinting and activity monitoring.	Concerns over data misuse in identifying and tracking sellers and buyers, as well as the risk of surveillance by monitoring device characteristics without explicit user consent.	Helps create a secure marketplace but could lead to invasive tracking, especially when user behavior is overly scrutinized.
Payment Processing Systems	Minimize fraud risk by verifying the identity of devices involved in transactions through digital fingerprinting. By analyzing device characteristics and behavioral patterns during login and transaction processes, these systems can flag unusual activity and prompt users for additional verification. This dual-layered approach enhances transaction security and builds user confidence.	Device fingerprinting with combined risk analysis	Concerns about continuous monitoring of financial activities and device data, as well as over-collection of transaction information for fraud detection.	Improves transaction security but may create a sense of over-surveillance among users. Could also slow down the transaction process if too many checks are performed.
Online Banking Services	Leverage digital fingerprinting to ensure secure transactions and identity verification for their users. By continuously analyzing device attributes and user behavior, these services can detect any anomalies during the login and transaction processes. This proactive monitoring helps prevent fraud, unauthorized access, and identity theft, thereby safeguarding sensitive financial information.	Multi-factor authentication with device fingerprints.	Privacy issues regarding the continuous collection and analysis of personal financial behavior, the potential for false positives leading to access issues, and the risk of data breaches.	Significantly improves security, but users might experience friction if legitimate transactions are flagged. Could also create a sense of being constantly monitored.

methods. Digital fingerprinting meets these demands by enabling platforms to uniquely identify users and devices based on hardware, software, and behavioral characteristics. Its versatility allows for wide application across numerous online services, enhancing both security and personalization while also raising concerns about privacy and user consent.

Table 1 highlights how digital fingerprinting is applied in cybersecurity across various platforms. Streaming services, e-commerce sites, social media networks, online marketplaces, payment processors, and online banking services utilize these techniques to enhance security, detect fraudulent activity, and improve user experiences. By analyzing the distinct characteristics of devices and monitoring user behavior, these platforms can effectively prevent unauthorized access and protect users from identity theft, fraud, and other malicious activities.

Each platform's use of digital fingerprinting is tailored to its unique requirements. For instance, streaming services rely on device and behavioral fingerprinting to detect account sharing, while e-commerce sites focus on preventing payment fraud through user behavior analysis. Social media networks and online banking services employ these techniques to enhance account security and safeguard sensitive personal and financial information. However, the use of digital fingerprinting also introduces privacy concerns, particularly regarding excessive data collection, the potential for third-party misuse, and the lack of transparency around data practices. These concerns underscore the importance of balancing security measures with user privacy to maintain trust in digital interactions.

The analysis further explores how these platforms' implementations impact user experience. While the security benefits are clear, over-surveillance and the perception of constant monitoring can lead to discomfort among users. Striking the right balance between security, personalization, and privacy is essential in fostering a secure yet user-friendly digital environment. By understanding the broader applications and implications of digital fingerprinting, this analysis provides key insights into its role within cybersecurity strategies.

B. HOW THE DATA GETS USED

Digital footprints, composed of information from our devices, online behavior, and interactions, are now instrumental in both cybersecurity and fields such as financial services, social media analytics, and user behavior prediction. While these footprints offer significant benefits, they also present privacy concerns, as they can be exploited for tracking, profiling, and identifying users in ways that may compromise anonymity. This section explores various studies that illustrate how digital footprints are being harnessed across different domains, raising important questions about security, privacy, and the ethical use of data.

In the study by [11], digital footprints particularly temporal patterns of computer and smartphone usage—are shown to be predictive of personality traits such as

Extroversion, Openness, and Neuroticism. Their research illustrates how seemingly mundane digital interactions, like screen-switching frequency or social media usage, can reveal valuable psychometric information akin to digital fingerprints. This raises critical concerns about the extent to which digital traces expose intimate personal details, often without users' awareness. These findings are particularly relevant in cybersecurity, where digital footprints can not only identify users but also infer behavioral traits, complicating efforts to maintain digital anonymity. Furthermore, in [12] is introduced mobile app fingerprinting attack that analyzes encrypted wireless traffic to identify user activities linked to specific apps, posing a considerable threat to user privacy. It operates in three stages—traffic preprocessing, segmentation, and recognition—and demonstrates robust performance in both closed-world and open-world scenarios. Extensive evaluations reveal its strong resilience against noise introduced by app multiplexing and packet loss from signal attenuation, thanks to features like pattern dropout regularization and an adaptive clustering threshold.

Similarly, [9] focuses on the growing importance of user footprints across multiple social networks. The study demonstrates how publicly available information—such as usernames, display names, locations, and profile images—can be used to track and link users across different platforms. This correlation of digital identities highlights both personalization opportunities and significant privacy risks, including identity theft and online profiling. With classifiers achieving an accuracy rate of 98%, the study underscores the precision of digital footprint analysis and the potential risks of privacy invasion.

To manage personal data more effectively, [8] introduce the Digital Me (DiMe) system, which prioritizes human-centric control over digital footprints. The study acknowledges the vast digital presence individuals leave behind due to constant interaction with digital systems. By offering tools for individuals to own, visualize, and manage their data, DiMe aims to give users more control over their digital presence. This not only protects personal privacy but also challenges the growing centralization of data by large corporations.

Beyond identification, digital footprints are increasingly being utilized for applications such as financial credit scoring. For instance, [10] discusses how FinTech companies are leveraging digital footprints—including device type, operating system, and email address characteristics—to assess consumer creditworthiness with accuracy similar to traditional credit bureaus. While effective, this practice raises privacy concerns as individuals leave behind traces through everyday online activities, such as browsing or shopping. These digital footprints can act as proxies for personal behavior and economic status, potentially leading to unintended consequences like discrimination. As such, the use of digital footprints in financial sectors emphasizes the need for careful regulation and scrutiny to ensure fairness and privacy in cybersecurity.

The ability to infer sensitive personal information, track behaviors across platforms, and exploit encrypted data raises ethical concerns about consent, data ownership, and potential misuse. As digital footprints become more ingrained in both technological and commercial practices, it is imperative to develop robust frameworks that balance the benefits of data utilization with the protection of individual privacy. Addressing these issues will require not only technological solutions but also thoughtful regulatory measures and increased user awareness.

III. FINGERPRINTING AND PRIVACY CONCERNS

As individuals interact with the digital world, the Internet and connected devices generate a vast amount of data, leaving behind distinct traces known as digital fingerprints. These traces provide unique identifiers for devices, browsers, and even user behavior, offering a powerful tool for identification and tracking. Unlike physical fingerprints, which are static, digital fingerprints are dynamic and evolve as configurations change and user interactions occur. While digital fingerprints play a crucial role in security and personalization, they also raise important privacy concerns, particularly when used without the user's consent.

Key concepts and definitions central to fingerprinting include:

- **Device Traces:** These traces analyze a device's unique hardware and software attributes—such as the operating system, screen resolution, installed fonts, and language settings. By combining these characteristics, a profile can be built to accurately identify the device.
- **Web-based Traces:** This category encompasses both browser-specific details, such as browser type, installed add-ons, and WebGL capabilities, as well as network traffic patterns like packet size and timing. These fingerprints can be used to track user's browsing habits and infer which websites they are accessing.
- **Behavioral Traces:** Unlike static device or browser traces, behavioral traces delve into user interactions, such as typing patterns, mouse movements, and scrolling behavior. These traces open a new frontier for identifying users based on their unique usage habits.

Table 2 and Figure 3 outline various digital fingerprinting techniques, highlighting their definitions, the types of data they collect, the scope of their tracking capabilities, key use cases, and the associated privacy concerns. These techniques span from device and browser fingerprints to more intricate patterns like behavioral and cross-device fingerprints. For the purposes of this paper, we will focus specifically on device, browser, and website fingerprints, as these play a pivotal role in bridging the gap between anonymity and identification within the cybersecurity domain.

While digital fingerprints offer significant benefits in enhancing security and personalization, they also raise serious privacy concerns. The ability to track users across devices, sessions, and networks without their explicit consent undermines user autonomy and data privacy. Particularly

troubling is the difficulty users face in detecting or preventing this tracking, as traditional methods like clearing cookies are often ineffective against more advanced fingerprinting techniques. This pervasive form of surveillance poses risks to individual privacy, especially in contexts where sensitive data is exposed or where government or corporate monitoring is prevalent.



FIGURE 3. Extensive overview of digital traces.

A. DEVICE FINGERPRINTS

Device fingerprinting is a critical technique for identifying network devices by analyzing their traffic patterns, playing a key role in strengthening cybersecurity and defending against cyber-attacks. This method enables the identification of devices without relying on traditional identifiers, such as IP or MAC addresses, which can be easily spoofed. Instead, it relies on unique characteristics like packet size, timing, and communication behavior, making it more resilient against tampering or manipulation.

In the context of IoT, device fingerprinting is especially important due to the vast number of connected devices and their varied security protocols. These devices often operate with limited resources, making traditional cryptographic methods impractical. Device fingerprinting addresses this challenge by providing a lightweight solution for monitoring and managing IoT networks, ensuring that only authorized devices are allowed to connect. It enhances security by detecting rogue devices, identifying potential vulnerabilities, and mitigating risks from cyber-attacks like device spoofing or unauthorized access.

Moreover, this technique supports real-time monitoring, enabling rapid detection of anomalies in device behavior, which is essential for preventing large-scale coordinated attacks. However, while device fingerprinting offers numerous advantages, it also raises privacy concerns. Adversaries

TABLE 2. Comparison of digital fingerprinting techniques.

Type of Fingerprint	Definition	Data Collected	Tracking Scope	Key Use Cases	Limitations/Privacy Concerns
Device Fingerprint	A unique identifier based on hardware and software characteristics of the user's device.	Device model, operating system, screen resolution, installed fonts, network interfaces, time zone, and more.	Tracks individual devices across different websites or apps.	Used to detect fraud, enhance security, and prevent account sharing by identifying specific devices.	May bypass user controls such as clearing cookies. Often difficult for users to detect or avoid.
Browser Fingerprint	A profile built from information about the user's browser and its configuration.	Browser type/version, plugins, extensions, headers, screen resolution, languages, and installed fonts.	Tracks user activity across web sessions on the same or different websites.	Used for targeted advertising, cross-site tracking, and user authentication.	Users are often unaware of this tracking, and blocking cookies does not prevent browser fingerprinting.
Website Fingerprint	A method of determining which websites a user has visited by analyzing network traffic, even when it is encrypted.	Network traffic patterns, timing information, packet sizes, and IP addresses.	Tracks user behavior on specific websites by examining traffic metadata.	Often used by state-level actors or attackers to track users across secure communications (like Tor).	Can be invasive and difficult for users to prevent, especially in countries with extensive surveillance systems.
App Fingerprint	A profile based on the characteristics and behaviors of mobile apps running on a user's device.	App version, permissions granted, network requests, unique app IDs, and device sensors used.	Tracks user behavior across different apps installed on the same device.	Used by app developers for personalization, security, and fraud detection.	Can often run in the background without user knowledge, potentially leading to privacy violations.
Cross-Device Fingerprint	Tracks users across multiple devices (e.g., smartphone, tablet, desktop) using shared identifiers like accounts or behaviors.	Combination of device fingerprints, IP addresses, browser cookies, and shared account information.	Tracks user behavior across different devices and environments.	Commonly used in advertising to deliver personalized content or measure campaign performance across platforms.	Requires large datasets and sophisticated techniques, raising privacy concerns over extensive cross-device surveillance.
Behavioral Fingerprint	A profile generated by monitoring how a user interacts with their device or website, including typing patterns, mouse movement, and touch gestures.	Keystroke dynamics, mouse movements, touch gestures, typing speed, scroll patterns, and other user interaction data.	Tracks user interactions and behaviors within specific sessions or across websites.	Used for fraud detection, especially in high-security applications like banking or secure access systems.	Can be highly invasive, especially when tracking subtle and continuous behavioral patterns, leading to significant privacy concerns.
Geolocation Fingerprint	Uses GPS or IP-based data to identify the physical location of the user.	Latitude, longitude, IP address, and location history.	Tracks user movements and locations over time.	Used for targeted advertising, location-based services, and security applications.	Raises significant privacy issues as it can reveal sensitive information about user habits and locations.
Email Fingerprint	Analyzes unique identifiers and metadata associated with email accounts to track user activities.	Sender/receiver email addresses, timestamps, and message headers.	Tracks interactions and behavior in email communication.	Used for security analysis, spam detection, and targeted advertising.	Privacy concerns arise from the ability to track user correspondence without their consent.
Social Media Fingerprint	Uses data collected from social media profiles and interactions to create a user profile.	Likes, shares, posts, comments, and follower information.	Tracks user behavior across various social media platforms.	Used for targeted marketing, social media analytics, and user profiling.	Can lead to privacy violations if users are unaware of how their data is being used for tracking.

could potentially exploit these fingerprints to track and profile devices, underscoring the need for robust countermeasures that balance security and privacy. As IoT ecosystems continue to expand, effective device fingerprinting will remain crucial for managing and securing the increasing number of connected devices, ensuring that networks can operate safely and efficiently.

Recent research has demonstrated the growing potential of device fingerprinting to enhance security and privacy, particularly in the context of IoT devices. The study conducted in [20] explores passive IoT device fingerprinting by analyzing WiFi packet signal levels and MAC layer information. By configuring a standard WiFi Access Point to passively monitor packets, their study shows that valuable data can be extracted to generate unique fingerprinting profiles for various IoT devices. While this approach improves the identification process, it raises privacy concerns, as attackers could exploit these fingerprints to track devices without user consent. The findings underscore the necessity for robust security measures to prevent unauthorized tracking and protect user anonymity in highly connected environments.

Similarly, [19] presents PoirIoT, a high-speed system designed to identify IoT devices using only packet metadata—specifically packet length and direction. This method allows for immediate detection of devices as they begin exchanging packets, representing a significant improvement over traditional methods that rely on offline data or payload analysis. PoirIoT, implemented on a Tofino-based programmable switch, demonstrated its ability to accurately detect devices using publicly available datasets while operating at a line rate with minimal resource overhead. This system highlights the critical importance of real-time device identification in maintaining cybersecurity and mitigating large-scale attacks across increasingly interconnected networks.

Further advancing the field, [17] proposes a method for generating unique device fingerprints by analyzing packet inter-arrival times. Using deep convolutional neural networks (CNNs) to process these patterns, they successfully classified 58 non-IoT devices across several categories. Their research reveals that models focusing on classifying device types are more accurate than those aimed solely at identifying individual devices, suggesting that understanding device types enhances overall classification accuracy. Moreover, while deep learning models can detect changes in device signatures during cyber-attacks, such changes can also result in misclassification, highlighting the need for more resilient cybersecurity strategies in device fingerprinting systems.

In another study, [13] presents a deep learning-based approach to enhance the security of LoRa-enabled IoT devices through RF fingerprinting. By leveraging out-of-band distortion caused by hardware impairments, the technique generates device-specific signatures that are difficult to replicate. This method is effective in distinguishing between devices, particularly when network conditions remain stable.

However, the study also points out that performance can degrade when there are variations in the network environment, such as changes in receiver hardware or channel conditions. This highlights the ongoing challenges in ensuring robust device authentication across dynamic IoT networks.

Additionally, [18] introduces DevTag, a benchmark designed specifically for IoT device fingerprinting. DevTag enables the extraction of packet-level features through both passive monitoring and active probing. The study employs two detection strategies: model-based and rule-based fingerprinting. While the model-based approach is effective for identifying broader device categories and vendors, the rule-based technique excels in capturing more detailed device-specific information. Despite its success, the study identifies challenges, such as difficulty in detecting specific product details due to the extensive variety of labels, and rule conflicts in the rule-based method. The release of DevTag as a prototype underscores its importance as a foundational tool for IoT device detection within the network community.

Finally, [16] delves into the concept of behavioral fingerprinting for IoT devices. Their research emphasizes that traditional device identifiers like IP or MAC addresses can be easily spoofed, and cryptographic methods are often unsuitable for resource-constrained IoT devices. Instead, they propose fingerprinting based on behavioral patterns, such as messaging entropy, payload length, and TCP window size—features that remain unique even in encrypted traffic. This approach proves highly effective, achieving a 99% identification accuracy and playing a pivotal role in enhancing device authentication and mitigating threats like device forgery and impersonation through more complex and difficult-to-spoof identifiers.

B. BROWSER FINGERPRINTS

Browser fingerprinting has become an increasingly powerful method for tracking users online, surpassing traditional cookie-based approaches. This technique utilizes a variety of features—including User-Agent strings, screen resolution, operating system details, and hardware characteristics—to create unique identifiers for each user. Unlike cookies, which require user consent for tracking, browser fingerprints can be collected without explicit permission and are resistant to privacy modes or cookie-blocking tools. The advancement of web technologies such as JavaScript, CSS, and HTML5 has further enhanced the ability to gather these fingerprints, allowing for accurate tracking across different browsers and devices. This evolution raises significant concerns about user privacy and anonymity, particularly as fingerprinting techniques become more sophisticated.

As highlighted in [43], browser fingerprinting has emerged as a powerful method for tracking users, surpassing traditional cookie-based methods. This technique leverages a combination of features such as User-Agent strings, screen resolution, operating system details, and even hardware characteristics to create unique identifiers. Unlike cookies,

browser fingerprints can be collected without user consent and are resilient to privacy modes or cookie-blocking tools. The rise of technologies like JavaScript, CSS, and HTML5 has significantly enhanced the ability to gather browser fingerprints, enabling cross-browser and cross-device tracking with high accuracy. This development underscores the growing concerns around user privacy and anonymity in the face of increasingly sophisticated fingerprinting techniques.

Research by [44] analyzed over 4 million browser fingerprints, showing that 81.3% were unique to a single browser, with 91% of attributes remaining stable over several months. This high distinctiveness and stability make browser fingerprints a valuable addition to multi-factor authentication. The study highlights their efficient deployment, requiring minimal data and no extra hardware, already adopted by companies like MicroFocus and SecureAuth. Additionally, the use of dynamic attributes like HTML5 canvas and WebGL further strengthens their security against replay attacks/

In a more recent study, [45] conducted a large-scale analysis of browser fingerprints used both for benign purposes and adversarial activities. They highlight how adversaries craft adversarial browser fingerprints to bypass detection systems, differentiating them from benign fingerprints used in regular browsing. The study emphasizes that adversarial fingerprints often utilize tools like scripting, emulated browsers, and virtual machines to modify browser characteristics, making them difficult to detect. This research provides valuable insights into how browser fingerprinting, traditionally used for tracking and personalization, is evolving as both a defensive mechanism in cybersecurity and a target for adversarial manipulation.

C. WEBSITE FINGERPRINTS

Website Fingerprinting (WF) is a sophisticated technique used to analyze network traffic patterns and infer which websites users are accessing, even when encryption and anonymity tools like Tor are employed. As internet usage grows and privacy concerns intensify, WF attacks have become a critical area of study in cybersecurity. These attacks exploit the unique characteristics of network traffic—such as packet size, timing, and order—to reveal user activity, often without the need for direct access to the content of the communication.

Recent developments in WF have introduced more advanced methods, often leveraging machine learning and deep learning techniques to enhance accuracy and efficiency in identifying users' browsing behavior. However, alongside these advancements, significant efforts are being made to develop robust defenses to protect user privacy and anonymity. From novel obfuscation techniques to automated models and traffic augmentation methods, researchers are continuously exploring ways to mitigate the risks posed by WF attacks.

Recent advancements in website fingerprinting (WF) attacks present a considerable threat to online anonymity,

even in privacy-focused systems like Tor. WF attacks rely on analyzing network traffic patterns to infer the websites users visit, despite encryption. This poses a significant vulnerability to both user privacy and anonymity. In response, [22] propose an innovative defense mechanism known as Random Bidirectional Padding (RBP). RBP employs time sampling and dummy packet padding in both directions to obscure the inter-arrival time (IAT) features that machine learning classifiers typically exploit in WF attacks. Their method significantly reduces the effectiveness of advanced WF techniques, such as Deep Fingerprinting (DF), lowering the accuracy of these attacks from 98% to 38%, representing a major leap in preserving user privacy on anonymous networks.

A comprehensive survey by [21] underscores the crucial role of WF attacks and defenses in privacy protection. The survey explores various deep learning models and architectures used in WF attacks, highlighting their effectiveness as well as the challenges, including multi-tab browsing and concept drift. It also reviews defensive strategies, emphasizing the trade-offs between performance and resource overhead when applying deep learning models. This survey serves as a valuable resource, offering insights into the intersection of deep learning and WF, and providing guidance for future research on privacy-enhancing technologies.

In [14], the authors address a key limitation in traditional WF attacks, known as the Single Page Assumption, which overlooks users' common practice of opening multiple tabs simultaneously. To overcome this, they developed an automated multi-tab WF attack that can accurately classify web traffic, even when several pages are open concurrently. Their approach leverages a split point classification technique to isolate traffic from the first opened page, improving the precision of the attack. Additionally, they introduce a chunk-based WF classifier that identifies websites based on initial clean traffic, underscoring the delicate balance between user anonymity and identification through digital fingerprints.

The study on [23] proposes a novel defense using Wasserstein Generative Adversarial Networks (WGAN) combined with a Genetic Algorithm (GA). This method generates adversarial samples to obscure web traffic, reducing the classification accuracy of WF attacks from 98% to 20-30%. Notably, the solution presented, WGAN-GA, achieves this significant reduction with only a 1% bandwidth overhead, making it more efficient compared to methods like Walkie-Talkie, which incurs a 31% overhead.

The study in [24] presents WebScanner, an advanced tool capable of detecting and isolating traffic flows corresponding to individual web pages and app loading sessions, even when multiple pages are accessed by the same device. Unlike traditional fingerprinting techniques that struggle with overlapping traffic, WebScanner disentangles concurrent sessions and uses machine learning-based fingerprinting to identify user actions. It achieves precision and recall rates above 95% for identifying the top 500 Alexa websites

TABLE 3. Summary of research on digital and web fingerprinting, attacks, defenses, and comparative analysis.

Paper	Focus	Key Features
Web Fingerprinting Attacks		
[31]	Trace attacks on anonymous networks	CNN-BiLSTM model, high accuracy and efficiency in WF attacks across Tor, JAP, and OpenVPN
[32]	Traffic analysis prevention	Spoofing strategies LRSO-Pad and DeOS, prevents traffic analysis in encrypted domains
[33]	Gene fingerprinting attack	Zero-shot learning (ZSL) for efficient cross-tunnel attacks, outperforms traditional WF attacks
[34]	Segmented Adversary Defense	Segments traffic sequence data, reduces WF attack accuracy from 96% to 3%
[35]	Local adversary detection	Deep learning methods achieve 98% detection accuracy, introduces Local Optimal Mutation (LOM) for defense
[36]	Deep learning-based WF attacks	Deep Fingerprinting (DF) with high accuracy, introduces Tiny WFP for dimensionality reduction
Web Fingerprinting Defenses		
[37]	Cloaked traffic defense	Genetic programming, inserts fake Tor cells, reduces attack success rate to below 0.4% with 8.1% bandwidth overhead
[38]	Lightweight protection (TED)	Uses adversarial examples, reduces WF attack accuracy by 40%, minimal additional network load
[39]	WF-UAP defense	Uses Universal Adversarial Perturbations (UAP), reduces WF attack accuracy from 98% to 15%, provides real-time protection
[40]	Traffic splitting strategies	Evaluates HyWF, ComPS, Traffic-Sliver BWR5, introduces Maturesc attack model for improved classification accuracy
[30]	Adaptive symbolization (PHMM)	Profile Hidden Markov Models (PHMM), preserves informational value, less time-consuming compared to traditional algorithms
[41]	Contemporary defense proposals	Examines defense proposals including DynaFlow within the Tor network, low operational overhead
[42]	Web tracking protection	Proposes an attack against RPD, introduces list-based protection and traffic sharing for improved security on popular browsers

and 92% for action-dependent app traffic, showcasing its effectiveness in monitoring encrypted network traffic.

The power of deep learning in WF attacks has significantly increased due to advancements like Neural Architecture Search (NAS). The study conducted on [25] explores the potential of NAS to enhance WF attacks, demonstrating that NAS-generated deep neural networks (DNNs) outperform the state-of-the-art Tik-Tok attack on undefended Tor traffic. In tests against defended traffic using the FRONT

random padding defense, AutoKeras-generated DNN models outperformed Tik-Tok by 5-8%, indicating that NAS could dramatically improve the adaptability and effectiveness of future WF attacks.

Maintaining high accuracy across diverse network conditions remains a challenge for WF attacks. Reference [26] addresses this issue by introducing NetAugment, an augmentation technique that generates network traces mimicking unobserved conditions such as changes in bandwidth or circuit configurations. Their approach enhances WF classifiers' accuracy in unpredictable environments. In closed-world scenarios with only five labeled samples, their self-supervised model, NetCLR, achieved 80% accuracy, surpassing the 64.4% accuracy of state-of-the-art models like Triplet Fingerprinting.

The introduction of Quick UDP Internet Connections (QUIC), particularly with HTTP/3, has improved latency and security over traditional TCP and TLS protocols. However, [27] reveals that QUIC is still vulnerable to WF attacks. They propose a QUIC-based WF technique that uses Automated Machine Learning (AutoML) to optimize feature selection, hyperparameter tuning, and model selection without manual intervention. Their method achieves impressive results, with an F1-score of 99.79% and precision of 92.60% in open-world scenarios, highlighting that even modern protocols remain susceptible to WF attacks.

The [28] explores how advanced feature manipulation can enhance website fingerprinting (WF) attacks on Tor, revealing critical vulnerabilities that compromise user anonymity in real-world scenarios. By focusing on onion service protocols and demonstrating that filtering out common connection-establishment packets significantly affects WF performance, the research highlights the nuanced impact of network traffic modifications. Despite achieving high effectiveness, the study acknowledges variability in real-world data and the challenges of scaling to large datasets, pointing to the need for further refinement in WF models and feature vectors. Performance optimization is also addressed, showing that equivalent accuracy can be maintained with fewer features, thus improving efficiency and reducing training time.

Finally, combating cache-based WF attacks, [29] introduces DefWeb, a defense mechanism that employs Variational Autoencoders (VAEs) and self-modifying code (SMC) to obfuscate website fingerprints. DefWeb significantly reduces attacker model accuracy to as low as 1.1% in simulations and 28.8% in real-world scenarios, across major browsers like Chrome, Firefox, and Tor. It achieves these results with a low-performance overhead of 9.5%, compared to 71.8% in previous methods, offering a practical and efficient solution for safeguarding user privacy.

Moreover, [30] presents an advanced method for identifying user actions through network traffic analysis using adaptive symbolization and Profile Hidden Markov Models (PHMM). This approach focuses on web transitions and packet distributions to construct detailed user action profiles,

TABLE 4. Comparison of the latest research on website fingerprinting defenses and attacks.

Paper	Methodology	Dataset Used	Key Findings	Limitations	Relevance to Digital Traces
	Techniques, models, or frameworks applied	Dataset type or source	Main results and contributions	Any identified weaknesses	How it contributes to or challenges current digital trace methodologies
[46]	Fusion of direction and length features, Enhanced Channel Attention mechanism	Few-shot datasets with 1-25 traces per website	Improved accuracy in few-shot scenarios; 81.16% precision in open-world	Requires auxiliary datasets for robust results	Enhances fingerprinting techniques in limited data environments.
[47]	Meta-learning with Ridge Regression, Task-adaptive Modulation Unit	Public Tor datasets	Maintains over 90% accuracy in 1-shot setting even after 42 days	Assumes single-tab browsing behavior	Introduces task-adaptive approaches to handle dynamic network environments.
[48]	Triplet network leveraging hard samples for classifier training	Real-world Tor traffic with distribution mismatches	Best recall rate of 98.43%, improved discrimination between monitored and unmonitored sites	Limited prior knowledge about user access sites	Focuses on real-world applicability by addressing distribution mismatches.
[49]	Joint learning framework with virtual fusion center	Multiple datasets from varied network conditions	Improves accuracy by 13.02% in closed-world, AUC by 0.085 in open-world	Challenges with Non-IID data across attackers	Enhances model adaptability through multi-attacker collaboration.
[50]	Object detection model (WFR-CNN) with S-matrix trace-to-image conversion	Manually merged multi-tab datasets	Achieves over 85% accuracy in two-tab settings	Assumes known number of tabs in browsing	Applies computer vision techniques to multi-tab website fingerprinting.
[51]	Causality correlation and context learning in multi-tab scenarios	Encrypted traffic datasets from Tor, VPN, SSH	14% improved accuracy in dynamic multi-tab settings	Limited adaptability in highly dynamic environments	Enhances WF robustness against packet loss and disorder
[52]	CNN-based model for closed and open-world scenarios	Tor traffic datasets	Achieves 98.2% accuracy in CW and 97.1% in OW	Focused on non-defended datasets, lacks generalizability against defenses	Demonstrates deep learning potential in non-defended WF contexts
[53]	Graph Neural Networks (GAT and SAGPool) for spatio-temporal correlation analysis	Real-world traffic dataset	Outperforms state-of-the-art methods in accuracy and time efficiency	Requires complex graph construction, impacting scalability	Introduces GNNs to model complex flow correlations for improved WF accuracy
[54]	Multi-channel feature representation with transformer-based attention models	Open-world dataset with obfuscated traffic	Achieves 96% accuracy against FRONT-defended traffic, 80% recall at 99% precision	Computational overhead due to multi-channel and transformer complexity	Advances WF attacks against defended traffic using multi-channel data
[55]	Probabilistic Graphical Models (PGMs) for scalable WF attacks	Large-scale dataset from 4,800 webpages across 96 sites	Precision and recall of 86.5% and 85.3% in CW, scalable to 424 pages/sec	Limited defense mechanisms tested, focus on scalability rather than defense resilience	Demonstrates feasibility of large-scale, real-time WF attacks using PGMs
[56]	Traffic cluster anonymization with k-anonymity sets	Real-world Tor traffic datasets	Reduces SOTA attack accuracy by 73.60%, improves defenses by 33.50%-43.47%	Limited adaptability in dynamic traffic	Provides real-time defense with minimal overhead using clustering techniques
[57]	Universal perturbations without traffic trace dependency	Public Tor datasets for closed and open-world scenarios	Reduces attack success rate to 12.68% in CW, 37.46% TPR in OW	Performance under advanced adversarial training scenarios requires further testing	Robust AE-based defense applicable in both CW and OW scenarios
[58]	Contrastive learning with few-shot learning for realistic attacks	Unlabeled Tor traffic for pre-training, small labeled sets for fine-tuning	Achieves 92.32% accuracy in CW, outperforms previous few-shot methods	Dependent on contrastive learning performance, possible overfitting in sparse data	Advances realistic WF attack scenarios with minimal labeled data.
[59]	Fuzzing-testing with gradient ascent for traffic morphing	Real-world Tor datasets for DL-based WF classifier evaluation	Decreases DL-based classifier accuracy to 4.43% with 11.04% bandwidth overhead	Requires continuous adaptation for evolving WF classifiers	Introduces fuzzing-testing as a novel defense approach against DL-based WF attacks.




FIGURE 4. The dual role of digital fingerprinting in balancing security and privacy.

improving the detection of user behaviors from encrypted traffic. By retaining critical information while reducing complexity, PHMM enhances accuracy in identifying both the web applications used and the specific actions taken by users, addressing the gaps in traditional fingerprinting methods.

Table 3 highlights foundational advancements in website fingerprinting (WF) attacks and defenses, demonstrating significant progress in each area. On the attack side, early innovations improved the accuracy and efficiency of fingerprinting methods, even within encrypted or anonymized networks. Meanwhile, defensive strategies focused on reducing the success rates of these attacks through obfuscation techniques and adversarial methods designed to protect user privacy. These developments marked the initial stages of a dynamic and evolving field, characterized by the continuous refinement of both offensive and defensive measures.

Building on this foundation, Table 4 summarizes the rapid evolution of WF research, showcasing more sophisticated attacks and increasingly robust defense mechanisms. The interplay between these advancements underscores the adversarial nature of the field, where each new attack methodology prompts the development of stronger, more adaptive defenses, and vice versa. As WF attacks become more effective at circumventing privacy protections, the focus has shifted towards real-time, adaptable defenses capable of responding to diverse network conditions. This cycle of innovation highlights the importance of maintaining a proactive stance in both offensive and defensive research, ensuring that privacy measures keep pace with emerging threats.

Together, the research captured in these tables emphasizes the critical need for ongoing monitoring and adaptation in the field of digital privacy, reflecting the continuously shifting landscape of cybersecurity challenges.

IV. CONCLUSION

In conclusion, digital traces play a critical role in cybersecurity by bridging the gap between anonymity and identification. As online activities continue to evolve, the ability to create unique digital profiles from device, browser, and behavioral data offers both opportunities for enhanced

security and challenges in maintaining privacy. While digital fingerprinting provide a powerful tool for identifying users, detecting fraud, and enhancing multi-factor authentication, they also raise significant concerns about surveillance and data misuse. As regulatory frameworks like GDPR push for stricter privacy standards, balancing the benefits of personalized security with the need to protect user anonymity becomes increasingly vital.

Building on these insights, this study provides a comprehensive analysis of digital fingerprinting technologies and their dual role in enhancing cybersecurity while posing privacy challenges. By tracing the evolution of tracking methods, we identify critical advancements in device, browser, and behavioral fingerprinting. Our findings underscore the importance of balancing personalization benefits with privacy-preserving techniques, especially as these technologies continue to evolve. Future research should focus on developing robust privacy-enhancing technologies and exploring policy frameworks to address the ethical implications of fingerprinting in diverse applications. We hope this paper serves as a foundation for both researchers and practitioners striving to reconcile the tensions between security and anonymity in the digital age.

Figure 4 visually represents the dual nature of digital fingerprinting. On the left, security benefits such as multi-factor authentication, fraud detection, and user identification are highlighted. On the right, privacy concerns like surveillance risks, data misuse, and loss of anonymity are presented. The intersection at Digital Fingerprinting illustrates where these aspects converge, emphasizing the need for balance. The Future Focus section suggests directions for future research, including privacy-enhancing technologies, ethical guidelines, and policy frameworks to mitigate risks while preserving security benefits.

A. KEY INSIGHTS AND IMPLICATIONS

The findings of this study shed light on several critical insights and their broader implications for the cybersecurity landscape. These insights highlight both the strengths and challenges of digital fingerprinting technologies, underscoring the importance of a balanced approach that leverages

security benefits while addressing privacy concerns. The following key points summarize the most significant aspects uncovered through our analysis:

- **Security Enhancements** - digital fingerprints significantly bolster security frameworks, offering robust tools for user identification and fraud prevention. These technologies are pivotal in securing online transactions and protecting against unauthorized access.
- **Privacy Concerns** - despite their security benefits, digital fingerprints pose significant risks to user privacy. The potential for misuse, unauthorized tracking, and data breaches necessitates stringent privacy protections and ethical considerations.
- **Regulatory Landscape** - with regulatory frameworks enforcing stricter data privacy standards, there is an urgent need to develop privacy-enhancing technologies that align with these regulations while maintaining the efficacy of digital fingerprinting.

B. FUTURE RESEARCH PRIORITIES

To address the evolving landscape of digital fingerprinting, future research should focus on:

- 1) **Developing Adaptive Fingerprinting Models** - creating systems that adjust dynamically to user behavior changes while minimizing false positives and negatives.
- 2) **Innovating Cross-Platform Privacy Solutions** - designing techniques to unify fragmented digital traces across multiple devices without compromising privacy.
- 3) **Formulating Ethical Frameworks** - establishing comprehensive guidelines that ensure responsible and transparent use of digital fingerprints, emphasizing user consent and data security.
- 4) **Strengthening Resilience Against Synthetic Behaviors** - enhancing detection mechanisms to counter AI-generated behavioral patterns intended to bypass fingerprinting systems.

C. OPEN CHALLENGES

Despite significant advancements, several challenges remain in the realm of digital fingerprinting:

- 1) **Dynamic User Behavior**: User behavior on the internet is dynamic and context-dependent, influenced by changes in devices, environments, or personal habits. Ensuring that digital fingerprinting systems remain accurate and effective despite these variations is a significant challenge.
- 2) **False Positives and Negatives**: Behavioral digital fingerprints can sometimes lead to misidentification due to similar patterns between different users or changes in a user's typical behavior. Developing models that minimize such errors while maintaining high accuracy is critical.
- 3) **Cross-Platform Integration**: Users frequently switch between devices and platforms, creating fragmented behavioral patterns. Developing methods to link and

unify these fragmented traces without compromising privacy is a complex but essential area for research.

- 4) **Privacy and Ethics**: The use of digital fingerprints inherently involves profiling user behavior, raising ethical questions about consent, fairness, and potential misuse. Establishing ethical guidelines and ensuring compliance with privacy regulations are critical for the responsible deployment of these systems.
- 5) **Resilience Against Synthetic Behaviors**: With advancements in AI, attackers can generate synthetic behavioral patterns or mimic legitimate users to bypass digital fingerprinting systems. Enhancing detection mechanisms to identify such fabricated or impersonated behaviors is an ongoing challenge.

Addressing these open challenges will require a multidisciplinary approach, combining advances in machine learning, cryptography, and human-computer interaction with insights from privacy law and ethics.

REFERENCES

- [1] D. M. Kristol, "HTTP cookies," *ACM Trans. Internet Technol.*, vol. 1, no. 2, pp. 151–198, Nov. 2001, doi: [10.1145/502152.502153](https://doi.org/10.1145/502152.502153).
- [2] N. Nikiforakis, A. Kapravelos, W. Joosen, C. Kruegel, F. Piessens, and G. Vigna, "Cookieless monster: Exploring the ecosystem of web-based device fingerprinting," in *Proc. IEEE Symp. Secur. Privacy*, May 2013, pp. 541–555, doi: [10.1109/SP.2013.43](https://doi.org/10.1109/SP.2013.43).
- [3] J. R. Mayer and J. C. Mitchell, "Third-party web tracking: Policy and technology," in *Proc. IEEE Symp. Secur. Privacy*, May 2012, pp. 413–427, doi: [10.1109/SP.2012.47](https://doi.org/10.1109/SP.2012.47).
- [4] S. Englehardt and A. Narayanan, "Online tracking," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur.*, Oct. 24, 2016, pp. 1388–1401, doi: [10.1145/2976749.2978313](https://doi.org/10.1145/2976749.2978313).
- [5] P. Eckersley, "How unique is your web browser?" in *Privacy Enhancing Technologies*. Berlin, Germany: Springer, 2010, pp. 1–18, doi: [10.1007/978-3-642-14527-8](https://doi.org/10.1007/978-3-642-14527-8).
- [6] G. Acar, C. Eubank, S. Englehardt, M. Juarez, A. Narayanan, and C. Diaz, "The web never forgets," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur.*, Nov. 3, 2014, pp. 674–689, doi: [10.1145/2660267.2660347](https://doi.org/10.1145/2660267.2660347).
- [7] M. S. Pour and E. Bou-Harb, "Fingerprinting IoT devices with machine learning," in *Encyclopedia of Machine Learning and Data Science*. Cham, Switzerland: Springer, 2021, pp. 1–4, doi: [10.1007/978-1-4899-7502-7_985-1](https://doi.org/10.1007/978-1-4899-7502-7_985-1).
- [8] M. Sjöberg, H. H. Chen, P. Floren, M. Koskela, K. Kuikkaniemi, T. Lehtiniemi, and J. Peltonen, "Digital me: Controlling and making sense of my digital footprint," in *Symbiotic Interaction (Lecture Notes in Computer Science)*. Cham, Switzerland: Springer, 2017, pp. 155–167, doi: [10.1007/978-3-319-57753-1_14](https://doi.org/10.1007/978-3-319-57753-1_14).
- [9] A. Malhotra, L. Totti, W. Meira Jr., P. Kumaraguru, and V. Almeida, "Studying user footprints in different online social networks," in *Proc. IEEE/ACM Int. Conf. Adv. Social Netw. Anal. Mining*, Aug. 2012, pp. 1065–1070, doi: [10.1109/ASONAM.2012.184](https://doi.org/10.1109/ASONAM.2012.184).
- [10] T. Berg, V. Burg, A. Gombavi, and M. Puri, "On the rise of FinTechs: Credit scoring using digital footprints," *Rev. Financial Stud.*, vol. 33, no. 7, pp. 2845–2897, Jul. 2020, doi: [10.1093/rfs/hhz099](https://doi.org/10.1093/rfs/hhz099).
- [11] T. Grover and G. Mark, "Digital footprints," in *Proc. ACM Int. Joint Conf. Pervasive Ubiquitous Comput. Proc. ACM Int. Symp. Wearable Comput.*, Sep. 11, 2017, pp. 41–44, doi: [10.1145/3123024.3123139](https://doi.org/10.1145/3123024.3123139).
- [12] J. Li, Z. Lin, J. Qu, S. Wu, H. Zhou, Y. Liu, X. Ma, T. Wang, X. Luo, and X. Guan, "Robust app fingerprinting over the air," *IEEE/ACM Trans. Netw.*, vol. 32, no. 6, pp. 5065–5080, Dec. 2024, doi: [10.1109/TNET.2024.3448621](https://doi.org/10.1109/TNET.2024.3448621).
- [13] B. Hamdaoui and A. Elmaghbbub, "Deep-learning-based device fingerprinting for increased LoRa-IoT security: Sensitivity to network deployment changes," *IEEE Netw.*, vol. 36, no. 3, pp. 204–210, May 2022, doi: [10.1109/MNET.001.2100553](https://doi.org/10.1109/MNET.001.2100553).

- [14] Q. Yin, Z. Liu, Q. Li, T. Wang, Q. Wang, C. Shen, and Y. Xu, "An automated multi-tab website fingerprinting attack," *IEEE Trans. Dependable Secure Comput.*, vol. 19, no. 6, pp. 3656–3670, Nov. 01, 2022, doi: [10.1109/TDSC.2021.3104869](#).
- [15] C. Yang, L. Wang, H. Cao, Q. Yuan, and Y. Liu, "User behavior fingerprinting with multi-item-sets and its application in IPTV viewer identification," *IEEE Trans. Inf. Forensics Security*, vol. 16, pp. 2667–2682, 2021, doi: [10.1109/TIFS.2021.3055638](#).
- [16] B. Bezawada, I. Ray, and I. Ray, "Behavioral fingerprinting of Internet-of-Things devices," *WIREs Data Mining Knowl. Discovery*, vol. 11, no. 1, Sep. 30, 2019, Art. no. e1337, doi: [10.1002/widm.1337](#).
- [17] S. Aneja, N. Aneja, B. Bhargava, and R. R. Chowdhury, "Device fingerprinting using deep convolutional neural networks," *Int. J. Commun. Netw. Distrib. Syst.*, vol. 28, no. 2, p. 171, 2022, doi: [10.1504/ijcnds.2022.121197](#).
- [18] S. Wan, Q. Li, H. Wang, H. Li, and L. Sun, "DevTag: A benchmark for fingerprinting IoT devices," *IEEE Internet Things J.*, vol. 10, no. 7, pp. 6388–6399, Apr. 1, 2023, doi: [10.1109/IJOT.2022.3225580](#).
- [19] C. Kuzniar, M. Neves, V. Gurevich, and I. Haque, "IoT device fingerprinting on commodity switches," in *Proc. IEEE/IFIP Netw. Operations Manage. Symp. (NOMS)*, Apr. 25, 2022, pp. 1–9, doi: [10.1109/NOMS54207.2022.9789865](#).
- [20] A. Nazerian and F. Parastar, "Passive IoT device fingerprinting using WiFi," in *Proc. 12th ACM Wireless Students, Students, Students (S3) Workshop*, Oct. 25, 2021, pp. 6–7, doi: [10.1145/3477087.3478381](#).
- [21] P. Liu, L. He, and Z. Li, "A survey on deep learning for website fingerprinting attacks and defenses," *IEEE Access*, vol. 11, pp. 26033–26047, 2023, doi: [10.1109/ACCESS.2023.3253559](#).
- [22] T. Luo, L. Wang, S. Yin, H. Shentu, and H. Zhao, "RBP: A website fingerprinting obfuscation method against intelligent fingerprinting attacks," *J. Cloud Comput.*, vol. 10, no. 1, May 20, 2021, Art. no. 29, doi: [10.1186/s13677-021-00244-8](#).
- [23] H. Bai, J. Yi, and R. Chen, "Web site fingerprint attack generation technology combined with genetic algorithm," *Electronics*, vol. 12, no. 6, p. 1449, Mar. 19, 2023, doi: [10.3390/electronics12061449](#).
- [24] P. Casas, N. Wehner, S. Wassermann, and M. Seufert, "Fingerprinting web pages and smartphone apps from encrypted network traffic with webscanner," in *Proc. IEEE 11th Int. Conf. Cloud Netw. (CloudNet)*, Nov. 07, 2022, pp. 1–9, doi: [10.1109/CLOUDNET55617.2022.9978877](#).
- [25] P. Singh, S. A. Naik, N. Malekghani, D. Barradas, and N. Limam, "A first look at generating website fingerprinting attacks via neural architecture search," in *Proc. 22nd Workshop Privacy Electron. Soc.*, Nov. 26, 2023, pp. 173–178, doi: [10.1145/3603216.3624961](#).
- [26] A. Bahramali, A. Bozorgi, and A. Houmansadr, "Realistic website fingerprinting by augmenting network traces," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur.*, Nov. 15, 2023, pp. 1035–1049, doi: [10.1145/3576915.3616639](#).
- [27] J. Ha and H. Roh, "QUIC website fingerprinting based on automated machine learning," *ICT Exp.*, vol. 10, no. 3, pp. 594–599, Jun. 2024, doi: [10.1016/j.ict.2023.12.008](#).
- [28] D. Kim, A. Booth, O. Akinyemi, E. Choo, and D. Hwang, "Website fingerprinting attacks with advanced features on tor networks," in *Proc. Cyber Awareness Res. Symp. (CARS)*, Oct. 28, 2024, pp. 1–6, doi: [10.1109/cars61786.2024.10778686](#).
- [29] S. Seonghun, D. D. Roy, and G. Berk, "DefWeb: Defending user privacy against cache-based website fingerprinting attacks with intelligent noise injection," in *Proc. Annu. Comput. Secur. Appl. Conf.*, Dec. 4, 2023, pp. 379–393, doi: [10.1145/3627106.3627191](#).
- [30] X. Yang, J. Xu, and G. Li, "Efficient fingerprinting attack on web applications: An adaptive symbolization approach," *Electronics*, vol. 12, no. 13, p. 2948, Jul. 4, 2023, doi: [10.3390/electronics12132948](#).
- [31] M. Guo and J. Fei, "Website fingerprinting attacks based on homology analysis," *Secur. Commun. Netw.*, vol. 2021, pp. 1–14, Oct. 04, 2021, doi: [10.1155/2021/6070451](#).
- [32] W. Yang, Z. Du, Y. Wu, and Y. Tang, "Confusing traffic against intradomain webpage fingerprinting attacks," in *Proc. IEEE Int. Conf. Trust, Secur. Privacy Comput. Commun. (TrustCom)*, Dec. 2022, pp. 1249–1254, doi: [10.1109/TRUSTCOM56396.2022.00173](#).
- [33] D. Li, C. Gu, and Y. Zhu, "Gene fingerprinting: Cracking encrypted tunnel with zero-shot learning," *IEICE Trans. Inf. Syst.*, vol. 105, no. 6, pp. 1172–1184, Jun. 1, 2022, doi: [10.1587/transinf.2021edp7179](#).
- [34] R. Tang, G. Shen, C. Guo, and Y. Cui, "SAD: Website fingerprinting defense based on adversarial examples," *Secur. Commun. Netw.*, vol. 2022, pp. 1–12, Apr. 7, 2022, doi: [10.1155/2022/7330465](#).
- [35] J. Wang, Y. Zhu, W. Lin, D. Li, and K. Tang, "LOM: A website fingerprinting defense method based on local optimal mutation," in *Proc. IEEE 10th Joint Int. Inf. Technol. Artif. Intell. Conf. (ITAIC)*, vol. 10, Jun. 17, 2022, pp. 1445–1451, doi: [10.1109/ITAIC54216.2022.9836674](#).
- [36] C. Tian, D. Ye, and C. Chen, "Tiny WFP: Lightweight and effective website fingerprinting via wavelet multi-resolution analysis," in *Applied Cryptography and Network Security*. Cham, Switzerland: Springer, 2023, pp. 237–259, doi: [10.1007/978-3-031-33488-7_9](#).
- [37] Z. Ling, G. Xiao, W. Wu, X. Gu, M. Yang, and X. Fu, "Towards an efficient defense against deep learning based website fingerprinting," in *Proc. IEEE Conf. Comput. Commun.*, May 2, 2022, pp. 310–319, doi: [10.1109/INFOCOM48880.2022.9796685](#).
- [38] C. Jiang, Z. Gao, and M. Shen, "Effective and lightweight defenses against website fingerprinting on encrypted traffic," in *Data Science (Communications in Computer and Information Science)*. Singapore: Springer, 2022, pp. 33–46, doi: [10.1007/978-981-19-5209-8_3](#).
- [39] B. Sun, W. Yang, M. Yan, Y. Zhu, and Z. Bai, "A practical website fingerprinting defense approach with universal adversarial perturbations," in *Proc. 7th Int. Conf. Comput. Commun. Syst. (ICCCS)*, Apr. 22, 2022, pp. 752–760, doi: [10.1109/ICCCS55155.2022.9846237](#).
- [40] M. Beckerle, J. Magnusson, and T. Pulls, "Splitting hairs and network traces," in *Proc. 21st Workshop Privacy Electron. Soc.*, Nov. 7, 2022, pp. 15–27, doi: [10.1145/3559613.3563199](#).
- [41] N. Mathews, J. K. Holland, S. E. Oh, M. S. Rahman, N. Hopper, and M. Wright, "SoK: A critical evaluation of efficient website fingerprinting defenses," in *Proc. IEEE Symp. Secur. Privacy (SP)*, May 2023, pp. 969–986, doi: [10.1109/SP46215.2023.10179289](#).
- [42] G. Huang, C. Ma, M. Ding, Y. Qian, C. Ge, L. Fang, and Z. Liu, "Efficient and low overhead website fingerprinting attacks and defenses based on TCP/IP traffic," in *Proc. ACM Web Conf.*, Apr. 30, 2023, pp. 1991–1999, doi: [10.1145/3543507.3583200](#).
- [43] D. Zhang, J. Zhang, Y. Bu, B. Chen, C. Sun, and T. Wang, "A survey of browser fingerprint research and application," *Wireless Commun. Mobile Comput.*, vol. 2022, pp. 1–14, Nov. 9, 2022, doi: [10.1155/2022/3363335](#).
- [44] N. Andriamianto, T. Allard, G. Le Guelvouit, and A. Garel, "A large-scale empirical analysis of browser fingerprints properties for web authentication," *ACM Trans. Web*, vol. 16, no. 1, pp. 1–62, Sep. 28, 2021, doi: [10.1145/3478026](#).
- [45] S. Wu, P. Sun, Y. Zhao, and Y. Cao, "Him of many faces: Characterizing billion-scale adversarial and benign browser fingerprints on commercial websites," in *Proc. Netw. Distrib. Syst. Secur. Symp.*, 2023, pp. 1–16, doi: [10.14722/NDSS.2023.24394](#).
- [46] Z. Wang, T. Li, M. Yin, X. Yuan, X. Luo, and L. Li, "WF3A: A N-shot website fingerprinting with effective fusion feature attention," *Comput. Secur.*, vol. 140, May 2024, Art. no. 103796, doi: [10.1016/j.cose.2024.103796](#).
- [47] Q. Lyu, H. Xie, W. Wang, Y. Cheng, Y. Chen, and Z. Wang, "TFAN: A task-adaptive feature alignment network for few-shot website fingerprinting attacks on Tor," *Comput. Secur.*, vol. 144, Sep. 2024, Art. no. 103980, doi: [10.1016/j.cose.2024.103980](#).
- [48] X. Yuan, T. Li, L. Li, R. Li, Z. Wang, and X. Luo, "HSWF: Enhancing website fingerprinting attacks on tor to address real world distribution mismatch," *Comput. Netw.*, vol. 241, Mar. 2024, Art. no. 110217, doi: [10.1016/j.comnet.2024.110217](#).
- [49] J. Tan, H. Wang, S. Han, D. Man, and W. Yang, "An adaptability-enhanced few-shot website fingerprinting attack based on collusion," *IEEE Trans. Inf. Forensics Security*, vol. 19, pp. 8220–8235, 2024, doi: [10.1109/TIFS.2024.3433586](#).
- [50] Y. Xu, L. Wang, J. Chen, and Q. Zhou, "Tor trace in images: A novel multi-tab website fingerprinting attack with object detection," *Comput. J.*, vol. 67, no. 8, pp. 2690–2701, May 4, 2024, doi: [10.1093/comjnl/bxae037](#).
- [51] S. Chen, S. Chen, H. He, X. Jiang, J. Yang, and S. Cheng, "Causality correlation and context learning aided robust lightweight multi-tab website fingerprinting over encrypted tunnel," in *Proc. IEEE Conf. Comput. Commun.*, May 20, 2024, pp. 761–770, doi: [10.1109/INFOCOM52122.2024.10621235](#).
- [52] M. Sinha and M. Dave, "Enhanced non-defended website fingerprinting attack model using deep learning," in *Proc. Int. Conf. Intell. Syst. Cybersecur. (ISCS)*, May 3, 2024, pp. 1–6, doi: [10.1109/iscs61804.2024.10581233](#).
- [53] X. Tan, C. Peng, P. Xie, H. Wang, M. Li, S. Chen, and C. Zou, "Inter-flow spatio-temporal correlation analysis based website fingerprinting using graph neural network," *IEEE Trans. Inf. Forensics Security*, vol. 19, pp. 7619–7632, 2024, doi: [10.1109/TIFS.2024.3441935](#).

- [54] N. Mathews, J. K. Holland, N. Hopper, and M. Wright, "Laserbeak: Evolving website fingerprinting attacks with attention and multi-channel feature representation," *IEEE Trans. Inf. Forensics Security*, vol. 19, pp. 9285–9300, 2024, doi: [10.1109/TIFS.2024.3468171](https://doi.org/10.1109/TIFS.2024.3468171).
- [55] P. Krämer, B. Baier, N. Landerer, P. Diederich, A. Griessel, O. Hohlfeld, A. Blenk, M. Mieth, and W. Kellerer, "ProFi: Scalable and efficient website fingerprinting," *IEEE Trans. Netw. Service Manage.*, vol. 21, no. 1, pp. 1271–1286, Feb. 2024, doi: [10.1109/TNSM.2023.3318508](https://doi.org/10.1109/TNSM.2023.3318508).
- [56] M. Shen, K. Ji, J. Wu, Q. Li, X. Kong, K. Xu, and L. Zhu, "Real-time website fingerprinting defense via traffic cluster anonymization," in *Proc. IEEE Symp. Secur. Privacy (SP)*, May 19, 2024, pp. 3238–3256, doi: [10.1109/SP54263.2024.00247](https://doi.org/10.1109/SP54263.2024.00247).
- [57] L. Qiao, B. Wu, H. Li, C. Gao, W. Yuan, and X. Luo, "Trace-agnostic and adversarial training-resilient website fingerprinting defense," in *Proc. IEEE Conf. Comput. Commun.*, May 20, 2024, pp. 211–220, doi: [10.1109/INFOCOM52122.2024.10621205](https://doi.org/10.1109/INFOCOM52122.2024.10621205).
- [58] S. Wang, Z. Wang, C. Li, D. Han, J. Yang, and H. Zhang, "TrafficSiam: More realistic few-shot website fingerprinting attack with contrastive learning," in *Proc. IEEE Netw. Oper. Manage. Symp. (NOMS)*, May 6, 2024, pp. 1–9, doi: [10.1109/NOMS59830.2024.10575874](https://doi.org/10.1109/NOMS59830.2024.10575874).
- [59] Z. Ling, G. Xiao, L. Luo, R. Wang, X. Xu, and G. Liu, "WFGuard: An effective fuzzing-testing-based traffic morphing defense against website fingerprinting," in *Proc. IEEE Conf. Comput. Commun.*, May 20, 2024, pp. 441–450, doi: [10.1109/INFOCOM52122.2024.10621121](https://doi.org/10.1109/INFOCOM52122.2024.10621121).



ARBENA MUSA received the master's degree in computer engineering, with a specialization in cybersecurity from the University of Pristina, Kosovo, where she is currently pursuing the Ph.D. degree in computer engineering. She is a Software Engineer and a Teaching Assistant with the University of Pristina. In addition to her academic responsibilities, she has contributed to various cybersecurity projects and is actively involved in mentoring students in the areas of secure software development and data protection. Her research interests include digital privacy, cybersecurity, and the impact of digital fingerprinting on user anonymity.



KAMER VISHI received the Ph.D. degree in cybersecurity from the University of Oslo, Norway. He is currently the Senior Security Operations Manager with The Norwegian Agency for Local Governments (KBN). He has a background in digital forensics and cyber threat intelligence with Sykehuspartner CERT. He is a Security Researcher with the University of Oslo, specializing in biometrics, privacy, cyber defense, post-quantum cryptography, and machine learning.



EDLIRA MARTIRI received the two Ph.D. degrees from the University of Tirana, in 2016 and NTNU, Norway, in 2022, respectively. She has a background in the fields of IT and information security. Her both dissertations focused on new algorithms for data protection, the first one on images, and the second one on template protection and machine learning, showcasing her expertise in the field of information security. For several years, she was a Research Fellow with NTNU. In this role, she designed, tested, and developed a new scheme for protecting sensitive data in biometric databases and adhering to industry standards. Her responsibilities and tasks throughout her career also included threat analysis, modeling attacker scenarios, designing defense strategies, risk management, vulnerability assessment, teaching and research, project management, and IT consultant in international organizations and companies.



BLERIM REXHA received the Ph.D. degree in data and web service security from the Institute of Computer Technology, Vienna University of Technology, in 2004. He is a Full Professor with the Faculty of Electrical and Computer Engineering, University of Pristina, Kosovo. During his decade-long tenure in Austria, he worked with several leading tech companies, including Siemens AG, where he contributed to the Program and System Engineering Department, Vienna. He has published in several international journals and conferences within his research domains and has been invited as a guest speaker at both national and international events. His current teaching portfolio includes courses on data, computer, and internet security.

...