Assignment Web Similarity Analysis

Generated on 2025-03-25 14:59:56

Executive Summary

Overall Web Similarity Score: 0%

Assessment: The assignment shows no significant similarity to the provided web sources.

Conclusion: Based on the analysis against the provided web sources, there is no evidence of plagiarism in the submitted assignment. The assignment content focuses on control system design calculations and observations from a laboratory experiment, which is unique and distinct from the content of the web pages provided. The formulas, equations, and specific numerical values presented in the assignment are not found in the web sources. While some common phrases like 'Table', 'Figure', and mathematical symbols might appear in both, these are considered common knowledge within an academic context and do not constitute plagiarism. It is important to note that this analysis only considers the provided web pages and does not preclude the possibility of similarity with other sources not provided.

Web Sources Analyzed

Source URL	Similarity Score	
https://www.emo.org.tr/ekler/b7e76e55da0d599_ek.pdf?tipi=1&turu=X⊆=	6 1	.79%
https://www.youtube.com/watch?v=YH4Pj8s9pQU&pp=ygUTl3NlY29uZG9yZ0	G¥foothfJboYo2V≠zgrve&i3£00	∕83% 0
https://pmc.ncbi.nlm.nih.gov/articles/PMC3326359/	2	6.54%

Detailed Content Matches

No specific content matches were identified.

Full Assignment with Highlighted Plagiarism

Sections highlighted in yellow with red text indicate potential plagiarism.

EE5351: CONTROL SYSTEM DESIGN LABORATORY 01

NAME

: BANDARA LRTD

REG No.

: EG/ 2021/ 4433

GROUP NO: CE07

DATE

: 24/01 /2025

Table 1: Summative Laboratory Form

Semester

Module Code

Module Name

Lab Number

Lab Name

Lab conduction date

Report Submission date

05

EE5351

Control System Design

01

Laboratory Section 1

2024.11.05

2025.01.24

Contents

1

OBSERVATION

6

2

CALCULATION

7

List of Tables

Table 1: Summative Laboratory Form

Table 2: Observations

6

List of Figures

Figure 1: MathLab code for the Speed Response

```
Figure 2: Speed Response Get by Mathlab
Figure 3: Speed Response Given by Simulink
Figure 4: Speed Response in the Model
Figure 5: Comparing of the Speed Response with Model and State Vector
Figure 6: The Speed Response when KP=1
Figure 7: Speed Response from Simulink when KP=1.25
Figure 8: Speed Response from Simulink when KP=1.50
Figure 9: Speed Response from Simulink when KP=1.75
Figure 10: Speed Response from Simulink when KP=2.0
8
8
8
11
11
12
13
13
14
14
1 OBSERVATION
Table 1: Observations
Terminal Resistance (Rm)
Rotor inductance (Lm)
Equivalent(Jen)
Torque constant (Kt)
Voltage constant (Km)
8.4
1.16
2.09×10■■
0.042
0.042
Ω
mΗ
kgm<sup>2</sup>
Nm/A
Nm/A
2 CALCULATION
Q1.
i
1. Voltage equation:
```

+

```
\blacksquare \blacksquare = \blacksquare \blacksquare \omega \blacksquare
3. Torque equation:
\blacksquare \omega
4. Motor torque relationship:
ii From equations (1), (2), (3), and (4), the speed control transfer function is derived as:
ω(■)
\blacksquare \blacksquare (\blacksquare) \blacksquare \blacksquare \blacksquare \blacksquare [\blacksquare \blacksquare + \blacksquare \blacksquare] + \blacksquare \blacksquare \blacksquare
ω(■)
0.042
=
-5
■■ (■) 2.09 \times 10 = [8.4 + 1.16 \times 10 - 3] + 0.042 \times 0.042
ω(■)
0.042
=
-8
2
■■ (■) 2.4244 \times 10 = +17.556 \times 10-5 = +1.764 \times 10-3
From equations (1), (2), (3), and (4):
θ■ (■)
\blacksquare \blacksquare (\blacksquare) \blacksquare \{\blacksquare \blacksquare \blacksquare \blacksquare [\blacksquare \blacksquare + \blacksquare \blacksquare \blacksquare] + \blacksquare \blacksquare \blacksquare \}
θ■ (■)
0.042
■■ (■) 2.4244 \times 10-8 = 3 + 17.556 \times 10-5 = 2 + 1.764 \times 10-3 = 10 \times 10^{-2}
iii
Figure 1: MathLab code for the Speed Response
Figure 2: Speed Response Get by Mathlab
Figure 3: Speed Response Given by Simulink
iν
Simplified Equations for Speed Control Transfer Function
ω(■)
ω(■)
```

2. Back EMF equation:

0.042

```
\blacksquare \blacksquare (\blacksquare) {2.09 × 10–5 · 8.4\blacksquare + 0.042 × 0.042}
ω(■)
0.042
=
-4
\blacksquare (\blacksquare) {1.7556 × 10 \blacksquare + 1.764 × 10–3 }
Simplified Equations for Position Control Transfer Function
θ■ (■)
θ■ (■)
0.042
=
■■ (■) ■{1.7556 × 10–4 ■ + 1.764 × 10–3 }
νi
From the equations 1, 2, 3, 4;
\blacksquare \blacksquare \blacksquare = - () \blacksquare \blacksquare - () \omega \blacksquare +
\blacksquare = () \blacksquare \blacksquare + 0 \times \omega \blacksquare + 0 \times \blacksquare \blacksquare
■eq
– (■ ■)
[■]=[■
(■)
- (■■ )
■eq
-7241.38
```

=

[■]=[

```
2009.57
0
 1
]\,[\,\,\blacksquare\,\,]\,+\,[\,\blacksquare\blacksquare\,\,]\,\,\blacksquare\blacksquare
0
-36.21 ■■
862.07
][]+[
]
0
 0
 vii
 From the simplified equations
 \theta \blacksquare \blacksquare = 0 \cdot \theta \blacksquare + \omega \blacksquare + 0 \cdot \blacksquare \blacksquare
\omega
\blacksquare = 0 \cdot \theta \blacksquare - (
) ω■ + (
)■
■■ ■eq
■eq ■■ ■
0
[] = [0
1
0
-\left(\blacksquare\blacksquare\right)]\left[\blacksquare\blacksquare\right]+\left[\left(\blacksquare\blacksquare\blacksquare\right)\right]\blacksquare\blacksquare
■ eq
```

eq ■

```
0
1
[■] = [
][■]+[
0 - 10.05
239.23 ■
Q2.
Figure 4: Speed Response in the Model
Figure 5: Comparing of the Speed Response with Model and State
Vector
2. According to my knowledge I think the basic thing for happening those kind of
the error is negiligence of the resistance where having in the rotor and also
mathlab is the software which required the best performance of the computers so
considering the computers which has been used there can be errors as the
performance.
Q3)
1.
Figure 6: The Speed Response when KP=1
2.
Steady State Error:
Overshoot =
1-0.938
1.335-0.938
0.938
= 42.324%
× 100%
0.062
3.
Figure 7: Speed Response from Simulink when KP=1.25
According to the Figure 5 when Kp = 1.25,
```

Steady state error = 1-1.012 = 0.012 Overshoot =

```
1.374-1.012
1.012
× 100%
= 35.770%
Figure 8: Speed Response from Simulink when KP=1.50
According to the Figure 6 when Kp = 1.5,
Steady state error = 1-1.009 = 0.009
Overshoot =
1.405-1.009
1.009
= 39.25%
× 100%
Figure 9: Speed Response from Simulink when KP=1.75
According to the Figure 7 when Kp = 1.75,
Steady state error = 1-0.96
=
0.04
Overshoot =
1.442-0.9603
0.9603
× 100%
= 50.161%
Figure 10: Speed Response from Simulink when KP=2.0
According to the Figure 8 when Kp = 2,
Steady state error = 3.35 \times 10-2
Overshoot =
1.466-0.9633
0.9633
= 52.19%
```

× 100%

Analysis Methodology

Web Similarity Analysis Method: This report analyzes the similarity between a student assignment and web content using multiple approaches:

- 1. **Basic similarity analysis** using TF-IDF vectorization and cosine similarity metrics to calculate statistical similarity between texts.
- 2. **Advanced semantic analysis** using Google's Gemini AI to identify conceptual similarities, common phrases, and potential plagiarism patterns.
- 3. **Source verification** by analyzing multiple sources to distinguish between common knowledge and unique content.

Interpretation Guide:

- 0-15%: Very low similarity Likely original content
- 16-30%: Low similarity Contains common phrases but largely original
- 31-50%: Moderate similarity May contain some paraphrased content
- 51-70%: High similarity Contains substantial similar content
- 71-100%: Very high similarity Significant portions may be unoriginal

Disclaimer: This automated similarity analysis provides an approximation of content similarity against web sources. Results should be interpreted by a human reviewer for context-appropriate assessment. Common knowledge, standard phrases, and coincidental matches may be flagged and require human judgment.