



Analysis of Algorithms




Running Time

- ❑ Most algorithms transform input objects into output objects.
- ❑ The running time of an algorithm typically **grows** with the input **size**.
- ❑ Average case time is often difficult to determine.
- ❑ We focus on the **worst case** running time.
 - Easier to analyze
 - Crucial to applications such as games, finance and robotics



Experimental Studies

- Write a program implementing the algorithm
- Run the program with inputs of varying **size and composition**
- Use a method like `System.currentTimeMillis()` to get an accurate measure of the actual running time
- Plot the results




Limitations of Experiments

- It is necessary to **implement** the algorithm, which may be difficult
- Results may **not** be indicative of the running time on other inputs not included in the experiment.
- In order to compare two algorithms, the **same** hardware and software environments must be used



Theoretical Analysis



- ❑ Uses a high-level description of the algorithm instead of an implementation
- ❑ Characterizes **running time as a function of the input size, n .**
- ❑ Takes into account **all possible inputs**
- ❑ Allows us to evaluate the speed of an algorithm **independent** of the hardware/software environment

Pseudocode

- ❑ High-level description of an algorithm
- ❑ More structured than English prose
- ❑ Less detailed than a program
- ❑ Preferred notation for describing algorithms
- ❑ Hides program design issues

Example: find max element of an array

Algorithm *arrayMax*(*A*, *n*)

Input array *A* of *n* integers

Output maximum element of *A*

currentMax $\leftarrow A[0]$

for *i* $\leftarrow 1$ **to** *n* - 1 **do**

if *A*[*i*] > *currentMax* **then**

currentMax $\leftarrow A[i]$

return *currentMax*

Pseudocode Details



- Control flow
 - **if ... then ... [else ...]**
 - **while ... do ...**
 - **repeat ... until ...**
 - **for ... do ...**
 - Indentation replaces braces
- Method declaration

Algorithm *method* (*arg* [, *arg...*])


Input ...

Output ...


- Method call
var.method (*arg* [, *arg...*])
- Return value
return *expression*
- Expressions
 - ← Assignment
(like = in Java)
 - = Equality testing
(like == in Java)
 - n^2 Superscripts and other
mathematical
formatting allowed

The Random Access Machine (RAM) Model

- A **CPU**



- An potentially **unbounded** bank of **memory** cells, each of which can hold an arbitrary number or character



- ◆ Memory cells are numbered and **accessing any cell in memory takes unit time.**

Primitive Operations




- Basic computations performed by an algorithm
 - Identifiable in pseudocode
 - Largely **independent** from the programming language
 - Exact definition not important (we will see why later)
 - Assumed to take a constant amount of time **in the RAM model**
- Examples:
 - Evaluating an expression
 - Assigning a value to a variable
 - Indexing into an array
 - Calling a method
 - Returning from a method

Counting Primitive Operations

- By inspecting the pseudocode, we can determine the maximum number of primitive operations executed by an algorithm, as a function of the input size

Algorithm <i>arrayMax</i> (<i>A</i> , <i>n</i>)	# operations
<i>currentMax</i> \leftarrow <i>A</i> [0]	2
for <i>i</i> \leftarrow 1 to <i>n</i> - 1 do	$2n$
if <i>A</i> [<i>i</i>] > <i>currentMax</i> then	$2(n - 1)$
<i>currentMax</i> \leftarrow <i>A</i> [<i>i</i>]	$2(n - 1)$
{ increment counter <i>i</i> }	$2(n - 1)$
return <i>currentMax</i>	1
Total	$8n - 2$


Estimating Running Time



- Algorithm *arrayMax* executes $8n - 2$ primitive operations in the worst case. Define:
 - a = Time taken by the fastest primitive operation
 - b = Time taken by the slowest primitive operation
- Let $T(n)$ be worst-case time of *arrayMax*. Then
$$a(8n - 2) \leq T(n) \leq b(8n - 2)$$
- Hence, the running time $T(n)$ is bounded by two linear functions in the input size n

Growth Rate of Running Time

- Changing the hardware/ software environment
 - Affects $T(n)$ by a constant factor, but
 - Does **not** alter the growth rate of $T(n)$
- The linear growth rate of the running time $T(n)$ is an intrinsic property of algorithm *arrayMax*




Seven Important Functions

- Seven functions that often appear in algorithm analysis:


- Constant ≈ 1
- Logarithmic $\approx \log n$
- Linear $\approx n$
- N-Log-N $\approx n \log n$
- Quadratic $\approx n^2$
- Cubic $\approx n^3$
- Exponential $\approx 2^n$

- In a log-log chart, the slope of the line corresponds to the growth rate









Functions Graphed Using "Normal" Scale

Slide by Matt Stallmann
included with permission.



$$g(n) = n \lg n$$




Why Growth Rate Matters

if runtime is...	time for $n + 1$	time for $2n$	time for $4n$
$c \lg n$	$c \lg (n + 1)$	$c (\lg n + 1)$	$c(\lg n + 2)$
cn	$c(n + 1)$	$2cn$	$4cn$
$cn \lg n$	$\sim cn \lg n + cn$	$2cn \lg n + 2cn$	$4cn \lg n + 4cn$
cn^2	$\sim cn^2 + 2cn$	$4cn^2$	$16cn^2$
cn^3	$\sim cn^3 + 3cn^2$	$8cn^3$	$64cn^3$
$c2^n$	$c2^{n+1}$	$c2^{2n}$	$c2^{4n}$

runtime
quadruples
when
problem
size doubles

Comparison of Two Algorithms



insertion sort is
 $n^2 / 4$

merge sort is
 $2 n \lg n$

sort a million items?

insertion sort takes
roughly **70 hours**


while

merge sort takes
roughly **40 seconds**

This is a slow machine, but if
100 x as fast then it's **40 minutes**
versus less than **0.5 seconds**

Constant Factors

- The growth rate is **not** affected by
 - constant factors or
 - lower-order terms
- Examples
 - $10^2n + 10^5$ is a linear function
 - $10^5n^2 + 10^8n$ is a quadratic function




Big-Oh Notation

- Given functions $f(n)$ and $g(n)$, we say that $f(n)$ is $O(g(n))$ if there are positive constants c and n_0 such that

$$f(n) \leq cg(n) \text{ for } n \geq n_0$$


- Example: $2n + 10$ is $O(n)$
 - $2n + 10 \leq cn$
 - $(c - 2)n \geq 10$
 - $n \geq 10/(c - 2)$
 - Pick $c = 3$ and $n_0 = 10$




Big-Oh Example

□ Example: the function n^2 is not $O(n)$

- $n^2 \leq cn$
- $n \leq c$
- The above inequality cannot be satisfied since c must be a constant



More Big-Oh Examples




◆ $7n-2$

■ $3n^3 + 20n^2 + 5$

■ $3 \log n + 5$

More Big-Oh Examples



◆ $7n-2$

$7n-2$ is $O(n)$

need $c > 0$ and $n_0 \geq 1$ such that $7n-2 \leq c \cdot n$ for $n \geq n_0$

this is true for $c = 7$ and $n_0 = 1$

■ $3n^3 + 20n^2 + 5$

$3n^3 + 20n^2 + 5$ is $O(n^3)$

need $c > 0$ and $n_0 \geq 1$ such that $3n^3 + 20n^2 + 5 \leq c \cdot n^3$ for $n \geq n_0$

this is true for $c = 4$ and $n_0 = 21$

■ $3 \log n + 5$

$3 \log n + 5$ is $O(\log n)$

need $c > 0$ and $n_0 \geq 1$ such that $3 \log n + 5 \leq c \cdot \log n$ for $n \geq n_0$

this is true for $c = 8$ and $n_0 = 2$

Big-Oh and Growth Rate

- ❑ The big-Oh notation gives an upper bound on the growth rate of a function
- ❑ The statement " $f(n)$ is $O(g(n))$ " means that the growth rate of $f(n)$ is no more than the growth rate of $g(n)$
- ❑ We can use the big-Oh notation to rank functions according to their growth rate

	$f(n)$ is $O(g(n))$	$g(n)$ is $O(f(n))$
$g(n)$ grows more	Yes	No
$f(n)$ grows more	No	Yes
Same growth	Yes	Yes

Big-Oh Rules



- If $f(n)$ is a polynomial of degree d , then $f(n)$ is $O(n^d)$, i.e.,
 1. Drop lower-order terms
 2. Drop constant factors
- Use the smallest possible class of functions
 - Say " $2n$ is $O(n)$ " instead of " $2n$ is $O(n^2)$ "
- Use the simplest expression of the class
 - Say " $3n + 5$ is $O(n)$ " instead of " $3n + 5$ is $O(3n)$ "

Asymptotic Algorithm Analysis


- The asymptotic analysis of an algorithm determines the running time in big-Oh notation
- To perform the asymptotic analysis
 - We find the **worst-case** number of primitive operations executed as a function of the input size
 - We express this function with big-Oh notation
- Example:
 - We determine that algorithm *arrayMax* executes at most $8n - 2$ primitive operations
 - We say that algorithm *arrayMax* “runs in $O(n)$ time”
- Since constant factors and lower-order terms are eventually dropped anyhow, we can disregard them when counting primitive operations

Computing Prefix Averages

- We further illustrate asymptotic analysis with two algorithms for prefix averages
- The i -th prefix average of an array X is average of the first $(i + 1)$ elements of X :

$$A[i] = (X[0] + X[1] + \dots + X[i]) / (i+1)$$

- Computing the array A of prefix averages of another array X has applications to financial analysis



Prefix Averages (Quadratic)

- ◆ The following algorithm computes prefix averages in quadratic time by applying the definition

Algorithm *prefixAverages1*(X, n)

Input array X of n integers

Output array A of prefix averages of X #operations

$A \leftarrow$ new array of n integers n

for $i \leftarrow 0$ **to** $n - 1$ **do** n

$s \leftarrow X[0]$ n

for $j \leftarrow 1$ **to** i **do** $1 + 2 + \dots + (n - 1)$


$s \leftarrow s + X[j]$ $1 + 2 + \dots + (n - 1)$

$A[i] \leftarrow s / (i + 1)$ n

return A 1

Arithmetic Progression

- The running time of *prefixAverages1* is $O(1 + 2 + \dots + n)$
- The sum of the first n integers is $n(n + 1) / 2$
 - There is a simple visual proof of this fact
- Thus, algorithm *prefixAverages1* runs in $O(n^2)$ time



Prefix Averages (Linear)

- ◆ The following algorithm computes prefix averages in linear time by keeping a **running sum**

Algorithm *prefixAverages2*(X, n)

Input array X of n integers

Output array A of prefix averages of X

$A \leftarrow$ new array of n integers

$s \leftarrow 0$

for $i \leftarrow 0$ **to** $n - 1$ **do**

$s \leftarrow s + X[i]$

$A[i] \leftarrow s / (i + 1)$

return A

#operations

n

1

n


n

n

1

- ◆ Algorithm *prefixAverages2* runs in $O(n)$ time

Math you need to Review



- ◆ **Summations**
- ◆ **Logarithms and Exponents**

- ◆ **Proof techniques**
- ◆ **Basic probability**

- **properties of logarithms:**
 - $\log_b(xy) = \log_b x + \log_b y$
 - $\log_b(x/y) = \log_b x - \log_b y$
 - $\log_b x^a = a \log_b x$
 - $\log_b a = \log_x a / \log_x b$
- **properties of exponentials:**
 - $a^{(b+c)} = a^b a^c$
 - $a^{bc} = (a^b)^c$
 - $a^b / a^c = a^{(b-c)}$
 - $b = a^{\log_a b}$
 - $b^c = a^{c \cdot \log_a b}$

Relatives of Big-Oh




◆ big-Omega

- $f(n)$ is $\Omega(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \geq c \cdot g(n)$ for $n \geq n_0$

◆ big-Theta

- $f(n)$ is $\Theta(g(n))$ if there are constants $c' > 0$ and $c'' > 0$ and an integer constant $n_0 \geq 1$ such that $c' \cdot g(n) \leq f(n) \leq c'' \cdot g(n)$ for $n \geq n_0$
- $f(n)$ is $O(g(n))$ and $\Omega(g(n))$
- $g(n)$ is $O(f(n))$ and $\Omega(f(n))$
- $f(n)$ is $O(g(n))$ and $g(n)$ is $O(f(n))$

Intuition for Asymptotic Notation



Big-Oh

- $f(n)$ is $O(g(n))$ if $f(n)$ is asymptotically **less than or equal** to $g(n)$


big-Omega

- $f(n)$ is $\Omega(g(n))$ if $f(n)$ is asymptotically **greater than or equal** to $g(n)$

big-Theta

- $f(n)$ is $\Theta(g(n))$ if $f(n)$ is asymptotically **equal** to $g(n)$

Example Uses of the Relatives of Big-Oh




■ $5n^2$ is $\Omega(n^2)$

■ $5n^2$ is $\Omega(n)$

■ $5n^2$ is $\Theta(n^2)$

Example Uses of the Relatives of Big-Oh



- $5n^2$ is $\Omega(n^2)$

$f(n)$ is $\Omega(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \geq c \cdot g(n)$ for $n \geq n_0$

let $c = 5$ and $n_0 = 1$

- $5n^2$ is $\Omega(n)$

$f(n)$ is $\Omega(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \geq c \cdot g(n)$ for $n \geq n_0$

let $c = 1$ and $n_0 = 1$

- $5n^2$ is $\Theta(n^2)$

$f(n)$ is $\Theta(g(n))$ if it is $\Omega(n^2)$ and $O(n^2)$. We have already seen the former, for the latter recall that $f(n)$ is $O(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \leq c \cdot g(n)$ for $n \geq n_0$

Let $c = 5$ and $n_0 = 1$