


Merge Sort



Divide-and-Conquer (§ 10.1.1)

- ◆ **Divide-and conquer** is a general algorithm design paradigm:
 - **Divide**: divide the input data S in two **disjoint** subsets S_1 and S_2
 - **Recur**: solve the subproblems associated with S_1 and S_2
 - **Conquer**: combine the solutions for S_1 and S_2 into a solution for S
- ◆ The base case for the recursion are subproblems of size 0 or 1
- ◆ **Merge-sort** is a sorting algorithm based on the divide-and-conquer paradigm
- ◆ Like heap-sort
 - It uses a comparator
 - It has $O(n \log n)$ running time
- ◆ Unlike heap-sort
 - It does not use an auxiliary priority queue
 - It accesses data in a sequential manner (suitable to sort data on a disk)

Merge-Sort (§ 10.1)

- ◆ Merge-sort on an input sequence S with n elements consists of three steps:
 - **Divide**: partition S into two sequences S_1 and S_2 of about $n/2$ elements each
 - **Recur**: recursively sort S_1 and S_2
 - **Conquer**: merge S_1 and S_2 into a unique sorted sequence

Algorithm *mergeSort*(S, C)

Input sequence S with n elements,
comparator C

Output sequence S sorted
according to C

if $S.size() > 1$

$(S_1, S_2) \leftarrow partition(S, n/2)$

mergeSort(S_1, C)

mergeSort(S_2, C)

$S \leftarrow merge(S_1, S_2)$

Merging Two Sorted Sequences

- ◆ The conquer step of merge-sort consists of merging two sorted sequences A and B into a sorted sequence S containing the union of the elements of A and B
- ◆ Merging two sorted sequences, each with $n/2$ elements and implemented by means of a doubly linked list, takes $O(n)$ time

Algorithm *merge*(A, B)

Input sequences A and B with $n/2$ elements each

Output sorted sequence of $A \cup B$

$S \leftarrow$ empty sequence

while $\neg A.isEmpty() \wedge \neg B.isEmpty()$

if $A.first().element() < B.first().element()$

$S.addLast(A.remove(A.first()))$

else

$S.addLast(B.remove(B.first()))$

while $\neg A.isEmpty()$

$S.addLast(A.remove(A.first()))$


while $\neg B.isEmpty()$

$S.addLast(B.remove(B.first()))$

return S


Merge-Sort Tree

- ◆ An execution of merge-sort is depicted by a binary tree
 - each node represents a recursive call of merge-sort and stores
 - ◆ unsorted sequence before the execution and its partition
 - ◆ sorted sequence at the end of the execution
 - the root is the initial call
 - the leaves are calls on subsequences of size 0 or 1




Execution Example

◆ Partition




Execution Example (cont.)

◆ Recursive call, partition




Execution Example (cont.)

◆ Recursive call, partition




Execution Example (cont.)

◆ Recursive call, base case




Execution Example (cont.)

◆ Recursive call, base case




Execution Example (cont.)

◆ Merge




Execution Example (cont.)

◆ Recursive call, ..., base case, merge




Execution Example (cont.)

◆ Merge




Execution Example (cont.)

◆ Recursive call, ..., merge, merge



Execution Example (cont.)

◆ Merge



Analysis of Merge-Sort

- ◆ The height h of the merge-sort tree is $O(\log n)$
 - at each recursive call we divide in half the sequence,
- ◆ The overall amount of work done at the nodes of depth i is $O(n)$
 - we partition and merge 2^i sequences of size $n/2^i$
 - we make 2^{i+1} recursive calls
- ◆ Thus, the total running time of merge-sort is $O(n \log n)$


depth	#seqs	size
-------	-------	------

0	1	n
---	---	-----

1	2	$n/2$
---	---	-------

i	2^i	$n/2^i$
-----	-------	---------

...
-----	-----	-----



Summary of Sorting Algorithms

Algorithm	Time	Notes
selection-sort	$O(n^2)$	<ul style="list-style-type: none">▪ slow▪ in-place▪ for small data sets (< 1K)
insertion-sort	$O(n^2)$	<ul style="list-style-type: none">▪ slow▪ in-place▪ for small data sets (< 1K)
heap-sort	$O(n \log n)$	<ul style="list-style-type: none">▪ fast▪ in-place▪ for large data sets (1K — 1M)
merge-sort	$O(n \log n)$	<ul style="list-style-type: none">▪ fast▪ sequential data access▪ for huge data sets (> 1M)