
Memory Layout

- We are going to dive deeper into different areas of memory used by our programs.
- The **stack** is the place where all local variables and parameters live for each function. A function's stack "frame" goes away when the function returns.
- The stack grows downwards when a new function is called and shrinks upwards when the function is finished.




The Stack

- The stack behaves like a...well...stack! A new function call **pushes** on a new frame. A completed function call **pops** off the most recent frame.
- Interesting fact: C does not clear out memory when a function's frame is removed. Instead, it just marks that memory as usable for the next function call. This is more efficient!
- A stack overflow is when you use up all stack memory. E.g. a recursive call with too many function calls.
- What are the limitations of the stack?

The Heap

- The heap is a part of memory that you can manage yourself.
- The heap is a part of memory below the stack that you can manage yourself. Unlike the stack, the memory only goes away when you delete it yourself.
- Unlike the stack, the heap grows upwards as more memory is allocated.

The heap is **dynamic memory** – memory that can be allocated, resized, and freed during **program runtime**.



malloc

```
void *malloc(size_t size);
```

To allocate memory on the heap, use the **malloc** function ("memory allocate") and specify the number of bytes you'd like.

- This function returns a pointer to the **starting address** of the new memory. It doesn't know or care whether it will be used as an array, a single block of memory, etc.
- void *means a pointer to generic memory. You can set another pointer equal to it without any casting.
- The memory is not cleared out before being allocated to you!
- If malloc returns NULL, then there wasn't enough memory for this request.

Exercise: malloc multiples

Let's write a function that returns an array of the first len multiples of mult.

Line 2: How should we declare arr?

```
A. int arr[len];
B. int arr[] = malloc(sizeof(int));
C. int *arr = malloc(sizeof(int) * len);
D. int *arr = malloc(sizeof(int) * (len + 1));
E. Something else
```

- Use a pointer to store the address returned by malloc.
- Malloc's argument is the number of bytes to allocate.
- This code is missing an assertion.

Always assert with the heap

Let's write a function that returns an array of the first len multiples of mult.

```
1 int *array_of_multiples(int mult, int len) {
2    int *arr = malloc(sizeof(int) * len);
3    assert(arr != NULL);
4    for (int i = 0; i < len; i++) {
5        arr[i] = mult * (i + 1);
6    }
7    return arr;
8 }</pre>
```

- If an allocation error occurs (e.g. out of heap memory!), malloc will return NULL. This is an important case to check **for robustness**.
- **assert** will crash the program if the provided condition is false. A memory allocation error is significant, and we should terminate the program.

Other heap allocations: calloc

```
void *calloc(size_t nmemb, size_t size);
calloc is like malloc that zeros out the memory for you—thanks, calloc!
```

You might notice its interface is also a little different—it takes two parameters, which are multiplied to calculate the number of bytes (nmemb * size).

```
// allocate and zero 20 ints
int *scores = calloc(20, sizeof(int));
// alternate (but slower)
int *scores = malloc(20 * sizeof(int));
for (int i = 0; i < 20; i++) scores[i] = 0;</pre>
```

• calloc is more expensive than malloc because it zeros out memory. Use only when necessary!

Other heap allocations: strdup

```
char *strdup(char *s);
```

strdup is a convenience function that returns a **null-terminated**, heap-allocated string with the provided text, instead of you having to **malloc** and copy in the string yourself.

```
char *str = strdup("Hello, world!"); // on heap
str[0] = 'h';
```

Cleaning Up with free

```
void free(void *ptr);
```

- If we allocated memory on the heap and no longer need it, it is our responsibility to delete it.
- To do this, use the free command and pass in the starting address on the heap for the memory you no longer need.
- Example:

```
char *bytes = malloc(4);
...
free(bytes);
```

free details

Even if you have multiple pointers to the same block of memory, each memory block should only be freed **once**.

You must free the address you received in the previous allocation call; you cannot free just part of a previous allocation.

```
char *bytes = malloc(4);
char *ptr = malloc(10);
...
free(bytes);
...
free(ptr + 1);
```

Memory Leaks

- A memory leak is when you allocate memory on the heap, but do not free it.
- Your program should be responsible for cleaning up any memory it allocates but no longer needs.
- If you never free any memory and allocate an extremely large amount, you may run out of memory in the heap!

However, memory leaks rarely (if ever) cause crashes.

- We recommend not to worry about freeing memory until your program is written. Then, go back and free memory as appropriate.
- Valgrind is a very helpful tool for finding memory leaks!
 - → More on Valgrind in Lab 3!

realloc

```
void *realloc(void *ptr, size_t size);
```

- The **realloc** function takes an existing allocation pointer and enlarges to a new requested size. It returns the new pointer.
- If there is enough space after the existing memory block on the heap for the new size, **realloc** simply adds that space to the allocation.
- If there is not enough space, **realloc** moves the memory to a larger location, frees the old memory for you, and returns a pointer to the new location.

realloc

- realloc only accepts pointers that were previously returned my malloc/etc.
- Make sure to not pass pointers to the middle of heap-allocated memory.
- Make sure to not pass pointers to stack memory.

Heap allocation interface: A summary

```
void *malloc(size_t size);
void *calloc(size_t nmemb, size_t size);
void *realloc(void *ptr, size_t size);
char *strdup(char *s);
void free(void *ptr);
```

Heap **memory allocation** guarantee:

- NULL on failure, so check with assert
- Memory is contiguous; it is not recycled unless you call free
- realloc preserves existing data
- calloc zero-initializes bytes, malloc and realloc do not

Undefined behavior occurs:

- If you overflow (i.e., you access beyond bytes allocated)
- If you use after free, or if free is called twice on a location.
- If you realloc/free non-heap address

Engineering principles: stack vs heap

Stack ("local variables")

- Fast
 - Fast to allocate/deallocate; okay to oversize
- Convenient.

 Automatic allocation/ deallocation;
 declare/initialize in one step
- Reasonable type safety
 Thanks to the compiler
- Not especially plentiful
 Total stack size fixed, default 8MB
- Somewhat inflexible

Cannot add/resize at runtime, scope dictated by control flow in/out of functions

Heap (dynamic memory)

- Plentiful.

 Can provide more memory on demand!
- Very flexible.
 Runtime decisions about how much/when to allocate, can resize easily with realloc
- Scope under programmer control
 Can precisely determine lifetime
- Lots of opportunity for error
 Low type safety, forget to allocate/free
 before done, allocate wrong size, etc.,
 Memory leaks (much less critical)

Stack and Heap

- Generally, unless a situation requires dynamic allocation, stack allocation is preferred. Often both techniques are used together in a program.
- Heap allocation is a necessity when:
 - you have a very large allocation that could blow out the stack
 - you need to control the memory lifetime, or memory must persist outside of a function call
 - you need to resize memory after its initial allocation