


Operating Systems

Lab 05

Content



Content
User Management
Environment Managment

User Management

- As the administrator, it is your job to create and manage the accounts for all required users.
- Since Linux is a multi-user operating system, several people may be logged in and actively working on a given machine at the same time.
 - For security purposes, it is never a good idea to allow users to share the credentials of the same account.
- We will use:
 - *useradd / adduser*
 - *userdel*
 - *usermod*
 - *groupadd*

User Management

useradd - add a user to the system.

- User accounts are stored in the */etc/passwd* file.

```
lvl3@lvl3-vm:~/Desktop$ useradd omar  
useradd: Permission denied.  
useradd: cannot lock /etc/passwd; try again later.
```

- The command requires root permissions

```
lvl3@lvl3-vm:~/Desktop$ sudo useradd omar  
[sudo] password for lvl3:
```

User Management

useradd - add a user to the system.

- You can see the account created in the *passwd* file

```
lvl3@lvl3-vm:~/Desktop$ tail /etc/passwd
whoopsie:x:120:125::/nonexistent:/bin/false
colord:x:121:126:colord colour management daemon,,,:/var/lib/colord:/usr/sbin/nologin
geoclue:x:122:127::/var/lib/geoclue:/usr/sbin/nologin
pulse:x:123:128:PulseAudio daemon,,,:/var/run/pulse:/usr/sbin/nologin
gnome-initial-setup:x:124:65534::/run/gnome-initial-setup:/bin/false
gdm:x:125:130:Gnome Display Manager:/var/lib/gdm3:/bin/false
sssd:x:126:131:SSSD system user,,,:/var/lib/sss:/usr/sbin/nologin
lvl3:x:1000:1000:lvl3,,,:/home/lvl3:/bin/bash
systemd-coredump:x:999:999:systemd Core Dumper:/:/usr/sbin/nologin
omar:x:1001:1001::/home/omar:/bin/sh
```

User Management

useradd - add a user to the system.

- When you first create a new user using the *useradd* command, you must set a new password for it to log in it.

```
lvl3@lvl3-vm:~/Desktop$ sudo passwd omar  
New password:  
Retype new password:  
passwd: password updated successfully
```

User Management

adduser – adds new user.

- Allows creating a new user with a specific password and additional details.

```
lvl3@lvl3-vm:~/Desktop$ sudo adduser ahmed
Adding user `ahmed' ...
Adding new group `ahmed' (1002) ...
Adding new user `ahmed' (1002) with group `ahmed' ...
Creating home directory `/home/ahmed' ...
Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for ahmed
Enter the new value, or press ENTER for the default
    Full Name []: Ahmed
    Room Number []:
    Work Phone []:
    Home Phone []:
    Other []:
Is the information correct? [Y/n] y
```

User Management

su – switch user.

- Allows switching user from terminal.

```
lvl3@lvl3-vm:~/Desktop$ su omar
Password:
$ █
```


User Management

userdel – delete a user account.

```
lvl3@lvl3-vm:~/Desktop$ sudo userdel omar  
[sudo] password for lvl3:
```

Option	Description
-f, --force	forces the removal of the user account, even if the user is still logged in.
-r, --remove	Files in the user's home directory will be removed along with the home directory itself

User Management

groupadd – create new group

- Allows creating new groups.

```
lvl3@lvl3-vm:~/Desktop$ sudo groupadd my_group  
[sudo] password for lvl3:
```

- You can show the groups on the system from the */etc/group* file.

```
lvl3@lvl3-vm:~/Desktop$ tail /etc/group  
pulse-access:x:129:  
gdm:x:130:  
sssd:x:131:  
lxd:x:132:lvl3  
lvl3:x:1000:  
smbashare:x:133:lvl3  
systemd-coredump:x:999:  
omar:x:1001:  
ahmed:x:1002:  
my group:x:1003:
```

User Management

usermod – modify a user account.

- Modifies the system account files to reflect the changes that are specified on the command line.
- This option must be used with an option.

Option	Description
-c, --comment	Add a comment to the user account.
-d, --home	Change the user's login directory.
-g, --gid	Change the primary group
-G, , --groups	Adding Supplementary Groups to a User Account.
-a, --append	Append the user to the supplemental GROUPS mentioned by the -G option without removing the user from other groups.
-L, --lock	Lock the user account.

User Management

usermod – modify a user account.

- Add comment.

```
lvl3@lvl3-vm:~/Desktop$ sudo usermod -c "This is an empty user account" ahmed
[sudo] password for lvl3:
lvl3@lvl3-vm:~/Desktop$ tail /etc/passwd
colord:x:121:126:colord colour management daemon,,,:/var/lib/colord:/usr/sbin/nologin
geoclue:x:122:127::/var/lib/geoclue:/usr/sbin/nologin
pulse:x:123:128:PulseAudio daemon,,,:/var/run/pulse:/usr/sbin/nologin
gnome-initial-setup:x:124:65534::/run/gnome-initial-setup:/bin/false
gdm:x:125:130:Gnome Display Manager:/var/lib/gdm3:/bin/false
sssd:x:126:131:SSSD system user,,,:/var/lib/sss:/usr/sbin/nologin
lvl3:x:1000:1000:lvl3,,,:/home/lvl3:/bin/bash
systemd-coredump:x:999:999:systemd Core Dumper:/:/usr/sbin/nologin
ahmed:x:1002:1002:This is an empty user account:/home/ahmed:/bin/bash
omar:x:1003:1004::/home/omar:/bin/sh
```

User Management

usermod – modify a user account.

- Append the user to another group.

```
lvl3@lvl3-vm:~/Desktop$ sudo usermod -aG my_group ahmed
```

```
lvl3@lvl3-vm:~/Desktop$ id ahmed  
uid=1002(ahmed) gid=1002(ahmed) groups=1002(ahmed),1003(my_group)
```

User Management

finger – user information lookup.

- This command is used by system admins to show details about the user.
- You need to install it.

```
lvl3@lvl3-vm:~/Desktop$ sudo apt install finger
```

```
lvl3@lvl3-vm:~/Desktop$ finger lvl3
```

```
Login: lvl3                                Name: lvl3
Directory: /home/lvl3                     Shell: /bin/bash
On since Sat Apr  2 21:14 (EET) on :0 from :0 (messages off)
No mail.
No Plan.
```

```
lvl3@lvl3-vm:~/Desktop$ finger ahmed
```


```
Login: ahmed                                Name: This is an empty user account
Directory: /home/ahmed                     Shell: /bin/bash
Never logged in.
No mail.
No Plan.
```

Content

Content

User Management

Environment Managment



Environment Management

- SHA-1 is a hash function used to verify a file has been unaltered.
 - This is done by producing a checksum before the file has been transmitted, and then again once it reaches its destination.
- The transmitted file can be considered genuine only if both checksums are identical.
- Example, when downloading Ubuntu, there is an option to check if the downloaded file is original file or not.

Your download should start automatically. If it doesn't, [download now](#).

You can [verify your download](#), or get [help on installing](#).

Run this command in your terminal in the directory the iso was downloaded to verify the SHA256 checksum:

```
echo "f92f7dca5bb6690e1af0052687ead49376281c7b64fbe4179cc44025965b7d1c*ubuntu-20.04.4-desktop-amd64.iso" | shasum -a 256 --check
```

You should get the following output:

```
ubuntu-20.04.4-desktop-amd64.iso: OK
```

Or follow this tutorial to learn [how to verify downloads](#)

Environment Management

sha1sum – computes the checksum of a file.

```
lvl3@lvl3-vm:~/Desktop$ sha1sum file.txt  
f5403843ceb694b0cb24a91ff3615083519356b9  file.txt
```

- Check if two files are the same or not using *sha1sum* and *diff* commands.

```
lvl3@lvl3-vm:~/Desktop$ sha1sum file.txt > hash1.txt  
lvl3@lvl3-vm:~/Desktop$ sha1sum xyz.txt > hash2.txt  
lvl3@lvl3-vm:~/Desktop$ diff -sq hash1.txt hash2.txt  
Files hash1.txt and hash2.txt differ
```

```
lvl3@lvl3-vm:~/Desktop$ sha1sum file.txt > hash1.txt  
lvl3@lvl3-vm:~/Desktop$ sha1sum file.txt > hash2.txt  
lvl3@lvl3-vm:~/Desktop$ diff -sq hash1.txt hash2.txt  
Files hash1.txt and hash2.txt are identical
```

- The *-sq* option tells *diff* command to print if the two files are identical or different.

Environment Management

type – display information about a command.

- You can easily find whether the given command is an alias, shell built-in, file, function, or keyword.

```
lvl3@lvl3-vm:~/Desktop$ type ls
ls is aliased to `ls --color=auto'
lvl3@lvl3-vm:~/Desktop$ type pwd
pwd is a shell builtin
lvl3@lvl3-vm:~/Desktop$ type type
type is a shell builtin
lvl3@lvl3-vm:~/Desktop$ type cd
cd is a shell builtin
lvl3@lvl3-vm:~/Desktop$ type mkdir
mkdir is /usr/bin/mkdir
```

Environment Management

chown – change owner.

- Allows changing the user and/or group ownership of a file or a directory.

```
chown [OPTIONS] USER[:GROUP] FILE(s)
```

- *USER* - If only the user is specified, the specified user will become the owner of the given files, the group ownership is not changed.
- *USER:* - When the username is followed by a colon :, and the group name is not given, the user will become the owner of the files, and the files group ownership is changed to user's login group.
- *USER:GROUP* - If both the user and the group are specified, the user ownership of the files is changed to the given user and the group ownership is changed to the given group.
- *:GROUP* - If the User is omitted and the group is prefixed with a colon :, only the group ownership of the files is changed to the given group.

Environment Management

chown – change owner.

```
lvl3@lvl3-vm:~/Desktop$ ls -l dummy.tx
-rwxr--r-x 1 lvl3 lvl3 0 10:27 29 مار dummy.tx
lvl3@lvl3-vm:~/Desktop$ sudo chown ahmed dummy.tx
[sudo] password for lvl3:
lvl3@lvl3-vm:~/Desktop$ ls -l dummy.tx
-rwxr--r-x 1 ahmed lvl3 0 10:27 29 مار dummy.tx
lvl3@lvl3-vm:~/Desktop$ sudo chown ahmed:ahmed dummy.tx
lvl3@lvl3-vm:~/Desktop$ ls -l dummy.tx
-rwxr--r-x 1 ahmed ahmed 0 10:27 29 مار dummy.tx
```

Environment Management

tac – read file from end.

- Similar to *cat* command but reads a file from the end.

```
lvl3@lvl3-vm:~/Desktop$ cat a1.txt
```

```
aa  
bc  
mona  
ahme  
ali
```

```
lvl3@lvl3-vm:~/Desktop$ tac a1.txt
```

```
ali  
ahme  
mona  
bc  
aa
```

Environment Management

find - search for files in a directory hierarchy.

- It supports searching by file, folder, name, creation date, modification date, owner and permissions.

```
$ find [where to start searching from]  
[expression determines what to find] [-options] [what to find]
```

- Example, find a file named “f1.txt” starting from Downloads directory.

```
lvl3@lvl3-vm:~/Desktop$ find ~/Downloads -name f1.txt  
/home/lvl3/Downloads/new_dir5/f1.txt  
/home/lvl3/Downloads/dir2/f1.txt  
/home/lvl3/Downloads/dir1/f1.txt
```

Environment Management

- Find all files that ends in `.sh` starting from home directory.

```
lvl3@lvl3-vm:~/Desktop$ find ~ -name '*.sh'  
/home/lvl3/Desktop/qqq/mydir/rand10.sh  
/home/lvl3/Desktop/qqq/mydir/rand9.sh  
/home/lvl3/Desktop/qqq/mydir/rand12.sh  
/home/lvl3/Desktop/qqq/mydir/rand11.sh
```

- Find all files that has permission 777 starting from home directory.

```
lvl3@lvl3-vm:~/Desktop$ find ~ -perm 777  
/home/lvl3/.mozilla/firefox/krqsl33c.default-release/lock  
/home/lvl3/Desktop/xyz.txt
```

Environment Management

- Find all files that any permission except 777 starting from home directory.

```
lvl3@lvl3-vm:~/Desktop$ find ~ -type f ! -perm 777
/home/lvl3/Pictures/Screenshot from 2022-03-06 17-14-59.png
/home/lvl3/.bashrc
/home/lvl3/.bash_logout
/home/lvl3/.config/dconf/user
/home/lvl3/.config/user-dirs.locale
```

- Find all directories that has permission 664 starting from home directory.

```
lvl3@lvl3-vm:~/Desktop$ find ~ -type d ! -perm 664
/home/lvl3
/home/lvl3/Public
/home/lvl3/Pictures
/home/lvl3/Templates
/home/lvl3/.config
/home/lvl3/.config/gnome-session
/home/lvl3/.config/gnome-session/saved-session
```


Summary

- *finger*
- *sha1sum*
- *useradd*
- *adduser*
- *groupadd*
- *usermod*
- *userdel*
- *su*
- *type*
- *chown*
- *tac*
- *find*

TASK

- Create a new user “user1” using *useradd*.
- Create a new user “user2” using *adduser*.
- Switch between the users. What do you notice? What is the main difference between *useradd* and *adduser*?
- What are the following commands: *groupdel* , *groupmod*.
- Write a command to display files changed in last 1 hour.
- Write a command to find files larger than 10MB.