CSE245 - Advanced Algorithms and Complexity

TASK 1: COLORED TROMINO TILING

Submitted to:

Dr. Gamal Abdel-Shafy

Eng. Sally Shaker

Razan Mohamed Mahmoud	**24P0001**
Farah Khaled Ahmed	**24P0123**

Task 1: Colored Tromino Tiling

Definition

Devise an algorithm for the following task: given a $2^n \times 2^n$ ($n > 1$) board with one missing square, tile it with right trominoes of only three colors so that no pair of trominoes that share an edge have the same color. Recall that the right tromino is an L-shaped tile formed by three adjacent squares. Use Divide and conquer technique to solve this problem.

Assumptions

- Input n is greater than one
- Input for missing cell is 1-based indexing
- Board is initially empty except for one missing square
- Any right tromino can take one of four different orientations
- Adjacency is only checked in four directions (up, down, left and right)

Explanation and Pseudo-Code

The problem we are addressing involves tiling a square board of size 2^n x 2^n, where $n > 1$, using L-shaped tiles known as right trominoes, under the constraint that exactly one square on the board is missing. The objective is to completely tile the rest of the board using these trominoes such that no two adjacent trominoes (i.e., those sharing an edge) are assigned the same color, using only three distinct colors. The right tromino is a polyomino consisting of three squares connected in an L-shape. Visually, it resembles the shape of the letter "L", covering two adjacent cells in a row and one additional cell in the next row (or vice versa depending on rotation).



Figure 1: Right tromino orientations (Left T, Mirrored L-shape, L-shape and Right T)

This problem has roots in classic algorithm design and is notably a variant of the defective chessboard problem, which was discussed by Donald E. Knuth in *The Art of Computer Programming, Volume 1* (Knuth, 1997). The problem is commonly used to illustrate the divide and conquer paradigm, a method where a problem is divided into smaller subproblems of the same type, solved recursively, and then the solutions are combined to solve the original problem.

The insight that makes this problem tractable using divide and conquer lies in the regularity and symmetry of the board size. Since the board is of size $2^n \times 2^n$, it can always be evenly divided into four smaller quadrants of equal size. Each time we divide the board into four parts, one of the

quadrants contains the missing cell. By cleverly placing a single tromino at the center —covering one square in each of the remaining three quadrants—we reduce the problem to four subproblems of smaller size, each now with its own missing square. This recursive structure continues until the base case is reached: a 1 x 1 board which requires no further action.



Figure 2: Initial overview of the tromino placement in a 8x8 grid

```
tromino_id = 0 // unique identifier for each placed tromino
```

To manage the identity of each tromino we place on the board, the algorithm introduces a global variable called tromino_id. This variable is initially set to zero and is incremented every time a new tromino is placed. Its role is to ensure that each tromino has a unique identifier that can be tracked independently across the entire board. This is crucial because, in later stages of the algorithm, particularly during the coloring phase, we need to differentiate between adjacent trominoes to avoid assigning the same color to two touching pieces. The uniqueness of the tromino IDs effectively creates a mapping from cells on the board to the tromino they belong to, which simplifies the task of building an adjacency graph and applying graph coloring techniques later on.

```
function locateTromino(board, size, istart, iend, jstart, jend, missing_i, missing_j):
    if size == 1:
        return

    determine which quadrant (quad 1 to 4) the missing cell is in

    increment global tromino_id

    based on the quadrant:
        place a tromino at the center of the current board
        (cover the other 3 quadrants' center cells)

    recursively call locateTromino on all 4 sub-quadrants:
        - for the original missing quadrant, pass the actual missing cell
        - for the other 3 quadrants, set a new "missing" at the position covered by the tromino
```

The core of the divide and conquer approach lies in the function locateTromino, which recursively places trominoes on sub-regions of the board. This function accepts as input the current board, the size of the sub-board being worked on, the starting and ending indices of rows and columns for the region, and the coordinates of the missing square within that region.

Upon each call, the function first checks for the base case: if the size of the sub-board is 1, it returns immediately because no tromino can be placed on a 1 x 1 board. Otherwise, the board is divided conceptually into four equal quadrants: the top-left, top-right, bottom-left, and bottom-right. The quadrant that contains the missing square is determined by comparing the coordinates of the missing cell to the midpoints of the row and column ranges.

Once the missing quadrant is identified, the function increments tromino_id and places a tromino in the center of the board such that it covers one square in each of the three remaining quadrants. For example, if the missing square is in the top-right quadrant, then the placed tromino will cover one square each in the top-left, bottom-left, and bottom-right quadrants—specifically the squares closest to the center. This strategically placed tromino creates new "missing" squares in the three other quadrants, enabling the recursion to proceed.

The function then makes four recursive calls, one for each quadrant. The quadrant containing the original missing square is passed down with the same missing coordinates. For the other three quadrants, the newly placed tromino has created a missing square at the center, and these new coordinates are passed instead. This systematic process guarantees that every quadrant always has exactly one missing square, thus maintaining the problem's invariant at every recursive level.

9	9	8	8	4	4	3	3
9	7	7	8	4	2	2	3
10	7	11	11	5		2	6
10	10	11	1	5	5	6	6
14	14	13	1	1	19	18	18
14	12	13	13	19	19	17	18
15	12	12	16	20	17	17	21
15	15	16	16	20	20	21	21

Figure 3: The result of the first function: a successfully tiled grid with unique tromino IDs

After the entire board has been successfully tiled using uniquely identified trominoes, the next task is to color them using only three colors in such a way that no two adjacent trominoes share the same color.

```
function colorBoard(board, size):
    // STEP 1: Build adjacency graph
    create an empty adjacency map: tromino_id → set of adjacent tromino_ids

    for each cell in the board:
        if cell has valid tromino_id:
            for each neighbor (up, down, left, right):
                if neighbor has a different tromino_id:
                    add mutual adjacency in the map

    // STEP 2: Greedy Coloring
    create empty map tromino_color

    for each tromino_id in adjacency:
        create boolean array used[3] initialized to false

        for each neighbor:
            if neighbor has a color assigned:
                mark used[color] = true

        assign the first available color (0, 1, or 2) to current tromino_id

    // STEP 3: Apply Colors to Board
    for each cell in the board:
        if cell has a valid tromino_id:
            overwrite board[i][j] with tromino_color[tromino_id] + 1
```

This requirement can be reframed as a graph coloring problem, where each tromino represents a node, and an edge exists between two nodes if the corresponding trominoes share at least one side on the board. The goal is then to color the nodes of this graph such that no two connected nodes have the sae color, using the minimum number of colors—in this case, restricted to three.

The coloring process begins with the construction of the adjacency graph. For every cell on the board, the algorithm examines its four immediate neighbors—up, down, left, and right. If any of these neighbors belong to a different tromino (i.e., their tromino_id is different), an undirected edge is added between the two IDs in an adjacency map. This is implemented using a hash map where the keys are tromino IDs and the values are sets containing the IDs of all adjacent trominoes. This ensures that each connection is recorded only once, preventing redundant computation in later steps.

With the adjacency graph constructed, the algorithm proceeds to apply a greedy coloring strategy. For each tromino ID, it examines the colors assigned to its adjacent trominoes and marks them as unavailable. It then selects the first available color (from the options 0, 1, or 2) that is not used by its neighbors and assigns it to the current tromino. This method ensures that no two adjacent trominoes receive the same color.

The use of only three colors is theoretically justified by results from graph theory. Specifically, in a planar tiling where each tile (tromino) touches only a limited number of neighbors (in this case, at most four), Brooks' Theorem (Brooks, 1941) tells us that the chromatic number of the graph is at most equal to the maximum degree of any vertex, unless the graph is a complete graph or an odd cycle. In this setting, our adjacency graph is neither of those special cases, and hence three colors suffice.

Finally, once the colors are determined, the function makes a final pass over the board. Each cell that was marked with a tromino_id is overwritten with the corresponding color code assigned to that ID. To convert from 0-based color codes to a more human-readable form, the colors are incremented by 1, resulting in final color values of 1, 2, or 3.

The output of this function is a completely tiled and colored board where no two adjacent trominoes are of the same color, satisfying all constraints of the original problem.



Figure 4: The result of the second function: a feasible coloring combination for the trominoes (1 is mapped to red, 2 to green and 3 to blue)

C++ Code

```
/*
Computer Engineering and Artificial Intelligence Program
CSE245: Advanced Algorithms and Complexity – Spring 2025
Task 1 - Tiling Trominoes
*/

#include <bits/stdc++.h>
using namespace std;

int tromino_id = 0;

// The main recursive function to place trominoes
void locateTromino(vector<vector<int>> &board, int size, int istart, int iend, int jstart, int jend,
int missing_i, int missing_j){

    // Base case (reached a single cell)
    if(size == 1) return;

    // Determine quad of missing cell
    int quad;
    if(missing_i >= istart && missing_i <= (istart+iend)/2){
        if(missing_j >= ((jstart+jend)/2)+1 && missing_j <= jend) quad = 1;
        else quad = 2;
    }
    else if(missing_i >= ((istart+iend)/2)+1 && missing_i <= iend){
        if(missing_j >= jstart && missing_j <= (jstart+jend)/2) quad = 3;
        else quad = 4;
    }

    // Increment tromino ID (to place a different one)
    tromino_id++;

    // Determine tromino orientation based on quad of missing cell
    switch(quad){
        case 1:
            // 1st quad: L shape
            board[(istart+iend)/2][(jstart+jend)/2] = tromino_id; // Top left
            board[((istart+iend)/2)+1][(jstart+jend)/2] = tromino_id; // Bottom left
            board[((istart+iend)/2)+1][((jstart+jend)/2)+1] = tromino_id; // Bottom right

            // Quadruple recursion
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart+(size/2), jstart+(size-
1), missing_i, missing_j); // 1ST QUAD
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart, jstart+(size/2)-1,
istart+(size/2)-1, jstart+(size/2)-1); // 2nd quad
            locateTromino(board, size/2, istart+(size/2), istart+(size-1), jstart, jstart+(size/2)-
1, istart+(size/2), jstart+(size/2)-1); // 3rd quad
            locateTromino(board, size/2, istart+(size/2), istart+size-1, jstart+(size/2),
jstart+size-1, istart+(size/2), jstart+(size/2)); // 4th quad
        break;

        case 2:
            // 2nd quad: Mirrored L  shape
            board[(istart+iend)/2][((jstart+jend)/2)+1] = tromino_id; // Top right
            board[((istart+iend)/2)+1][(jstart+jend)/2] = tromino_id; // Bottom left
            board[((istart+iend)/2)+1][((jstart+jend)/2)+1] = tromino_id; // Bottom right

            // Quadruple recursion
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart+(size/2), jstart+(size-
1), istart+(size/2)-1, jstart+(size/2)); // 1st quad
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart, jstart+(size/2)-1,
missing_i, missing_j); // 2ND QUAD
```

```
            locateTromino(board, size/2, istart+(size/2), istart+(size-1), jstart, jstart+(size/2)-
1, istart+(size/2), jstart+(size/2)-1); // 3rd quad
            locateTromino(board, size/2, istart+(size/2), istart+size-1, jstart+(size/2),
jstart+size-1, istart+(size/2), jstart+(size/2)); // 4th quad
        break;

        case 3:
            // 3rd quad: Left T
            board[(istart+iend)/2][((jstart+jend)/2)+1] = tromino_id; // Top right
            board[(istart+iend)/2][(jstart+jend)/2] = tromino_id; // Top left
            board[((istart+iend)/2)+1][((jstart+jend)/2)+1] = tromino_id; // Bottom right

            // Quadruple recursion
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart+(size/2), jstart+(size-
1), istart+(size/2)-1, jstart+(size/2)); // 1st quad
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart, jstart+(size/2)-1,
istart+(size/2)-1, jstart+(size/2)-1); // 2nd quad
            locateTromino(board, size/2, istart+(size/2), istart+(size-1), jstart, jstart+(size/2)-
1, missing_i, missing_j); // 3RD QUAD
            locateTromino(board, size/2, istart+(size/2), istart+size-1, jstart+(size/2),
jstart+size-1, istart+(size/2), jstart+(size/2)); // 4th quad
        break;

        case 4:
            // 4th quad: Right T
            board[(istart+iend)/2][(jstart+jend)/2] = tromino_id; // Top left
            board[(istart+iend)/2][((jstart+jend)/2)+1] = tromino_id; // Top right
            board[((istart+iend)/2)+1][(jstart+jend)/2] = tromino_id; // Bottom left

            // Quadruple recursion
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart+(size/2), jstart+(size-
1), istart+(size/2)-1, jstart+(size/2)); // 1st quad
            locateTromino(board, size/2, istart, istart+(size/2)-1, jstart, jstart+(size/2)-1,
istart+(size/2)-1, jstart+(size/2)-1); // 2nd quad
            locateTromino(board, size/2, istart+(size/2), istart+(size-1), jstart, jstart+(size/2)-
1, istart+(size/2), jstart+(size/2)-1); // 3rd quad
            locateTromino(board, size/2, istart+(size/2), istart+size-1, jstart+(size/2),
jstart+size-1, missing_i, missing_j); // 4TH QUAD
        break;
    }
}

// To display board in the console
void displayBoard(vector<vector<int>> &board, int n){
    for(int i = 0; i < pow(2, n); i++){
        for(int j = 0; j < pow(2, n); j++){
            cout << setw(3) << board[i][j] << " ";
        }
        cout << endl;
    }
    cout << endl;
}
```

```
// Coloring the board after filling the board with trominoes
void colorBoard(vector<vector<int>> &board, int size){

    // STEP 1: ADJACENCY GRAPH
    // Mapping each node ID to its adjacent node IDs (used a set to prevent repetition)
    unordered_map<int, unordered_set<int>> adjacency;
    for (int i  = 0;  i <  size; i++) {
        for (int j = 0; j < size; j++) {
            int current = board[i][j];
            if (current <= 0) continue; // Ignore missing cell
            // To check all adjacent cells of a single cell (left, right, down, up)
            vector<pair<int, int>> directions = {{-1,0},  {1,0}, {0,-1}, {0,1}};
            for (auto [di, dj] : directions) {
                int xi = i + di, xj = j + dj;
                if (xi >= 0 && xi < size && xj >= 0 && xj < size) {
                    int neighbor = board[xi][xj];
                    // Ignore the neighbor if its missing OR has the same ID as the current cell
                    if (neighbor > 0 && neighbor != current) {
                        // Add adjacency to both nodes: current and neighbor
                        adjacency[current].insert(neighbor);
                        adjacency[neighbor].insert(current);
                    }
                }
            }
        }
    }

    // STEP 2: GREEDY COLORING
    // To track each tromino ID and its color
    unordered_map<int, int> tromino_color;
    for (auto &entry : adjacency) {
        int tromino_id = entry.first;
        const unordered_set<int> &neighbors = entry.second;

        // Track used colors by neighbors for EACH entry
        bool used[3] = {false, false, false};

        for (int neighbor : neighbors) {
            if (tromino_color.count(neighbor)) { // Returns 1 if it has been colored before, 0 if
not
                used[tromino_color[neighbor]] = true; // Mark it as used to prevent the current

tromino_id to be the same color
            }
        }

        // Assign the first available color (GREEDY COLORING)
        for (int c = 0; c < 3; c++) { // 0, 1, 2 to navigate used array and also colors
            if (!used[c]) {
                tromino_color[tromino_id] = c;
                break;
            }
        }
    }

    // STEP 3: OVERWRITE EXISTING IDS WITH COLORS
    for (int i  = 0;  i <  size; i++) {
        for (int j = 0; j < size; j++) {
            if (board[i][j] > 0) { // If not missing
                board[i][j] = tromino_color[board[i][j]] + 1; // Shifted all colors by 1 to make
them 1, 2, 3
             }
        }
    }
}
```

```
int main() {

    int n;
    cout << "n: ";
    cin >> n;

    int missing_row, missing_col;
    cout << "Row of missing cell: ";
    cin >> missing_row;
    cout << "Column of missing cell: ";
    cin >> missing_col;

    int size = pow(2, n);
    // Initialize board
    vector<vector<int>> board(size, vector<int>(size, 0));
    // Remove missing cell
    board[missing_row-1][missing_col-1]  =  -1;

    // Display board
    displayBoard(board, n);

    // Start the divide and conquer algorithm
    locateTromino(board, size, 0, size-1, 0, size-1, missing_row-1, missing_col-1);
    // Color the board after tromino placement
    colorBoard(board, size);

    // Display board
    displayBoard(board, n);

    return 0;
}
```

The program begins by declaring a global variable named tromino_id and initializing it to zero. This variable is essential to the tiling process as it uniquely labels each L-shaped tromino placed on the board. The uniqueness is important for identifying which group of three connected cells belong together and later for distinguishing each tromino during the coloring process.

The first core function in the program is locateTromino, which performs the recursive tiling. It takes in a reference to the board (a two-dimensional vector), the size of the current sub-board, and the starting and ending row and column indices for that region. It also receives the coordinates of the missing cell within that sub-region. The function first checks whether the current region is a single cell in size. If so, it returns immediately, as no tromino can be placed in a 1x1 space. This serves as the base case for the recursive process.

Next, the function determines which quadrant of the current board region contains the missing square. The quadrants are calculated by finding the midpoint of the row and column ranges. If the missing square falls in the top half and right side, it is considered to be in quadrant 1. If it is in the top-left, it is in quadrant 2. If it is in the bottom-left, it falls into quadrant 3, and if it is in the bottom-right, it is in quadrant 4. This quadrant detection is key to placing the L-shaped tromino in the correct orientation such that it avoids the real missing cell while simulating a new "missing" cell in the other three quadrants.

After identifying the quadrant with the real missing square, the program increments the tromino ID to assign a new, unique label to the tromino that is about to be placed. It then places the tromino in the center of the board, such that it covers one square from each of the three quadrants that do not contain the actual missing cell. The placement is done manually by referencing the midpoint rows and columns of the current region and assigning the current tromino_id to three specific cells forming the L-shape.

Following this placement, the function calls itself recursively on each of the four quadrants. The quadrant that originally contained the missing square is passed the original coordinates of the missing cell, ensuring consistency in the recursive breakdown. The other three quadrants are each passed the coordinates of the square just filled in by the center tromino, effectively treating them as the new missing cells. Each recursive call is made on a region of half the size, and this process continues until all subregions are reduced to size one, at which point recursion terminates.

After the board has been completely filled with tromino IDs, the function colorBoard is called to assign one of three colors to each distinct tromino. This function begins by building an adjacency graph that maps each tromino ID to a set of neighboring IDs. This is done by iterating through every cell on the board. For each cell, if its value is greater than zero, the function checks its four immediate neighbors: up, down, left, and right. If any neighbor is within bounds and has a different tromino ID, the function adds an edge between the current cell's ID and the neighbor's ID in an adjacency list represented by an unordered map of sets. This adjacency map ensures that we can later assign colors such that no two adjacent trominoes are the same.

Once the adjacency graph is complete, the function proceeds with the coloring phase using a greedy algorithm. It iterates over each entry in the adjacency list, representing a tromino and its set of neighbors. For each tromino, the function initializes a boolean array of size three to keep track of which colors are already used by its neighbors. It then loops through the set of adjacent trominoes and, if any of them have already been assigned a color, it marks that color as used. After this check, the function selects the first unused color and assigns it to the current tromino. Because each tromino is adjacent to at most four others and only three colors are needed, the greedy approach guarantees that no two connected trominoes end up sharing the same color.

Following the coloring, the function makes one last pass through the board. For each cell with a positive value (indicating that it belongs to a tromino), it replaces the tromino ID with its assigned color plus one. The color values originally ranged from 0 to 2, so adding one shifts them to 1, 2, and 3, making them more readable for output. The missing cell, which was marked with -1, remains unchanged.

The main function of the program acts as the entry point. It begins by prompting the user to enter the value of n. It then asks the user for the row and column of the missing square. These indices are adjusted from 1-based to 0-based to match the internal representation used in the board vector. A two-dimensional vector is created and initialized to all zeroes, and the missing cell is marked with -1. The board is then displayed to show the initial state. After that, the recursive tiling function is invoked to fill the board with trominoes, and the coloring function is applied to assign colors to each tromino. Finally, the board is displayed again, now showing the completed and colored result. The output confirms that the board has been tiled correctly and that the color constraints are met.

Time Complexity Analysis

The locateTromino function is a recursive divide-and-conquer algorithm responsible for tiling the entire board with L-shaped trominoes. In each invocation, the function first checks whether the size of the current sub-board is 1. If so, it returns immediately as no tromino can be placed in such a space. Otherwise, it determines which quadrant contains the missing square and places one L-shaped tromino in the center of the current sub-board to balance the problem. This placement covers three cells and takes constant time. Following that, the function recursively calls itself four times, each on a quadrant of size exactly half the current side length. Since each level of recursion divides the board into four smaller sub-boards and performs only constant-time work at that level (placing one tromino), the time complexity follows the recurrence relation

$$T(n) = 4T\left(\frac{n}{2}\right) + O(1)$$

where n is the length of one side of the board. By solving this recurrence using the Master Theorem:

$$T(n) = aT\left(\frac{n}{b}\right) + O(n^d)$$
$$such\ that\ a = 4, b = 2\ and\ d = 1$$

we find that the total time complexity of the locateTromino function is

$$O(\mathrm{n}^{\log_2 4}) = O(n^2)$$

which corresponds to the number of cells on the board. In the worst-case scenario, the function recursively visits and processes every section of the board until all $n^2 - 1$ cells (excluding the missing one) are tiled, resulting in a total of $(n^2 - 1)/3$ trominoes being placed, confirming the quadratic time.

The colorBoard function is responsible for coloring all the trominoes on the board such that no two adjacent trominoes share the same color, using only three distinct colors. This function consists of three major phases, each of which runs in worst-case linear time with respect to the number of cells on the board.

In the first phase, it builds an adjacency graph by scanning every cell on the board. For each of the n × n cells, it checks up to four neighbors to detect connections between different trominoes. Since each neighbor check and graph insertion operation is constant time, this phase takes time proportional to $O(n^2)$.

In the second phase, the function performs greedy coloring on each unique tromino. The total number of trominoes is also proportional to $O(n^2)$, and each tromino can be adjacent to at most four others. For each tromino, the function examines its neighbors and selects one of the three available colors that hasn't been used, all in constant time. This results in another $O(n^2)$ step.

Finally, in the third phase, the function updates the board by replacing every cell's tromino ID with its assigned color. This final sweep again processes all n^2 cells, performing a constant-time operation per cell. As all three phases individually run in $O(n^2)$ time, the overall worst-case time complexity of the colorBoard function is $O(n^2)$.

Since both the tiling and coloring functions independently run in $O(n^2)$ time, the overall worst-case time complexity of the entire program:

$$O(n^2)$$

Output

```
n: 4
Row of missing cell: 7
Column of missing cell: 7
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0  -1   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0   0   0   0   0   0   0   0   0

  1   1   3   3   1   1   2   2   1   1   2   2   1   1   2   2
  1   2   2   3   1   3   3   2   1   3   3   2   1   3   3   2
  3   2   1   1   2   2   3   1   2   3   1   1   2   2   3   1
  3   3   1   1   1   2   1   1   2   2   1   3   3   2   1   1
  1   1   2   1   3   3   2   2   1   1   2   2   3   1   2   2
  1   3   2   2   3   1   1   2   1   3   3   2   1   1   3   2
  2   3   3   1   2   1  -1   1   2   2   3   1   2   3   3   1
  2   2   1   1   2   2   1   1   3   2   1   1   2   2   1   1
  1   1   2   2   1   1   2   3   3   1   2   2   1   1   2   2
  1   3   3   2   1   3   2   2   1   1   3   2   1   3   3   2
  2   3   1   1   2   3   3   1   2   3   3   1   2   2   3   1
  2   2   1   3   2   2   1   1   2   2   1   1   3   2   1   1
  1   1   2   3   3   1   2   2   1   1   2   3   3   1   2   2
  1   3   2   2   1   1   3   2   1   3   2   2   1   1   3   2
  2   3   3   1   2   3   3   1   2   3   3   1   2   3   3   1
  2   2   1   1   2   2   1   1   2   2   1   1   2   2   1   1
```

```
n: 3
Row of missing cell: 1
Column of missing cell: 1
 -1   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0

 -1   1   2   2   1   1   3   3
  1   1   3   2   1   2   2   3
  2   3   3   1   3   3   2   1
  2   2   1   1   2   3   1   1
  1   1   1   2   2   1   2   2
  1   3   1   1   1   1   3   2
  2   3   3   1   2   3   3   1
  2   2   1   1   2   2   1   1
```

```
n: 3
Row of missing cell: 2
Column of missing cell: 1
  0   0   0   0   0   0   0   0
 -1   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0

  1   1   2   2   1   1   3   3
 -1   1   3   2   1   2   2   3
  2   3   3   1   3   3   2   1
  2   2   1   1   2   3   1   1
  1   1   1   2   2   1   2   2
  1   3   1   1   1   1   3   2
  2   3   3   1   2   3   3   1
  2   2   1   1   2   2   1   1
```

```
n: 3
Row of missing cell: 6
Column of missing cell: 7
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0  -1   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0

  1   1   3   3   1   1   3   3
  1   2   2   3   1   2   2   3
  3   2   1   1   3   3   2   1
  3   3   1   2   2   3   1   1
  1   1   1   2   1   1   2   2
  1   3   1   1   1   3  -1   2
  2   3   3   1   2   3   3   1
  2   2   1   1   2   2   1   1
```

```
n: 3
Row of missing cell: 4
Column of missing cell: 5
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0  -1   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0

  1   1   3   3   1   1   3   3
  1   2   2   3   1   2   2   3
  3   2   1   1   3   3   2   1
  3   3   1   2  -1   3   1   1
  1   1   1   2   2   1   2   2
  1   3   1   1   1   1   3   2
  2   3   3   1   2   3   3   1
  2   2   1   1   2   2   1   1
```

Visualization







Comparison

Brute-Force Approach

Explore all possible tromino placements on the board. For each configuration, try assigning each of the 3 colors to the trominoes. Backtrack if any two adjacent trominoes share the same color or if the board cannot be fully covered. This can be seen in the following pseudo-code:

```
function brute_force(board, trominoes, position):
    if board is fully covered:
        return is_valid_coloring(trominoes)

    for each possible L-shaped placement starting from current position:
        for color in {red, green, blue}:
            if  placement is  valid:
                place tromino with color
                if brute_force(updated_board, trominoes + new_tromino, next_position):
                    return true
                undo placement
    return false
```

Let T be the number of trominoes on the board. For a board of size 2^n x 2^n with one missing square, the number of trominoes is T = $(4^n - 1) / 3$. For each tromino, we consider up to three color choices and up to four tromino orientations, and for each board configuration, we attempt every possible placement of trominoes. Since tilings and colorings must be validated recursively and backtracked, the total time complexity is

$$O(12^T)$$

where T is the number of trominoes on the board.

Dynamic Programming Approach

The dynamic programming solution applies recursion with memoization to cache solutions of subproblems involving smaller boards. Each subproblem captures the configuration of a subboard along with the coloring of its boundary edges to ensure valid merges of adjacent subboards. The recursion proceeds by dividing the board into four quadrants and solving them individually while placing a central tromino in the region that does not contain the missing square. The key insight is to reuse previously computed solutions of subboards by encoding the missing square's position and boundary constraints into the state.

The pseudocode below captures the essence of this recursive, memoized dynamic programming strategy:

```
function dp(x, y, size, missing, boundary_colors):
    key = (x, y, size, missing, boundary_colors)
    if key in memo:
        return memo[key]

    if size == 2:
        return base_case(x, y, missing, boundary_colors)

    mid = size / 2
    split board into 4 quadrants
    place central tromino at the center avoiding the quadrant with the missing square

    total_ways = 0
    for each valid coloring of the central tromino:
        propagate boundary constraints
        for each quadrant:
            total_ways += dp(quadrant_parameters)

    memo[key] = total_ways
    return total_ways
```

Let B(n) denote the number of distinct boundary configurations for subproblems of size n. For each subproblem, there are approximately $O(n^2)$ positions and B(n) configurations to evaluate. The total number of subproblems is therefore $O(n^2 * B(n))$. For a 2^n x 2^n board, the number of trominoes is $T = (4^n - 1) / 3$. Each subproblem requires constant or low-degree polynomial time depending on how efficiently the boundary constraints are propagated. Consequently, the overall time complexity of the dynamic programming approach is:

$$O(4^n * B(n))$$

The following table below provides a comparative overview of the three well-known techniques. Each method varies significantly in its strategy, efficiency, and suitability depending on the structure and constraints of the input board. The Divide and Conquer method, which is the one used in this report, stands out for its optimal performance. In contrast, brute-force methods attempt to exhaustively explore all possible configurations, making them highly inefficient. Dynamic Programming approaches, though powerful in counting valid configurations under certain constraints, are generally better suited for analytical purposes.

Algorithm Comparison

Technique	Description	Time Complexity	Advantages	Disadvantages
Divide and Conquer	Recursively divide the board into quadrants, place one tromino at center, and recurse with a simulated missing cell in each sub-board.	$O(n^2)$	- Reuses subproblem solutions - Lowest complexity	- Complex state representation
Bruteforce	Try every possible placement of trominoes and backtrack when a solution fails. Explores all configurations.	Exponential	- Simple to implement - Guaranteed to find all solutions	- Extremely slow and unscalable
Dynamic Programming	Use memorization to count the number of valid tiling configurations under certain constraints.	Exponential or polynomial	- Efficient use of overlapping subproblems	- Requires careful state encoding - Large memory



Figure 5: Divide and Conquer (green) versus Dynamic Programming (blue)

Additional Notes

An alternative coloring approach was explored during the development phase. Instead of building an adjacency graph to identify neighboring trominoes and applying a separate coloring phase afterward, the initial idea was to assign a color to each tromino immediately upon placement during the recursive tiling by calling the function determineColor.

```
// Determine tromino color
short determineColor(vector<vector<int>>& board, int center_i, int center_j, short quad) {
    // Track whether each color is used or not
    vector<bool> used(3, false);

    // Get the cells of the current tromino based on its orientation
    vector<pair<int, int>> trominoCells;
    switch(quad)  {
        case 1: // Standard L-shape
            trominoCells = {{center_i, center_j}, {center_i+1, center_j}, {center_i+1, center_j+1}};
            break;
        case 2: // Mirrored L-shape
            trominoCells = {{center_i, center_j+1}, {center_i+1, center_j}, {center_i+1,
center_j+1}};
            break;
        case 3: // Rotated L-shape
            trominoCells = {{center_i, center_j}, {center_i, center_j+1}, {center_i+1, center_j}};
            break;
        case 4: // Other rotated L-shape
            trominoCells = {{center_i, center_j}, {center_i, center_j+1}, {center_i+1, center_j+1}};
            break;
    }

    // Check adjacent cells
    for (auto& cell : trominoCells) {
        int i = cell.first, j = cell.second;

        // Check all 4 directions
        if (i > 0 && board[i-1][j] > 0 && board[i-1][j] <= 3) // Up
            used[board[i-1][j]-1] = true;
        if (i < board.size()-1 && board[i+1][j] > 0 && board[i+1][j] <= 3) // Down
            used[board[i+1][j]-1] = true;
        if (j > 0 && board[i][j-1] > 0 && board[i][j-1] <= 3) // Left
            used[board[i][j-1]-1] = true;
        if (j < board.size()-1 && board[i][j+1] > 0 && board[i][j+1] <= 3) // Right
            used[board[i][j+1]-1] = true;

        // Each check makes sure i and j are within limits and the board number is between 1 and 3
(inclusive)
    }

    // Find the first available color
    for (short color = 1; color <= 3; color++) {
        if (!used[color-1]) {
            return color;
        }
    }

    // This should NEVER happen
    return -1;
}
```

While this greedy strategy seemed promising in early test cases, it ultimately failed in more complex configurations—especially where multiple adjacent trominoes converged at the quadrant centers. The lack of contextual awareness during placement meant that trominoes could unknowingly be colored the same as a neighbor, violating the adjacency constraint.

```
n: 3
Row of missing cell: 2
Column of missing cell: 1

  0   0   0   0   0   0   0   0
 -1   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0
  0   0   0   0   0   0   0   0

  1   1   2   2   3   3   2   2
 -1   1   1   2   3   1   1   2
  2   1   1   3   2   2   1   3
  2   2   3   3   1   2   3   3
  3   3   2   1   1   3   2   2
  3   1   2   2   3   3   1   2
  2   1   1   3   2   1   1   3
  2   2   3   3   2   2   3   3
```

These errors highlighted the importance of building a proper adjacency graph and using a global greedy coloring algorithm after tiling is complete. This correction ensured that no two connected trominoes share a color, and that the final visual output is both accurate and clean.

Conclusion

Through this thorough research, we managed to successfully implement and analyze a classic algorithm for solving the tromino tiling problem using a divide and conquer approach. By recursively dividing the board into quadrants and placing a central L-shaped tromino to simulate missing cells, the algorithm achieves an efficient and elegant solution with a guaranteed runtime of $O(n^2)$ on a $2^n \times 2^n$ board with one missing square. Beyond simply tiling the board, the project extends this technique to apply a valid 3-coloring to the trominoes using an adjacency graph and a greedy coloring algorithm, ensuring no two adjacent tiles share the same color. Visual examples, benchmark comparisons, and complexity plots further support the correctness and efficiency of the method. Compared to other common strategies—such as brute force, greedy filling, or dynamic programming—the divide and conquer method proves to be not only more scalable but also mathematically grounded and visually interpretable. The project also includes comprehensive testing across a variety of board sizes and missing cell positions to validate both correctness and performance.

References

[1] Knuth, D. E. The Art of Computer Programming, Volume 1: Fundamental Algorithms. 3rd Edition. Section 2.2.2, Exercise 6 (Defective Chessboard Problem).

[2] Golomb, S. W. Polyominoes: Puzzles, Patterns, Problems, and Packings. Dover Publications, 1996.

[3] I-Ping Chu, Richard Johnsonbaugh: Tiling and recursion. SIGCSE 1987: 261-263