



Module 2 Cheat Sheet: Introduction to the Hadoop Ecosystem

Package/Method	Description	Code Example
bin/hadoop	All Hadoop commands are invoked by the bin/hadoop script.	Running Hadoop script without arguments: <pre>1. 1</pre>
	Running the Hadoop script without any arguments prints the description for all commands.	<pre>1. bin/hadoop</pre> <div>Copied!</div>
cat	Reads each file parameter in sequence and writes it to standard output. If you do not specify a file name, the cat command reads from standard input.	Create two sample files. <pre>1. 1 2. 2 1. echo "This is file 1" > file1.txt 2. echo "This is file 2" > file2.txt</pre> <div>Copied!</div>
	You can also specify a file name of - (dash) for standard input.	Use the cat command to read and display the contents of both files <pre>1. 1 1. cat file1.txt file2.txt</pre> <div>Copied!</div>
cd	Used to move efficiently from the existing working directory to different directories on your system.	Sample output (Contents of file1.txt and file2.txt): <pre>1. 1 2. 2 1. This is file 1 2. This is file 2</pre> <div>Copied!</div>
		Basic syntax of cd command: <pre>1. 1 1. cd [options]... [directory]</pre> <div>Copied!</div>
		Example 1: Change directory location to "folder1" <pre>1. 1 1. cd /usr/local/folder1</pre> <div>Copied!</div>
		Example 2: Get back to the previous working directory

Package/Method	Description	Code Example
		<div>1. 1</div> <div>1. cd -</div> <div>Copied!</div> <div>Example 3: Move up one level from the present working directory tree</div> <div>1. 1</div> <div>1. cd ..</div> <div>Copied!</div>
create table	Used to create a new table in a database	<div>Create a new database (if not already created).</div> <div>1. 1</div> <div>1. CREATE DATABASE your_database;</div> <div>Copied!</div> <div>Use the newly created database.</div> <div>1. 1</div> <div>1. USE your_database;</div> <div>Copied!</div> <div>Create a new table named "employees" in Hive.</div> <div>1. 1</div> <div>2. 2</div> <div>3. 3</div> <div>4. 4</div> <div>5. 5</div> <div>6. 6</div> <div>7. 7</div> <div>8. 8</div> <div>9. 9</div> <div>10. 10</div> <div>1. CREATE TABLE employees (2. id INT, 3. first_name STRING, 4. last_name STRING, 5. email STRING, 6. hire_date DATE 7.) 8. ROW FORMAT DELIMITED 9. FIELDS TERMINATED BY ',' 10. STORED AS TEXTFILE;</div> <div>Copied!</div> <div>Show the list of tables in the database.</div> <div>1. 1</div> <div>1. SHOW TABLES;</div> <div>Copied!</div> <div>Sample Output (List of Tables):</div> <div>1. 1</div> <div>2. 2</div>

Package/Method	Description	Code Example
curl	A command-line tool (pronounced "curl") that allows data to be exchanged between a device and a server through a terminal. The user specifies the server URL, the location where they want to send the request, and the data they want to send to the server URL using this command-line interface (CLI).	<div><div>1. OK</div><div>2. employees</div></div> <div>Copied!</div> <div>Example 1: Sending a GET request and displaying the response</div> <div>Send a GET request to a server and display the response.</div> <div><div>1. 1</div><div>1. curl https://www.example.com</div></div> <div>Copied!</div> <div>In this example, we use the curl command to send a GET request to https://www.example.com and display the HTML response from the server.</div> <div>-----</div> <div>Example 2: Sending data to a server using POST Request:</div> <div>Send a POST request with data to a server and display the response.</div> <div><div>1. 1</div><div>1. curl -X POST -d "name=John&age=30" https://www.example.com/api</div></div> <div>Copied!</div> <div>In this example, we use the curl command to send a POST request to https://www.example.com/api with data name=John&age=30 and display the JSON response from the server.</div>
		<div>Running a command in a running Docker container:</div> <div>Run a new command inside a running Docker container.</div> <div><div>1. 1</div><div>1. docker exec -it container_name_or_id ls /app</div></div> <div>Copied!</div> <div>Sample Output (List of files in the '/app' Directory inside the container):</div> <div><div>1. 1</div><div>2. 2</div><div>3. 3</div><div>1. file1.txt</div><div>2. file2.txt</div><div>3. subdirectory</div></div> <div>Copied!</div> <div>In this example:</div> <div><div><div>• docker exec is used to run a new command (ls /app) inside a running Docker container.</div><div>• -it enables an interactive terminal session, which allows you to see the output of the command.</div><div>• container_name_or_id is the name or ID of the running Docker container you want to execute the command in.</div></div></div>
docker exec	Runs a new command in a running container. It only runs when the container's primary process is running, and it is not restarted if the container is restarted.	

Package/Method	Description	Code Example
		<div><div><ul style="list-style-type: none">ls /app is the command that lists the files and directories in the '/app' directory inside the container.</div></div>
		<div>Starting Docker containers using docker-compose:</div>
		<div>Suppose you have a docker-compose.yml file like this:</div>
docker-compose	Compose is a tool for defining and running multi-container Docker applications. It uses the YAML file to configure the services and enables us to create and start all the services from just one configuration file.	<div><div><div><div>1. 1</div><div>2. 2</div><div>3. 3</div><div>4. 4</div><div>5. 5</div><div>6. 6</div><div>7. 7</div><div>8. 8</div><div>9. 9</div><div>10. 10</div></div><div><pre>1. version: '3' 2. services: 3. web: 4. image: nginx:latest 5. ports: 6. - "80:80" 7. db: 8. image: postgres:latest 9. environment: 10. POSTGRES_PASSWORD: example_password</pre></div></div></div>
		<div><div>Copied!</div><div>You can use docker-compose to start the services defined in the docker-compose.yml file as follows:</div></div>
		<div><div>Navigate to the directory containing the docker-compose.yml file.</div></div>
		<div><div><div>1. 1</div><div>1. cd /path/to/your/docker-compose-project</div></div><div><div>Copied!</div></div></div>
		<div>Start the Docker containers defined in the docker-compose.yml file</div>
docker pull	You can download Docker images from the internet.	<div><div><div>1. 1</div><div>1. docker-compose up</div></div><div><div>Copied!</div></div></div>
		<div><div><div>1. 1</div><div>1. docker pull [OPTIONS] IMAGE_NAME[:TAG]</div></div><div><div>Copied!</div></div></div>
docker run	It runs a command in a new container, getting the image and starting the container if needed.	<div><div><div>1. 1</div><div>1. docker run [OPTIONS] IMAGE [COMMAND] [ARG...]</div></div><div><div>Copied!</div></div></div>
git clone	You can create a copy of a specific	<div><div><div>1. 1</div><div>1. git clone REPOSITORY_URL [DESTINATION_DIRECTORY]</div></div></div>

Package/Method	Description	Code Example
hdfs dfs	repository or branch within a repository.	<div>Copied!</div> <div>Example-1: Listing files and directories in HDFS: List files and directories in the root directory of HDFS. 1. 1 1. hdfs dfs -ls / <div>Copied!</div> Example-2: In this example, we use the hdfs dfs -ls command to list files and directories in the root directory of HDFS. 1. 1 1. hdfs dfs -ls / <div>Copied!</div> Sample output: 1. 1 2. 2 3. 3 1. drwxr-xr-x - hdfs hduser 0 2023-09-13 10:00 /user 2. drwxrwxrwx - hdfs hduser 0 2023-09-13 10:05 /tmp 3. drwxrwxrwx - mapred hduser 0 2023-09-13 10:10 /mapred <div>Copied!</div> Create a new directory named "mydata" in HDFS. 1. 1 1. hdfs dfs -mkdir /user/your_username/mydata <div>Copied!</div> Display the contents of a file in HDFS.</div>
hdfs dfs -cat	Display the contents for a file.	<div>Copied!</div> Create a directory in HDFS. 1. 1 1. hdfs dfs -mkdir /user/username/mydirectory <div>Copied!</div> Upload a file from the local file system to HDFS.
hdfs dfs -mkdir	Creates a directory named path in HDFS	<div>Copied!</div> Upload a file or folder from the local disk to HDFS. 1. 1 1. hdfs dfs -put localfile.txt /user/username/hdfsfile.txt <div>Copied!</div>
hdfs dfs -put		

Package/Method	Description	Code Example
LOAD DATA INPATH	Hive provides the functionality to load precreated table entities either from the local file system or from HDFS. This command is used to load data into the hive table.	Load data from HDFS into a Hive table. 1. 1 2. 2 1. LOAD DATA INPATH '/user/username/hdfsfile.txt' INTO TABLE 2. mytable;
	Writes to standard output the contents of each specified Directory parameter or the name of each specified file parameter, along with any other information you ask for with the flags. If you do not specify a file or directory parameter, the ls command displays the contents of the current directory.	Basic command syntax 1. 1 1. ls [options] [file/directory] Copied! Example 1: Sorts the file names displayed in the order of last modification time. 'r' is for displaying in reverse order 1. 1 2. 2 1. ls -lt 2. ls -ltr Copied! Example 2: Displays hidden files 1. 1 1. ls -a Copied!
mkdir	Used to create one or more directories specified by the Directory parameter. Each new directory contains the standard entries dot (.) and dot dot (..). You can specify the permissions for the new directories with the -m Mode flag.	Create a new directory named "myfolder." 1. 1 1. mkdir myfolder Copied!

Package/Method	Description	Code Example
SELECT * FROM	Lists all the rows from the table to check if the data has been loaded from the file.	<div>Select all rows from a table. 1. 1 1. SELECT * FROM tablename; <div>Copied!</div></div>
show tables	Used to see all the tables in the database that have been selected.	<div>Show all tables in the selected database. 1. 1 1. SHOW TABLES; <div>Copied!</div></div>
tar	Looks for archives on the default device (usually tape) unless you specify another device. When writing to an archive, the tar command uses a temporary file (the /tmp/tar* file) and maintains in memory a table of files with several links.	<div>Create a tar archive of a directory. 1. 1 1. tar -cvf archive.tar /path/to/directory <div>Copied!</div></div>
wget	Stands for web get. The wget is a free, noninteractive file downloader command. Noninteractive means it can work in the background when the user is not logged in.	<div>Basic syntax of the wget command; commonly used options are [-V], [-h], [-b], [-e], [-o], [-a], [-q] 1. 1 1. wget [options]... [URL]... <div>Copied!</div><div>Example 1: Specifies to download file.txt over HTTP website URL into the working directory. 1. 1 1. wget http://example.com/file.txt <div>Copied!</div><div>Example 2: Specifies to download the archive.zip over the HTTP website URL in the background and returns you to the command prompt in the interim. 1. 1 1. wget -b http://www.example.org/files/archive.zip <div>Copied!</div></div></div></div>

Changelog

Date	Version	Changed by	Change Description
2023-09-20	2.0	Kunal Merchant	QC Reviewed
2023-09-20	1.0	Gagandeep Singh	Initial version created

IBM Corporation 2023. All rights reserved.