

1. A (Jobs)
2. B (: before)
3. C (Configure a single-column page layout)
- 4.

```
<!DOCTYPE html>
<html lang="en">
<head>
<title>Find the Error</title>
<meta charset="utf-8">
<style>
body { background-color: #d5edb3;
color: #000066;
font-family: Verdana, Arial, sans-serif; }
nav { float: right;
width: 120px; }
main { padding: 20px 150px 20px 20px;
background-color: #ffffff;
color: #000000; }
</style>
</head>
<body>
<header role="banner">
<h1>Trillium Media Design</h1>
</header>
<nav role="navigation">
<ul>
<li><a href="index.html">Home</a></li>
```

```
<li><a href="services.html">Services</a></li>
```

```
<li><a href="contact.html">Contact</a></li>
```

```
</ul>
```

```
</nav>
```

```
<main role="main">
```

```
<p>Our professional staff takes pride in its working relationship with our clients by offering personalized services that listen to their needs, develop their target areas, and incorporate these items into a website that works.</p>
```

```
</main>
```

```
</body>
```

```
</html>
```

Web Research:

Mobile Web Design and Accessibility

The W3C's Web Accessibility Initiative argues that mobile web design and web accessibility are deeply interconnected. Rather than maintaining separate guidelines, the latest WCAG covers mobile web content, native apps, and hybrid apps under a single standard.

Shared principles include:

Alternative text — Required under WCAG for blind/low-vision users relying on screen readers, alt text also benefits mobile users on limited data plans who disable images or experience low bandwidth.

Heading hierarchy and semantic HTML — Screen reader users navigate pages via headings, so a logical structure is essential for accessibility. This same structure aids mobile browsers in rendering content efficiently on narrow viewports. Semantic elements like `<nav>`, `<main>`, and `<article>` help both assistive technologies and mobile browsers interpret page layout correctly.

Color contrast and font resizing — WCAG requires sufficient contrast for users with low vision or color blindness; this equally benefits mobile users in bright sunlight. Text resizing without loss of functionality aligns with mobile best practices, as content should reflow smoothly when font sizes increase or viewports narrow.

Touch targets and input modality — WCAG 2.1 added success criteria for touch target size and spacing, driven by the rise of touchscreens. These rules also help users with motor impairments. Similarly, avoiding complex gestures aids both one-handed mobile users and people with physical disabilities.

The core takeaway: Accessible design is simply good design. Using responsive design, clean semantic HTML, and testing with real assistive technologies improves the experience for everyone — regardless of device. Building with all users in mind benefits all users.