

# Genesis Protect Acute v1

## Claim Verification Map

On-Chain/Off-Chain Boundary · PHI Separation · LP Capital Protection

|                |                                                |
|----------------|------------------------------------------------|
| Date           | May 10, 2026                                   |
| Version        | 1.0                                            |
| Status         | Pre-Mainnet Review                             |
| Audience       | Investors · LPs · Sponsors · External Auditors |
| Classification | Internal — Pre-Mainnet Analysis                |
| Network        | Solana (Devnet at publication)                 |

Three Protocol-Level Guarantees — No Operator Trust Required

- 1. Reserve capital cannot leave the vault without a valid, attested, settled ClaimCase
- 2. Evidence integrity is tamper-evident — hash is permanently immutable once the oracle attests
- 3. Raw patient data (PHI) never appears on Solana in any form — only 32-byte SHA-256 hashes

Every claim state · Every verification event · Every hash anchor · Fully auditable from public chain data

## Executive Summary

Genesis Protect Acute v1 processes health insurance claims through a cryptographically verifiable truth chain anchored on Solana. This document is the authoritative map of that chain — for investors, LPs, sponsors, and auditors who need to understand what the protocol guarantees and how to verify those guarantees from public on-chain data, **without accessing any patient health records**.

**Three properties are enforced at the protocol level — no operator trust required:**

| # | Property                                                               | How it is enforced                                                                                                              |
|---|------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| 1 | Reserve capital cannot leave the vault on an unauthorized claim        | Only outflow path: PDA-signed SPL transfer gated on ClaimCase.intake_status = SETTLED (4) with a valid oracle attestation chain |
| 2 | Claim evidence is tamper-evident — retrospective forgery is impossible | evidence_ref_hash immutable once attestation_count $\geq 1$ ; hash equality enforced on-chain at attest_claim_case              |
| 3 | Raw patient data (PHI) never appears on Solana in any form             | Only 32-byte SHA-256 fingerprints written on-chain; raw documents stay encrypted on the off-chain oracle portal                 |

**What LPs and sponsors can verify independently — from public Solana explorer data alone:**

- Every claim opened, every evidence hash committed, every oracle attestation, every adjudication decision, and every payout — each with timestamp and signing authority
- That vault balances decrease only on settled, attested claims
- That oracle attestations reference exactly the evidence packet that was reviewed (hash equality enforced on-chain — transaction reverts on mismatch)
- That protocol fees were correctly carved out at settlement

**Phase 0 posture:** Operator-backed oracle review with all material state transitions anchored on-chain. The roadmap toward fully decentralized adjudication is documented in §10.

## §1 — Legend & Pre-Claim Foundation

| Symbol | Meaning                                                                 |
|--------|-------------------------------------------------------------------------|
| ■      | Solana instruction (on-chain transaction)                               |
| ■      | On-chain proof anchor (hash or state written to Solana)                 |
| ■      | Off-chain only (raw PHI, operator workflow, AI logs)                    |
| ■      | TEE only (MagicBlock private review — hash exits, plaintext never does) |

Before any claim opens, the protocol anchors the policy terms, pricing, and evidence requirements on-chain as **immutable hash commitments** inside the PolicySeries account. These are the root of the verification chain — every claim is evaluated against these anchored parameters. All material is locked (material\_locked = true) before the series goes live.

| PolicySeries field         | What it commits to                                        | Set by              |
|----------------------------|-----------------------------------------------------------|---------------------|
| terms_hash                 | Full coverage terms and exclusion schedule                | Protocol governance |
| pricing_hash               | Premium structure and benefit tiers                       | Protocol governance |
| payout_hash                | Benefit amounts per tier (T1/T2/T3) and reimbursement cap | Protocol governance |
| reserve_model_hash         | Reserve methodology and VaR parameters                    | Protocol governance |
| evidence_requirements_hash | Required document types per claim tier                    | Protocol governance |
| schema_binding_hash        | Binding to the verified OutcomeSchema (HealthPlan)        | Plan admin          |

The **OutcomeSchema** (genesis-protect-acute-claim v1) is separately registered on-chain and must be marked verified = true by governance before any oracle can attest. Its schema\_key\_hash and schema\_hash are snapshotted into every ClaimAttestation.

## §2 — Claim State Machine

The ClaimCase account's intake\_status field drives the complete claim lifecycle. No state can be skipped or forged without a valid signed Solana transaction from the authorized role.

| State                | intake_status | On-chain trigger                                     | Who signs                               | Money moves?                  |
|----------------------|---------------|------------------------------------------------------|-----------------------------------------|-------------------------------|
| <b>OPEN</b>          | 0             | open_claim_case                                      | Member or claims_operator or plan_admin | No                            |
| <b>UNDER_REV IEW</b> | 1             | Operator queue pickup (off-chain)                    | —                                       | No                            |
| <b>APPROVED</b>      | 2             | adjudicate_claim_case (approved_amount > 0)          | claims_operator                         | No — reserve booked           |
| <b>DENIED</b>        | 3             | adjudicate_claim_case (approved_amount == 0)         | claims_operator                         | No — obligation void          |
| <b>SETTLED</b>       | 4             | settle_claim_case / settle_claim_case_selected_asset | claims_operator                         | <b>YES — USDC exits vault</b> |
| <i>CLOSED</i>        | 5             | Reserved — Phase 1 dispute-case state                | —                                       | —                             |

### S3 — Instruction-to-Verification Map

Every step that produces an on-chain proof is listed with the exact account written, the hash anchored, and the event emitted. Off-chain steps (■) are shown for completeness — they leave no on-chain footprint at that point.

#### Step 1 — open\_claim\_case ■

|                           |                                                                                                  |
|---------------------------|--------------------------------------------------------------------------------------------------|
| Authorized signers        | Member wallet OR health_plan.claims_operator OR health_plan.plan_admin                           |
| PDA created               | ClaimCase — seeds: ["claim_case", health_plan.key(), claim_id]                                   |
| State transition          | → CLAIM_INTAKE_OPEN (0)                                                                          |
| ■ On-chain writes         | claim_case.claimant · .policy_series · .funding_line · .evidence_ref_hash (initial) · .opened_at |
| Event emitted             | ClaimCaseStateChangedEvent { claim_case, intake_status: 0, approved_amount: 0 }                  |
| ■ Off-chain at this point | Raw incident report, member identity docs — not yet submitted                                    |
| PHI on-chain?             | NO                                                                                               |
| ■ Security (PT-04)        | claimant constrained to member_position.wallet — operators cannot spoof claimant                 |

#### Step 2 — authorize\_claim\_recipient ■ (optional)

|                    |                                                        |
|--------------------|--------------------------------------------------------|
| Authorized signers | Member wallet ONLY — operators cannot set this         |
| State transition   | None                                                   |
| ■ On-chain writes  | claim_case.delegate_recipient (payout routing address) |
| Event emitted      | None                                                   |
| PHI on-chain?      | NO                                                     |

#### Step 3 — Evidence upload & human review ■

|                    |                                                                                  |
|--------------------|----------------------------------------------------------------------------------|
| Where              | OmegaX Health oracle portal (off-chain, encrypted)                               |
| ■ Member uploads   | Discharge summary · itemized invoice · location proof · doctor note              |
| ■ AI pre-screening | Completeness check, anomaly flags → operator queue                               |
| ■ Human review     | Claims operator reviews raw PHI against policy_series.evidence_requirements_hash |
| PHI on-chain?      | NO — raw documents never touch Solana                                            |

#### Step 4 — attach\_claim\_evidence\_ref ■

|                            |                                                                                                            |
|----------------------------|------------------------------------------------------------------------------------------------------------|
| Authorized signers         | health_plan.claims_operator                                                                                |
| Precondition               | claim_case.attestation_count == 0 (mutable only before first oracle attestation)                           |
| State transition           | None                                                                                                       |
| ■ On-chain writes — hash 1 | claim_case.evidence_ref_hash [SHA-256 of full evidence packet]                                             |
| ■ On-chain writes — hash 2 | claim_case.decision_support_hash [SHA-256 of operator review bundle]                                       |
| Event emitted              | None                                                                                                       |
| PHI on-chain?              | NO — only 32-byte hashes                                                                                   |
| Evidence lock              | Once attestation_count ≥ 1: evidence_ref_hash permanently immutable. Revised evidence → new ClaimCase PDA. |

## Step 5 — attest\_claim\_case ■

|                    |                                                                                                                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Authorized signers | oracle_profile.oracle                                                                                                                                                                            |
| Preconditions      | outcome_schema.verified == true · oracle has ATTEST_CLAIM permission · args.attestation_ref_hash == claim_case.evidence_ref_hash (enforced on-chain — reverts on mismatch) · finality hold clear |
| PDA created        | ClaimAttestation — seeds: ["claim_attestation", claim_case.key(), oracle.key()]                                                                                                                  |
| State transition   | claim_case.attestation_count++                                                                                                                                                                   |
| ■ On-chain writes  | Full ClaimAttestation — see §3.5 field breakdown below                                                                                                                                           |
| Event emitted      | ClaimCaseAttestedEvent { claim_attestation, claim_case, oracle_profile, oracle, decision, attestation_hash }                                                                                     |
| PHI on-chain?      | NO — only hash fields                                                                                                                                                                            |
| ■ Security (PT-07) | Oracle registration requires signer == args.oracle — no third-party registration possible                                                                                                        |

## Step 6 — adjudicate\_claim\_case ■

|                            |                                                                                                               |
|----------------------------|---------------------------------------------------------------------------------------------------------------|
| Authorized signers         | health_plan.claims_operator                                                                                   |
| State transition (approve) | → APPROVED (2) if approved_amount > 0                                                                         |
| State transition (deny)    | → DENIED (3) if approved_amount == 0                                                                          |
| ■ On-chain writes          | claim_case.intake_status · .adjudicator [Pubkey] · .approved_amount · .denied_amount · .decision_support_hash |
| Event emitted              | ClaimCaseStateChangedEvent { claim_case, intake_status, approved_amount }                                     |
| Denial path                | No Obligation PDA created. Denial reason anchored via decision_support_hash — full rationale off-chain.       |
| PHI on-chain?              | NO — only amounts and pubkeys                                                                                 |

## Step 7 — reserve\_obligation ■

|                    |                                                                                            |
|--------------------|--------------------------------------------------------------------------------------------|
| Authorized signers | health_plan.claims_operator                                                                |
| State transition   | Obligation.status → RESERVED (1)                                                           |
| ■ On-chain writes  | obligation.reserved_amount · funding_line.reserved_amount ↑ · claim_case.linked_obligation |
| Event emitted      | ObligationStatusChangedEvent { obligation, funding_line, status: 1, amount }               |
| Visibility         | Encumbered reserve is visible on the public protocol console in real time                  |
| PHI on-chain?      | NO                                                                                         |

## Step 8 — settle\_claim\_case / settle\_claim\_case\_selected\_asset ■

|                       |                                                                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Authorized signers    | health_plan.claims_operator                                                                                                                                              |
| Preconditions         | reserve_asset_rail.payout_enabled == true · price freshness within rail bounds · recipient token account owner matches resolved recipient                                |
| State transition      | → SETTLED (4) when paid_amount ≥ approved_amount                                                                                                                         |
| ■ On-chain writes     | claim_case.paid_amount ↑ · .intake_status → SETTLED · .closed_at · domain_asset_vault.total_assets ↓                                                                     |
| SPL transfer          | transfer_from_domain_vault (PDA-signed CPI) — THE ONLY AUTHORIZED OUTFLOW PATH                                                                                           |
| Events emitted        | ClaimCaseStateChangedEvent + FeeAccruedEvent (protocol fee) + optional FeeAccruedEvent (oracle revshare if LP-backed)                                                    |
| Multi-asset variant   | settle_claim_case_selected_asset → ClaimCaseSelectedAssetPayoutEvent { claim_asset_mint, payout_asset_mint, claim_credit_amount, payout_amount, settlement_reason_hash } |
| PHI on-chain?         | NO                                                                                                                                                                       |
| ■ Security (PT-01/02) | transfer_from_domain_vault requires vault PDA signature via seeds — no unsigned outflow possible                                                                         |

### ClaimAttestation — Complete On-Chain Fields (from Step 5):

| Field                 | Size     | What it represents                                            |
|-----------------------|----------|---------------------------------------------------------------|
| oracle                | Pubkey   | Oracle authority public key                                   |
| oracle_profile        | Pubkey   | OracleProfile PDA reference                                   |
| claim_case            | Pubkey   | Parent ClaimCase reference                                    |
| health_plan           | Pubkey   | HealthPlan reference                                          |
| policy_series         | Pubkey   | PolicySeries reference                                        |
| decision              | u8       | 0=approve / 1=deny / 2=request_review / 3=abstain             |
| attestation_hash      | 32 bytes | Oracle's own hash commitment (off-chain signed artifact)      |
| attestation_ref_hash  | 32 bytes | MUST equal claim_case.evidence_ref_hash — enforced on-chain   |
| evidence_ref_hash     | 32 bytes | Snapshot of evidence hash at attestation time                 |
| decision_support_hash | 32 bytes | Snapshot of operator review bundle hash                       |
| schema_key_hash       | 32 bytes | Hash of the OutcomeSchema key ("genesis-protect-acute-claim") |
| schema_hash           | 32 bytes | Hash of the schema content at attestation time                |
| schema_version        | u16      | Schema version at attestation time                            |
| created_at_ts         | i64      | Unix timestamp of attestation                                 |

## §4 — PHI vs. Proof Anchoring: Complete Separation

This table is the canonical reference for what lives where. Nothing in the left column ever appears on Solana in any form. The right column is what external parties can read and verify.

| Category              | Data (■ off-chain only)                           | ■ On-chain proof anchor                                              |
|-----------------------|---------------------------------------------------|----------------------------------------------------------------------|
| Member identity       | Passport, ID document, KYC data                   | member_position.subject_commitment [identity commitment hash]        |
| Medical evidence      | Discharge summary, doctor notes, clinical records | claim_case.evidence_ref_hash [SHA-256 of evidence packet]            |
| Billing documents     | Itemized invoice, proof of payment, receipts      | claim_case.evidence_ref_hash (included in evidence packet)           |
| Operator review       | Review checklist, internal notes, AI flag log     | claim_case.decision_support_hash [SHA-256 of review bundle]          |
| Oracle decision       | Full oracle assessment document                   | claim_attestation.attestation_hash [oracle's 32-byte commitment]     |
| Policy terms          | Full coverage terms text (PDF / doc)              | policy_series.terms_hash [SHA-256 of terms document]                 |
| Evidence requirements | Required document checklist per tier              | policy_series.evidence_requirements_hash                             |
| Fraud notes           | Investigation notes, referral details             | <i>Not anchored on-chain in Phase 0</i>                              |
| AI screening logs     | Pre-screening output, anomaly scores              | <i>Not anchored on-chain in Phase 0</i>                              |
| TEE evidence packet   | Plaintext PHI inside MagicBlock TEE (never exits) | private_review_session.review_artifact_hash (exits TEE as hash only) |

**Summary:** Every byte of raw PHI stays off-chain. What Solana records are the SHA-256 fingerprints of that data — sufficient for a third party to verify that the reviewed evidence matches what was attested, **without accessing the underlying medical content**.

## §5 — Complete On-Chain Hash Chain

The chain below shows how each hash links to the next, forming a tamper-evident path from raw PHI to final USDC settlement on Solana.

### RAW PHI (off-chain only)

Medical records + invoices + location proof + doctor note Stored encrypted on OmegaX Health oracle portal

▼ *SHA-256 by operator after human review*

### ■ ClaimCase.evidence\_ref\_hash [32 bytes — Solana]

Set by: attach\_claim\_evidence\_ref (claims\_operator) Immutable after: first attest\_claim\_case (attestation\_count ≥ 1)

▼ *Oracle verifies: attestation\_ref\_hash == evidence\_ref\_hash*

Enforced on-chain — transaction reverts if hashes do not match

### ■ ClaimAttestation PDA [Solana — permanent]

attestation\_hash · attestation\_ref\_hash · evidence\_ref\_hash decision\_support\_hash · schema\_key\_hash · schema\_hash decision [u8] · oracle [Pubkey]

▼ *adjudicate\_claim\_case (claims\_operator)*

### ■ ClaimCase — adjudication record [Solana — permanent]

intake\_status: APPROVED (2) or DENIED (3) adjudicator [Pubkey] · approved\_amount [u64] ·  
decision\_support\_hash

▼ [reserve\\_obligation](#) → [settle\\_claim\\_case](#)

#### ■ Settlement — SPL token transfer [Solana — permanent]

intake\_status: SETTLED (4) · paid\_amount [u64] · closed\_at [i64] recipient: member\_position.wallet or  
delegate\_recipient domain\_asset\_vault.total\_assets ↓ · tx signature immutable

**Verification property:** A third party who holds the original evidence packet can SHA-256 hash it and compare against `claim_case.evidence_ref_hash`. If they match, the evidence anchored on Solana is identical to what was reviewed — and the oracle's attestation applies to exactly that packet.



## §6 — MagicBlock TEE Private Review Path

For claims requiring TEE-private handling, an adjunct program `omegax_private_claim_review` runs on MagicBlock Ephemeral Rollups. This path integrates at steps 4–5 of the standard lifecycle. **The main protocol vaults, funding lines, and obligations are never delegated to MagicBlock.**

| Standard path                            | MagicBlock TEE private path                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ■ Evidence upload (off-chain)            | ■ Evidence upload (off-chain)                                                                                                                                                                                                                                                                                                                                                                          |
| ■ <code>attach_claim_evidence_ref</code> | ■ TEE receives private packet ■ <code>open_review_session</code>                                                                                                                                                                                                                                                                                                                                       |
| ■ <code>attest_claim_case</code>         | ■ <code>delegate_review_session</code> (→ MagicBlock ER) ■ Private review inside TEE — plaintext never leaves enclave ■ <code>record_private_review</code> (review_artifact_hash only) ■ <code>record_private_payment_ref</code> (payment_reference_hash only) ■ <code>commit_and_close_review_session</code> (→ Solana base) ■ <code>attest_claim_case</code> (main program — consumes artifact hash) |

### PHI boundary in the MagicBlock path:

| What                                        | Where                                                        |
|---------------------------------------------|--------------------------------------------------------------|
| Private evidence packet (plaintext)         | ■ TEE enclave only — never on Solana, never on MagicBlock ER |
| <code>review_artifact_hash</code>           | ■ MagicBlock ER → committed to Solana base                   |
| <code>private_payment_reference_hash</code> | ■ MagicBlock ER → committed to Solana base                   |
| Oracle attestation hash                     | ■ Standard ClaimAttestation PDA on Solana base               |

## §7 — Unhappy Paths: Verification Map

| Scenario                                | On-chain state                                                                      | What's verifiable                                                          |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| Incomplete evidence                     | <code>intake_status</code> = OPEN (0), no <code>evidence_ref_hash</code> set        | Chain shows claim opened but no evidence attached                          |
| Evidence resubmission (pre-attestation) | New <code>attach_claim_evidence_ref</code> updates <code>evidence_ref_hash</code>   | Each update is a distinct Solana tx; full history recoverable from tx logs |
| Evidence revision (post-attestation)    | New ClaimCase PDA opened                                                            | Both cases publicly visible; original attestation chain immutable          |
| Partial approval (Travel 30 top-up)     | <code>approved_amount</code> = fixed tier cap; second adjudication round for top-up | Two separate ClaimCaseStateChangedEvent entries on-chain                   |
| Denial                                  | <code>intake_status</code> = DENIED (3); <code>decision_support_hash</code> updated | Hash-committed reason; no obligation created; no funds reserved            |
| Settlement deferred                     | <code>obligation.status</code> = CLAIMABLE_PAYABLE (2)                              | Encumbered reserve visible; vault balance unchanged                        |
| Impairment                              | <code>obligation.status</code> = IMPAIRED (5) after <code>mark_impairment</code>    | ImpairmentRecordedEvent on-chain; LP junior class absorbs loss             |
| Appeal (Phase 0)                        | New ClaimCase PDA with appeal evidence                                              | New claim on-chain; original denial chain intact and immutable             |

## §8 — Obligation State Lifecycle

The Obligation account runs in parallel with ClaimCase. Every status transition emits `ObligationStatusChangedEvent` `\{ obligation, funding_line, status, amount \}`.

| Status            | Value | Trigger                          | Effect                                                        |
|-------------------|-------|----------------------------------|---------------------------------------------------------------|
| PROPOSED          | 0     | adjudicate_claim_case (approved) | Obligation PDA created; no reserve yet                        |
| RESERVED          | 1     | reserve_obligation               | funding_line.reserved_amount ↑ — LP capacity encumbered       |
| CLAIMABLE_PAYABLE | 2     | Internal transition              | Ready for settlement payout                                   |
| SETTLED           | 3     | settle_claim_case                | Funds disbursed; obligation closed                            |
| CANCELED          | 4     | Denial / void path               | No reserve taken; obligation void                             |
| IMPAIRED          | 5     | mark_impairment                  | LP junior class absorbs loss; ImpairmentRecordedEvent emitted |
| RECOVERED         | 6     | Post-impairment recovery         | Partial or full recovery credited back to LP                  |

## §9 — Independent Auditor Verification Checklist

For any Genesis Protect Acute claim, an independent auditor can verify the following from **public on-chain data alone**. No access to raw PHI is required.

| Question                                     | Where to look on-chain                                                                                                                                             |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Who opened the claim and when?               | <code>claim_case.claimant</code> · <code>.opened_at</code> · opening tx signature                                                                                  |
| Was the claimant an active policy member?    | <code>member_position.active == true</code> · <code>.eligibility_status == ELIGIBLE</code> at claim time                                                           |
| What evidence hash was committed?            | <code>claim_case.evidence_ref_hash</code>                                                                                                                          |
| Was evidence locked before attestation?      | <code>claim_case.attestation_count ≥ 1</code> → hash is immutable                                                                                                  |
| Who attested and with what decision?         | <code>ClaimAttestation.oracle</code> · <code>.decision</code> · <code>.attestation_hash</code>                                                                     |
| Was the schema governance-verified?          | <code>outcome_schema.verified == true</code> at attestation time                                                                                                   |
| Does the attestation match the evidence?     | <code>claim_attestation.attestation_ref_hash == claim_case.evidence_ref_hash</code> (enforced on-chain)                                                            |
| Who adjudicated and what was the outcome?    | <code>claim_case.adjudicator</code> · <code>.intake_status</code> · <code>.approved_amount</code>                                                                  |
| What funding line was reserved?              | <code>claim_case.funding_line</code> · <code>obligation.reserved_amount</code>                                                                                     |
| Was payout made and to whom?                 | <code>claim_case.paid_amount</code> · <code>.closed_at</code> · settlement tx · recipient = <code>delegate_recipient</code> or <code>member_position.wallet</code> |
| Were fees correctly carved out?              | <code>FeeAccruedEvent</code> on settlement tx · <code>protocol_fee_vault.accrued_fees</code>                                                                       |
| Was policy material unchanged at claim time? | <code>policy_series.material_locked == true</code> · <code>terms_hash</code> unchanged since issuance                                                              |

## §10 — Phased Decentralization Roadmap

The protocol launches in a deliberately phased approach: Phase 0 achieves on-chain anchoring of all material claim state while retaining operator-supervised workflows for review queuing and oracle key management. The table below is an honest accounting of what each phase adds.

| Item                       | Phase 0 posture                                                           | Phase 1 target                                                                |
|----------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| UNDER_REVIEW state         | Off-chain queue pickup — not a distinct on-chain intake_status transition | Explicit on-chain set_claim_under_review instruction                          |
| Appeal linkage             | New ClaimCase PDA for appeals; correlated off-chain                       | On-chain dispute-case linkage between original denial and appeal PDA          |
| Fraud referral record      | Internal notes; hash not yet committed on-chain                           | fraud_referral_hash field or dedicated instruction in protocol-oracle-service |
| Oracle key custody         | Claims operator hot wallet signs oracle transactions                      | HSM / KMS boundary enforced before mainnet (see claims-processing-spec §13)   |
| Provider direct settlement | Payout goes to member wallet or delegated recipient                       | Provider KYB + delegate_recipient = verified provider wallet                  |

**Phase 0 communication standard:** Any external claim communication — to members, partners, or press — must describe the current posture as **operator-backed oracle review**, not fully decentralized adjudication. The on-chain record is authoritative; the governance of who writes to it is progressively decentralizing.

## §11 — LP Capital Protection Summary

For LPs deploying capital into OmegaX Protocol liquidity pools, the claim architecture provides the following hard guarantees at the smart contract level.

| LP Concern                                            | Answer           | Detail                                                                                                                                               |
|-------------------------------------------------------|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Can an operator drain the vault without a real claim? | <b>NO</b>        | Funds leave only via transfer_from_domain_vault PDA-signed CPI, gated on ClaimCase.intake_status = SETTLED (4) with a valid oracle attestation chain |
| Can a fraudulent claim override a valid attestation?  | <b>NO</b>        | adjudicate_claim_case is gated on the oracle attestation chain; adjudicator pubkey permanently recorded on-chain                                     |
| Can evidence be altered after oracle review?          | <b>NO</b>        | evidence_ref_hash is immutable once attestation_count ≥ 1; any revision requires a new ClaimCase PDA                                                 |
| Can LP losses be hidden?                              | <b>NO</b>        | ImpairmentRecordedEvent emitted on-chain; ObligationStatusChangedEvent at every obligation state transition                                          |
| Can payout routing be changed by the operator?        | <b>PARTIALLY</b> | Operator cannot override a member-set delegate_recipient; authorize_claim_recipient is member-only                                                   |
| Is the oracle schema governance-controlled?           | <b>YES</b>       | outcome_schema.verified == true enforced on-chain at attestation; schema changes require governance authority signature                              |

## §12 — References

| Document                                 | Path                                                              |
|------------------------------------------|-------------------------------------------------------------------|
| Step-by-step claim truth chain narrative | docs/architecture/genesis-protect-claim-trace.md                  |
| Claims processing specification (KR 1.2) | docs/architecture/genesis-protect-acute-claims-processing-spec.md |
| Full operational protect flow (KR 1.1)   | docs/architecture/genesis-protect-acute-full-protect-flow.md      |
| MagicBlock private claim room            | docs/architecture/magicblock-private-claim-room.md                |
| Evidence schema (JSON)                   | frontend/public/schemas/genesis-protect-acute-claim-v1.json       |

|                                     |                                           |
|-------------------------------------|-------------------------------------------|
| Anchor source — claim instructions  | programs/omegax_protocol/src/claims.rs    |
| Anchor source — account states      | programs/omegax_protocol/src/state.rs     |
| Anchor source — protocol events     | programs/omegax_protocol/src/events.rs    |
| Anchor source — constants and seeds | programs/omegax_protocol/src/constants.rs |

© 2026 OmegaX Health Capital Markets · omegax.health · Internal — Pre-Mainnet · Program ID:  
Bn6eixac1QEEVErGBvBjxAd6pgB9e2q4XHvAkinQ5y1B