

Portfolio Milestone Module 3: Neural Networks for CubeSat Telemetry Anomaly Detection

Alexander Ricciardi

Colorado State University Global

CSC510: Foundations of Artificial Intelligence

Professor: Dr. Isaac Gang

August 9, 2026

Portfolio Milestone Module 3: Neural Networks for CubeSat Telemetry Anomaly Detection

The “Portfolio Milestone Module 2: Use-Case Scenario Proposal” (Ricciardi, 2026) proposes using a combination of an Artificial Neural Network (ANN) and an A* symbolic planner for a CubeSat telemetry anomaly-detection system. Within this hybrid approach, the ANN will handle OPS-SAT telemetry segment classification by labeling them as having normal or anomalous behavior, while the A* symbolic planner will organize diagnostic actions into an investigation sequence, and a similarity search will retrieve historical telemetry cases. The process of labeling the telemetry segment is defined “fuzzy” tasks because it requires recognizing uncertain, noisy, and nonlinear patterns within sensor measurements, and ANNs are well suited for such tasks (Ruszczak et al., 2025). This paper defines the learning method and initial architecture of the neural network component of the hybrid CubeSat telemetry anomaly-detection system. The ANN will integrate Supervised Learning (SL) within a binary-classification process using the labeled OPSSAT-AD data. The available OPSSAT-AD dataset contains telemetry segment data labeled as normal or anomalous that can be used as SL targets during training. The ANN model will benefit most from having a small deep feedforward network architecture implemented as a fully connected Multilayer Perceptron (MLP) with three hidden layers containing 32, 16, and 8 neurons. This architecture should provide the needed depth to learn nonlinear relationships from the telemetry data while being small enough to prevent overfitting. During supervised training, the model will compare its classification prediction against the labels from the OPSSAT-AD dataset. This will allow the model to adjust its weights and biases through backpropagation by reducing the error between the predicted and target outputs (Sharda et al., 2024). Additionally, a Rectified Linear Unit (ReLU) activation function will be implemented within the hidden layers to learn nonlinear relationships, and a

sigmoid activation function in the output layer will be used to generate anomaly probabilities between 0 and 1. Finally, the A* symbolic planner will use the model ANN outputs, together with the system's diagnostic rules, to organize diagnostic actions into an investigation sequence.

References

- Ricciardi, A. (2026). *Portfolio milestone module 2: Use-case scenario proposal* [Unpublished course assignment]. CSC-510 Fundamentals of Artificial Intelligence. Colorado State University Global.
- Ruszczak, B., Kotowski, K., Evans, D., & Nalepa, J. (2025). The OPS-SAT benchmark for detecting anomalies in satellite telemetry. *Scientific Data*, 12, Article 710.
<https://doi.org/10.1038/s41597-025-05035-3>
- Sharda, R., Delen, D., & Turban, E. (2024). *Business intelligence, analytics, data science, & AI* (5th ed.). Pearson Education.