

CS2109S Tutorial 10

AY 25/26 Sem 1 — github/omgeta

- A.
1. $w^\top x = -0.1 < 0$ so SVM classifies x as Not-VIP
 2. We need 17 support vectors, each of 30 attributes, and 17 α coefficients, giving total cost of $17 \times 30 + 17 = 527$
- B.
1. Total variance $= \frac{6^2 + 4.5^2 + 2^2 + 1^2 + 0.5^2}{n-1} = \frac{61.5}{n-1}$
Keeping 6, 4 gives variance $\frac{6^2 + 4^2}{61.5} = 0.915 > 0.9$ so suffice to keep just them.
 2. For compressing $64 \times 64 = 4096$ mean-centered features to 50 features, we need compression matrix $\tilde{U} \in \mathbb{R}^{4096 \times 50}$, the 4096 feature means for normalisation and denormalisation. For decompression of the original image, we already have \tilde{U} , so we only need the additional compressed images of $50 \times 500 = 25000$ values. So in total we have $(4096 \times 50) + 25000 + 4096 = 233896$.
- C.
1. $\hat{y} = \text{ReLU}(W^{[2]\top}(W^{[1]\top} \begin{bmatrix} 1 \\ 1 \end{bmatrix})) = \text{ReLU}(W^{[2]\top} \begin{bmatrix} 3 \\ 2 \end{bmatrix}) = \text{ReLU}(8) = 8$
 2. Note $J(W) = L_1 + L_2 = \frac{1}{2 \times 2}((\hat{y}^{(1)} - y^{(1)})^2 + (\hat{y}^{(2)} - y^{(2)})^2)$ so:

$$\frac{\partial J(W)}{\partial W_{11}^{[1]}} = \frac{\partial L_1}{\partial W_{11}^{[1]}} + \frac{\partial L_2}{\partial W_{11}^{[1]}}$$

Note also for any sample i , $\hat{y}^{(i)}$ predicted as:

$$\begin{aligned} L_i &= \frac{1}{4}(\hat{y}^{(i)} - y^{(i)})^2 \implies \frac{\partial L_i}{\partial \hat{y}^{(i)}} = \frac{1}{2}(\hat{y}^{(i)} - y^{(i)}) \\ \hat{y}^{(i)} &= \text{ReLU}(f^{(i)}) \implies \frac{\partial y^{(i)}}{\partial f^{(i)}} = 1_{f^{(i)} > 0} \\ f^{(i)} &= W_{11}^{[2]}a_1^{(i)} + W_{21}^{[2]}a_2^{(i)} \implies \frac{\partial f^{(i)}}{\partial a_1^{(i)}} = W_{11}^{[2]} \\ a_1^{(i)} &= W_{11}^{[1]}x_1^{(i)} + W_{21}^{[1]}x_2 \implies \frac{\partial a_1^{(i)}}{\partial W_{11}^{[1]}} = x_1^{(i)} \end{aligned}$$

Then by chain rule, $\frac{\partial L_i}{\partial W_{11}^{[1]}} = \frac{1}{2}(\hat{y}^{(i)} - y^{(i)})1_{f^{(i)} > 0}W_{11}^{[2]}x_1^{(i)}$ so $\frac{\partial J(W)}{\partial W_{11}^{[1]}} = 4 + 0 = 4$

- D.
1. Kernel size $= 2 \times 2 \times 3$ ($H \times W \times C$), with 5 kernels to produce 5-channel output. Therefore, total parameters $= 2 \times 2 \times 3 \times 5 = 60$
 2. Kernel size $= 1 \times 1 \times 3$ with all 3 weights as $\frac{1}{3}$, stride $= 1$, padding $= 0$