Esercitazione 4 Modulo 4 -Alessio Russo

Cracking password from db utilizzando john the ripper:

Salvo gli hash delle password in un file di testo pass.txt

Utilizzando il seguente comando e possibile craccare le password precedenti
john --format=raw-md5 --wordlist=/home/kali/Desktop/rockyou.txt/home/kali/Desktop/hash.txt

```
┌──(kali㉿kali)-[/usr/sbin]
└─$ john --format=raw-md5 --wordlist=/home/kali/Desktop/rockyou.txt /home/kali/Desktop/hash.txt
stat: /home/kali/Desktop/hash.txt: No such file or directory

┌──(kali㉿kali)-[/usr/sbin]
└─$ john --format=raw-md5 --wordlist=/home/kali/Desktop/rockyou.txt /home/kali/Desktop/passw.txt
Using default input encoding: UTF-8
Loaded 4 password hashes with no different salts (Raw-MD5 [MD5 256/256 AVX2 8x3])
Warning: no OpenMP support for this hash type, consider --fork=6
Press 'q' or Ctrl-C to abort, almost any other key for status
password         (?)
abc123           (?)
letmein          (?)
charley          (?)
4g 0:00:00:00 DONE (2024-02-10 13:15) 200.0g/s 153600p/s 153600c/s 230400C/s my3kids..dangerous
Warning: passwords printed above might not be all those cracked
Use the "--show --format=Raw-MD5" options to display all of the cracked passwords reliably
Session completed.

┌──(kali㉿kali)-[/usr/sbin]
└─$
```