PRODUCT SUBMITTAL - AIR-COOLED CHILLERS CH-1/CH-2

Manufacturer: Frostline Thermal Systems (fictional). Model: FL-AC500M (fictional). Quantity: 2.

Performance at AHRI 550/590 conditions

Item	Value
Net capacity	1,700 kW
Full-load efficiency	1.18 kW/ton
IPLV	0.78 kW/ton
Refrigerant	R-1234ze(E), GWP < 1
Sound pressure	80 dBA at 10 m
Maximum ambient	52 °C

Electrical

460 V / 3 ph / 60 Hz, single-point power connection with non-fused disconnect. Panel SCCR: 35 kA.

Construction

Compressors: two oil-free magnetic-bearing centrifugal compressors with integral variable-speed drives.

Condenser fans: EC fan motors with variable speed control.

Coils: standard aluminum microchannel condenser coils. Corrosion-resistant coating available as an option (not included).

Free cooling: integral free-cooling coil section with automatic changeover valve.

Controls: Frostline FT-Touch controller with BACnet MS/TP. BACnet/IP available via optional communication card.

Physical

Operating weight: 13,600 kg per unit. Shipping weight: 12,900 kg.

Warranty

Compressor warranty: 5 years parts only; labor covered for the first year from startup.