Empirical–generated learning-curve comparisons
Shared observed subset-size ranges

A BRCA miRNA-seq
TC · cVAE 1:5
No AE head
Mean source ARI: 0.0055

B HNSC miRNA-seq
raw · cVAE 1:50
No AE head
Mean source ARI: 0.0058

C HNSC miRNA-seq
TC · cVAE 1:50
No AE head
Mean source ARI: 0.0080

D COAD RNA-seq
TC · cVAE 1:50
AE head (2 iterations)
Mean source ARI: 0.00014

	A	B	C	D
LR Accuracy	B +0.057 D 0.057	B +0.008 D 0.017	B +0.139 D 0.139	B +0.123 D 0.123
SVM Accuracy	B -0.001 D 0.013	B -0.003 D 0.010	B +0.117 D 0.117	B +0.077 D 0.078
KNN Accuracy	B -0.008 D 0.009	B -0.008 D 0.016	B +0.129 D 0.129	B +0.069 D 0.075
RF Accuracy	B -0.008 D 0.009	B -0.010 D 0.016	B +0.113 D 0.113	B +0.056 D 0.056
XGB Accuracy	B +0.003 D 0.009	B -0.027 D 0.032	B +0.089 D 0.089	B +0.060 D 0.062

Accuracy: 0.00, 0.25, 0.50, 0.75, 1.00
Candidate subset size: A 250, 500, 750, 1000; B 150, 300, 450; C 150, 300, 450; D 150, 300, 450

Empirical
Generated

Points: observed means ±1 draw SD. Lines/bands: archived fit / pointwise 95% fitted-mean interval.
Each column uses its shared observed range; x-axis ranges differ between tasks.
B: signed average gap; D: absolute average gap. Both use shared observed means. ARI: mean of five fidelity draws.