

ZARAVI Supplier-Ready Packaging Handoff Brief

ZARAVI Supplier-Ready Packaging Handoff Brief

Project: The Wing Archive, seam-based packaging system

Brand: ZARAVI Jewelry

Revision: Rev A, supplier handoff draft

Date: 03 September 2026

Units: Millimetres unless noted

 These files are production-intent concepts, not final tooling approval. Supplier must prototype with the specified board, wrap and insert materials, then return physical samples for sign-off before mass production.

1. Handoff package

Supplier should receive:

- Ring Box dieline: **72 × 72 × 54 mm finished**
- Necklace Drawer dieline: **178 × 178 × 44 mm finished**
- Artwork supplied as vector paths, with ZARAVI wordmark and seam artwork on separate layers
- This brief, material swatches, physical color standards and prototype testing checklist
- One finished jewelry-fit sample for each format

Dieline conventions: red = knife cut, cyan dashed = V-groove or crease, magenta dashed = bleed or safe area, green tint = adhesive zone. Print at 100%. Do not fit to page.

2. Shared design intent

The packaging is quiet, tactile and exact. The primary recognition code is a **single center seam that splits and rejoins**. Do not add literal butterfly illustrations, decorative wing repeats or extra foil. The seam must remain legible through construction, not as a printed decoration.

Use a restrained material hierarchy:

1. Mineral Sage wrapped exterior
2. Warm Ivory interior and jewelry insert
3. Deep Espresso for information and secondary print
4. Oxide Copper only for textile pull tabs and approved edition details

3. Ring Box

Finished specification

- Finished outer size: **72 W × 72 D × 54 H mm**
- Format: rigid wrapped drawer with sleeve
- Target drawer running clearance: **0.8 to 1.0 mm after wrap buildup**
- Target drawer pull force: **0.8 to 1.5 N**

Construction

- Structural board: **1.2 mm FSC compact board**
- Grooves: 90° V-groove, target residual board thickness **0.25 mm**
- Outer wrap: **120 gsm dyed-through Mineral Sage paper**
- Insert: **1.0 mm molded fiber board**, laminated with approximately **0.6 mm plant-suede surface**
- Pull: **10 mm cotton herringbone tape**, approximately **28 mm exposed loop**
- Adhesive: pH-neutral PVA, full coverage, low-moisture application

Dieline and artwork

- Sleeve structural blank total panel run: **264 mm**, excluding production allowances
- Sleeve panel sequence: 12 mm glue zone, 72 mm bottom, 54 mm side, 72 mm top, 54 mm side
- Wrap turn-in: **15 mm at open ends**, 10 mm overlap at seam
- Top wordmark: approximately **23 mm wide**, blind deboss only
- Keep seam and deboss at least **5 mm from wrapped edges**
- Minimum blind-detail rule: **0.25 mm**

Assembly sequence

1. Cut and V-groove structural board.
2. Dry-fold and check squareness before wrapping.
3. Apply wrap with grain parallel to drawer travel.
4. Wrap long edges first, then open-end turn-ins.
5. Trap pull anchor between board and wrap over at least **35 mm**.
6. Fit insert after adhesive cure.
7. Condition assembled boxes for 24 hours before jewelry-fit testing.

4. Necklace Drawer

Finished specification

- Finished outer size: **178 W × 178 D × 44 H mm**
- Format: rigid drawer with four-panel sleeve and removable necklace platform
- Target drawer running clearance: **1.0 to 1.3 mm per side**

- Target drawer pull force: **1.2 to 2.2 N**

Construction

- Structural board: **1.2 mm FSC compact board**
- Grooves: 90° V-groove, target residual board thickness **0.25 mm**
- Outer wrap: **120 gsm dyed-through Mineral Sage paper**
- Tray: **400 gsm SBS folding tray**, approximately **0.55 mm caliper**, with reinforced perimeter rails
- Platform: **1.0 mm molded fiber**, laminated with approximately **0.6 mm plant-suede surface**
- Pull: **10 mm Oxide Copper cotton herringbone**, approximately **24 mm exposed loop**
- Pull reinforcement: minimum **45 × 25 mm** patch trapped under the front-wall laminate

Dieline and artwork

- Sleeve structural blank total panel run: **456 mm**, excluding production allowances
- Sleeve panel sequence: 12 mm glue zone, 178 mm bottom, 44 mm side, 178 mm top, 44 mm side
- Wrap turn-in: **15 mm at open ends**
- Top wordmark: approximately **38 mm wide**, blind deboss only
- Platform target: **173.6 × 173.6 mm**, R3 corners
- Chain channel depth: **1.5 mm target**
- Pendant slot: **14 × 1.2 mm target**, adjust to actual pendant family after fit test
- Keep seam, deboss and platform cuts at least **5 mm from wrapped edges**

Assembly sequence

1. Cut and V-groove sleeve board.
2. Dry-fold and verify four-panel alignment.
3. Apply wrap with grain parallel to drawer travel.
4. Fit and reinforce pull anchor under front wall.
5. Form inner tray and inspect all corners for spring-back.
6. Laminate removable platform with plant-suede surface.
7. Fit platform and confirm chain channel is flush, not proud.
8. Condition assembled drawers for 24 hours before jewelry-fit testing.

5. Artwork controls

- Supplier must use supplied vector artwork, not recreate the wordmark from a font.
- No generative or rasterized logo substitutions.
- Blind deboss depth target: **0.25 to 0.30 mm**, subject to paper approval.

No metallic foil on the hero boxes unless separately approved.

- Seam geometry must be centered to **±0.5 mm** on the visible face.
- Artwork registration target: **±0.6 mm** on wrapped surfaces.
- Do not extend seam artwork across a groove, hinge or open edge without written approval.
- Submit one deboss proof at 10× magnification before production tooling.

6. Color and material standards

Element	Target	Approval condition
Mineral Sage exterior	#8DA28C	Approve against physical swatch under D50; target $\Delta E_{00} \leq 2$
Warm Ivory interior	#EEE9C1	Must not yellow visibly against jewelry metal
Oxide Copper pull	#A4530C approximate	Approve textile strike-off; no color bleeding
Exterior paper	120 gsm dyed-through	Uncoated, tactile, no gloss varnish
Insert	Molded fiber + plant suede	No shedding, odor, staining or tarnish interaction
Board	FSC compact board	Supplier to state actual caliper and density

7. Required supplier submissions

Before approval, supplier must return:

- PDF proof at 100% with dimensions and material callouts
- Native dieline file with cut, crease, glue and artwork layers separated
- Board and paper technical data sheets
- Material swatches and textile pull strike-off
- One unwrapped structural dummy per format
- One wrapped white-ink or blank prototype per format
- One final-color prototype per format
- Jewelry-fit photographs with ring and necklace installed
- Measurement report for finished size, squareness, gaps and pull force
- Drop-test report inside the intended shipping mailer
- Updated quotation including tooling, sampling, MOQ, lead time and waste assumptions

8. Quality-control tolerances

Check	Ring Box	Necklace Drawer
Finished width / depth	±0.5 mm	±0.7 mm
Board caliper	±0.08 mm	±0.08 mm
Artwork registration	±0.6 mm	±0.6 mm
Deboss registration	±0.5 mm	±0.5 mm
Drawer clearance	0.8 to 1.0 mm	1.0 to 1.3 mm per side
Corner squareness	±0.5 mm	±0.7 mm
Wrap seam visibility	underside only	underside only

9. Testing gate

Supplier must complete the following before production release:

- 25 open-close cycles per sample
- Jewelry fit with at least three ring widths and three necklace chain lengths
- Pull-tab cycle test, 50 pulls minimum
- Six-face drop test from **1 m** inside intended mailer
- Compression and corner-impact inspection
- Color review under D50 lighting
- Surface inspection for bubbles, wrinkles, lifting, glue marks and fiber shedding
- Tarnish and staining compatibility check with intended jewelry materials
- Final photography from closed, open, side and top views

10. Approval criteria

APPROVE only when all of the following are true:

- Finished dimensions and clearances are within tolerance.
- Drawers open smoothly without rattling or binding.
- Jewelry is secure, centered and removable without damage.
- Seam is the dominant graphic behavior; no decorative clutter has been added.
- Logo and deboss remain crisp at production scale.
- Paper, insert and textile pass tactile and contamination checks.
- Prototype survives transit testing inside the real mailer.
- Supplier has documented the exact approved materials and processes.

Release status: HOLD until physical samples, jewelry-fit review, color review and transit test are signed off.

11. Supplier questions to answer in quotation

1. What exact board grade, caliper and density will be used?
2. What is the finished wrap buildup used to calculate drawer clearance?
3. Can the supplier hold the requested color under D50 across paper and textile?
4. What adhesive is used, and what is its cure time and odor profile?
5. How is the pull-tab anchor reinforced?
6. What is the minimum practical blind-deboss line and depth on the selected wrap paper?
7. What tooling is required for each format and artwork treatment?
8. What are the sample lead time, production lead time, MOQ and expected waste rate?
9. Can the supplier provide a physical color standard for repeat orders?
10. Which tests are included in the quoted price, and which require separate approval?

Final sign-off owner: ZARAVI creative direction and production lead. Supplier may not alter dimensions, materials, logo artwork, seam geometry or pull construction without written approval.