Week 3: Trace Processing and Workload Characterization

Oct 11, 2026

Week 3 turned TraceLab's raw logs into a pause dataset for our cost model, and described what those pauses look like.

Summary

Every pause in the TraceLab trace is now one row in a shared table (346,820 usable pauses), and five findings shape the rest of the project.

- **Tool pauses are mostly short; human pauses are mostly long.** At a 10 s break-even, 85% of tool pauses end in time (keep the cache), but only 11% of human pauses do (evict).
- **That split is known when the pause starts.** If the model just called a tool, it is a tool pause; if not, the agent is waiting on a person.
- **Within tool pauses, the tool name alone predicts little.** Deciding by tool name is 87.8% correct versus 87.4% for always keeping, and catches only 16% of long pauses.
- **Three tools carry the hard cases.** Bash, exec_command and write_stdin make up about two-thirds of tool pauses, and each runs from under 0.1 s to tens of seconds.
- **The break-even time differs per pause.** Idle caches have a median of about 125K tokens, so b spans about 4–26 s at an assumed prefill speed of 10,000 tokens/s.

Data

We use the public TraceLab trace, release v0.0.1 (repo, paper): real Claude Code and Codex sessions recorded from September 2025 to June 2026.

Measure	Value
Sessions	4,265
Users (pseudonymous)	43
LLM rounds	357,161 (Claude 140,338, Codex 216,823)

Measure	Value
Tool calls	432,510
File	`syfi_coding_trace.duckdb`, about 100 MB

We read three of its tables: `rounds` (one row per LLM call), `tool_calls`, and `timing_events` (one row per timestamped input or output inside a round).

Defining a pause

A pause runs from the last thing the model produced in round k to the last input that arrives for round k+1. During that span the session's KV cache sits idle, so its length is T in the cost model.

- **Model outputs** are `reasoning`, `text` and `tool_call` events, plus Codex's `usage_report`, which marks the moment the model finished.
- **Inputs** are `tool_result` and `user_message` events.
- **One rule covers both providers.** Older Codex logs stamp a tool call and its result with the same time, but the gap from `usage_report` to the result still measures the pause.

Each pause gets a cause from what arrived in round k+1.

Cause	Meaning	Pauses
tool	only tool results arrived	310,628
user	only a user message arrived: the agent finished and waited for a person	31,992
tool+user	both arrived	5,230
end	the session ended, so there is no next round	4,265
unknown	the next round has no recorded input	5,046

We checked the rule against each tool's own recorded duration (agreement = within 1 s or 20%). Claude tool pauses agree 99% of the time and Codex 82%; the Codex gap is overhead around the command, such as approval waits, when the cache is idle too.

The pause table

`pauses.parquet` holds one row per round (357,161 rows, about 4.5 MB); analyses should keep only rows where `usable` is true.


Column	Meaning	Known when the pause starts?
provider, user, session_id, round_index, model	identifiers, used for train/test splits	yes
pause_s	T: seconds the cache sat idle	no, it is the target
cause	tool, user, tool+user, end or unknown	partly: n_tools = 0 means a user wait
usable	true for rows we trust	used to filter rows
context_tokens	tokens in the cache (input plus output of round k); drives B	yes
n_tools	number of tools running during the pause	yes
tool_names	their names, comma-joined	yes
tool_input_chars	total size of their inputs	yes

Excluded rows. 10,341 rows have `usable = false`: session ends (4,265), unknown causes (5,046), and 1,030 rows next to repeated round numbers or with negative gaps.

Left out on purpose. Result size, error flags and tool latency are known only after the pause ends, so a predictor that used them would be cheating.

Finding 1: tool pauses mostly beat the break-even time; human pauses mostly don't

At b = 10 s, keeping the cache wins for 85% of tool pauses but only 11% of pauses involving a human.




Break-even b	Tool pauses shorter than b	Human pauses shorter than b	All pauses
1 s	57.7%	4.3%	52.0%
5 s	77.5%	7.1%	69.9%
10 s	85.1%	11.2%	77.2%
30 s	93.3%	24.7%	85.9%
60 s	96.3%	37.2%	90.0%

The sharp jumps at 1 s and 5 s are Codex `exec_command` and `write_stdin` calls that wait a fixed time before returning partial output. Those pauses are very predictable.

Finding 2: the tool name alone predicts little

On held-out sessions, deciding keep or evict at b = 10 s by tool name alone is 87.8% correct, barely above always keeping (87.4%). It catches only 16.4% of the long pauses.




- **Easy calls.** Read, Grep, Edit and TaskUpdate almost never pass 10 s, so keep; AskUserQuestion (93%) and Agent (82%) almost always do, so evict.
- **Hard calls.** Bash (17% over 10 s), exec_command (11%) and write_stdin (31%) are about two-thirds of tool pauses, and their ranges straddle b.
- **Hidden human waits.** AskUserQuestion is a person answering. Codex `apply_patch` is usually instant but runs past 10 s 13% of the time, likely waiting for approval.

The check learns each tool's majority answer on 80% of sessions and tests on the other 20%.

Finding 3: idle caches are large, so b differs per pause

The median pause leaves about 125K tokens in the cache, so b spans about 4–26 s (10th to 90th percentile) at 10,000 tokens/s.



Claude's human waits carry the largest caches: a median of 213K tokens and a 90th percentile of 740K. Codex stays near 120–126K. For scale, a Llama-3-8B-class model stores about 128 KB of cache per token, so 125K tokens is about 16 GB.

Giving each pause its own b = context_tokens ÷ prefill speed (queueing delay 0) keeps the picture from Finding 1:

Prefill speed (placeholder)	Median b	Keep wins: tool pauses	Keep wins: human pauses	Keep wins: all
5,000 tokens/s	24.9 s	91.1%	24.0%	83.9%
10,000 tokens/s	12.5 s	85.7%	15.6%	78.2%
20,000 tokens/s	6.2 s	78.3%	10.0%	71.0%

The speed moves these shares by several points, so final results need M5's measured speed or a sweep across this range.

What this means for each workstream

Every workstream can start from `pauses.parquet` now; each has one or two specific changes.

Workstream	What to take from Week 3
M1 Algorithm	Use a per-pause b = prefill(context_tokens) + queueing delay. Session ends (4,265) never return, so OPT = 0 there; the safety window caps that loss at B/λ per session end.
M2 Workloads	The pause table and three figures are the Week 3 deliverable. Replace the proposal's 38 s / 44 min figures: they are TraceLab's whole-request response times, not single pauses.
M3 Prediction	n_tools separates tool from human pauses for free; the real work is the tail of Bash, exec_command and write_stdin. Add input size and recent pauses in the session, and consider the command details the JSONL release keeps.
M3 splits	Split by session. Claude versus Codex is a ready-made distribution shift for C4.
M4 Simulation	Drive the simulator from `pauses.parquet` and sweep prefill speed. TraceLab's `eviction_tradeoff` experiment already sweeps a fixed timeout, a ready-made fixed-TTL check.
M5 Systems	Measure prefill time against context length on the GPU we plan to use; it moves the keep-wins shares by several points.

For the novelty map: TraceLab's related work cites CacheWise, which builds predictive eviction from tool-call metadata. It is close to C1 and C3, so it belongs on the literature map.

Limitations and open questions

The pause measurements are solid; the break-even numbers rest on two placeholders.

- **Prefill speed is assumed** (5,000–20,000 tokens/s, linear in context). Real prefill grows faster than linearly at long contexts.
- **Queueing delay is set to 0.** Under load, b grows, so the simulator should model it.
- **Some user messages may be automatic.** Permission replies or injected notes can be logged as `user_message`, so a few "human" pauses may not involve a person.
- **Codex timing is less exact.** 18% of Codex tool pauses differ from the tool's own duration by more than 1 s or 20%; we count the extra as idle time.
- **The trace is narrow.** It covers 43 developers in one lab using two closed models, so habits and context sizes may differ elsewhere.
- **Open: which model and GPU will M5 measure prefill on?**

How to reproduce

Everything rebuilds from the public data in under a minute. The commands below are for Windows PowerShell, such as the VS Code terminal; Mac and Linux differences are at the end.

1. Set up TraceLab (once)

Clone outside OneDrive or any other synced folder, since the data file is about 100 MB.

```
cd $HOME
git clone https://github.com/uw-syfi/TraceLab.git
cd TraceLab
powershell -ExecutionPolicy ByPass -c "irm https://astral.sh/uv/install.ps1 |
iex"
```

Close and reopen the terminal so it finds `uv`, then run this from the TraceLab folder:

```
uv --version
uv sync
```

If `uv` is still not found, run `$env:Path = "$HOME\.local\bin;$env:Path"`, which fixes it for that terminal only.

2. Download and check the data

```
curl.exe -L --fail --ssl-no-revoke -o trace\syfi_coding_trace.duckdb
https://github.com/uw-
syfi/TraceLab/releases/download/v0.0.1/syfi_coding_trace.duckdb
uv run python artifacts\trace_facts\overview_summary\analyze.py --db
trace\syfi_coding_trace.duckdb
```

The summary should report 357,161 LLM rounds, 432,510 tool calls and 43 distinct users.

3. Add our scripts

Copy the six `.py` files from our repo's `week3` folder into a new `our_work` folder inside TraceLab:

```
mkdir our_work
Copy-Item <path-to-our-repo>\week3\*.py our_work\
```

4. Run the scripts from the TraceLab folder

The scripts use paths relative to the TraceLab folder, so run them from there, in this order:

```
uv run python our_work\build_pause_table.py
uv run python our_work\look_at_pauses.py
uv run python our_work\plot_pause_cdf.py
uv run python our_work\plot_pause_by_tool.py
uv run python our_work\plot_context_size.py
```

`build_pause_table.py` must run first, because the other four read the `pauses.parquet` file it writes. The three plot scripts save `fig_pause_cdf.png`, `fig_pause_by_tool.png` and `fig_context_size.png` in `our_work`. To view any one session's raw events, run `uv run python our_work\look_at_session.py <session_id>`.

5. Check the results

Check	Expected
Rows in `pauses.parquet`	357,161, of which 346,820 usable
Claude tool pauses (build_pause_table)	median 0.12 s, 90th percentile 14.3 s
Codex tool pauses (build_pause_table)	median 1.05 s, 90th percentile 20.7 s

Check	Expected
Check session (look_at_pauses)	0.043, 4.56, 3.285, 5.809, 37.615, 40.533, 1.206, 94.702 and 42.993 s, then end
Shorter than b = 10 s (plot_pause_cdf)	tool 85.1%, human 11.2%, all 77.2%
Keep/evict check (plot_pause_by_tool)	87.4% always keep, 87.8% by tool name, 16.4% of long pauses caught
Prefill at 10,000 tokens/s (plot_context_size)	median b 12.5 s; keep wins 85.7% tool, 15.6% human, 78.2% all

The keep/evict check's train/test split depends on the DuckDB version, so its three numbers may differ by a fraction of a percent.

Mac and Linux

- Install uv with `curl -LsSf https://astral.sh/uv/install.sh | sh`.
- Use `curl` instead of `curl.exe`, and drop `--ssl-no-revoke`.
- Use `/` instead of `\` in paths, and `cp <path-to-our-repo>/week3/*.py our_work/` to copy the scripts.