

API Documentation for Outbound (User) for Bigship Direct

Table Of Contents & List of APIs

1. [Overview](#)
2. [Changelog](#)
3. [Base URL](#)
4. [Authentication](#)
5. [API Rate Limiting](#)
6. [Currency Format](#)
7. [Common Response Format](#)
8. [Error Handling & Sample Response](#)
9. [Environment Information](#)
10. [Support & Contact](#)
11. [Pagination Rules](#)
12. [Other Helpful Notes](#)
13. API: [User Login](#)
14. API: [Get Profile](#)
15. API: [Save Warehouse \(Save Pickup Location\)](#)
16. API: [Get Warehouse List \(Get Pickup Location List\)](#)
17. API: [Update Warehouse API \(Update Pickup Location\)](#)
18. API: [Get Package Types List](#)
19. API: [Get Payment Mode List](#)
20. API: [Get Risk Types List](#)
21. API: [Rate Calculator](#)
22. API: [Create Order \(Draft Mode\)](#)
23. API: [Get Serviceable Couriers and Rate Quotation for Draft Order](#)
24. API: [Place/Manifest Order](#)
25. API: [Cancel Order](#)
26. API: [Track Order](#)
27. API: [Order Information\(Order Detail\)](#)
28. API: [Download Shipment Documents \(Invoice, Label, Manifest, EwayBill\)](#)

Overview

This document provides details about the Unified Outbound APIs offered by Bigship. Please read this section carefully before you begin integrating the APIs.

Changelog

Date	Version	Changes Made
------	---------	--------------

07-06-2025	1.0	◇ Initial draft of Hyperlocal Outbound API documentation created, including core APIs for login, warehouse management, order creation, courier rates, and order lifecycle.
19-09-2025	1.1	◇ Updated the Hyperlocal Outbound API documentation: • In the Order Creation API, the fields Length, Width, and Height have been changed from <i>mandatory</i> to <i>optional</i>. • If these fields are not provided in the request payload, the backend will now automatically apply default dimensions of 10 × 10 × 10.
10-10-2025	1.2	◇ Added Two New APIs: Track Order and Order Information
08-04-2026	1.3	◇ Allow Domestic (B2B & B2C) APIs for complete flow.
09-06-2026	1.4	◇ Added New APIs: • Get Payment Modes List • Get Risk Types List • Rate Calculator • Download Shipment Documents (Invoice, Label, Manifest, EwayBill)
14-09-2026	1.5	◇ Updated the Outbound API documentation: • In the Order Creation & Warehouse Creation API, the fields state, city, and country have been changed from <i>mandatory</i> to <i>optional</i>. • In the Track Order API, TrackingNumber has been added as an additional parameter. The API now supports tracking using either CustomGlobalOrderId or TrackingNumber. • In the Track Order API, the response JSON has also been added for both Hyperlocal and Domestic shipment tracking. • In the Order Detail API, lr_number has been added to the response JSON.

✓ Base URL

<https://api.bigship.direct/>

To form the full URL for any endpoint, append the **API path** to the base URL.

For example, If the endpoint is: [api/outbound/login](#). The full URL is:

<https://api.bigship.direct/api/outbound/login>

🔒 Authentication

All APIs (except login) require a valid Bearer Token in the request header:

Authorization: Bearer {token}

You can obtain this token by calling the **User Login** API.

🚫 API Rate Limiting

To maintain system performance and prevent abuse, rate limiting may be applied:

- **Standard rate limit:** 100 requests per minute per IP (can be customized based on integration level)
- Exceeding limits may result in a **429 Too Many Requests** error.

💰 Currency Format

All amounts (e.g., wallet balance, rates, invoice amounts) are in **Indian Rupees (₹)**, not in paise.

Example: A balance of "[1000.00](#)" represents ₹1,000.00.

⚠️ Common Response Format

Most APIs follow a standard response format with keys like [status](#), [message](#), [status_code](#), and [data](#).

Refer to each API's response section for examples.

📄 Error Handling

- **400 Bad Request:** Invalid input or missing parameters.
- **401 Unauthorized:** Token is missing or expired.
- **403 Forbidden:** You do not have permission to access this resource.
- **404 Not Found:** Endpoint or resource does not exist.
- **409 Conflict:** Request could not be completed due to a conflict with the current state of the resource.
- **422 Unprocessable Entity:** The request was well-formed but contains semantic errors.
- **429 Too Many Requests:** You have sent too many requests in a given amount of time. Please slow down.
- **500 Internal Server Error:** An error occurred on the server.

Success Response:

```
{  
  "status": true,  
  "message": "Error message description appears here.",  
  "status_code": 200,  
  "data": ""
```

```
}
```

Error Response:

```
{  
  "status": false,  
  "message": "Error message description appears here.",  
  "status_code": 400,  
  "data": ""  
}
```

Validation Error Response:

```
{  
  "status": false,  
  "type": "validation",  
  "message": "First Key error message appears here.",  
  "status_code": 422,  
  "data": "",  
  "errors": {  
    "example_key": [  
      "Example Key is required or invalid."  
    ]  
  }  
}
```

Unauthorized Error Response:

```
{  
  "status": false,  
  "message": "Unauthenticated",  
  "status_code": 401,  
  "error": "Invalid token or session expired."  
}
```



Pagination Rules

When fetching paginated data from endpoints (e.g., warehouse list, drop locations list), follow the rules below:

- The **perPage** value must be a multiple of 5.
- You can request **a maximum of 25 records per page**.
- If these rules are not followed, the API will respond with an appropriate error message:
 - You can view up to 25 records per page at a time.
 - You can get records in multiples of 5.

☒ Valid values for **perPage**: 5, 10, 15, 20, 25



Support & Contact

If API users face issues or need assistance, they should have a clear support contact:

-  Support Email: support@bigship.in

Environment Information

APIs are accessible in different environments based on your stage of integration. Use the appropriate **Base URL** according to your environment:

Environment	Base URL	Description
Production	https://api.bigship.direct/	Live environment for real operations

Other Helpful Notes

- Always use Content-Type: application/json in headers.
- Some APIs have conditional mandatory fields. Be sure to review the notes under each parameter.
- Payload field types like *segment_type*, *latitude*, etc., must match the required case and data type.
- Date/time values returned by APIs are in UTC format.

1. API: User Login/Token Generation

Purpose: This endpoint allows users to log in to the system by providing their credentials. Upon successful authentication, the API returns user-specific data along with a session token.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/login`

Request Headers:

- **Content-Type:** application/json

Request Body:

The request body should be in JSON format and contain the following parameters:

- **username** (string, required): The email address of the user.
- **password** (string, required): The password associated with the user's account.
- **access_key** (string, required): A key used for additional access control.

Sample Request Body:

```
{  
  "username": "your_email@example.com",  
  "password": "your_password",  
  "access_key": "your_access_key"  
}
```

Response Structure:

This information is crucial for managing user sessions and accessing user-specific data within the application.

On a successful login, the API responds with a JSON object that includes the following keys:

- **status** (boolean): Indicates whether the login was successful.
- **message** (string): A message providing additional information about the login attempt.
- **status_code** (integer): The HTTP status code of the response.
- **data** (object): Contains user-specific information, including:
 - **firstName** (string): The first name of the user.
 - **lastName** (string): The last name of the user.
 - **EmailID** (string): The email address of the user.
 - **mobileNumber** (string): The mobile number of the user.
 - **countryname** (string): The name of the country associated with the user.

- **IsEmailVerified** (boolean): Indicates whether the user's email has been verified.
- **token** (string): The session token for the authenticated user.
- **tokenExpiringAt** (string): The expiration time of the session token.
- **is_outbound_service_enabled** (boolean): Indicates if outbound services are enabled for the user.
- **api_master_client_account** (object): Contains details about the user's API account, including:
 - **access_key** (string): The access key for the API account.
 - **access_key_generated_date** (string): The date when the access key was generated.
 - **is_account_enabled** (boolean): Indicates if the account is enabled.
 - **created_date** (string): The date when the account was created.
 - **updated_date** (string): The date when the account was last updated.
- **userWallet** (object): Contains wallet information for the user, including:
 - **Balance** (string): The current balance in the user's wallet.
 - **kycCurrency** (string): The currency used for KYC (Know Your Customer) purposes.

Response JSON:

```
{
  "status": true,
  "message": "Logged in Successfully",
  "status_code": 200,
  "data": {
    "firstName": "Sudhanshu",
    "lastName": "Mittal",
    "EmailID": "your_email@example.com",
    "mobileNumber": "9879879870",
    "countryname": "India",
    "IsEmailVerified": "1",
    "token": "your_generated_bearer_token",
    "tokenExpiringAt": "2025-05-29T12:25:30.664918Z",
    "is_outbound_service_enabled": "1",
    "api_master_client_account": {
      "access_key": "your_access_key",
      "access_key_generated_date": "2025-05-28 08:04:59.9980000",
      "is_account_enabled": "1",
      "created_date": "2025-05-27T13:54:34.940000Z",
      "updated_date": "2025-05-28T08:05:06.547000Z"
    },
    "userWallet": {
      "Balance": "1192826.66",
      "kycCurrency": "₹"
    }
  }
}
```

2. API: Get Profile

Purpose: This API endpoint makes an HTTP GET request to retrieve the user profile information.

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/profile`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body: No body or parameters are required for this GET request.

Response Structure:

The API response returns a JSON object with the following keys:

1. **status** (boolean): Indicates the success of the request.
2. **message** (string): A message related to the response.
3. **status_code** (integer): The HTTP status code of the response.
4. **data** (object): The profile data object containing the following keys:
 - a. **firstName** (string): The first name of the user.
 - b. **lastName** (string): The last name of the user.
 - c. **EmailID** (string): The email ID associated with the profile.
 - d. **mobileNumber** (string): The mobile number associated with the profile.
 - e. **countryname** (string): The name of the country.
 - f. **IsEmailVerified** (string): Indicates if the email is verified.
 - g. **is_outbound_service_enabled** (string): Indicates if the outbound service is enabled.
 - h. **api_master_client_account** (object): The API master client account object containing the following keys:
 - i. **access_key** (string): The access key for the account.
 - ii. **access_key_generated_date** (string): The date when the access key was generated.
 - iii. **is_account_enabled** (string): Indicates if the account is enabled.
 - iv. **created_date** (string): The date when the account was created.
 - v. **updated_date** (string): The date when the account was last updated.
- i. **userWallet** (object): The user's wallet information containing the following keys:
 - i. **Balance** (string): The current balance in the wallet.
 - ii. **kycCurrency** (string): The currency used for KYC.

Response JSON:

```
{
  "status": true,
  "message": "User profile fetched successfully.",
  "status_code": 200,
  "data": {
    "firstName": "Sudhanshu",
    "lastName": "Mittal",
    "EmailID": "your_email@example.com",
    "mobileNumber": "9879879870",
    "countryname": "India",
    "IsEmailVerified": "1",
    "is_outbound_service_enabled": "1",
    "api_master_client_account": {
      "access_key": "your_access_key",
      "access_key_generated_date": "2025-06-04 13:44:04.7740000",
      "is_account_enabled": "1",
      "created_date": "2025-05-27T13:54:34.940000Z",
      "updated_date": "2025-06-04T13:44:04.916000Z"
    },
    "userWallet": {
      "Balance": "1192516.48",
      "kycCurrency": "₹"
    }
  }
}
```

3. API: Save Warehouse API (Save Pickup Location Data)

Purpose: This API endpoint is used to save warehouse data for logistics operations.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/save-warehouse-data`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body:

The request body should be in JSON format and contain the following parameters:

- **segment_type** (text, required): The type of segment (e.g., hyperlocal, local).
- **warehouseContactPerson** (text, required): The contact person at the warehouse.
- **warehouseAddressPhone** (text, required): The phone number of the warehouse.
- **warehouseCountry** (text, optional): The country where the warehouse is located. It must be India when segment_type is hyperlocal or local.
- **warehouseState** (text, optional): The state where the warehouse is located.
- **warehouseCity** (text, optional): The city where the warehouse is located.
- **warehousePinCode** (text, required): The pin code of the warehouse.
- **warehouseAddressLine1** (text, required): Primary address of the warehouse. Must contain a minimum of 3 words and a maximum of 75 words.
- **warehouseAddressLine2** (text, optional): Secondary address of the warehouse. Must contain a minimum of 3 words and a maximum of 75 words.
- **warehouseAddressLandMark** (text, required): Landmark near the warehouse. Must contain a minimum of 3 words and a maximum of 50 words.
- **latitude** (text, required): The latitude of the warehouse. Only required when segment_type is hyperlocal.
- **longitude** (text, required): The longitude of the warehouse. Only required when segment_type is hyperlocal.
- **address_type** (text, required): Specifies the type of address. This field is required only when segment_type is hyperlocal. Allowed values are: Home, Office, Shop, Factory, Hotel, Other.

Sample Request Body:

```
{
  "segment_type": "hyperlocal", //hyperlocal, local
  "warehouseContactPerson": "Siddharth",
  "warehouseAddressPhone": "7854693258",
  "warehouseCountry": "India", //optional or it must be India when segment_type is hyperlocal or local.
```

```

"warehouseState": "Karnataka",
"warehouseCity": "BANGALORE",
"warehousePinCode": "560113",
"warehouseAddressLandMark": "Hudda City Centre",
"warehouseAddressLine1": "Sector 29",
"warehouseAddressLine2": "Sector 29",
"latitude": "12.947146336879577", // required only when segment_type is hyperlocal.
"longitude": "77.62102993895199", // required only when segment_type is hyperlocal.
"address_type": "home" // required only when segment_type is hyperlocal.
}

```

Response Structure:

The response will be a JSON object containing the following keys:

- **status:** Indicates the status of the request (e.g., success, error).
- **message:** Message providing additional information about the request outcome.
- **data:** An object containing:
 - **warehouseId:** The ID of the warehouse where the data was saved.
 - **is_phone_verified:** Indicates if the phone number of the warehouse is verified (0 for not verified, 1 for verified).
 - **phone_number:** The phone number associated with the warehouse.

Response JSON:

```

{
  "status": true,
  "message": "Warehouse added successfully.",
  "status_code": 200,
  "data": {
    "warehouseId": 218,
    "is_phone_verified": 0,
    "phone_number": "7854693258"
  }
}

```

4. API: Get Warehouse List API (List Saved Pickup Locations)

Purpose: This API endpoint is used to retrieve a list of warehouses.

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/get-warehouse-list`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body:

The request body should be in JSON format and contain the following parameters:

- **page:** (string, required) Page number for pagination.
- **perPage:** (string, required) Number of warehouses per page (Minimum 10, Maximum 25 records at a time).
- **segment_type:** (string, required) Type of segment to filter warehouses (e.g., hyperlocal, local).
- **status:** (string, optional) Filter by warehouse status and it can be 0 or 1.
- **filter_type:** (string, optional) Type of filter to be applied (Options: warehouse_name, warehouse_phone, warehouse_pin, warehouse_contact_person).
- **filter_value:** (string, optional) The value to apply for the selected filter type. Filtering is applied only if the **filter_type** key has a predefined value.

Sample Request Parameters:

```
{
  "perPage": "1",
  "page": "1",
  "segment_type": "hyperlocal", //hyperlocal, local
  "status": "", //optional, can be 0 or 1
  "filter_type": "", // warehouse_name, warehouse_phone, warehouse_pin, warehouse_contact_person
  "filter_value": "" //Bigship , 9842175668
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status:** (boolean) Indicates the success of the request.
- **message:** (string) Additional information or message from the server.
- **status_code:** (number) HTTP status code of the response.
- **data:** (object) Contains the warehouse data.

- **warehouse:** (array) List of warehouses matching the filter criteria.
- **total:** (number) Total count of warehouses matching the filter criteria.

Response JSON:

```
{
  "status": true,
  "message": "Warehouses get successfully.",
  "status_code": 200,
  "data": {
    "warehouse": [
      {
        "warehouseId": 218,
        "warehouseName": "HYP_Siddharth_1749123891",
        "warehouseContactPerson": "Siddharth",
        "warehouseAddressLine1": "Sector 29",
        "warehouseAddressLine2": "Sector 29",
        "warehouseAddressLandMark": "Hudda City Centre",
        "warehouseAddressPhone": "7854693258",
        "isActive": "1",
        "isShipped": "0",
        "isEditable": 1,
        "country": "India",
        "state": "KARNATAKA",
        "city": "BANGALORE",
        "pincode": "560113",
        "is_location_enabled": "1",
        "addedOn": "2025-06-05T11:44:51.223000Z",
        "hyperlocal": {
          "type": "warehouse",
          "latitude": "12.947146",
          "longitude": "77.621030",
          "mapLocationId": null,
          "addressType": "home"
        }
      }
    ],
    "total": 16
  }
}
```

5. API: Update Warehouse API (Edit Saved Pickup Location)

Purpose: This API endpoint is used to edit warehouse data for hyperlocal logistics operations.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/edit-warehouse-data`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body:

The request body should be in JSON format and contain the following parameters:

- **warehouseId** (text, required): The ID of the warehouse to be edited.
- **warehouseName** (text, required): The name of the warehouse.
- **warehouseContactPerson** (text, required): The contact person at the warehouse.
- **warehouseAddressPhone** (text, required): The phone number of the warehouse.
- **warehouseCountry** (text, optional): The country where the warehouse is located. It must be India when segment_type is hyperlocal or local.
- **warehouseState** (text, optional): The state where the warehouse is located.
- **warehouseCity** (text, optional): The city where the warehouse is located.
- **warehousePinCode** (text, required): The pin code of the warehouse.
- **warehouseAddressLine1** (text, required): Primary address of the warehouse. Must contain a minimum of 3 words and a maximum of 75 words.
- **warehouseAddressLine2** (text, optional): Secondary address of the warehouse. Must contain a minimum of 3 words and a maximum of 75 words.
- **warehouseAddressLandMark** (text, required): Landmark near the warehouse. Must contain a minimum of 3 words and a maximum of 50 words.
- **latitude** (text, required): The latitude of the warehouse. Only required when the warehouse was created for hyperlocal.
- **longitude** (text, required): The longitude of the warehouse. Only required when the warehouse was created for hyperlocal.
- **address_type** (text, required): Specifies the type of address. This field is required only when the warehouse is created for hyperlocal. Allowed values are: **Home**, **Office**, **Shop**, **Factory**, **Hotel**, **Other**.

Sample Request Body:

```
{  
  "warehouseId": "214",  
  "warehouseName": "Hyperlocal BANGALORE Pickup Rohit",  
}
```

```

"warehouseContactPerson": "Siddharth",
"warehouseAddressPhone": "7854693258",
"warehouseCountry": "India", //optional or it must be India when segment_type is hyperlocal or local.
"warehouseState": "Karnataka",
"warehouseCity": "BANGALORE",
"warehousePinCode": "560113",
"warehouseAddressLandMark": "Hudda City Centre",
"warehouseAddressLine1": "Sector 52",
"warehouseAddressLine2": "Sector 29",
"latitude": "12.947146336879577", // only when segment_type is hyperlocal.
"longitude": "77.62102993895199", // only when segment_type is hyperlocal.
"address_type": "home" // only when segment_type is hyperlocal.
}

```

Response Structure:

The response will be a JSON object containing the following keys:

- **status:** Indicates the status of the request (e.g., success, error).
- **message:** Message providing additional information about the request outcome.
- **data:** An object containing:
 - **is_phone_verified:** Indicates if the phone number of the warehouse is verified (0 for not verified, 1 for verified).
 - **phone_number:** The phone number associated with the warehouse.

Response JSON:

```

{
  "status": true,
  "message": "Warehouse updated successfully",
  "status_code": 200,
  "data": {
    "is_phone_verified": 1,
    "phone_number": "7854693258"
  }
}

```

6. API: Get Packages Type List API

Purpose: This API endpoint is used to edit warehouse data for hyperlocal logistics operations.

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/hyperlocal/get-packages-list`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body: No body is required for this API request.

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional information about the request status. This may be empty.
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data** (array): An array of package objects, each containing:
 - **HyperlocalPackageTypeId** (integer): The unique identifier for the package type.
 - **PackageType** (string): The name or type of the package.
 - **Description** (string): A description of the package type.
 - **IsEnabled** (string): A flag indicating whether the package type is enabled.

Response JSON:

```
{
  "status": true,
  "message": "HyperLocalPackages List get successfully.",
  "status_code": 200,
  "data": [
    {
      "HyperlocalPackageTypeId": 1,
      "PackageType": "Electronics",
      "Description": "Electronic gadgets, devices, and accessories",
      "IsEnabled": "1"
    }
  ]
}
```

7. API: Get Payment Mode List API

Purpose: This API endpoint is used to retrieve the payment modes based on the specified shipment category: hyperlocal, domestic_b2b, or domestic_b2c

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/get-payment-mode?segment_type=domestic_b2b`

Request Headers:

1. Content-Type: application/json
2. Authorization: Bearer Token

Request Body: Request parameters are required for this GET request.

Request Structure:

- **segment_type (string, required):** Specifies the shipment segment type and return applicable payment modes based on either 'hyperlocal', 'domestic_b2c' and 'domestic_b2b'.

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional information about the request status. This may be empty.
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data** (array): An array of payment modes, each containing:
 - **paymentModelId(string):** The unique identifier for the payment type.
 - **paymentModeName(string):** The name of the payment mode.

Response JSON:

```
{
  "status": true,
  "message": "Payment mode retrieved successfully.",
  "status_code": 200,
  "data": [
    {
      "paymentModelId": "1",
      "paymentModeName": "Prepaid"
    }
  ]
}
```

8. API: Get Risk Type List

Purpose: This API endpoint is used to retrieve the risk types.

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/domestic/risk-types`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body: Request parameters are not required for this GET request.

Response Structure: The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional information about the request status. This may be empty.
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data** (array): An array of payment modes, each containing:
 - **riskTypeId(string)**: The unique identifier for the risk type.
 - **riskName(string)**: The name of the risk type mode.
 - **slug(string)**: The unique slug for risk type.

Response JSON:

```
{  
  
  "status": true,  
  "message": "Risk Types Retrieved Successfully!",  
  "status_code": 200,  
  "data": [  
    {  
      "riskTypeId": 1,  
      "riskName": "Third Party Insurance",  
      "slug": "third-party-insurance"  
    },  
    {  
      "riskTypeId": 2,  
      "riskName": "Owner Risk",  
      "slug": "owner-risk"  
    }  
  ]  
}
```

9. API: Rate Calculator API

Purpose: This API endpoint is used to calculate the shipping rates without create an order based on the provided source and destination details along with the provided details.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/user-rate-calculator`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body: The request body should be in JSON format.

Payload Structures

Hyperlocal segment is not available for this api. Supported `segment_type` values are `domestic_b2b` and `domestic_b2c`. However, for **B2C shipments**, the `boxes` array must contain only one box.

Below is the sample payload structure that is used for both B2B and B2C shipment categories.

- **segment_type (string, required):** The type of segment for the order. Options are: `"domestic_b2b"`, `"domestic_b2c"`.
- **sourcePincode (string, required):** Pickup pincode.
- **destPincode (string, required):** Destination pincode.
- **invoicevalue(string, required):** The total invoice amount for the order.
- **PaymentModelId (string, required):** The payment mode ID for the shipment.
- **codAmount(string, optional):** Only required when payment mode is COD and the amount must be less than invoice amount.
- **riskTypeId(string, required):** Risk type is the insurance type for the shipment, else the default risk type is Owner Risk.
- **boxes (array, required):** Contains details about the boxes in the order(An array of dimensions with weight and no of boxes for each box). And in case of B2C, the array size must be 1.
 - **box_length (integer, required):** The length of the box.
 - **box_width (integer, required):** The breadth of the box.
 - **box_height (integer, required):** The height of the box.
 - **box_dead_weight (integer, required):** The weight of the box.
 - **no_of_box (integer, required):** The number of the box.

Sample Request Body:

```
// B2B, B2C
{
  "segment_type": "domestic_b2b",
  "sourcePincode": 302017, //320008: Dehradun, 110001: Delhi
  "destPincode": 110006, //462001, 110006,302017
  "invoiceValue": 5000,
  "paymentModelId": 2, //1: Prepaid, 2: COD 3: ToPay
  // "codAmount": 1000, //when paymentModelId is 2
  "riskTypeId": 2, // 1: Third Party Insurance, 2: Owner Risk, 3: Carrier Risk
  "boxes": [
    {
      "no_of_box": "10",
      "box_length": "10",
      "box_width": "10",
      "box_height": "10",
      "box_dead_weight": "10"
    }
  ]
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status (boolean):** Indicates if the request was successful.
- **message (string):** A message related to the request.
- **status_code (integer):** The HTTP status code of the response.
- **data (object):** Contains the data related to the rate estimation of couriers.
 - **courierName (string):** Name of the courier.
 - **courierImage (string):** URL of the courier's logo.
 - **courierType (string):** Type of courier service (e.g., Surface).
 - **riskTypeName (string):** Name of the risk type associated with the rate.
 - **planName (string):** Name of the pricing plan.
 - **courier_partner_id (number):** Unique ID of the courier partner.
 - **courierCharge (number):** Base courier charge.
 - **tat (string):** Turnaround time (in days).
 - **weight (number):** Chargeable weight of the shipment.
 - **zone (string):** Zone classification for the source and destination.
 - **restricted_pincode_message (string):** Message indicating any pincode restrictions, if applicable and comes only for special state scenarios.
 - **codCharges (number):** COD charges applicable to the shipment.
 - **riskType (string):** Risk charge for the selected risk type.
 - **lrCost (string):** Logistic Receipt (LR) cost.
 - **handlingCharge (string):** Handling charge for the shipment.
 - **greenTax (number):** Green tax applicable to the shipment.
 - **toPay (number):** ToPay charges, if payment mode is ToPay.
 - **oda (string):** Out-of-Delivery-Area (ODA) charges, if destination pincode is ODA.

- **warai_Charge (number):** Warai charges, if applicable.
- **state_Tax (string):** State tax applicable to the shipment, if applicable.
- **minimum_weight (string):** Minimum chargeable weight.
- **pickup_Charge (number):** Pickup charge applicable to the shipment.
- **whatsappNotificationCharge (number):** WhatsApp notification charge, if notify setting is enabled for WhatsApp.
- **emailNotificationCharge (number):** Email notification charge, if notify setting is enabled for email.
- **smsNotificationCharge (number):** SMS notification charge, if applicable.
- **totalCharge (number):** Total charge payable for the shipment.

Response JSON:

```
{
  "status": true,
  "message": "All Charges Retrieved Successfully!",
  "status_code": 200,
  "data": [
    {
      "courierName": "LTL Delhivery",
      "courierImage": "https://storage.bigship.direct/files/1759153246_18.svg",
      "courierType": "Surface",
      "riskTypeName": "Owner Risk",
      "planName": "Franchise",
      "courier_partner_id": 18,
      "courierCharge": 760,
      "tat": "3",
      "weight": 100,
      "zone": "N1-N1",
      "restricted_pincode_message": null,
      "codCharges": 0,
      "riskType": "33.00",
      "IrCost": "80.00",
      "handlingCharge": "0.00",
      "greenTax": 100,
      "toPay": 0,
      "oda": "0.00",
      "warai_Charge": 0,
      "state_Tax": "0.00",
      "minimum_weight": "25.00",
      "pickup_Charge": 100,
      "whatsappNotificationCharge": 0,
      "emailNotificationCharge": 0,
      "smsNotificationCharge": 0,
      "totalCharge": 1073
    }
  ]
}
```

10. API: Create Order API (Draft Order)

Purpose: This API endpoint is used to create a new order with the provided details.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/create-order`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body: The request body should be in JSON format and contain the following parameters:

Important Note About Segments

The request payload **changes based on the selected `segment_type`**, and the **purpose/meaning of fields also differs** for each segment. Every segment has its own required fields and its own payload structure.

Supported `segment_type` values:

- `hyperlocal`
- `domestic_b2b`
- `domestic_b2c`

Common Request Fields (Applicable to Most Segments)

- **`segment_type` (string, required):** The type of segment for the order, e.g., `"hyperlocal"`, `"domestic_b2b"`, `"domestic_b2c"`.
- **`MasterOrderPickUpLocation` (integer, required):** The warehouse ID for order pickup.
- **`MasterOrderPaymentMode` (integer, required):** The mode of payment for the order.
- **`MasterOrderShippingName` (string, required):** The name of the shipping entity.
- **`MasterOrderShippingEmail` (string, optional):** The email of the shipping entity.
- **`MasterOrderShippingMobileNo` (string, required):** The mobile number of the shipping entity.
- **`MasterOrderShippingZipCode` (string, required):** The zip code of the shipping address.
- **`MasterOrderShippingCity` (string, optional):** The city of the shipping address.
- **`MasterOrderShippingState` (string, optional):** The state of the shipping address.
- **`MasterOrderShippingCountry` (string, optional):** The country of the shipping address.
- **`MasterOrderShippingAddress` (string, required):** The primary address of the shipping entity.
- **`MasterOrderShippingAddress2` (string, optional):** Additional address details for the shipping entity.
- **`MasterOrderShippingLandmark` (string, optional):** Landmark of the shipping address.

Segment-Wise Payload Structures

Below are the **final sample payloads**, updated and aligned with the actual requirement for each segment type.

1. Hyperlocal Payload

- **MasterOrderShippingLatitude (string, required):** The latitude of the shipping location.
- **MasterOrderShippingLongitude (string, required):** The longitude of the shipping location.
- **OrderInvoiceNo (string, optional):** The invoice number for the order.
- **MasterOrderInvoiceAmount (integer, required):** The total invoice amount for the order.
- **PackageTypeId (integer, required):** The ID representing the type of package and only used for hyperlocal only.
- **pickup_instructions (string, optional):** Instructions for the pickup.
- **additional_comments (string, optional):** Any additional comments regarding the order.
- **boxes (object, required):** Contains details about the boxes in the order.
 - **weight_unit (string, required):** The unit of weight for the boxes.
 - **dimension_unit (string, required):** The unit of dimensions for the boxes.
 - **dimensions (array, required):** An array of dimensions for each box.
 - **length (integer, optional):** The length of the box.
 - **breadth (integer, optional):** The breadth of the box.
 - **height (integer, optional):** The height of the box.
 - **weight (integer, required):** The weight of the box.

Sample Request Body:

```
{
  "segment_type": "hyperlocal", //hyperlocal, domestic_b2b, domestic_b2c
  "MasterOrderPickUpLocation": 96, //Sender Warehouse Id
  "PackageTypeId": 5,
  "MasterOrderInvoiceAmount": 100, //package_value
  "OrderInvoiceNo": "1234", //optional
  "MasterOrderPaymentMode": 1, //fixed
  //Start::Receiver Information
  "MasterOrderShippingName": "Tony carreiro",
  "MasterOrderShippingMobileNo": "9166761588",
  "MasterOrderShippingZipCode": "110002",
  "MasterOrderShippingCity": "DELHI",
  "MasterOrderShippingState": "DELHI",
  "MasterOrderShippingCountry": "India",
  "MasterOrderShippingAddress": "asq",
  "MasterOrderShippingAddress2": "wqewq",
  "MasterOrderShippingLandmark": "N/A",
  "MasterOrderShippingLatitude": "28.641909999999999",
  "MasterOrderShippingLongitude": "77.222053000000002",
  //End::Receiver Information
  "pickup_instructions": "", //optional
}
```

```

"additional_comments": "", //optional
//Start::Box Dimesion Details
"boxes": {
  "weight_unit": "kg", //fixed
  "dimension_unit": "cm", //fixed
  "dimensions": [
    {
      "length": 40, //optional
      "breadth": 40, //optional
      "height": 40, //optional
      "weight": 20, //required
    }
  ]
}
//End::Box Dimesion Details
}

```

2. Domestic B2B Payload

- **MasterOrderReturnLocation (integer, required):** The warehouse ID for order pickup.
- **MasterOrderDate (datetime, required):** When your order has been created, and it must be UTC time format, (Y-m-d H:i:s)
- **OrderInvoiceNo (string, required):** The invoice number for the order.
- **MasterOrderInvoiceAmount (integer, required):** The total invoice amount for the order.
- **MasterOrderCollectableAmount (string, optional):** When payment mode is COD of the order.
- **ProductName (string, required):** Any additional comments regarding the order.
- **boxes (array, required):** Contains details about the boxes in the order.
 - **weight_unit (string, required):** The unit of weight for the boxes.
 - **dimension_unit (string, required):** The unit of dimensions for the boxes.
 - **dimensions (array, required):** An array of dimensions for each box.
 - **length (integer, required):** The length of the box.
 - **breadth (integer, required):** The breadth of the box.
 - **height (integer, required):** The height of the box.
 - **weight (integer, required):** The weight of the box.
 - **noOfBoxes (string, required):** An array of dimensions for each box.

Sample Request Body:

```

// B2B
{
  "segment_type": "domestic_b2b",
  "MasterOrderPickUpLocation": 258,
  "MasterOrderReturnLocation": 258, //only required for domestic
  "MasterOrderDate": "2025-11-15 01:05:15",
  "MasterOrderPaymentMode": 1,

```

```

"OrderInvoiceNo": "1234", //required
"MasterOrderInvoiceAmount": 1000,
"MasterOrderCollectableAmount": "", //only when payment mode is COD
//Start::Receiver Information
"MasterOrderShippingEmail": "test@gmail.com", //optional
"MasterOrderShippingName": "test company",
"MasterOrderShippingMobileNo": 8956231470,
"MasterOrderShippingAddress": "test",
"MasterOrderShippingAddress2": "",
"MasterOrderShippingLandmark": "test",
"MasterOrderShippingZipCode": "110011",
"MasterOrderShippingCountry": "India",
"MasterOrderShippingState": "DELHI",
"MasterOrderShippingCity": "DELHI",
//End::Receiver Information
"totalNumOfBoxes": 2, // sum of the noOfBoxes field from all boxes listed below
"ProductName": "test product",
"boxes": [
  {
    "weight_unit": "kg", //fixed
    "dimension_unit": "cm", //fixed
    "noOfBoxes": 1,
    "dimensions": [
      {
        "length": 101,
        "breadth": 40,
        "height": 40,
        "weight": 20
      }
    ]
  },
  {
    "weight_unit": "kg", //fixed
    "dimension_unit": "cm", //fixed
    "noOfBoxes": 1,
    "dimensions": [
      {
        "length": 40,
        "breadth": 40,
        "height": 40,
        "weight": 20
      }
    ]
  }
]
}

```

3. Domestic B2C Payload

- **MasterOrderReturnLocation (integer, required):** The warehouse ID for order pickup.

- **MasterOrderDate (date, required):** When your order has been created, and it must be UTC time format, (Y-m-d H:i:s)
- **OrderInvoiceNo (string, required):** The invoice number for the order.
- **MasterOrderInvoiceAmount (required):** The total invoice amount of the order and it must be equal to the sum of totalAmount field for every product item.
- **boxes (array, required):** Contains details about the boxes in the order.
 - **weight_unit (string, required):** The unit of weight for the boxes.
 - **dimension_unit (string, required):** The unit of dimensions for the boxes.
 - **dimensions (array, required):** An array of dimensions for each box.
 - **length (integer, required):** The length of the box.
 - **breadth (integer, required):** The breadth of the box.
 - **height (integer, required):** The height of the box.
 - **weight (integer, required):** The weight of the box.
 - **noOfBoxes (string, required):** An array of dimensions for each box.
 - **products (array, required when segment_type is domestic_b2c):** An array of products for each box.
 - **productName (string, required):** The length of the box.
 - **hsn (string, optional):** The breadth of the box.
 - **qty (integer, optional):** The height of the box.
 - **amount (integer, required):** The weight of the box.
 - **totalAmount (integer, required):** The weight of the box.
 - **collectableAmount (integer, required):** The weight of the box.
 - **categoryID (string, required):** The weight of the box.

Sample Request Body:

```
// B2C
{
  "segment_type": "domestic_b2c",
  "MasterOrderPickUpLocation": 258,
  "MasterOrderReturnLocation": 258,
  "MasterOrderDate": "2025-08-28 01:05:15",
  "MasterOrderPaymentMode": 1,
  "OrderInvoiceNo": "1234", //required
  "MasterOrderInvoiceAmount": 1000, //sum of all products total amount
  //Start::Reciever Information
  "MasterOrderShippingEmail": "test@gmail.com", //optional
  "MasterOrderShippingName": "test company",
  "MasterOrderShippingMobileNo": 8956231470,
  "MasterOrderShippingAddress": "test",
  "MasterOrderShippingAddress2": "",
  "MasterOrderShippingLandmark": "test",
  "MasterOrderShippingZipCode": "110011",
  "MasterOrderShippingCountry": "India",
  "MasterOrderShippingState": "DELHI",
  "MasterOrderShippingCity": "DELHI",
  //End::Reciever Information
}
```

```

"totalNumOfBoxes": 1, // sum of the noOfBoxes field from all boxes listed below
"boxes": [
  {
    "weight_unit": "kg",
    "dimension_unit": "cm",
    "noOfBoxes": 1,
    "dimensions": [
      {
        "length": 101,
        "breadth": 40,
        "height": 40,
        "weight": 20
      }
    ],
    "products": [
      {
        "productName": "soap",
        "hsn": "1111", //optional
        "qty": "1",
        "amount": "4000",
        "totalAmount": 4000,
        "collectableAmount": 4000,
        "categoryId": "1"
      },
      {
        "productName": "balti",
        "hsn": "1111", //optional
        "qty": "1",
        "amount": "4000",
        "totalAmount": 4000,
        "collectableAmount": 4000,
        "categoryId": "1"
      }
    ]
  }
]
}

```

Response Structure:

The response will be a JSON object containing the following keys:

- **status (boolean):** Indicates if the request was successful.
- **message (string):** A message related to the request.
- **status_code (integer):** The HTTP status code of the response.
- **data (object):** Contains the data related to the order creation.
 - **CustomGlobalOrderId (string):** The unique order ID for tracking the order.

Response JSON:

```
{  
  "status": true,  
  "message": "Order Created Successfully.",  
  "status_code": 200,  
  "data": {  
    "CustomGlobalOrderId": "311276742"  
  }  
}
```

11. API: Order Rate Calculation API (Fetch Serviceable couriers for Order)

Purpose: This API is designed to calculate the shipping cost for a given shipment based on various parameters. This API allows users to obtain the estimated shipping costs associated with a specific order, facilitating better decision-making for shipping logistics.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/courier-wise-shipment-cost`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body:

The request body should be in JSON format and contain the following parameters:

- **MasterCustomOrderId (string, required):** A unique identifier for the custom order. This ID is essential for retrieving the relevant shipment details and calculating the associated costs.

Sample Request Body:

```
{
  "MasterCustomOrderId": "311276742"
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional context about the request status (may be empty).
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data** (object): Contains the calculated shipping cost details, which include:
 - **segment_type** (string): The type of shipment segment (e.g., domestic, international).
 - **calculatedRates** (array): An array of objects containing detailed rate information for each courier option:
 - **courierId** (integer): A unique identifier for the courier.
 - **courierName** (string): The name of the courier service.
 - **courierImage** (string): A URL or path to the courier's logo/image.
 - **vehicle_type** (string): The type of vehicle used for shipping.

- **capacity** (string): The capacity of the vehicle.
- **planName** (string): The name of the shipping plan offered by the courier.
- **base_freight** (number): The base freight charge for the shipment.
- **gst_amount** (number): The Goods and Services Tax applicable to the shipment.
- **total_freight** (number): The total freight cost, including base freight and taxes.
- **currency** (string): The currency in which the costs are denominated.

Response JSON:

1. Hyperlocal Response

```
{
  "status": true,
  "message": "Rates Retrieved successfully.",
  "status_code": 200,
  "data": {
    "segment_type": "hyperlocal",
    "calculatedRates": [
      {
        "courierId": 25,
        "courierName": "Borzo",
        "courierImage": "https://storage.bigship.direct/files/1743485968_25.svg",
        "vehicle_type": "TWO_WHEELER",
        "capacity": "20kg",
        "planName": "Sprint",
        "base_freight": 278.55,
        "gst_amount": 50.14,
        "total_freight": 328.69,
        "currency": "₹"
      }
    ]
  }
}
```

2. Domestic B2B Response

```
{
  "status": true,
  "message": "Rates Retrieve successfully.",
  "status_code": 200,
  "data": {
    "segment_type": "domestic_b2b",
    "calculatedRates": [
      {
        "planName": "Franchise",
        "courierName": "Delhivery LTL",
        "courierId": "18",
        "pickup": "DELHI",

```

```

"destination": "DELHI",
"charged_weight": 56,
"weight_unit": "kg",
"base_freight": 425.6,
"riskTypeName": "Owner Risk",
"courierType": "Surface",
"zone": "N1-N1",
"riskCharge": "33.00",
"lrCost": "80.00",
"handlingCharge": ".00",
"greenTax": "100.00",
"codCharges": 0,
"toPay": ".00",
"oda": ".00",
"tat": 3,
"warai_Charge": 0,
"state_Tax": 0,
"pickup_Charge": "75.00",
"smsNotificationCharge": 0,
"emailNotificationCharge": 0,
"whatsappNotificationCharge": 0,
"total": "713.60",
"kycCurrency": "₹",
"courierImage": "https://storage.bigship.direct/files/1759153246_18.svg",
"riskCharges": [
  {
    "typeId": 2,
    "name": "Owner Risk",
    "chargeValue": "33.00",
    "isRisk": true
  },
  {
    "typeId": 3,
    "name": "Carrier Risk",
    "chargeValue": "63.00",
    "isRisk": false
  }
]
}
]
}
}

```

3. Domestic B2C Response

```

{
  "status": true,
  "message": "Rates Retrieve successfully.",
  "status_code": 200,
  "data": {
    "segment_type": "domestic_b2c",

```

```
"calculatedRates": [
  {
    "planName": "Max",
    "courierName": "Amazon 10KG",
    "courierId": "64",
    "pickup": "DELHI",
    "destination": "DELHI",
    "charged_weight": 33,
    "weight_unit": "kg",
    "base_freight": 528,
    "riskTypeName": "Owner Risk",
    "courierType": "Surface",
    "zone": "A-A",
    "riskCharge": ".00",
    "lrCost": ".00",
    "handlingCharge": ".00",
    "greenTax": ".00",
    "codCharges": 0,
    "toPay": ".00",
    "oda": ".00",
    "tat": 1,
    "warai_Charge": 0,
    "state_Tax": 0,
    "pickup_Charge": ".00",
    "smsNotificationCharge": 0,
    "emailNotificationCharge": 0,
    "whatsappNotificationCharge": 0,
    "total": "528.00",
    "kycCurrency": "₹",
    "courierImage": null,
    "riskCharges": [
      {
        "typeId": 1,
        "name": "Third Party Insurance",
        "chargeValue": "120.00",
        "isRisk": false
      },
      {
        "typeId": 2,
        "name": "Owner Risk",
        "chargeValue": "0.00",
        "isRisk": true
      }
    ]
  }
]
```

12. API: Place/Manifest Order API

Purpose: This API endpoint is used to place an order with the provided details.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/place-order`

Request Headers:

- Content-Type: application/json (Only for hyperlocal)
- Authorization: Bearer Token

Note: Please ensure the Order Rate Calculation API must be executed before this API call.

Request Body:

The request body should be in JSON format and contain the following parameters:

- **MasterCustomOrderId (string, required):** A unique identifier for the custom order. This ID is essential for retrieving the relevant shipment details and calculating the associated costs.
- **courierId (integer, required):** The ID of the courier for the order which you received in Order Rate Calculation API.

Sample Request Body:

1. Hyperlocal Payload

```
{
  "MasterCustomOrderId": "311276742",
  "courierId": 25
}
```

2. Domestic B2B/B2C Payload

It must be form-data & in headers, Content-Type must be multipart/form-data.

```
{
  "MasterCustomOrderId": "774827072",
  "courierId": "64",
  "invoiceType": "uploaded",
  "InvoiceData": (binary file data), // only required for b2b courier orders.
  "EwaybillNo": "", // required when order InvoiceAmount is gte 50k and for b2b courier orders only.
  "EwayBillData": (binary file data), // required when order InvoiceAmount is gte 50k and for b2b courier orders only.
  "riskTypeId": "2" // 1:Third-Party 2:Owner 3:Carrier
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional context about the request status (may be empty).
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data (object)**: Contains additional data related to the order placement.
- **reference_number** (string): The reference number for the order.
- **awb_assigned** (string): The assigned AWB number for the order.

Response JSON:

```
{
  "status": true,
  "message": "Order placed successfully.",
  "status_code": 200,
  "data": {
    "reference_number": 305585,
    "awb_assigned": 305585
  }
}
```

13. API: Cancel Order API

Purpose: This API endpoint cancels the order with the provided details.

API Request:

- **Method:** POST
- **URL:** `{{url}}api/outbound/cancel-order`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Cases: An order can only be cancelled before it reaches the *Rider-Assigned* status.

Request Body: The request body should be in JSON format and contain the following parameters:

- **MasterCustomOrderId (string, required):** A unique identifier for the custom order. This ID is essential for retrieving the relevant shipment details.

Sample Request Body:

```
{  
  "CustomGlobalOrderId": "311276742",  
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional context about the request status (may be empty).
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data (array):** An array that may contain details of the cancelled order or additional data related to the cancellation, and it can be a blank array.

Response JSON:

```
{  
  "status": true,  
  "message": "Order cancelled successfully",  
  "status_code": 200,  
  "data": []  
}
```

14. API: Track Order API

Purpose: This API endpoint displays order tracking information.

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/track-order`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body:

The request body should be in JSON format and contain the following parameters:

- **CustomGlobalOrderId (string, required):** A unique identifier for the custom order. This ID is essential for retrieving the relevant shipment details. Either CustomGlobalOrderId or TrackingNumber must be provided.
- **TrackingNumber (string, required):** A unique identifier for the shipment/order tracking. This can be used to retrieve the relevant shipment details. Either TrackingNumber or CustomGlobalOrderId must be provided.

Validation:

At least one of the following parameters is required:

- CustomGlobalOrderId
- TrackingNumber

Both parameters may also be provided in the same request.

Sample Request Body:

```
{
  "CustomGlobalOrderId": "311276742",
}
OR
{
  "TrackingNumber": "152724550046092",
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.

- **message** (string): A message providing additional context about the request status (may be empty).
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data (array)**: An array that may contain details of the order tracking, or it can be a blank array.

Response JSON:

1. Hyperlocal Response

```
{
  "status": true,
  "message": "Data retrieved successfully.",
  "status_code": 200,
  "data": {
    "CustomGlobalOrderId": "383123781",
    "order_place_time": "2025-05-03T06:17:53.277000Z",
    "tracking_number": "65948160",
    "courier_name": "Borzo",
    "courier_image": "https://storage.bigship.direct/files/1748353411_25.svg",
    "tag": "Delivered",
    "order_status": "Delivered",
    "latest_checkpoint_time": "2025-05-03T08:13:43.092000Z",
    "source_coordinate": {
      "latitude": "28.577874",
      "longitude": "77.313792",
      "mapLocationId": "ChIJ1SWqHADIDDkRiy5a9enrjZ4",
      "addressType": "Office"
    },
    "drop_coordinate": {
      "latitude": "28.623762",
      "longitude": "77.294691",
      "mapLocationId": "ChIJxhljK7kDDkRd33o-87f5ws",
      "addressType": "other"
    },
    "tracking_current_status": {
      "tracking_status": "Delivered",
      "partner_details": {
        "name": "Nishu Ratan Vashudev Singh",
        "vehicle": {
          "number": null,
          "type": "TWO_WHEELER"
        }
      },
      "contact": {
        "primary": {
          "country_code": "+91",
          "number": "8287623320"
        }
      }
    }
  }
}
```

```
    "secondary": {
      "country_code": "+91",
      "number": "8287623320"
    }
  },
  "location": {
    "latitude": null,
    "longitude": null
  },
  "timestamps": {
    "pickup": null,
    "order": {
      "accepted": null,
      "started": null,
      "ended": "2025-05-03 08:13:42"
    }
  },
  "fare_details": {
    "currency": "INR",
    "amount": "110.43"
  },
  "tracking_histories": [
    {
      "location": {
        "latitude": null,
        "longitude": null
      },
      "tag": "Delivered",
      "order_status": "Delivered",
      "checkpoint_time": "2025-05-03T08:13:42.984000Z",
      "message": "Order has been successfully delivered."
    },
    {
      "location": {
        "latitude": "28.6258068",
        "longitude": "77.3141718"
      },
      "tag": "In-Transit",
      "order_status": "In-Transit",
      "checkpoint_time": "2025-05-03T08:13:35.472000Z",
      "message": "Rider is on the way."
    },
    {
      "location": {
        "latitude": "28.57778",
        "longitude": "77.3136367"
      },

```

```

        "tag": "In-Transit",
        "order_status": "In-Transit",
        "checkpoint_time": "2025-05-03T06:47:11.978000Z",
        "message": "Rider is on the way."
    }
}
}
}

```

2. Domestic Response

```

{
  "status": true,
  "message": "Data retrieved successfully.",
  "status_code": 200,
  "data": {
    "CustomGlobalOrderId": "547626962",
    "order_place_time": "2026-09-08T00:02:07.052000Z",
    "tracking_number": "152724550046092",
    "courier_name": "Xpressbees 0.5Kg",
    "courier_image": "https://storage.bigship.direct/files/1781687427_79.svg",
    "tag": "RTO DELIVERED",
    "order_status": "RTO Delivered",
    "latest_checkpoint_time": "2026-09-08T07:37:16.000000Z",
    "date_expected_delivery": null,
    "date_promised_delivery": null,
    "checkpoints": [
      {
        "location": null,
        "tag": "RTO Delivered",
        "order_status": "RTO Delivered",
        "checkpoint_time": "2026-09-08T07:37:16.000000Z",
        "message": "Order status updated to RTO Delivered -M"
      },
      {
        "location": null,
        "tag": "RTO In-Transit",
        "order_status": "RTO In Transit",
        "checkpoint_time": "2026-09-08T07:35:00.000000Z",
        "message": "Order status updated to RTO In Transit -M"
      },
      {
        "location": null,
        "tag": "RTO Delivered",
        "order_status": "RTO Delivered",
        "checkpoint_time": "2026-09-08T07:21:06.000000Z",
        "message": "Order status updated to RTO Delivered -M"
      },
      {
        "location": null,
        "tag": "RTO In-Transit",

```

```
    "order_status": "RTO In Transit",
    "checkpoint_time": "2026-09-08T07:19:10.000000Z",
    "message": "Order status updated to RTO In Transit -M"
  },
  {
    "location": null,
    "tag": "Delivered",
    "order_status": "Delivered",
    "checkpoint_time": "2026-09-08T07:18:29.000000Z",
    "message": "Order status updated to Delivered -M"
  },
  {
    "location": null,
    "tag": "Out for Delivery",
    "order_status": "Out for Delivery",
    "checkpoint_time": "2026-09-08T07:16:50.000000Z",
    "message": "Order status updated to Out for Delivery -M"
  },
  {
    "location": null,
    "tag": "In-Transit",
    "order_status": "In-Transit",
    "checkpoint_time": "2026-09-08T07:10:15.000000Z",
    "message": "Order status updated to In-Transit -M"
  }
]
}
```

15. API: Order Detail API

Purpose: This API is used to get the complete order details.

API Request:

- **Method:** GET
- **URL:** `{{url}}api/outbound/order-shipment-details`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body: The request body should be in JSON format and contain the following parameters:

- **MasterCustomOrderId (string, required):** A unique identifier for the custom order. This ID is essential for retrieving the relevant shipment details.

Sample Request Body:

```
{
  "MasterCustomOrderId": "311276742",
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional context about the request status (may be empty).
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data (array):** An array that may contain details of the order details or it can be a blank array.

Response JSON:

```
{
  "status": true,
  "message": "Orders shipment details retrieved successfully.",
  "status_code": 200,
  "data": {
    "segment_type": "domestic_b2b",
    "getOrderDetails": {
      "MasterCustomOrderId": "891784492",
      "InvoiceNumber": "591183664",
      "MasterOrderCurrency": "INR",
      "AwbNumber": "40325311964303",
      "created_at": "2026-09-11T06:41:58.032000Z",
    }
  }
}
```

```
"updated_at": "2026-09-11T18:05:34.186000Z",
"MasterCustomInvoiceId": "591183664",
"PaymentMode": "ToPay",
"InvoiceStatusId": "2",
"InvoiceStatus": "Uploaded",
"status_id": "4",
"status": "Cancelled",
"products_name": "test",
"product_details": [
  {
    "numberOfProducts": "1",
    "detailsIdentifier": "353356-1",
    "products": [
      {
        "hsn": null,
        "qty": "1",
        "currency": "₹",
        "amount": "5000.00",
        "totalAmount": "5000.00",
        "productName": "test"
      }
    ],
    "box_details": [
      {
        "parameterName": "Length",
        "parameterValue": "40",
        "parameterCategory": "CM"
      },
      {
        "parameterName": "Breadth",
        "parameterValue": "27",
        "parameterCategory": "CM"
      },
      {
        "parameterName": "Height",
        "parameterValue": "32",
        "parameterCategory": "CM"
      }
    ],
    "weight": {
      "value": "32",
      "unit": "KG"
    }
  }
],
"MasterOrderShippingZipCode": "360024",
"totalNoOfBoxes": "1",
"consignorType": "Self",
"consignor": {
  "companyName": "Testing f Bigship Pvt Ltd",
```

```
"companyEmailId": "indu.rautela@bigship.in",
"companyMobile": "9310643058",
"orderCountry": "India",
"orderState": "DELHI",
"orderCity": "DELHI",
"orderPin": "110025",
"billingAddress": "Testing Account",
"billingAddress2": "Testing Account",
"landmark": "Nodia",
"consignorBusinessType": "Individual"
},
"consignee": {
  "companyName": "Test Shipper",
  "companyEmailId": "test@bigship.in",
  "companyMobile": "9876543210",
  "orderCountry": "India",
  "orderState": "GUJARAT",
  "orderCity": "RAJKOT",
  "orderPin": "360024",
  "billingAddress": "TEST ADDRESS LINE 1 - NO ACTUAL LOCATION TEST ADDRESS LINE 2 - DO NOT",
  "billingAddress2": "DISPATCH",
  "landmark": "",
  "consigneeBusinessType": "Company"
},
"consigneeBilling": {
  "companyName": "Test Shipper",
  "companyEmailId": "test@bigship.in",
  "companyMobile": "9876543210",
  "orderCountry": "India",
  "orderState": "GUJARAT",
  "orderCity": "RAJKOT",
  "orderPin": "360024",
  "billingAddress": "TEST ADDRESS LINE 1 - NO ACTUAL LOCATION TEST ADDRESS LINE 2 - DO NOT",
  "billingAddress2": "DISPATCH",
  "landmark": "",
  "consigneeBillingBusinessType": "Company"
}
},
"pickupDetail": {
  "warehouseName": "TEST Kondhwa WAREHOUSE",
  "warehouseContactPerson": "TEST ACCOUNT",
  "warehouseAddressLine1": "TEST ADDRESS LINE 1 - NO ACTUAL LOCATION",
  "warehouseAddressLine2": "TEST ADDRESS LINE 2 - DO NOT DISPATCH",
  "warehouseAddressLandMark": "TEST LANDMARK - IGNORE DELIVERY",
  "warehouseAddressPhone": "9876543210",
  "warehousePin": "411048",
  "warehouseCity": "PUNE",
  "warehouseState": "MAHARASHTRA",
  "warehouseCountry": "India"
},
```

```
"returnWarehouseDetail": null,
"totalInvoiceAmount": "5000.00",
"invoiceCurrency": "₹",
"weight": "32.00",
"weightUnit": "kg",
"box_dimensions": [
  {
    "length": "40",
    "breadth": "27",
    "height": "32",
    "each_box_weight": "32",
    "no_of_box": "1"
  }
],
"dimensions": [
  "40x27x32"
],
"orderDate": "2026-09-11 06:40:00.0000000",
"collectableAmount": "873.00",
"EwaybillNumber": null,
"lr_number": "314752761"
}
}
```

16. API: Download Shipment Documents API

Purpose: This API endpoint is used to download shipment documents of the order like Labels, Manifest, Invoices and EWayBill.

API Request:

- **Method:** GET
- **URL:** `{{url}}/api/outbound/download-shipment-documents`

Request Headers:

- Content-Type: application/json
- Authorization: Bearer Token

Request Body:

The request body should be in JSON format and contain the following parameters:

- **CustomGlobalOrderId (string, required):** A unique identifier for the custom order. This ID is essential for retrieving the relevant shipment details.
- **document_type (string, required):** The type of document. (Eg: invoice, label, ewaybill, manifest)

Sample Request Body:

```
{  
  "CustomGlobalOrderId": "664736461",  
  "document_type": "label" //invoice, label, ewaybill, manifest  
}
```

Response Structure:

The response will be a JSON object containing the following keys:

- **status** (boolean): Indicates whether the request was successful.
- **message** (string): A message providing additional context about the request status (may be empty).
- **status_code** (integer): A code representing the status of the response (200 typically indicates success).
- **data (array):** An array that may contain details of the shipment documents or it can be blank when data is not available.
 - **AttachmentData(string):** The URL of the requested document.
 - **File_extention(string):** MIME Type of the document file.

Response JSON:

1. When document is found:

```
{  
  "status": true,  
  "message": "Order label document downloaded.",  
  "status_code": 200,  
  "data": {  
    "AttachmentData": "https://storage.bigship.direct/files/1773817727\_4983.pdf",  
    "File_extention": "application/pdf"  
  }  
}
```

2. When document does not exist:

```
{  
  "status": false,  
  "message": "Order Ewaybill document not found.",  
  "status_code": 400,  
  "data": ""  
}
```