Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

3173/3195/3196
LEAD WIRE

LEAD WIRE — 600 Volts, 125°C



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class K stranding per ASTM B174.
Size:	#18 AWG – #2 AWG
Insulation:	Extruded cross-linked Polyethylene (XLPE)
Color:	Available in 10 standard colors
Options:	Available with class H stranding per ASTM B173. Available with tinned copper conductors.

APPLICATIONS/INSTALLATION:

Internal wiring of appliances. For use in transformers, motors, ballasts and sollenoids where processing temperatures of the coils and windings does not exceed 160°C.

FEATURES AND BENEFITS:

Temperature rating of 125°C. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and is resistant to moisture, most oils, and chemicals.

APPROVALS:

Insulated Conductor: – UL Appliance wire

Passes UL 44 Horizontal flame test
Type CL 1251
CSA (Specification C22.2, No. 116)
UL (Subject 758)

AWG	STRANDING	INSULATION THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	16/.0100	0.030	0.110	10
16	26/.0100	0.030	0.120	14
14	41/.0100	0.030	0.135	19
12	65/.0100	0.030	0.148	27
10	105/.0100	0.030	0.180	42
8	133/.0113	0.045	0.264	72
6	133/.0142	0.060	0.340	120
4	133/.0179	0.060	0.394	185
2	133/.0226	0.060	0.460	240

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

RHH/RHW-2 USE-2 LEAD WIRE

LEAD WIRE — 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#14 AWG – #2 AWG
Insulation:	Extruded cross-linked Polyethylene (XLPE)
Color:	Available in 10 standard colors
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with tinner copper conductors. Available with VW-1 flame test rating.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, power or control wire in switchboards, lighting or power circuits, or in utility sub-stations or generating plants. The wire is approved for wet or dry locations.

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and is resistant to moisture, most oils, and chemicals.

APPROVALS:

Insulated Conductor: – RHH/RHW-2, USE-2, VW-1 (Optional)

Passes UL 44 Horizontal flame test

Telephone: 800-645-9473 or 717-845-5100 • Fax 717-848-6859

AWG	STRANDING	INSULATION THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
14	7/.0242	0.045	0.165	25
12	7/.0305	0.045	0.185	35
10	7/.0385	0.045	0.205	50
8	7/.0486	0.060	0.235	75
6	7/.0612	0.060	0.305	110
4	7/.0772	0.060	0.355	165
2	7/.0974	0.060	0.415	245

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

SIS
LEAD WIRE

LEAD WIRE — 600 Volts, 90°C Dry



DESCRIPTION:

Conductor:	Tinned, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG** – #2 AWG
Insulation:	Extruded cross-linked Polyethylene (XLPE)
Color:	Available in 10 standard colors
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with VW-1 flame test rating.

APPLICATIONS/INSTALLATION:

For use as a 600 volt wire in switchboards and control panels at 90°C maximum operating temperature in dry locations in accordance with NEC Article 384**

FEATURES AND BENEFITS:

Temperature rating of 90°C dry, 75°C wet. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and is resistant to moisture, most oils, and chemicals.

APPROVALS:

Insulated Conductor: – #18 AWG – #16 AWG UL AWM 3320
#14 AWG – #2 AWG UL TYPE SIS

VW-1 (Optional)

Passes UL 44 Horizontal flame test

**SIS is UL recognized on sizes #14 AWG and larger only

AWG	STRANDING	INSULATION THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18**	7/.0152	0.030	0.110	10
16**	7/.0192	0.030	0.120	14
14	7/.0242	0.030	0.135	19
12	7/.0305	0.030	0.152	27
10	7/.0385	0.030	0.175	42
8	7/.0486	0.045	0.235	72
6	7/.0612	0.045	0.278	101
4	7/.0772	0.045	0.326	146
2	7/.0974	0.045	0.386	232

AWG	STRANDING	INSULATION THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18**	16/.0100	0.030	0.110	10
16**	26/.0100	0.030	0.120	14
14	41/.0100	0.030	0.135	19
12	65/.0100	0.030	0.148	27
10	105/.0100	0.030	0.180	42
8	133/.0113	0.045	0.265	72
6	133/.0142	0.045	0.304	105
4	133/.0179	0.045	0.360	152
2	133/.0226	0.045	0.429	240

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

**UL recognizes TYPE SIS on sizes #14 AWG and larger only.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

XHHW-2
LEAD WIRE

LEAD WIRE — 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B3. Class B stranding per ASTM B8.
Size:	#14 AWG – #2 AWG
Insulation:	Extruded cross-linked Polyethylene (XLPE)
Color:	Available in 10 standard colors
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with tinner copper conductors. Available with VW-1 flame test rating.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, power or control wire in appropriate raceways. The wire is approved for wet or dry locations.

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and is resistant to moisture, most oils, and chemicals.

APPROVALS:

Insulated Conductor: – XHHW-2, VW-1 (Optional)

Passes UL 44 Horizontal flame test

Telephone: 800-645-9473 or 717-845-5100 • Fax 717-848-6859

AWG	STRANDING	INSULATION THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
14	7/.0242	0.030	0.135	19
12	7/.0305	0.030	0.155	28
10	7/.0385	0.030	0.175	41
8	7/.0486	0.045	0.235	69
6	7/.0612	0.045	0.281	103
4	7/.0772	0.045	0.329	155
2	7/.0974	0.045	0.389	237

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

THERMOCOUPLE CABLE
FREP/CPE – EX, JX, KX, TX

INDUSTRIAL TRAY CABLE
EX, JX, KX, TX

600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Thermocouple alloy per ANSI MC 96.1 – 1982.
Size:	#20 AWG – #16 AWG
Insulation:	Extruded flame-retardant ethylene propylene rubber (EPR).
Pair:	Conductors twisted together with a drain wire and aluminum mylar shield.
Cable:	Shielded pairs cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	Pairs are color coded per thermocouple type with pair number printed on the negative (red) conductor. See chart on back for specific color codes.
Jacket:	Black, flame-retardant, sunlight resistant, Chlorinated Polyethylene (CPE).
Options:	Available with class B stranding per ASTM B174. Available with color coded jacket.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi pair thermocouple instrumentation cable where flame-retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−40°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-82-552, 90°C Wet or Dry, 600V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF SHIELDED PAIRS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
20	1	0.025	0.045	0.270	35
20	2	0.025	0.045	0.430	70
20	3	0.025	0.045	0.450	85
20	4	0.025	0.045	0.500	105
20	6	0.025	0.060	0.600	160
20	8	0.025	0.060	0.670	210
20	10	0.025	0.060	0.735	240
20	12	0.025	0.060	0.790	280
20	16	0.025	0.080	0.890	360
20	24	0.025	0.080	1.060	500
18	1	0.025	0.045	0.300	50
18	2	0.025	0.045	0.480	90
18	3	0.025	0.045	0.510	115
18	4	0.025	0.060	0.595	165
18	6	0.025	0.060	0.670	220
18	8	0.025	0.060	0.750	280
18	10	0.025	0.060	0.820	340
18	12	0.025	0.080	0.930	430
18	16	0.025	0.080	1.045	540
18	24	0.025	0.080	1.235	760
16	1	0.025	0.045	0.325	60
16	2	0.025	0.045	0.570	130
16	3	0.025	0.060	0.600	160
16	4	0.025	0.060	0.660	200
16	6	0.025	0.060	0.740	270
16	8	0.025	0.060	0.880	380
16	10	0.025	0.080	0.970	460
16	12	0.025	0.080	1.035	530
16	16	0.025	0.080	1.165	570
16	24	0.025	0.080	1.400	960

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

EX – Color Code	Chromel (Positive) Constantan (Negative)	PURPLE RED	TX – Color Code	Copper (Positive) Constantan (Negative)	BLUE RED
JX – Color Code	Iron (Positive) Constantan (Negative)	WHITE RED	KX – Color Code	Chromel (Positive) Alumel (Negative)	YELLOW RED

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

FREP/CPE SHIELDED TRIADS INSTRUMENTATION CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Tinned, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG – #16 AWG
Insulation:	Extruded flame-retardant ethylene propylene rubber (EPR).
Triad:	Three conductors twisted together with a drain wire and aluminum mylar shield.
Cable:	Shielded triads cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	Triads are black, white and red with the triad number printed on the white conductor.
Jacket:	Flame-retardant, sunlight resistant, Chlorinated Polyethylene (CPE).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with bare copper conductors.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi triad instrumentation cable where flame-retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−40°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-82-552, 90°C Wet or Dry, 600V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

Telephone: 800-645-9473 or 717-845-5100 • Fax 717-848-6859

AWG	NUMBER OF SHIELDED TRIADS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	1	0.025	0.045	0.310	55
18	2	0.025	0.060	0.560	140
18	3	0.025	0.060	0.590	170
18	4	0.025	0.060	0.645	210
18	6	0.025	0.060	0.730	295
18	8	0.025	0.060	0.860	395
18	10	0.025	0.080	0.945	470
18	12	0.025	0.080	1.015	535
18	16	0.025	0.080	1.145	690
18	24	0.025	0.080	1.365	1005
16	1	0.025	0.045	0.340	70
16	2	0.025	0.060	0.620	160
16	3	0.025	0.060	0.655	210
16	4	0.025	0.060	0.720	260
16	6	0.025	0.060	0.815	365
16	8	0.025	0.060	0.960	500
16	10	0.025	0.080	1.055	600
16	12	0.025	0.080	1.135	705
16	16	0.025	0.080	1.285	890
16	24	0.025	0.080	1.540	1310

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

FREP/CPE POWER CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Tinned, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#12 AWG – #2 AWG
Insulation:	Extruded flame-retardant ethylene propylene rubber (EPR).
Cable:	Conductors cabled together with fillers and an uninsulated ground wire, to form a round core.
Color Code:	Per ICEA Method 4.
Jacket:	Flame-retardant, sunlight resistant, Chlorinated Polyethylene (CPE).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with bare copper conductors. Available with copper tape shield. Available with insulated ground wires. Available with E1 or E2 color code.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi conductor power cable where flame-retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−40°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – XHHW-2, VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-68-516, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF CONDUCTORS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
12	2	0.030	0.045	0.405	105
12	3	0.030	0.045	0.430	140
12	4	0.030	0.045	0.470	170
10	2	0.030	0.045	0.455	135
10	3	0.030	0.045	0.480	180
10	4	0.030	0.060	0.560	240
8	2	0.045	0.060	0.600	225
8	3	0.045	0.060	0.635	295
8	4	0.045	0.060	0.700	370
6	2	0.045	0.060	0.685	325
6	3	0.045	0.060	0.730	430
6	4	0.045	0.060	0.800	535
4	2	0.045	0.080	0.785	440
4	3	0.045	0.080	0.875	595
4	4	0.045	0.080	0.965	750
2	2	0.045	0.080	0.950	685
2	3	0.045	0.080	1.015	915
2	4	0.045	0.080	1.115	1155

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

FREP/CPE CONTROL CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Tinned, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#14 AWG – #10 AWG
Insulation:	Extruded flame-retardant ethylene propylene rubber (EPR).
Cable:	Conductors cabled together with fillers as needed to form a round core. A binder tape is applied over the core.
Color Code:	E1 Per ICEA S-73-532 Table E1 (Old K1) E2 Per ICEA S-73-532 Table E2 (Old K2) (See Technical section for color code tables)
Jacket:	Flame-retardant, sunlight resistant, Chlorinated Polyethylene (CPE).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with bare copper conductors. Available with copper tape shield.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi conductor control cable where flame-retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−40°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – XHHW-2, VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-68-516, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF CONDUCTORS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
14*	2	0.030	0.045	.235x.365	70
14	3	0.030	0.045	0.390	85
14	4	0.030	0.045	0.425	105
14	5	0.030	0.045	0.445	125
14	7	0.030	0.045	0.505	175
14	9	0.030	0.060	0.600	230
14	12	0.030	0.060	0.670	295
14	15	0.030	0.060	0.735	360
14	19	0.030	0.060	0.810	440
14	25	0.030	0.080	0.950	600
14	37	0.030	0.080	1.120	840
12*	2	0.030	0.045	.250x.410	95
12	3	0.030	0.045	0.430	120
12	4	0.030	0.045	0.470	150
12	5	0.030	0.045	0.495	180
12	7	0.030	0.060	0.600	250
12	9	0.030	0.060	0.665	320
12	12	0.030	0.060	0.750	410
12	15	0.030	0.060	0.820	490
12	19	0.030	0.080	0.950	660
12	25	0.030	0.080	1.060	840
12	37	0.030	0.080	1.250	1180
10*	2	0.030	0.045	.275x.460	130
10	3	0.030	0.045	0.480	160
10	4	0.030	0.060	0.560	220
10	5	0.030	0.060	0.590	260
10	7	0.030	0.060	0.665	350
10	9	0.030	0.060	0.745	440
10	12	0.030	0.080	0.880	600
10	15	0.030	0.080	0.960	735
10	19	0.030	0.080	1.060	910
10	25	0.030	0.080	1.190	1170
10	37	0.030	0.080	1.410	1680

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

*Flat construction.

Continental WIRE AND CABLE
Moving ahead with revolutionary concepts

FREP/CPE MULTI CONDUCTOR SHIELDED INSTRUMENTATION CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Tinned, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG – #16 AWG
Insulation:	Extruded flame-retardant ethylene propylene rubber (EPR).
Cable:	Conductors cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	E1 Per ICEA S-73-532 Table E1 (Old K1) E2 Per ICEA S-73-532 Table E2 (Old K2) (See Technical section for color code tables)
Jacket:	Flame-retardant, sunlight resistant, Chlorinated Polyethylene (CPE).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with bare copper conductors.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi conductor instrumentation cable where flame-retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−40°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-82-552, 90°C Wet or Dry, 600V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF CONDUCTORS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	2	0.025	0.045	.300	50
18	3	0.025	0.045	.310	55
18	4	0.025	0.045	.335	65
18	5	0.025	0.045	.370	75
18	6	0.025	0.045	.395	90
18	7	0.025	0.045	.405	95
18	9	0.025	0.045	.440	110
18	12	0.025	0.045	.500	140
18	15	0.025	0.060	.590	190
18	19	0.025	0.060	.625	230
16	2	0.025	0.045	.325	60
16	3	0.025	0.045	.340	70
16	4	0.025	0.045	.370	80
16	5	0.025	0.045	.400	95
16	6	0.025	0.045	.425	110
16	7	0.025	0.045	.435	125
16	9	0.025	0.045	.500	155
16	12	0.025	0.060	.600	210
16	15	0.025	0.060	.660	260
16	19	0.025	0.060	.700	310

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

FREP/CPE SHIELDED PAIRS INSTRUMENTATION CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Tinned, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG – #16 AWG
Insulation:	Extruded flame-retardant ethylene propylene rubber (EPR).
Pair:	Conductors twisted together with a drain wire and aluminum mylar shield.
Cable:	Shielded pairs cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	Pairs are black & white with pair number printed on the white conductor.
Jacket:	Flame-retardant, sunlight resistant, Chlorinated Polyethylene (CPE).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with bare copper conductors.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi pair instrumentation cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−40°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-82-552, 90°C Wet or Dry, 600V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF SHIELDED PAIRS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	1	0.025	0.045	0.300	50
18	2	0.025	0.045	0.480	90
18	3	0.025	0.045	0.510	115
18	4	0.025	0.060	0.595	165
18	6	0.025	0.060	0.670	220
18	8	0.025	0.060	0.750	280
18	10	0.025	0.060	0.820	340
18	12	0.025	0.080	0.930	430
18	16	0.025	0.080	1.045	540
18	24	0.025	0.080	1.235	760
16	1	0.025	0.045	0.325	60
16	2	0.025	0.060	0.570	130
16	3	0.025	0.060	0.600	160
16	4	0.025	0.060	0.660	200
16	6	0.025	0.060	0.740	270
16	8	0.025	0.060	0.880	380
16	10	0.025	0.080	0.970	460
16	12	0.025	0.080	1.035	530
16	16	0.025	0.080	1.165	570
16	24	0.025	0.080	1.400	960

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

THERMOCOUPLE CABLE
XLP/PVC – EX, JX, KX, TX

INDUSTRIAL TRAY CABLE
EX, JX, KX, TX

600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Thermocouple alloy per ANSI MC 96.1 – 1982.
Size:	#20 AWG – #16 AWG
Insulation:	Extruded flame-retardant cross-linked polyolefin (XLP).
Pair:	Conductors twisted together with a drain wire and aluminum mylar shield.
Cable:	Shielded pairs cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	Pairs are color coded per thermocouple type with pair number printed on the negative (red) conductor. See chart on back for specific color codes.
Jacket:	Black, flame-retardant, sunlight resistant, Polyvinyl Chloride (PVC).
Options:	Available with class B stranding per ASTM B174. Available with color coded jacket.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi pair thermocouple instrumentation cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−25°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)

ICEA S-66-524, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 383 Flame Test (70,000 BTU/hr)

AWG	NUMBER OF SHIELDED PAIRS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
20	1	0.025	0.045	0.270	35
20	2	0.025	0.045	0.430	70
20	3	0.025	0.045	0.450	85
20	4	0.025	0.045	0.500	105
20	6	0.025	0.060	0.600	160
20	8	0.025	0.060	0.670	210
20	10	0.025	0.060	0.735	240
20	12	0.025	0.060	0.790	280
20	16	0.025	0.080	0.890	360
20	24	0.025	0.080	1.060	500
18	1	0.025	0.045	0.300	50
18	2	0.025	0.045	0.480	90
18	3	0.025	0.045	0.510	115
18	4	0.025	0.060	0.595	165
18	6	0.025	0.060	0.670	220
18	8	0.025	0.060	0.750	280
18	10	0.025	0.060	0.820	340
18	12	0.025	0.080	0.930	430
18	16	0.025	0.080	1.045	540
18	24	0.025	0.080	1.235	760
16	1	0.025	0.045	0.325	60
16	2	0.025	0.045	0.570	130
16	3	0.025	0.060	0.600	160
16	4	0.025	0.060	0.660	200
16	6	0.025	0.060	0.740	270
16	8	0.025	0.060	0.880	380
16	10	0.025	0.080	0.970	460
16	12	0.025	0.080	1.035	530
16	16	0.025	0.080	1.165	570
16	24	0.025	0.080	1.400	960

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

EX – Color Code	Chromel (Positive) Constantan (Negative)	PURPLE RED	TX – Color Code	Copper (Positive) Constantan (Negative)	BLUE RED
JX – Color Code	Iron (Positive) Constantan (Negative)	WHITE RED	KX – Color Code	Chromel (Positive) Alumel (Negative)	YELLOW RED

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

XLP/PVC POWER CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#12 AWG – #2 AWG
Insulation:	Extruded flame-retardant cross-linked polyolefin (XLP).
Cable:	Conductors cabled together with fillers and an uninsulated ground wire, to form a round core.
Color Code:	Per ICEA Method 4.
Jacket:	Flame-retardant, sunlight resistant, Polyvinyl Chloride (PVC).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with tinned copper conductors. Available with copper tape shield. Available with insulated ground wires. Available with E1 or E2 color code.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi conductor power cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−25°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – XHHW-2, VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-66-524, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF CONDUCTORS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
12	2	0.030	0.045	0.405	105
12	3	0.030	0.045	0.430	140
12	4	0.030	0.045	0.470	170
10	2	0.030	0.045	0.455	135
10	3	0.030	0.045	0.480	180
10	4	0.030	0.060	0.560	240
8	2	0.045	0.060	0.600	225
8	3	0.045	0.060	0.635	295
8	4	0.045	0.060	0.700	370
6	2	0.045	0.060	0.685	325
6	3	0.045	0.060	0.730	430
6	4	0.045	0.060	0.800	535
4	2	0.045	0.080	0.785	440
4	3	0.045	0.080	0.875	595
4	4	0.045	0.080	0.965	750
2	2	0.045	0.080	0.950	685
2	3	0.045	0.080	1.015	915
2	4	0.045	0.080	1.115	1155

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

XLP/PVC CONTROL CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#14 AWG – #10 AWG
Insulation:	Extruded flame-retardant cross-linked polyolefin (XLP).
Cable:	Conductors cabled together with fillers as needed to form a round core. A binder tape is applied over the core.
Color Code:	E1 Per ICEA S-73-532 Table E1 (Old K1) E2 Per ICEA S-73-532 Table E2 (Old K2) (See Technical section for color code tables)
Jacket:	Flame-retardant, sunlight resistant, Polyvinyl Chloride (PVC).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with tinned copper conductors. Available with copper tape shield.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi conductor control cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−25°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – XHHW-2, VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-66-524, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF CONDUCTORS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
14*	2	0.030	0.045	.235x.365	70
14	3	0.030	0.045	0.390	85
14	4	0.030	0.045	0.425	105
14	5	0.030	0.045	0.445	125
14	7	0.030	0.045	0.505	175
14	9	0.030	0.060	0.600	230
14	12	0.030	0.060	0.670	295
14	15	0.030	0.060	0.735	360
14	19	0.030	0.060	0.810	440
14	25	0.030	0.080	0.950	600
14	37	0.030	0.080	1.120	840
12*	2	0.030	0.045	.250x.410	95
12	3	0.030	0.045	0.430	120
12	4	0.030	0.045	0.470	150
12	5	0.030	0.045	0.495	180
12	7	0.030	0.060	0.600	250
12	9	0.030	0.060	0.665	320
12	12	0.030	0.060	0.750	410
12	15	0.030	0.060	0.820	490
12	19	0.030	0.080	0.950	660
12	25	0.030	0.080	1.060	840
12	37	0.030	0.080	1.250	1180
10*	2	0.030	0.045	.275x.460	130
10	3	0.030	0.045	0.480	160
10	4	0.030	0.060	0.560	220
10	5	0.030	0.060	0.590	260
10	7	0.030	0.060	0.665	350
10	9	0.030	0.060	0.745	440
10	12	0.030	0.080	0.880	600
10	15	0.030	0.080	0.960	735
10	19	0.030	0.080	1.060	910
10	25	0.030	0.080	1.190	1170
10	37	0.030	0.080	1.410	1680

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

*Flat construction.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

XLP/PVC MULTI CONDUCTOR SHIELDED INSTRUMENTATION CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG – #16 AWG
Insulation:	Extruded flame-retardant cross-linked polyolefin (XLP).
Cable:	Conductors cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	E1 Per ICEA S-73-532 Table E1 (Old K1) E2 Per ICEA S-73-532 Table E2 (Old K2) (See Technical section for color code tables)
Jacket:	Flame-retardant, sunlight resistant, Polyvinyl Chloride (PVC).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with tinned copper conductors.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi conductor instrumentation cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−25°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-66-524, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF CONDUCTORS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	2	0.025	0.045	.300	50
18	3	0.025	0.045	.310	55
18	4	0.025	0.045	.335	65
18	5	0.025	0.045	.370	75
18	6	0.025	0.045	.395	90
18	7	0.025	0.045	.405	95
18	9	0.025	0.045	.440	110
18	12	0.025	0.045	.500	140
18	15	0.025	0.060	.590	190
18	19	0.025	0.060	.625	230
16	2	0.025	0.045	.325	60
16	3	0.025	0.045	.340	70
16	4	0.025	0.045	.370	80
16	5	0.025	0.045	.400	95
16	6	0.025	0.045	.425	110
16	7	0.025	0.045	.435	125
16	9	0.025	0.045	.500	155
16	12	0.025	0.060	.600	210
16	15	0.025	0.060	.660	260
16	19	0.025	0.060	.700	310

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

XLP/PVC SHIELDED TRIAD INSTRUMENTATION CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG – #16 AWG
Insulation:	Extruded flame-retardant cross-linked polyolefin (XLP).
Triad:	Three conductors twisted together with a drain wire and aluminum mylar shield.
Cable:	Shielded triads cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	Triads are black, white and red with the triad number printed on the white conductor.
Jacket:	Flame-retardant, sunlight resistant, Polyvinyl Chloride (PVC).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with tinned copper conductors.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi triad instrumentation cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−25°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-66-524, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

Telephone: 800-645-9473 or 717-845-5100 • Fax 717-848-6859

AWG	NUMBER OF SHIELDED TRIADS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	1	0.025	0.045	0.310	55
18	2	0.025	0.060	0.560	140
18	3	0.025	0.060	0.590	170
18	4	0.025	0.060	0.645	210
18	6	0.025	0.060	0.730	295
18	8	0.025	0.060	0.860	395
18	10	0.025	0.080	0.945	470
18	12	0.025	0.080	1.015	535
18	16	0.025	0.080	1.145	690
18	24	0.025	0.080	1.365	1005
16	1	0.025	0.045	0.340	70
16	2	0.025	0.060	0.620	160
16	3	0.025	0.060	0.655	210
16	4	0.025	0.060	0.720	260
16	6	0.025	0.060	0.815	365
16	8	0.025	0.060	0.960	500
16	10	0.025	0.080	1.055	600
16	12	0.025	0.080	1.135	705
16	16	0.025	0.080	1.285	890
16	24	0.025	0.080	1.540	1310

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Continental
WIRE AND CABLE
Moving ahead with revolutionary concepts

XLP/PVC SHIELDED PAIRS INSTRUMENTATION CABLE

INDUSTRIAL TRAY CABLE 600 Volts, 90°C Wet or Dry



DESCRIPTION:

Conductor:	Bare, annealed copper per ASTM B33. Class B stranding per ASTM B8.
Size:	#18 AWG – #16 AWG
Insulation:	Extruded flame-retardant cross-linked polyolefin (XLP).
Pair:	Conductors twisted together with a drain wire and aluminum mylar shield.
Cable:	Shielded pairs cabled together with fillers as needed to form a round core. An overall aluminum mylar shield and drain wire is applied over the core.
Color Code:	Pairs are black & white with pair number printed on the white conductor.
Jacket:	Flame-retardant, sunlight resistant, Polyvinyl Chloride (PVC).
Options:	Available with class K stranding per ASTM B174. Available with class H stranding per ASTM B173. Available with bare copper conductors.

APPLICATIONS/INSTALLATION:

For use as a 600 volt, multi pair instrumentation cable where flame retardance, and moisture/chemical resistance is critical. Cable can be installed in free air, in raceways or direct burial. The cable is also approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC 501-4(b) for (UL) Type tray cables (TC).

FEATURES AND BENEFITS:

Temperature rating of 90°C wet or dry. Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance and resistant to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (−25°C) cold bend characteristics.

APPROVALS:

Insulated Conductor: – VW-1

Cable: – Direct Burial

UL Type TC, 90°C Wet or Dry, 600V
Passes UL 1277 Flame Test (70,000 BTU/hr)
Passes IEEE 383 Flame Test (70,000 BTU/hr)

ICEA S-66-524, 90°C Wet or Dry, 600V & 1000V
Passes IEEE 1202 Flame Test (70,000 BTU/hr)
Passes ICEA T-29-520 Flame Test (210,000 BTU/hr)

AWG	NUMBER OF SHIELDED PAIRS	INSULATION THICKNESS	JACKET THICKNESS	OVERALL DIAMETER	WEIGHT LBS/1000 FT
18	1	0.025	0.045	0.300	50
18	2	0.025	0.045	0.480	90
18	3	0.025	0.045	0.510	115
18	4	0.025	0.060	0.595	165
18	6	0.025	0.060	0.670	220
18	8	0.025	0.060	0.750	280
18	10	0.025	0.060	0.820	340
18	12	0.025	0.080	0.930	430
18	16	0.025	0.080	1.045	540
18	24	0.025	0.080	1.235	760
16	1	0.025	0.045	0.325	60
16	2	0.025	0.060	0.570	130
16	3	0.025	0.060	0.600	160
16	4	0.025	0.060	0.660	200
16	6	0.025	0.060	0.740	270
16	8	0.025	0.060	0.880	380
16	10	0.025	0.080	0.970	460
16	12	0.025	0.080	1.035	530
16	16	0.025	0.080	1.165	570
16	24	0.025	0.080	1.400	960

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

Table E-1 *(formerly K-1)*
COLOR SEQUENCE INCLUDING WHITE AND GREEN

CONDUCTOR NUMBER	BACKGROUND OR BASE COLOR	FIRST TRACER COLOR	SECOND TRACER COLOR	CONDUCTOR NUMBER	BACKGROUND OR BASE COLOR	FIRST TRACER COLOR	SECOND TRACER COLOR
1*	Black	—	—	20	Red	Green	—
2	White	—	—	21	Orange	Green	—
3	Red	—	—	22	Black	White	Red
4	Green	—	—	23	White	Black	Red
5	Orange	—	—	24	Red	Black	White
6	Blue	—	—	25	Green	Black	White
7	White	Black	—	26	Orange	Black	White
8	Red	Black	—	27	Blue	Black	White
9	Green	Black	—	28	Black	Red	Green
10	Orange	Black	—	29	White	Red	Green
11	Blue	Black	—	30	Red	Black	Green
12	Black	White	—	31	Green	Black	Orange
13	Red	White	—	32	Orange	Black	Green
14	Green	White	—	33	Blue	White	Orange
15	Blue	White	—	34	Black	White	Orange
16	Black	Red	—	35	White	Red	Orange
17	White	Red	—	36	Orange	White	Blue
18	Orange	Red	—	37	White	Red	Blue
19	Blue	Red	—				

* This conductor is on the inside of the assembly.

Table E-2 *(formerly K-2)*
COLOR SEQUENCE WITHOUT WHITE AND GREEN

CONDUCTOR NUMBER	BACKGROUND OR BASE COLOR	TRACER COLOR	CONDUCTOR NUMBER	BACKGROUND OR BASE COLOR	TRACER COLOR
1*	Black	—	19	Orange	Blue
2	Red	—	20	Yellow	Blue
3	Blue	—	21	Brown	Blue
4	Orange	—	22	Black	Orange
5	Yellow	—	23	Red	Orange
6	Brown	—	24	Blue	Orange
7	Red	Black	25	Yellow	Orange
8	Blue	Black	26	Brown	Orange
9	Orange	Black	27	Black	Yellow
10	Yellow	Black	28	Red	Yellow
11	Brown	Black	29	Blue	Yellow
12	Black	Red	30	Orange	Yellow
13	Blue	Red	31	Brown	Yellow
14	Orange	Red	32	Black	Brown
15	Yellow	Red	33	Red	Brown
16	Brown	Red	34	Blue	Brown
17	Black	Blue	35	Orange	Brown
18	Red	Blue	36	Yellow	Brown

* This conductor is on the inside of the assembly.
NOTE: See E2 for National Electrical Code applications.
For sequence counts higher than 36 the color code repeats.