ADVANCED DIGITAL CABLE INC.

Product Data Sheet

94 Eagle Fork Rd Hayesville, NC 28904
Ph: 800.343.2579 Fax: 828.389.3922

Part Number: **9912DB**

Description: **75 OHM RG 59/U With one pair 18 awg overall Direct Burial PVC jacket**

Application: **Video Cable**

Construction Details Component A:

Awg	20
Stranding	Solid
Conductor Material	Bare copper
Insulation Material	Gas injected foam polyethylene
Insulation/Dielectric Thickness	.057”
Nominal Insulation Diameter	.145”
Braid Material	Bare Copper
Braid Coverage	95%

Construction Details Component B:

Conductors	2
AWG	18
Stranding	7 strand
Conductor Material	Bare copper
Insulation Material	Polyvinylchloride
Nominal Diameter	.066
Color Code	Black, White
Cabling Lay	2 1/2” left hand lay
Nominal Cabling Diameter	.132

Final Jacket Details:

Final Jacket Material	Direct Burial Polyvinylchloride
Nominal Thickness	.034” Coax, .028” Pair
Jacket Color	Black
Nominal Jacket Diameter	.237”x.427”

INKJET PRINT:

1C/20 AWG RG 59/U 2C/18AWG TYPE CL2 OR CM (ETL)us 3054335 DIR BUR SUN RES

Nominal Attenuation:

Impedance:	75 Ohms
Capacitance	16.3 pF/foot
Velocity of Prop	78%

Frequency	Db/100ft
5	.75
55	1.84
211	3.36
400	4.66
700	6.28
900	7.14
1000	7.68

Applicable Standards:

ETL Type	CL2,CM
ROHS Compliant	Yes

Customer Name: _____Date Signed: _____

Customer Approval: _____

Specification Issue Date: 6/22/12