Advanced Digital Cable, Inc.	Specification Sheet for RG 6/U with 60% braid, moisture block tape, and PE jacket.	Date:	1/14/02
		Part Number:	4061FPE
Drawn by:	Customer Approval:	UL Type:	None

Construction Details:

This cable is constructed with a core composed of an 18 awg copper clad steel center conductor insulated with foamed polyethylene. The core is shielded with a bonded aluminum/polyester/aluminum moisture inhibiting tape wrap and a 60% coverage aluminum braid. A black weather resistant polyethylene jacket completes the package.

Physical Specifications

Conductors: 1 – 18 awg copper clad steel .040”

Dielectric: 70 mil wall of foamed polyethylene to a nominal diameter of .180”.

Shield: Bonded Aluminum / polyester / aluminum tape wrap with dry moisture inhibiting coating for 100% shielding.

Braid: 34 awg aluminum braid with 60% coverage.

Jacket: 30 mil wall of black weather resistant polyethylene to a nominal diameter of .270”

Print: White ink **:**
WEATHER-TITE RG 6/U 18 AWG DIRECT BURIAL

Put Up: Reels or boxes per customer specification.

Electrical Specifications

Nominal Attenuation

MHz	dB/100 feet
1	.26
10	.80
50	1.46
100	2.05
200	2.83
400	4.15
700	5.60
900	6.25
1000	6.70

Impedance: 75 Ohms

Capacitance: 16.2 pF/foot

Velocity of Prop.: 82%