ADVANCED DIGITAL CABLE INC.

Product Data Sheet

94 Eagle Fork Rd Hayesville, NC 28904
Ph: 800.343.2579 Fax: 828.389.3922

Part Number: **914**

Description: **High Flex GTO-15 14 awg integral sleeve with a PVC core and PVC jacket**

Suitable Application: **Gas Tube Sign Cable**

Construction Details:

Total Number Conductors	1
Awg	14
Stranding	19 Strand
Conductor Material	Bare copper
Insulation Material	PVC Mixture
Insulation/Dielectric Thickness	.049”
Nominal Insulation Diameter	.170”
Color Code	Black
Final Jacket Material	PVC Mixture
Nominal Thickness	.045”
Jacket Color	Black
Nominal Jacket Diameter	.260”

Print

Printed in white ink	Yes
Sequential foot marks on jacket	Yes

Print Legend:

HIGH FLEX GTO-15 15,000V 105°C 14 AWG (UL) OR c(UL) GTO-15 15,000V 105°C 14 AWG E201474

Operating voltage	15000v

Applicable Standards:

UL Type	GTO, UL 814
ROHS Compliant	Yes

Customer Name: _____Date Signed: _____

Customer Approval: _____

Specification Issue Date: 1/24/12