9/3/2014 REV. 1

TECHNICAL DATA SHEET

47337AS

I. DESCRIPTION:

TYPE TC: 2 CONDUCTORS - 16(7X) AWG BARE CU CONDUCTORS WITH PVC-NYLON INSULATION, OVERALL BELDFOIL® SHIELD WITH DRAIN, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	4.2 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	8 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C DRY, 75C WET
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL:	PVC, SUN RES, DIR BUR
SHIELD TYPE - COVERAGE:	OVERALL BELDFOIL® SHIELD WITH DRAIN - 100%
NOMINAL OVERALL DIAMETER:	0.3"
MINIMUM BEND RADIUS:	3"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	40 LBS.
ESTIMATED CABLE WEIGHT:	51 LBS/1000 FT
COLOR CODE:	ICEA METHOD 1, Table E1
APPLICABLE SPECIFICATION(S):	NEC TYPE TC (UL1277)
FLAME RATING(S):	UL 1685, CSA FT4, IEEE 1202

OTHER:

© 2014 Belden, Inc. All Rights Reserved.
Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications