11/29/2011

TECHNICAL DATA SHEET

123090A

I. DESCRIPTION:

TYPE MC: 1 PAIRS - 16(7X) AWG BARE CU CONDUCTORS WITH PVC-NYLON INSULATION, OVERALL BELDFOIL® SHIELD WITH DRAIN, FILLER AS REQUIRED, PVC JACKET, OVERALL ALUMINUM INTERLOCKED ARMOR AND PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	4.2 OHMS/1000'

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C DRY, 75C WET
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL:	PVC, SUN RES, BURIAL
SHIELD TYPE - COVERAGE:	OVERALL BELDFOIL® SHIELD WITH DRAIN - 100%
NOMINAL OVERALL DIAMETER:	0.64"
MINIMUM BEND RADIUS:	7.6"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	40 LBS.
COLOR CODE:	BLACK & WHITE, NUMBERED
APPLICABLE SPECIFICATION(S):	NEC TYPE MC (UL1569)
FLAME RATING(S):	UL 1685, CSA FT4, IEEE 1202

AN OVERALL ALUMINUM INTERLOCKED ARMOR AND PVC JACKET ARE APPLIED OVER THE BELDEN CORE.

DIAMETER OF CORE:	0.290”
DIAMETER OVER ARMOR:	0.510”
DIAMETER OVER JACKET:	0.640”

© 2011 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.