10/12/2010

TECHNICAL DATA SHEET

121055A

I. DESCRIPTION:

TYPE MC: 2 PAIRS - 16(7X) AWG BARE CU CONDUCTORS WITH PVC-NYLON INSULATION, INDIVIDUAL & OVERALL BELDFOIL® SHIELDS WITH DRAINS, FILLER AS REQUIRED, PVC JACKET, OVERALL ALUMINUM INTERLOCKED ARMOR AND PVC JACKET

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	4.2 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	6.4 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C DRY, 75C WET
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL:	PVC, SUN RES
SHIELD TYPE - COVERAGE:	INDIVIDUAL & OVERALL BELDFOIL® SHIELDS WITH DRAINS - 100%/100%
NOMINAL OVERALL DIAMETER:	SEE BELOW
MINIMUM BEND RADIUS OF CORE:	4.7"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	81 LBS.
COLOR CODE:	ICEA METHOD 1, Table E1
APPLICABLE SPECIFICATION(S):	NEC TYPE TC (UL1277)
FLAME RATING(S):	UL 1685, CSA FT4, IEEE 1202

AN OVERALL ALUMINUM INTERLOCKED ARMOR AND PVC JACKET ARE APPLIED OVER THE BELDEN CORE.

DIAMETER OF CORE:	0.466"
DIAMETER OVER ARMOR:	0.666"
DIAMETER OVER JACKET:	0.776"

© 2012 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

peng: dob