6/22/2012 REV. 1

TECHNICAL DATA SHEET

48643AZ

I. DESCRIPTION:

TYPE TC-ER: 2 CONDUCTORS PLUS INSULATED GROUND - 10(7X) AWG BARE CU CONDUCTORS WITH PVC-NYLON INSULATION, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	1.04 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	40 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C DRY, 75C WET
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL:	PVC, SUN RES
SHIELD TYPE - COVERAGE:	NONE
NOMINAL OVERALL DIAMETER:	0.447"
MINIMUM BEND RADIUS:	4.4"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	166 LBS.
ESTIMATED CABLE WEIGHT:	162 LBS/1000 FT
COLOR CODE:	BLACK, WHITE, GREEN
APPLICABLE SPECIFICATION(S):	NEC TYPE TC-ER (UL1277)
FLAME RATING(S):	UL 1685 VERTICAL TRAY

OTHER:

© 2012 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
peng: dob