07/07/2010

TECHNICAL DATA SHEET

28150AC

I. DESCRIPTION:

TYPE TC-ER: 3 CONDUCTORS - 8(7X) AWG BARE CU CONDUCTORS WITH PVC-NYLON INSULATION, OVERALL 5-MIL CORRUGATED COPPER TAPE SHIELD, 10 AWG BARE COPPER GROUND, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	0.64 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	55 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C DRY, 75C WET
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL:	PVC, SUN RES, DIR BUR
SHIELD TYPE - COVERAGE:	CORRUGATED COPPER TAPE - 100%
NOMINAL OVERALL DIAMETER:	.666"
MINIMUM BEND RADIUS:	8.0"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	399 LBS.
ESTIMATED CABLE WEIGHT:	337 LB/1000 FT
COLOR CODE:	ICEA METHOD 4 (BLK / #)
APPLICABLE SPECIFICATION(S):	NEC TYPE TC-ER (UL1277)
FLAME RATING(S):	UL 1685 VERTICAL TRAY

OTHER:

© 2009 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.