07/07/2010

TECHNICAL DATA SHEET

28085C

I. DESCRIPTION:

TYPE TC-ER: 7 CONDUCTORS - 14(7X) AWG BARE CU CONDUCTORS WITH XLPE INSULATION, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	2.52 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	12.5 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C WET OR DRY
INSULATION MATERIAL:	XLPE
JACKET MATERIAL:	PVC, SUN RES, DIR BUR
SHIELD TYPE - COVERAGE:	NONE
NOMINAL OVERALL DIAMETER:	0.5"
MINIMUM BEND RADIUS:	5"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	225 LBS.
ESTIMATED CABLE WEIGHT:	173 LB/1000 FT
COLOR CODE:	ICEA METHOD 1, Table E2
APPLICABLE SPECIFICATION(S):	NEC TYPE TC-ER (UL1277)
FLAME RATING(S):	UL 1685 VERTICAL TRAY

OTHER:

© 2009 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.