8/13/2012

TECHNICAL DATA SHEET

28153C

I. DESCRIPTION:

TYPE TC-ER: 3 CONDUCTORS - 6(7X) AWG BARE CU CONDUCTORS WITH XLP INSULATION, BARE GROUND, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	0.41 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	75 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C WET OR DRY
INSULATION MATERIAL:	XLP
JACKET MATERIAL:	PVC, SUN RES
SHIELD TYPE - COVERAGE:	NONE
NOMINAL OVERALL DIAMETER:	0.71"
MINIMUM BEND RADIUS:	7.1"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	792 LBS.
ESTIMATED CABLE WEIGHT:	386 LBS/1000 FT
COLOR CODE:	ICEA METHOD 4 (BLK / #)
APPLICABLE SPECIFICATION(S):	NEC TYPE TC-ER (UL1277)
FLAME RATING(S):	UL 1685 VERTICAL TRAY

BELDEN 28153C E64067-G 3/C #6 + 1/C #8 GROUND 600V TYPE TC-ER (UL) XLPE/PVC XHHW-2 CDRS 90C DRY/WET SUN RES DIR BUR --- FT4 IEEE 1202 CANADA ROHS {DATE} {COUNTER} FT

© 2011 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.