BELDEN
SENDING ALL THE RIGHT SIGNALS

Technical
Data Sheet

02-11-10 REV. 0

27643AS

I. DESCRIPTION:

TRAY CABLE - 10 AWG (7 X #18H) BARE COPPER, 2 CONDUCTOR, PVC/NYLON INSULATION, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 V RMS
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	40 A
NOM. CONDUCTOR DC RESISTANCE @ 20 DEG. C:	1.04 OHMS/1000 FT

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30 TO(+90C DRY,+75C WET)
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL (COLOR):	PVC (BLACK), SUNLIGHT RESISTANT, DIRECT BURIAL
MAX. PULL TENSION:	166 LBS. ESTIMATED
NOM. DIAMETER:	.432" ESTIMATED
MIN. BEND RADIUS:	4.40" ESTIMATED
NOM. WEIGHT/1000 FT.:	131 LBS. ESTIMATED
APPLICABLE SPECIFICATION:	UL SUBJECT 1277 (UL TYPE TC)
COLOR CODE:	ICEA METHOD 1 - E2
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY FT4 IEEE 1202

© 2010 Belden Wire & Cable Company All Rights Reserved.
Although Belden Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.