1/27/2011

TECHNICAL DATA SHEET

31P1601

I. DESCRIPTION:

TYPE PLTC: 1 PAIRS - 16(7X) AWG BARE CU CONDUCTORS WITH PVC INSULATION, OVERALL BELDFOIL® SHIELD WITH DRAIN, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	300 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20℃:	4.2 OHMS/1000'

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 105C
INSULATION MATERIAL:	PVC
JACKET MATERIAL:	PVC, SUN RES
SHIELD TYPE - COVERAGE:	OVERALL BELDFOIL® SHIELD WITH DRAIN - 100%
NOMINAL OVERALL DIAMETER:	0.26"
MINIMUM BEND RADIUS:	2.7"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	40 LBS.
ESTIMATED CABLE WEIGHT:	43 LB/1000 FT
COLOR CODE:	ICEA METHOD 1, Table E1
APPLICABLE SPECIFICATION(S):	NEC TYPE PLTC (UL13)
FLAME RATING(S):	UL 1685, CSA FT4, IEEE 1202

OTHER:

© 2009 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.