4/29/2011

# TECHNICAL DATA SHEET

## YM57790 LINE 51

I. DESCRIPTION:

TYPE PLTC: 24 PAIRS - 16(7X) AWG BARE CU CONDUCTORS WITH PVC INSULATION, INDIVIDUAL & OVERALL BELDFOIL® SHIELDS WITH DRAINS, FILLER AS REQUIRED, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

| | |
|---|---|
| MAX. OPERATING VOLTAGE: | 300 VOLTS RMS |
| NOM. CONDUCTOR DC RESISTANCE @ 20°C: | 4.2 OHMS/1000' |

III. PHYSICAL CHARACTERISTICS:

| | |
|---|---|
| TEMPERATURE RATING: | -30C TO 105C |
| INSULATION MATERIAL: | PVC |
| JACKET MATERIAL: | PVC, SUN RES, DIR BUR |
| SHIELD TYPE - COVERAGE: | INDIVIDUAL & OVERALL BELDFOIL® SHIELDS WITH DRAINS - 100%/100% |
| NOMINAL OVERALL DIAMETER: | 1.18" |
| MINIMUM BEND RADIUS: | 11.8" |
| MAXIMUM PULLING TENSION (CONDUCTORS ONLY): | 970 LBS. |
| ESTIMATED CABLE WEIGHT: | 881 LBS/1000 FT |
| COLOR CODE: | ICEA METHOD 1, Table E1 |
| APPLICABLE SPECIFICATION(S): | NEC TYPE PLTC (UL13) |
| FLAME RATING(S): | UL 1685 VERTICAL TRAY |

OTHER:

© 2011 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.