07/06/2010

TECHNICAL DATA SHEET

61P1602

I. DESCRIPTION:

TYPE TC: 2 PAIRS - 16(7X) AWG BARE CU CONDUCTORS WITH PVC-NYLON INSULATION, OVERALL BELDFOIL® SHIELD WITH DRAIN, PVC JACKET.

II. ELECTRICAL CHARACTERISTICS:

MAX. OPERATING VOLTAGE:	600 VOLTS RMS
NOM. CONDUCTOR DC RESISTANCE @ 20°C:	4.2 OHMS/1000'
MAX. CONTINUOUS CURRENT PER CONDUCTOR @ 30°C:	6.4 AMPS

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-30C TO 90C DRY, 75C WET
INSULATION MATERIAL:	PVC-NYLON
JACKET MATERIAL:	PVC, SUN RES, DIR BUR
SHIELD TYPE - COVERAGE:	OVERALL BELDFOIL® SHIELD WITH DRAIN - 100%
NOMINAL OVERALL DIAMETER:	0.45"
MINIMUM BEND RADIUS:	4.5"
MAXIMUM PULLING TENSION (CONDUCTORS ONLY):	81 LBS.
ESTIMATED CABLE WEIGHT:	86 LB/1000 FT
COLOR CODE:	ICEA METHOD 1, Table E1
APPLICABLE SPECIFICATION(S):	NEC TYPE TC (UL1277)
FLAME RATING(S):	UL 1685, CSA FT4, IEEE 1202

OTHER:

© 2009 Belden Wire & Cable Company All Rights Reserved.
Although Belden Americas Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.