
Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION

31P1801 Multi-Conductor - 300V Power-Limited Tray Cable



For more Information
please call

1-800-Belden1

Description

18 AWG pairs stranded (7x26) bare copper conductors, twisted pairs, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	18	7x26	BC - Bare Copper	0.047

Total Number of Conductors	2

Insulation:

Insulation Material

Insulation Material
PVC - Polyvinyl Chloride

Outer Shield:

Outer Shield Material

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Jacket:

Outer Jacket Material

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.037

Outer Jacket Ripcord	Yes

Overall Cable:

Overall Nominal Diameter:	0.233 in.

Pair:

Pair Color Code Chart

Number	Color
1	Black & White

Mechanical Characteristics (Overall):

Operating Temperature Range	-30°C To +105°C
Bulk Cable Weight:	32.500 lbs/1000 ft.
Max. Recommended Pulling Tension:	67.200 lbs.
Min. Bend Radius/Minor Axis:	2.300 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards & Environmental Programs:

NEC/(UL) Specification	ITC, PLTC
CEC/C(UL) Specification	CMG
AWM Specification	UL Style 2464 (300 V 80°C)

EU Directive 2011/65/EU (ROHS II)	Yes
EU CE Mark	Yes
EU Directive 2000/53/EC (ELV)	Yes
EU Directive 2002/95/EC (RoHS)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	04/01/2005
EU Directive 2002/96/EC (WEEE)	Yes
EU Directive 2003/11/EC (BFR)	Yes
CA Prop 65 (CJ for Wire & Cable)	Yes
MII Order #39 (China RoHS)	Yes

Flame Test:

UL Flame Test	UL1685 FT4 Loading
CSA Flame Test	FT4
IEEE Flame Test	1202

Suitability:

Suitability - Burial	No
Sunlight Resistance	Yes

Plenum/Non-Plenum:

Plenum (Y/N)	No

Electrical Characteristics (Overall):

Nom. Inductance

Inductance (µH/ft)
0.190

Nom. Capacitance Conductor to Conductor

Capacitance (pF/ft)
51.000

Nom. Capacitance Cond. to Other Conductor & Shield

Capacitance (pF/ft)
95.000

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
5.860

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
5.070

Max. Operating Voltage - UL

Voltage
300 V RMS

Max. Recommended Current

Current
8 Amps per conductor @ 25°C

Notes (Overall):

Notes Alternate color coding available upon request.

Revision Number: 0 Revision Date: 08-18-2016

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect,

incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.
All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor’s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden’s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.