1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192


PRODUCT DATA SHEET

Controlled Document - Engineering Drive

Royal® Diesel Locomotive (DLO)

2000V Type DLO, UL 2000V Type RHH/RHW-2, CSA 1000V Type RW90

Construction Parameters:



CONDUCTOR: 8 AWG - 1111.1 kcmil stranded tin copper
Flexible, fully annealed, Class I, tin-coated, copper
in accordance with AAR 585. Bare Copper available on request.

INSULATION: Premium Grade, lead free, Ethylene Propylene Rubber (EP)

JACKET: Lead free, Chlorinated Polyethylene (CPE)
JACKET COLOR: Black
Other jacket colors available upon request.

PRINT LEGENDS:

8 AWG - 1 AWG: CCI ROYAL XX AWG (XX.Xmm^2) DLO 90C 2000V -- E137925 (UL) RHH/RHW-2 90C 2000V SUN RES VW-1 -40C PRI PRII - - 156016 CSA RW90 90C DRY 90C WET 1000V PRI PRII SR -40C FT1

1/0 AWG - 1111.0 KCMIL: CCI ROYAL XX AWG (XX.Xmm^2) DLO 90C 2000V -- E137925 (UL) RHH/RHW-2 90C 2000V SUN RES VW-1 -40C PRI PRII FOR CT USE - - 156016 CSA RW90 90C DRY 90C WET 1000V PRI PRII SR -40C FT1 FT4/IEEE 1202

INDENT PRINT: (all sizes) P-07-KA100013-MSHA

PHYSICAL PROPERTIES:
TEMPERATURE RANGE: -40°C to 90°C Dry, 90C Wet

ELECTRICAL PROPERTIES:
VOLTAGE RATING: UL 2000V rms, Max, CSA 1000V rms Max

Industry Approvals:

- o ASTM B-8, B-33
- o AAR RP-585
- o UL 44 Type RHH/RHW-2, 2000V, Sunlight Resistant, FOR CT USE (1/0 AWG and larger), PRI, PRII, -40C
- o CSA RW90, PRI, PRII, 1000V, SR, -40C
- o Flame Tests: UL VW-1, CSA 8 AWG - 1 AWG FT1. 1/0 AWG and larger FT1 & FT4/IEEE 1202
- o MSHA (Indent Printed)
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG, kcmil	No. Cond.	Stranding	Insulation Wall, Nom.		Jacket Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Nom. DCR Ω/1M'
				Inches	mm	Inches	mm	Inches	mm	Lb./kft.	kg/km		
167014	**8**	**1**	37/24	0.055	1.40	0.030	0.76	0.349	8.86	94	140	80	0.679
167015	**6**	**1**	61/24	0.060	1.52	0.030	0.76	0.382	9.70	131	195	105	0.423
167017	**4**	**1**	105/24	0.060	1.52	0.030	0.76	0.431	10.95	190	283	140	0.246
167018	**3**	**1**	133/24	0.060	1.52	0.030	0.76	0.461	11.71	242	360	165	0.210
167019	**2**	**1**	161/24	0.060	1.52	0.030	0.76	0.496	12.60	268	399	190	0.160
167020	**1**	**1**	210/24	0.080	2.03	0.045	1.14	0.610	15.49	379	564	220	0.123
167021	**1/0**	**1**	266/24	0.080	2.03	0.045	1.14	0.640	16.26	448	667	260	0.097
167022	**2/0**	**1**	342/24	0.080	2.03	0.045	1.14	0.678	17.22	543	808	300	0.075
167023	**3/0**	**1**	418/24	0.080	2.03	0.045	1.14	0.739	18.77	673	1001	350	0.617
167024	**4/0**	**1**	532/24	0.080	2.03	0.045	1.14	0.806	20.47	833	1240	405	0.048
167026	**262.6**	**1**	646/24	0.090	2.29	0.065	1.65	0.926	23.52	986	1467	467	0.040
167027	**313.3**	**1**	779/24	0.090	2.29	0.065	1.65	0.990	25.15	1158	1723	518	0.033
167029	**373.7**	**1**	931/24	0.090	2.29	0.065	1.65	1.043	26.49	1435	2136	588	0.028
167030	**444.4**	**1**	1102/24	0.090	2.29	0.065	1.65	1.128	28.65	1686	2509	649	0.023
167031	**535.3**	**1**	1330/24	0.090	2.29	0.065	1.65	1.150	29.21	1941	2889	725	0.019
167032	**646.4**	**1**	1591/24	0.090	2.29	0.065	1.65	1.272	32.31	2383	3546	814	0.020
167033	**777.7**	**1**	1924/24	0.090	2.29	0.065	1.65	1.361	34.57	2816	4191	900	0.010
167036	**929.9**	**1**	2317/24	0.090	2.29	0.065	1.65	1.471	37.36	3162	4706	1010	0.011
167035	**1111.1**	**1**	2745/24	0.115	2.92	0.095	2.41	1.640	41.66	3845	5721	1100	0.013

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

**** Ampacity values based onNEC Table 310.15(B)(17) & CEC Table 12A (8 AWG thru 4/0) 90 °C. Larger sizes based on single conductor in free air, 30 °C ambient and 90 °C conductor temperature.***

This product complies with European Directive 2011/65/EU (RoHS-2)
The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Company Name: _____ Date: _____

Customer Approval: _____ Customer Title: _____

Specification Issue Date: March 27, 2013

© 2013 CCI