# COMMODITY CABLES, INC.

## 1 RG6 QUAD + 1 CAT5E 350MHz. PVC Siamese

### Description

Description: 1 RG-6 Quad Shd cable + 1 CAT5E 350MHz. Siamese Construction

Application: Horizontal Wiring in LAN

Reference Standard: EIA/TIA568 & ISO/EIC 11801

### RG-6 Quad Specifications:



### Structure Specs

| | | |
|---|---|---|
| Center Conductor | 18 AWG | 1.024mm |
| | CCS | CCS –Copper Cladding Steel |
| Dielectric | Foam Polyethylene | Diameter Over Dielectric: 4.57mm |
| Inner Shield | Foil: Alum | Alum Braid: 60% Coverage |
| Outer Shield | Foil: Alum | Alum Braid: 40% Coverage |
| Jacket | PVC | Diameter Over Jacket: 8.2 mm |
| Average Thickness(mm) | | 0.75 |
| Jacket Colors | | 1- Black |

### Electrical Spec

| | |
|---|---|
| Test Object | Jacket |
| Test Material | PVC |
| Before Tensile Strength (Mpa) | > = 13.8 |
| Aging Elongation (%) | > = 100 |
| Aging Condition (Cxhrs) | 100 x 168 |
| After Tensile Strength (Mpa) | > = 85% of unaged |
| After Elongation (%) | > = 85% of unaged |
| Cold Bend (-20+/-2 Cx4hrs) | No crack |

### RG-6 Quad Performance

| MHz | dB/100ft |
|---|---|
| 55 MHz | 5.25 |
| 300 MHz | 11.64 |
| 550 MHz | 16.08 |
| 750 MHz | 18.54 |
| 865 MHz | 20.01 |
| 1000 MHz | 21.49 |
| 1450 MHz | 26.6 |
| 2050 MHz | 31.9 |
| 2200 MHz | 33.8 |
| 2550 MHz | 36.37 |
| 3000 MHz | 39.82 |


| | | | |
|---|---|---|---|
| Return loss | dB | 5-300Mhz | 22 |
| | | 300-2200Mhz | 20 |

### Standard Packaging/Jacket Color



*1000'*
*Wooden Reel*
*White or Orange Jacket*
*Weight: 62 lbs.*

### Part No.:16Q5ECMRRx




### Cat5E 350MHz. Specifications:



### Structure Specs:

| | |
|---|---|
| Conductor: | 1/ 0.50 mm, 24 AWG Solid Copper |
| Insulation: | PE |
| Average Thickness (mm): | 0.205 |
| Min. Point Thickness (mm): | 0.202 |
| Insulation Dia. (+/-0.01mm): | 0.91 |
| Twisted Pair Dia (+/-0.02mm): | 1.82 |
| Assembly Dia. (+/-0.1mm): | 3.80 |
| Outer Dia. (+/-0.2mm): | 5.10 |
| Jacket: | PVC |
| Jacket Colors: | Green |

### Electrical Specs:

| | | |
|---|---|---|
| Characteristic Impedance: | 100 Ohm +- 15 Ohm @ 1 ~ 100 MHz | |
| Delay Skew: | (ns/100m) | < = 45 |
| Pair-to-Ground Capacitance Unbalance (pF/100m): | | < = 300 |
| Max. Conductor DC Resistance 20C (ohms/km): | | 93.8 |
| Resistance Unbalanced (%): | | <=5% |

### Cat 5E 350MHz. Performance

| Frequency MHz | RL dB | Attenuation dB/100m | NEXT dB | ACR dB/100m |
|---|---|---|---|---|
| 0.772 | 19.4 | 1.8 | 67 | 67.2 |
| 1 | 20 | 2 | 65.3 | 66.3 |
| 4 | 23 | 4.1 | 56.3 | 55.2 |
| 8 | 24.5 | 5.8 | 51.8 | 49 |
| 10 | 25 | 6.5 | 50.3 | 45.8 |
| 16 | 25 | 8.2 | 47.3 | 41 |
| 20 | 25 | 9.3 | 45.8 | 38.5 |
| 25 | 24.3 | 10.4 | 44.3 | 36.9 |
| 31.25 | 23.6 | 11.7 | 42.9 | 32.2 |
| 62.5 | 21.5 | 17 | 38.4 | 22.4 |
| 100 | 20.1 | 22 | 35.3 | 13.3 |
| 200 | 18 | 32.4 | 30.8 | |
| 300 | 16.8 | 41 | 28.02 | |
| 350 | 16.3 | 44.9 | 27.2 | |

| Frequency MHz | Delay Max (ns/100m) | ELFEXT dB/100m | PSELFEXT dB/100m | PSNEXT dB |
|---|---|---|---|---|
| 0.772 | 575 | 66 | 63 | 64 |
| 1 | 570 | 63.8 | 60.8 | 62.3 |
| 4 | 552 | 51.7 | 48.7 | 53.3 |
| 8 | 546.7 | 45.7 | 42.7 | 48.8 |
| 10 | 545.4 | 43.8 | 40.8 | 47.3 |
| 16 | 543 | 39.7 | 36.7 | 44.3 |
| 20 | 542 | 37.7 | 34.7 | 42.8 |
| 25 | 541.2 | 35.8 | 32.8 | 41.3 |
| 31.25 | 540.4 | 33.9 | 30.9 | 39.9 |
| 62.5 | 538.6 | 27.8 | 24.8 | 35.4 |
| 100 | 537.6 | 23.8 | 20.8 | 32.3 |

*All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%.

It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.