Comtran Cable LLC
330A Turner Street
South Attleboro, MA 02703-7714
(P) 508-399-7004
(F) 508-399-7360
www.ComtranCorp.com

Design Specification
Part Number: 32805

DESCRIPTION: 18 AWG 2 conductor shielded sound and security cable — Nom. O.D. (in.)

CONSTRUCTION:

Conductors:	18 AWG 7 stranded bare copper	
Insulation:	0.0073" nominal wall SR PVC	.060
Core Assembly:	2 conductors cabled together with a 2" nominal left hand lay	
Shield:	Aluminum/polyester tape helically applied with the foil side out	
Drain Wire:	24 AWG 7 strand tinned copper helically applied over the foil shield	
Jacket:	0.014" nominal wall Chrome Gray PVC	.151
	Parallel ripcord located under jacket	

COLOR CODE: Black, Red

SPECIFICATIONS:
UL 13, Power Limited Circuit Cable
UL 444, Communication Cables
UL 1424 Power Limited Fire Alarm Cable
UL 1666, Riser Cable Flame Test
NEC Article 725,760 and 800

CERTIFICATIONS:
UL Listed Type CL3R/FPLR
C(UL)US Type CMR
California State Fire Marshal Approved

ELECTRICAL PERFORMANCE:
Capacitance: 72 pF/ft nominal conductor – conductor @ 1 KHz
Impedance: 38 Ω nominal @ 1 MHz

SIGNATURE:_____DATE:_____

DRAWING	REV.	DATE	DRWN.	APP.	REMARKS	
32805	.11	1/10/13	BC	PA	Drain	**32805**
2805	.10	06/02/06	2me	RHW	Add ripcord; revise print	
2805	.09	05/11//05	2me	RHW	Revised and redrawn	Page 1 of 1
2805	.08	7/28/04	rhw	RHW	Added electrical performance	